


ENGINEERING
YOUR SPRAY SOLUTION



PRECISION SPRAY NOZZLES AND ACCESSORIES

for industrial spray solutions | Edition 221

GENERAL INDUSTRY





INDUSTRIAL NOZZLE TECHNOLOGY FROM EUROPE'S LEADING SUPPLIER

CONTENTS

	Introduction	4
	Pneumatic atomizing nozzles	24
	Hollow cone nozzles	60
	Full cone nozzles	78
	Flat fan nozzles	102
	Solid stream nozzles	152
	Compressed air nozzles	160
	Tank cleaning nozzles	196
	Nozzle-valve combinations	254
	Accessories	264
	Planning aids	292





➤➤ WHERE TRADITION MEETS THE FUTURE



1879

Company founded
by Paul Lechler

1893

Patent for
liquid atomization

1967

Relocation of production
to Metzingen

1978

Expansion to the
USA and then to
other countries

1995

Production, sales and
administration are
concentrated in Metzingen

140

1879 - 2019

2010

Expansion of production
with a new, 13,000 m²
production hall

2016

Opening of the
state-of-the-art
Development and
Technology Center
in Metzingen

2019

Lechler celebrates
140th anniversary

2021

New factory
in China

2022

New logistics center
in Metzingen

2023

Start of construction
of the new
Lechler Campus



THERE ARE MANY REASONS TO CHOOSE NOZZLES FROM LECHLER

The first choice for your nozzle solution

You only become a market leader and Europe's number one in nozzle technology when you can offer your customers a variety of engineered spray solutions. Lechler embodies our relationships with customers on every level.

Measurement Technology Center

In our globally incomparable development and technology center, we analyze the spray behavior of our nozzles. Equipped with cutting-edge test rigs, highly developed nozzle measurement technology and state of the art infrastructure. Lechler's research and development center offers various opportunities that serve all of our customers needs; from practical testing, droplet analysis, measurement technology, and more.

Unrivalled product diversity

Boasting over 45,000 different nozzles and nozzle systems, Lechler is able to solve the challenges of virtually every process in every industry. If there is not a product for you in our portfolio, Lechler will develop solutions working with our customers and their requirements.

Highly qualified employees

Employee management at Lechler is characterized by the promotion of continuous development and team spirit in the workplace. This is the secret recipe behind our companies success and true passion and commitment of our people throughout the organization.

Over 140 years of experience

Lechler has been atomizing liquids since 1879. Today, we understand spray technology better than anyone else. With this experience, we not only develop the perfect nozzle for each application, but also offer expert advice on optimising spraying processes.

Creating Solutions

The needs and requirements of our customers are at the forefront of everything we do. Our goal is to always offer the ideal solution for every task, and if it is not yet available, we develop it.

State of the Art Manufacturing

Whether you are looking for state-of-the-art metal processing, precision injection moulding, metal injection molding (MIM), ceramic sintering or 3D printing: We have the experience and knowledge to offer all manufacturing techniques.


Long Lasting Customer Relationships

Longevity and quality is the foundation to which our business is built upon. We thrive on mutual trust and attach great importance to excelling through performance, know-how and long-term partnerships.





GERMAN ENGINEERING EUROPE'S NO. 1 GLOBAL MARKET LEADER




Headquarters



Subsidiary



Sales office/
Sales agent



 **Headquarters**
 **Production**
 **Sales**
 **Service Points**
**Germany**

Lechler GmbH
Paul-Lechler-Straße 11
72555 Metzingen
Phone +49 7123 962-0
info@lechler.de

**India**

Lechler (India) Pvt. Ltd.
Plot B-2
Main Road
Wagle Industrial Estate Thane
400604 Maharashtra
Phone +91 22 40634444
lechler@lechlerindia.com

**ASEAN**

Lechler Spray Technology
Sdn. Bhd.
No. 22, Jalan Astaka 4B/KU2
Bandar Bukit Raja
41050 Klang, Selangor
Malaysia
Phone +603 3359 1118
info@lechler.com.my

**Finland**

Lechler Oy
Ansatie 6 a C 3 krs
01740 Vantaa
Phone +358 207 856880
info@lechler.fi

**Great Britain**

Lechler Ltd.
1 Fell Street, Newhall
Sheffield, S9 2TP
Phone +44 114 2492020
info@lechler.com

**Spain**

Lechler, S.A.
C / Isla de Hierro, 7 –
Oficina 1.3
28703 San Sebastián de los
Reyes (Madrid)
Phone +34 91 6586346
info@lechler.es

**China**

Lechler Nozzle Systems
(Changzhou) Co., Ltd.
No.99 Decheng Rd, Jintan
Changzhou, JS 213200, P.R.C
Phone +86 400-004-1879
info@lechler.com.cn

**USA**

Lechler Inc.
445 Kautz Road
St. Charles, IL 60174
Phone +1 630 3776611
info@lechlerusa.com

**Belgium**

Lechler S.A./N.V.
Avenue Newton 4
1300 Wavre
Phone +32 10 225022
info@lechler.be

**France**

Lechler France SAS
Parc de la Haute Maison
6, Allée Képler, Bâtiment C2
77420 Champs-sur-Marne
Phone +33 1 49882600
info@lechler.fr

**Italy**

Lechler Spray Technology S.r.l.
Via Don Dossetti, 2
20074 Carpiano (MI)
Phone +39 02 98859027
info@lechleritalia.com

**Sweden**

Lechler AB
Hävertgatan 29
254 42 Helsingborg
Phone +46 18 167030
info@lechler.se



- Subsidiary
- Sales office/
Sales agent



DIVERSITY IN TOP FORM

Lechler's services go far beyond the development and production of nozzles. Thanks to an extensive portfolio of products and services, we are able to ensure optimum spraying results in a wide range of industries and applications.

MEASURING TECHNOLOGY

At Lechler, high-precision spray measurements and analysis are not only used for nozzle developments, they are also offered as a service.



For detailed information about
our range of services, please visit:
www.lechler.com

NOZZLES

In addition to the nozzles presented in this catalogue, our portfolio also includes numerous special nozzles – for applications in many other industries, from agriculture to steel production.

CFD

Computational Fluid Dynamics (CFD) not only enables us to develop nozzles quickly and precisely, it also ensures customer-specific process optimization.

ENGINEERING

Our experienced engineering team strives to provide you with a system solution tailored to your application and installation-specific conditions.



DROPLET SEPARATORS

Our droplet separators play a key role in process optimizations. They are primarily designed to separate liquids from gas flows and are currently used in over 100 different applications worldwide.

LANCES AND CUSTOM SOLUTIONS

With custom nozzle lances, spray headers and spray systems, we ensure the implementation of customized solutions for your specific application.

➤➤ FOUR BUSINESS DIVISIONS DIVERSITY AT ITS FINEST

There's more to spraying than meets the eye. Various industries have their own focus and requirements. To meet all of them, we develop and sell industry-oriented solutions in four individual business sectors.

Our diversity and experience spanning over 140 years gives us a wealth of knowledge that is shared to guarantee the best engineered spray solution across all industries.




GENERAL INDUSTRY

Food and Beverage Industry, Pharmaceutical Industry, Chemical Industry, Automotive Industry, just to name a few. Lechler Nozzles can be found in almost every production environment. With a deep understanding of customer processes, we ensure an optimized engineered spray solution for every application.



AGRICULTURE

From plant protection and liquid fertilization to irrigation – Lechler offers the ideal nozzles for precise application, thereby achieving the best results with minimal effort in the shortest possible time. This helps to increase yields and protect the environment.



METALLURGY

Steel and aluminium producers face immense competitive pressure worldwide. The required product qualities can only be produced with maximum energy efficiency through optimization of your process. Lechler nozzles make a decisive contribution to producing innovative material grades and reducing CO₂ emissions.



PROCESS TECHNOLOGY

Increasingly stringent emission requirements but also a growing number of voluntary commitments mean air quality control systems are in the spotlight more than ever. With its wide range of nozzles and efficient gas treatment systems, Lechler offers the perfect answer for every application.

➤➤ AT HOME IN MANY INDUSTRY SECTORS

We understand your processes and engineer every solution to match each nozzle to the respective environmental conditions. Our specialists will help you choose the right nozzle and aid in engineering services to meet your application needs.

APPLICATIONS



CLEANING
REMOVING
COOLING
SURFACE TREATMENT
SURFACE SPRAYING
ATOMIZING
MIXING


AUTOMOTIVE INDUSTRY



CHEMICAL INDUSTRY



ELECTRONICS INDUSTRY





INDUSTRIAL CLEANING TECHNOLOGY



FOOD AND BEVERAGE INDUSTRY



SURFACE TREATMENT





PHARMACEUTICAL AND COSMETICS INDUSTRY



SHIPBUILDING INDUSTRY AND MANY MORE ...

A BRIEF INTRODUCTION TO MORE THAN 45,000 PRODUCTS





QUESTION OF SHAPE: THE IDEAL SPRAY PATTERN FOR YOUR APPLICATION

Form follows function – and vice-versa. The search for the right nozzle begins with the choice of atomization type (single fluid nozzle or pneumatic atomizing nozzle) and the appropriate spray pattern. This determines the essential properties of the nozzle.

Single fluid nozzles

By narrowing the cross section in the nozzle, the flow velocity of the fluid being atomized increases. Potential energy is converted into kinetic energy (speed). The fluid exiting the nozzle orifice discharges the liquid into droplets of various sizes and distribution.

Solid stream nozzles



Precise, solid jet with the highest impact and limited atomization.

Main applications:

- Cleaning
- Injection
- Targeted cooling

Flat fan nozzles



Defined spray, linear impact. A wide range of nozzles with various flow rates, spray angles and materials.

Main applications:

- Cleaning
- Coating
- Humidification

Hollow cone nozzles



Ring-shaped impact, various flow rates and fine atomization. Available in two designs (axial and tangential).

Main applications:

- Cooling
- Humidification
- Chemical engineering

Full cone nozzles



A wide range of nozzles with full surface impact. Available in two designs (axial and tangential).

Main applications:

- Cleaning
- Surface spraying
- Chemical engineering

Pneumatic atomizing nozzles

With pneumatic atomization, the various flow velocities of gases and liquids in a nozzle result in the desired shearing of the liquid into extremely fine droplets.



Finest atomization even of viscous fluids. Full cone or flat fan versions are available.

Main applications:

- Cooling
- Humidification
- Chemical engineering

Compressed air nozzles

Compressed air nozzles are used for dispersing air or saturated steam in a concentrated fan. Generally, they are flat fan, solid stream or round jet nozzles. Our multi-channel compressed air nozzles are extremely quiet and also economical in terms of air consumption.



High blowing force with maximum efficiency and reduced noise level.


Main applications:

- Blowing off and out
- Cooling
- Drying

Tank cleaning nozzles


For years now, our tank cleaning nozzles have been making a name for themselves as both an economical and highly effective solution for tank and equipment cleaning. The portfolio is divided into static spray balls and rotating cleaning nozzles.

Static nozzles



Extremely robust version for easy rinsing even at high temperatures.

Rotating nozzles



High cleaning performance in the low pressure range for any amount of soiling. Enables cleaning in place and saves on expensive cleaning chemicals.



OVERVIEW OF KEY NOZZLE PARAMETERS

FLOW RATE

TEMPERATURE

LIQUID

PRESSURE



In addition to the spray pattern, each nozzle has specific properties, which in turn depend on various – mutually influencing – operating parameters. An overview of the key factors can be found in the planning aids section starting on Page 266.

IMPACT

SPRAY ANGLE

DROPLET SIZE


LIQUID DISTRIBUTION

OUR PRODUCT NUMBERS: EVERYTHING YOU NEED TO KNOW IN TEN CHARACTERS


Each Lechler product number not only serves as an order number, it also describes all the essential properties of the associated nozzle.

Product number

632.301.16.CA



A SPRAY PATTERN



B NOZZLE TYPE/SERIES

C FLOW RATE



The flow rate depends on the respective nozzle type. The exact specifications are shown in the tables on the product pages. The values refer to the measurement with water.

D SPRAY ANGLE



Flat fan: 1 = 20°, 2 = 30°, 3 = 45°, 4 = 60°, 5 = 75°, 6 = 90°, 7 = 120°
Hollow and full cone: 3 = 45°, 4 = 60°, 5 = 80°, 6 = 90°, 8 = 120°/130°
Solid stream: 0 = 0°

E MATERIAL



1Y = stainless steel 1.4404 (316L), 11 = stainless steel 1.4104 (430F), 16 = stainless steel 1.4305 (303), 17 = stainless steel 1.4571 (316Ti), G9 = stainless steel 1.4435 (316L), H1 = stainless steel 1.4408, 21 = Alloy 22, 30 = brass 2.0401, 42 = aluminum, 5E = PVDF, 51 = PA, 53 = PP, 55 = PTFE, 56 = POM. For individual series, the material may deviate from this numbering system. Refer to the respective product page for details. Special material available on request.

F CONNECTION



1/8" to 4" connections. The exact specifications are shown in the tables on the product pages.

Spray angle	Type	Ordering no.								Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]								Spray diameter D [mm] (at p = 2 bar) 	
		Mat. no.				Code						p [bar]									
		16	17	30	5E																
		Stainless steel 303/304	Stainless steel 316Ti/316L	Brass	PVDF	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT			0.5	1.0	2.0*	3.0	5.0	7.0	10.0	H = 200 [mm]	H = 500 [mm]	
20°	632.301	●	●	●	●	CA	CC			0.70	0.60	0.16	0.23	0.32	0.39	1.44	1.65	1.90	160	400	
	632.441	●	●	●	●	CA	CC			1.00	1.10	0.62	0.88	1.25	1.53	4.54	5.20	6.00	160	400	
	632.481	●	●	●	●	CA	CC			1.50	1.20	0.80	1.13	1.60	1.96	5.77	6.60	7.61	160	400	
60°	632.364	●	●	●	●	CA	CC			1.00	0.60	0.31	0.44	0.63	0.77	1.00	1.18	1.40	230	460	
	632.404	●	●	●	●	CA	CC			1.20	0.80	0.50	0.71	1.00	1.23	1.58	1.87	2.24	245	485	
	632.444	●	●	●	●	CA	CC			1.35	0.90	0.62	0.88	1.25	1.53	1.98	2.34	2.80	255	495	
	632.484	●	●	●	●	CA	CC			1.50	1.00	0.80	1.13	1.60	1.96	2.53	2.99	3.58	260	510	

* All the nozzles are designed for a specific reference pressure. This pressure is highlighted in bold in the tables on the product pages. The flow rate specifications at the reference pressure are measured values. The flow rate specifications for a deviating pressure level are calculated values.

Ordering examples

- You are looking for a flat fan nozzle with a 20° spray angle and an approx. 0.3 l/min flow rate at 2 bar. It should be made of stainless steel 303 and come with a 1/8" male thread.

Type	+	Material no.	+	Code	=	Ordering no.
632.301	+	16	+	CA	=	632.301.16.CA

- You are looking for a flat fan nozzle with a 60° spray angle and an approx. 0.6 l/min flow rate at 3 bar. It should be made of brass and come with a 1/4" male threaded connection.

Type	+	Material no.	+	Code	=	Ordering no.
632.364	+	30	+	CC	=	632.364.30.CC

Information on dimensions

- All dimensions in technical drawings and tables are in millimetres (unless stated otherwise).
- Thread sizes BSPP and BSPT are given in inches.

Description of variables in technical drawings


B = bore diameter
 E = narrowest cross-section
 G = thread
 Hex = wrench size
 Flats = wrench size

Product images

The images on the product pages are provided as examples and may deviate in individual cases depending on the actual nozzle size.



PNEUMATIC ATOMIZING NOZZLES



PNEUMATIC ATOMIZING NOZZLES GENERAL INFORMATION




Pneumatic atomizing nozzles produce extremely fine droplets with a small droplet spectrum. They can be split into two types: Internal mixing (for low viscous fluids) and external mixing (for viscous fluids). Gas and liquid are mixed on the inside or outside of the nozzle. Depending on the actual design of the nozzle, the liquid is self-aspirated or supplied under pressure. Various spray jet shapes can be achieved through the design of the nozzle tip.

Pneumatic atomizing nozzles




- Produces extremely fine droplets
- Wide range of liquid-supply
- Internal or external mixing
- Suitable for humidification, cooling and the atomization of viscous fluids


Liquid pressure principle



Siphon principle



Supply principle





PNEUMATIC ATOMIZING NOZZLES OVERVIEW OF SERIES

		Pneumatic atomizing nozzles				
						
Series		140	176 ViscoMist	170	150	77X, 78X, 79X
Information on page		53	54	on request	on request	on request
Spray character	Full cone spray	•	•	•	•	•
	Flat fan		•			
	Solid stream		•			
Type of liquid supply	Pressure principle		•	•	•	•
	Siphon and/or supply principle	•				
Mixing of media	Internal mixing	•		•		
	External mixing		•		•	•
Flow rate	I/h	4.50–12.00	7.80–307.00	8.50–290.00 [l/min]	0.15–63.00 [l/min]	3.00–1,164.00
Spray angle	Small (15°–30°)	•	•	•	•	•
	Medium (45°)					
	Large (60°–80°)					





					
Series		136.1	136.2	136.3	136.4
Information on page		30	32	33	36
 Spray character	Full cone spray	•	•	•	
	Flat fan				•
	Solid stream				
 Type of liquid supply	Pressure principle	•	•		•
	Siphon and/or supply principle			•	
 Mixing of media	Internal mixing	•	•		•
	External mixing			•	
 Flow rate	I/h	0.40–93.20	0.40–132.90	0.30–66.72	0.10–76.10
 Spray angle	Small (15°–30°)	•		•	
	Medium (45°)				•
	Large (60°–80°)		•		•

Pneumatic atomizing nozzles

					
136.5	136.6	166.1	166.2	166.4	166.6
38	40	44	46	47	49
		•	•		
•	•			•	•
	•	•	•	•	•
•					
•		•	•	•	
	•				•
0.80–3.20	1.68–102.10	0.40–93.20	0.40–132.90	0.10–76.10	1.68–102.10
		•			
	•			•	•
•	•		•	•	•

Pneumatic atomizing nozzles, full cone, pressure principle, internal mixing Series 136.1




Features:



- Fine full cone atomization
- Liquid pressure principle
- Internal mixing

Applications:

- Humidification of air
- Cooling



Series 136.1



Liquid connection G ₁	Air connection G ₂	Screw plug thread (size 11)	Weight [g] (Stainless steel 303)
1/4 BSPP	1/4 BSPP	5/16-24 UNF-2A	220

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.																		
		1Y	16																	
		Stainless steel 316L	Stainless steel 303		p air [bar]	$\dot{V}$ water [l/h]	$\dot{V}_n$ air [m³/h]	p air [bar]	$\dot{V}$ water [l/h]	$\dot{V}_n$ air [m³/h]	p air [bar]	$\dot{V}$ water [l/h]	$\dot{V}_n$ air [m³/h]	p air [bar]	$\dot{V}$ water [l/h]	$\dot{V}_n$ air [m³/h]	p air [bar]	p water [bar]	Ø D ₁ [mm]	Ø D ₂ [mm]
20°	136.115.xx.A2	●	●	0.5	0.4	5.9	0.3	1.4	5.8	0.8	2.4	9.1	1.1	3.0	11.0	1.2	0.8	0.7	60	100
0.8					3.8	0.6	1.8	4.1	1.0	2.8	7.5	1.2	3.4	9.6	1.4	1.8	1.5	60	95	
1.2					1.7	0.9	2.2	2.2	1.4	3.2	5.9	1.5	3.8	8.2	1.6	2.6	2.0	60	100	
–					–	–	2.6	1.2	1.7	3.6	4.4	1.8	4.2	6.8	1.9	3.2	3.0	55	95	
–					–	–	–	–	–	4.0	2.9	2.1	4.6	5.5	2.2	4.4	4.0	55	100	
–					–	–	–	–	–	4.4	2.0	2.5	5.0	4.1	2.5	–	–	–	–	
–					–	–	–	–	–	4.8	1.1	2.8	5.4	2.9	2.8	–	–	–	–	
–					–	–	–	–	–	5.2	0.4	3.0	5.8	2.1	3.1	–	–	–	–	
136.125.xx.A2	●	●	0.5	0.8	4.7	1.5	1.2	7.0	1.8	2.8	9.1	3.3	3.4	10.6	3.9	1.4	0.7	55	90	
				1.2	4.4	1.9	1.6	6.6	2.2	3.2	8.7	3.7	3.8	10.3	4.3	2.2	1.5	55	95	
				1.6	4.0	2.3	2.0	6.2	2.6	3.6	8.4	4.1	4.2	9.9	4.6	2.8	2.0	55	100	
				2.0	3.5	2.6	2.4	5.8	3.0	4.0	8.0	4.5	4.6	9.6	5.0	3.4	3.0	60	100	
				2.4	3.0	3.0	2.8	5.4	3.4	4.4	7.7	4.8	5.0	9.3	5.4	4.2	4.0	60	100	
				2.8	2.7	3.2	3.2	4.9	3.7	4.8	7.3	5.2	5.4	8.9	5.8	–	–	–	–	
				3.2	2.0	3.7	3.6	4.4	4.1	5.2	7.0	5.6	5.8	8.6	6.1	–	–	–	–	
				3.6	1.6	4.1	4.0	3.9	4.5	5.6	6.6	5.9	–	–	–	–	–	–	–	
				4.0	1.3	4.5	4.4	3.5	4.8	6.0	6.2	6.3	–	–	–	–	–	–	–	
				4.4	1.0	4.9	4.8	3.1	5.2	–	–	–	–	–	–	–	–	–	–	
				4.8	0.6	5.2	5.2	2.7	5.6	–	–	–	–	–	–	–	–	–	–	
				–	–	–	5.6	2.3	5.9	–	–	–	–	–	–	–	–	–	–	
				–	–	–	6.0	1.9	6.3	–	–	–	–	–	–	–	–	–	–	

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.																		
		1Y	16		0.7			1.5			3.0			4.0			p air [bar]	p water [bar]	Ø D ₁ [mm]	Ø D ₂ [mm]
		Stainless steel 316L	Stainless steel 303		p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]				
20°	136.134.xx.A2	●	●	0.7	1.2	13.2	2.7	2.0	19.4	3.9	3.0	28.3	5.2	3.8	32.6	6.2	1.8	0.7	55	95
1.6					12.4	3.3	2.4	18.1	4.4	3.4	27.5	5.7	4.2	32.0	6.8	2.8	1.5	60	105	
2.0					11.8	3.9	2.8	17.3	4.9	3.8	26.7	6.3	4.6	31.3	7.3	3.8	2.0	60	105	
2.4					11.4	4.4	3.2	16.7	5.5	4.2	25.9	6.8	5.0	30.6	7.8	5.2	3.0	65	110	
2.8					11.1	4.9	3.6	16.1	6.0	4.6	25.0	7.3	5.4	29.9	8.4	6.0	4.0	65	110	
3.2					10.8	5.5	4.0	15.6	6.5	5.0	24.2	7.8	5.8	29.3	8.9	-	-	-	-	
3.6					10.6	6.0	4.4	15.2	7.0	5.4	23.6	8.4	-	-	-	-	-	-	-	
4.0					10.4	6.5	4.8	15.0	7.6	5.8	23.1	8.9	-	-	-	-	-	-	-	
4.4					10.1	7.0	5.2	14.6	8.1	-	-	-	-	-	-	-	-	-	-	
4.8					9.9	7.6	5.6	14.1	8.6	-	-	-	-	-	-	-	-	-	-	
5.2					9.5	8.1	6.0	13.8	9.1	-	-	-	-	-	-	-	-	-	-	
5.6					9.0	8.6	-	-	-	-	-	-	-	-	-	-	-	-	-	
6.0					8.5	9.2	-	-	-	-	-	-	-	-	-	-	-	-	-	
136.142.xx.A2	●	●	2.5	1.4	24.2	5.1	1.6	53.4	4.7	3.2	70.8	8.0	3.8	93.2	9.2	0.8	0.7	60	100	
				1.8	20.4	6.3	2.0	42.6	5.9	3.6	62.5	9.2	4.2	83.1	10.1	1.6	1.5	65	105	
				2.2	20.0	7.2	2.4	35.3	7.2	4.0	55.7	10.6	4.6	75.3	11.3	3.0	2.0	60	105	
				2.6	19.3	8.2	2.8	30.4	8.4	4.4	49.3	11.7	5.0	69.0	12.5	4.0	3.0	65	110	
				3.0	17.6	9.3	3.2	28.6	9.5	4.8	44.6	12.9	5.4	63.4	13.7	6.0	4.0	65	110	
				3.4	16.5	10.4	3.6	28.2	10.5	5.2	41.9	14.1	5.8	57.5	14.9	-	-	-	-	
				3.8	17.0	11.4	4.0	27.3	11.5	5.6	40.4	15.1	-	-	-	-	-	-	-	
				4.2	16.3	12.4	4.4	25.9	12.5	6.0	39.7	16.1	-	-	-	-	-	-	-	
				4.6	15.1	13.3	4.8	24.3	13.5	-	-	-	-	-	-	-	-	-	-	
				5.0	14.0	14.3	5.2	22.3	14.6	-	-	-	-	-	-	-	-	-	-	
				5.4	13.1	15.3	5.6	21.8	15.7	-	-	-	-	-	-	-	-	-	-	
				5.8	12.4	16.2	6.0	21.4	16.7	-	-	-	-	-	-	-	-	-	-	

Ordering Type + Material no. = Ordering no.
example: 136.134.xx.A2 + 1Y = 136.134.1Y.A2

➤ Pneumatic atomizing nozzles, full cone, pressure principle, internal mixing Series 136.2




Features:



- Fine full cone atomization
- Liquid pressure principle
- Internal mixing
- Especially wide spray angle of 60°

Applications:

- Humidification of air
- Cooling



Series 136.2



Liquid connection G ₁	Air connection G ₂	Screw plug thread (size 11)	Weight [g] (Stainless steel 303)
1/4 BSPP	1/4 BSPP	5/16-24 UNF-2A	220

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.			0.7				1.5				3.0				4.0			
		1Y	16		p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	p water [bar]	Ø D ₁ [mm]	Ø D ₂ [mm]
		Stainless steel 316L	Stainless steel 303																	
60°	136.215.xx.A2	●	●	0.5	1.0	3.0	1.3	1.6	5.8	1.7	2.8	8.5	2.4	3.8	9.4	3.1	1.0	0.7	200	330
					1.2	1.8	1.5	1.8	4.9	1.9	3.2	7.2	2.8	4.2	8.2	3.5	1.6	1.5	230	380
					1.4	0.7	1.8	2.0	3.8	2.1	3.6	5.7	3.2	4.6	6.9	3.9	2.4	2.0	230	385
					–	–	–	2.2	2.8	2.3	4.0	4.0	3.6	5.0	5.4	4.2	3.2	3.0	245	390
					–	–	–	2.4	1.7	2.5	4.4	2.2	4.1	5.4	3.8	4.7	4.2	4.0	250	410
					–	–	–	2.6	0.8	2.8	4.8	0.8	4.5	5.8	2.3	5.2	–	–	–	–
					–	–	–	–	–	–	5.0	0.4	4.6	6.0	1.4	5.6	–	–	–	–
					–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–
	136.222.xx.A2	●	●	1.0	0.8	17.5	2.8	1.6	25.9	4.0	3.0	40.4	5.8	3.8	54.9	6.4	0.8	0.7	250	450
					1.0	6.0	4.3	1.8	14.7	5.3	3.2	31.5	6.9	4.0	45.6	7.3	1.6	1.5	245	465
					–	–	–	2.0	6.7	6.7	3.4	22.2	8.2	4.2	37.6	8.5	2.3	2.0	245	465
					–	–	–	2.2	1.9	8.1	3.6	14.6	9.5	4.4	29.6	9.7	3.2	3.0	250	465
					–	–	–	–	–	–	3.8	8.5	11.0	4.6	21.6	11.2	4.2	4.0	245	465
					–	–	–	–	–	–	4.0	4.5	12.3	4.8	15.3	12.4	–	–	–	–
					–	–	–	–	–	–	–	–	–	5.0	9.7	13.8	–	–	–	–
					–	–	–	–	–	–	–	–	–	5.2	6.0	15.2	–	–	–	–
	136.231.xx.A2	●	●	1.4	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–
					1.6	25.6	5.1	2.6	44.2	7.0	3.6	93.7	7.9	4.2	132.9	7.3	2.0	0.7	235	380
					2.0	17.8	6.2	3.0	33.0	8.2	4.0	78.3	9.3	4.6	117.2	9.0	2.6	1.5	245	415
					2.4	11.3	7.2	3.4	24.7	9.2	4.4	65.8	10.6	5.0	101.1	10.4	2.4	2.0	255	420
					2.8	6.9	8.1	3.8	18.1	10.2	4.8	54.9	11.9	5.4	87.9	11.8	3.6	3.0	255	425
					–	–	–	4.2	13.2	11.2	5.2	45.6	13.0	5.8	76.6	13.2	4.2	4.0	265	430
					–	–	–	4.6	9.3	12.0	5.6	38.0	14.1	6.0	71.2	13.8	–	–	–	–
					–	–	–	–	–	–	6.0	36.1	14.4	–	–	–	–	–	–	–

Ordering Type + Material no. = Ordering no.
example: 136.215.xx.A2 + 1Y = 136.215.1Y.A2

Pneumatic atomizing nozzles, full cone, siphon principle, external mixing Series 136.3

Features:




- Particularly fine full cone atomization
- Siphon principle
- External mixing

Applications:

- Cooling
- Atomization of viscous liquids
- Chemical industry



Series 136.3



Liquid connection G ₁	Air connection G ₂	Screw plug thread (size 11)	Weight [g] (Stainless steel 303)
1/4 BSPP	1/4 BSPP	5/16-24 UNF-2A	220

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Air		V̇ water [l/h]									Spray dimensions			
	Type	Mat. no.					Water column [mm WS]					Aspiration height [mm WS]				p air [bar]	Aspiration height [mm WS]	Ø D ₁ [mm]	Ø D ₂ [mm]
		1Y	16																
		Stainless steel 316L	Stainless steel 303		p [bar]	V _n [m³/h]	150	300	450	100	200	300	600	900					
20°	136.316.xx.A2	●	●	0.40	0.60	0.70	–	1.38	1.32	–	–	–	–	–	1.40	300	60	110	
0.80					0.90	1.29	1.44	1.38	–	–	–	–	–	3.20	300	60	120		
1.20					1.10	1.47	1.62	1.53	1.02	0.84	–	–	–	4.80	300	80	135		
1.40					1.20	1.50	1.68	1.62	1.14	0.96	0.66	–	–	6.00	300	70	120		
1.80					1.40	1.62	1.80	1.71	1.26	1.11	0.90	–	–	–	–	–	–		
2.00					1.60	1.68	1.86	1.77	1.32	1.17	0.96	–	–	–	–	–	–		
2.40					1.80	1.74	1.92	1.86	1.44	1.32	1.14	0.51	–	–	–	–	–		
2.60					1.90	1.80	1.98	1.89	1.50	1.32	1.20	0.63	–	–	–	–	–		
3.00					2.10	1.92	2.07	1.95	1.59	1.44	1.29	0.84	0.39	–	–	–	–		
3.20					2.20	1.95	2.10	1.98	1.65	1.50	1.35	0.96	0.48	–	–	–	–		
3.60					2.40	2.07	2.19	2.10	1.80	1.65	1.50	1.14	0.72	–	–	–	–		
3.80					2.60	2.13	2.25	2.16	1.83	1.71	1.59	1.23	0.81	–	–	–	–		
4.20					2.80	2.22	2.37	2.28	1.95	1.80	1.68	1.38	1.08	–	–	–	–		
4.40					2.90	2.25	2.40	2.34	1.98	1.89	1.77	1.44	1.14	–	–	–	–		
4.80					3.10	2.25	2.34	2.28	1.92	1.86	1.77	1.50	1.14	–	–	–	–		
5.00					3.20	2.25	2.31	2.22	1.89	1.83	1.71	1.41	0.84	–	–	–	–		
5.40					3.40	2.13	2.25	2.16	1.80	1.68	1.56	1.05	0.30	–	–	–	–		
5.60					3.60	2.07	2.19	2.10	1.74	1.65	1.44	0.72	–	–	–	–	–		
6.00					3.80	1.98	2.10	1.95	1.56	1.50	1.26	–	–	–	–	–	–		



Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Air		V̇ water [l/h]								Spray dimensions			
	Type	Mat. no.					Water column [mm WS]			Aspiration height [mm WS]								
		1Y	16		150	300	450	100	200	300	600	900	p air [bar]	Aspiration height [mm WS]	Ø D ₁ [mm]	Ø D ₂ [mm]		
		Stainless steel 316L	Stainless steel 303															
20°	136.324.xx.A2	●	●	0.70	0.80	0.90	–	–	–	2.49	1.71	–	–	–	1.20	300	60	115
1.20					1.10	–	–	–	3.12	2.53	1.86	–	–	3.20	300	65	125	
1.40					1.20	–	–	–	3.36	2.78	2.22	–	–	4.80	300	70	135	
1.80					1.50	–	–	–	3.75	3.22	2.67	–	–	6.00	300	80	135	
2.00					1.60	–	–	–	3.96	3.39	2.85	0.66	–	–	–	–	–	
2.40					1.80	–	–	–	4.29	3.73	3.21	1.41	–	–	–	–	–	
2.60					1.90	–	–	–	4.41	3.91	3.39	1.68	–	–	–	–	–	
3.00					2.10	5.43	–	–	4.71	4.18	3.75	2.07	–	–	–	–	–	
3.20					2.20	5.55	–	–	4.80	4.31	3.90	2.25	–	–	–	–	–	
3.60					2.40	5.82	–	–	5.07	4.56	4.20	2.61	–	–	–	–	–	
3.80					2.60	6.03	–	–	5.22	4.72	4.38	2.88	2.10	–	–	–	–	
4.20					2.80	6.30	6.66	–	5.64	5.15	4.71	3.21	2.85	–	–	–	–	
4.40					2.90	6.36	6.72	7.05	5.88	5.38	4.92	3.60	2.97	–	–	–	–	
4.80					3.10	6.27	6.57	6.84	5.97	5.47	5.22	3.93	1.93	–	–	–	–	
5.00					3.20	6.12	6.42	6.75	5.88	5.36	5.10	4.05	–	–	–	–	–	
5.40					3.40	5.82	6.12	6.48	5.49	5.03	4.71	3.81	–	–	–	–	–	
5.60					3.50	5.67	5.97	6.30	5.22	4.84	4.53	3.63	–	–	–	–	–	
6.00					3.80	5.31	5.58	6.00	4.80	4.48	4.08	1.92	–	–	–	–	–	
136.334.xx.A2	●	●	0.70	0.60	1.20	–	–	–	2.19	–	–	–	–	0.80	300	65	120	
				0.80	1.40	–	–	–	2.64	2.28	1.44	–	–	3.20	300	65	115	
				1.20	1.80	–	–	–	3.39	3.00	2.73	0.78	–	4.80	300	70	115	
				1.40	2.00	–	–	–	3.69	3.33	3.06	1.11	–	6.00	300	75	120	
				1.80	2.30	5.19	–	–	4.20	3.87	3.51	2.16	–	–	–	–	–	
				2.00	2.50	5.43	5.97	6.42	4.47	4.08	3.78	2.58	0.84	–	–	–	–	
				2.40	2.80	5.79	6.27	6.72	4.86	4.53	4.20	3.30	1.44	–	–	–	–	
				2.60	3.00	6.00	6.48	6.90	4.98	4.68	4.41	3.57	1.77	–	–	–	–	
				3.00	3.40	6.30	6.75	7.14	5.37	5.07	4.71	3.87	2.31	–	–	–	–	
				3.20	3.50	6.42	6.90	7.29	5.52	5.19	4.89	4.02	2.52	–	–	–	–	
				3.60	3.90	6.75	7.17	7.59	5.82	5.55	5.19	4.29	3.42	–	–	–	–	
				3.80	4.00	6.87	7.32	7.80	6.03	5.73	5.37	4.47	3.81	–	–	–	–	
				4.20	4.40	7.29	7.80	8.34	6.39	6.09	5.79	4.83	4.17	–	–	–	–	
				4.40	4.60	7.62	8.16	8.73	6.69	6.39	6.09	5.13	4.38	–	–	–	–	
				4.80	4.90	8.37	8.85	9.21	7.32	6.99	6.69	5.76	4.86	–	–	–	–	
				5.00	5.10	8.52	8.85	9.15	7.71	7.32	7.05	6.06	5.19	–	–	–	–	
				5.40	5.40	8.34	8.64	8.88	7.71	7.53	7.29	6.48	5.67	–	–	–	–	
				5.60	5.60	8.19	8.49	8.76	7.59	7.41	7.20	6.45	5.73	–	–	–	–	
6.00	5.90	7.86	8.16	8.43	7.26	7.05	6.84	6.15	5.64	–	–	–	–					

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Air		V̇ water [l/h]								Spray dimensions			
	Type	Mat. no.					Water column [mm WS]			Aspiration height [mm WS]								
		1Y	16		150	300	450	100	200	300	600	900	p air [bar]	Aspiration height [mm WS]	Ø D ₁ [mm]	Ø D ₂ [mm]		
		Stainless steel 316L	Stainless steel 303															
20°	136.342.xx.A2	●	●	1.50	1.40	3.60	–	–	–	8.82	–	–	3.93	–	1.80	300	70	120
1.80					4.20	–	–	–	9.45	8.49	7.50	5.22	3.39	3.00	300	70	120	
2.00					4.50	11.97	–	–	9.75	8.91	7.95	5.76	4.05	4.20	300	70	120	
2.40					5.20	12.18	–	–	10.26	9.51	8.73	6.75	5.19	6.00	300	70	120	
2.60					5.50	12.27	13.32	–	10.47	9.75	9.03	7.14	5.58	–	–	–	–	
3.00					6.10	12.27	13.23	14.16	10.65	10.05	9.42	7.74	6.39	–	–	–	–	
3.20					6.40	12.30	13.17	14.07	10.74	10.23	9.63	8.13	6.81	–	–	–	–	
3.60					7.00	12.42	13.20	14.07	11.01	10.53	10.05	8.85	7.86	–	–	–	–	
3.80					7.30	12.54	13.26	14.10	11.28	10.86	10.44	9.30	8.46	–	–	–	–	
4.20					8.00	13.17	13.83	14.49	12.12	11.76	11.40	10.41	9.69	–	–	–	–	
4.40					8.30	13.53	14.13	14.73	12.48	12.15	11.76	10.80	10.08	–	–	–	–	
4.80					8.90	13.98	14.52	15.15	12.99	12.63	12.18	11.19	10.29	–	–	–	–	
5.00					9.20	14.04	14.52	15.15	13.05	12.66	12.30	11.16	10.11	–	–	–	–	
5.40					9.80	13.74	14.31	14.94	12.66	12.24	11.79	10.62	9.21	–	–	–	–	
5.60					10.10	13.35	14.04	14.64	12.27	11.82	11.37	10.08	8.52	–	–	–	–	
6.00					10.80	12.21	12.90	–	10.98	10.50	10.17	8.70	7.05	–	–	–	–	
136.351.xx.A2	●	●	2.50	3.20	11.50	–	–	–	–	38.92	–	–	–	3.80	300	95	135	
				3.60	12.50	–	–	–	45.73	41.94	–	33.17	–	4.60	300	95	145	
				3.80	13.10	–	–	–	47.81	45.14	42.29	35.36	–	5.40	300	100	150	
				4.20	14.20	–	–	–	51.61	49.07	46.46	39.58	29.94	6.00	300	95	150	
				4.40	14.80	–	–	–	53.10	50.87	48.30	41.59	31.59	–	–	–	–	
				4.80	15.90	–	63.39	–	55.30	53.40	51.26	45.06	34.68	–	–	–	–	
				5.00	16.50	–	63.75	66.69	56.05	54.15	52.18	46.29	35.88	–	–	–	–	
				5.40	17.60	61.12	64.17	66.72	56.71	55.04	53.17	47.62	37.83	–	–	–	–	
				5.60	18.10	60.93	63.87	66.48	56.66	55.04	53.22	47.68	38.43	–	–	–	–	
6.00	19.20	59.89	62.88	65.43	55.69	53.98	52.11	45.78	37.05	–	–	–	–					

Ordering Type + Material no. = Ordering no.
 example: 136.342.xx.A2 + 1Y = 136.342.1Y.A2

Pneumatic atomizing nozzles, flat fan, pressure principle, internal mixing Series 136.4

Features:




- Fine flat fan atomization
- Pressure principle
- Internal mixing

Applications:

- Humidification of goods
- Cooling
- Belt humidification



Series 136.4



Liquid connection G ₁	Air connection G ₂	Screw plug thread (size 11)	Weight [g] (Stainless steel 303)
1/4 BSPP	1/4 BSPP	5/16-24 UNF-2A	220

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions				
	Type	Mat. no.			0.7				1.5			3.0			4.0			p air [bar]	p water [bar]	B ₁ [mm]	B ₂ [mm]
		1Y	16		p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]								
		Stainless steel 316L	Stainless steel 303																		
45°	136.414.xx.A2	●	●	0.7	1.0	7.7	1.3	1.4	14.3	1.5	2.2	22.4	2.0	3.0	25.1	2.5	1.4	0.7	85	125	
					1.2	6.0	1.5	1.6	13.0	1.6	2.6	20.0	2.3	3.4	23.0	2.8	2.4	1.5	100	145	
					1.4	4.2	1.7	1.8	11.6	1.8	3.0	17.7	2.6	3.8	20.9	3.1	3.2	2.0	105	155	
					1.6	2.7	1.9	2.0	10.2	2.0	3.4	15.5	3.0	4.2	18.9	3.5	3.8	3.0	120	170	
					1.8	1.3	2.1	2.2	8.9	2.2	3.8	13.3	3.4	4.6	16.9	3.8	4.6	4.0	130	210	
					–	–	–	2.4	7.4	2.4	4.2	11.0	3.7	5.0	14.9	4.2	–	–	–	–	
					–	–	–	2.6	5.9	2.6	4.6	8.8	4.1	5.4	12.8	4.6	–	–	–	–	
					–	–	–	2.8	4.6	2.8	5.0	6.6	4.5	5.8	10.8	5.0	–	–	–	–	
					–	–	–	3.0	3.2	3.0	5.4	4.3	4.9	6.0	9.8	5.2	–	–	–	–	
					–	–	–	3.2	2.1	3.2	5.8	2.5	5.3	–	–	–	–	–	–	–	
					–	–	–	3.4	1.1	3.4	6.0	1.6	5.5	–	–	–	–	–	–	–	
	136.443.xx.A2	●	●	1.0	1.2	13.9	1.5	1.6	26.6	1.6	3.0	37.1	2.6	3.6	45.6	2.9	1.2	0.7	110	165	
					1.4	11.9	1.7	1.8	24.3	1.8	3.4	33.1	3.0	4.0	41.9	3.3	2.0	1.5	115	190	
					1.6	9.5	1.9	2.0	22.0	2.0	3.8	29.5	3.4	4.4	38.3	3.7	2.8	2.0	145	190	
					1.8	7.8	2.1	2.2	19.9	2.2	4.2	26.2	3.8	4.8	35.0	4.0	3.8	3.0	150	210	
					–	–	–	2.4	18.0	2.4	4.6	23.0	4.2	5.2	31.8	4.5	4.8	4.0	160	230	
					–	–	–	2.6	16.2	2.6	5.0	20.2	4.6	5.6	29.0	4.9	–	–	–	–	
					–	–	–	2.8	14.4	2.8	5.4	17.6	4.9	6.0	26.2	5.2	–	–	–	–	
					–	–	–	3.0	12.8	3.0	5.8	14.9	5.3	–	–	–	–	–	–	–	
					–	–	–	3.2	11.3	3.2	6.0	14.1	5.5	–	–	–	–	–	–	–	
					–	–	–	3.4	9.9	3.4	–	–	–	–	–	–	–	–	–	–	
					–	–	–	3.6	8.8	3.6	–	–	–	–	–	–	–	–	–	–	

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.																		
		1Y	16																	
		Stainless steel 316L	Stainless steel 303		p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	p water [bar]	B1 [mm]	B2 [mm]
45°	136.462.xx.A2	●	●	1.5	1.2	19.0	2.6	2.0	22.0	2.0	3.0	61.8	4.0	3.8	76.1	4.6	1.2	0.7	120	140
					1.6	12.2	3.4	2.4	18.0	2.4	3.4	51.9	4.8	4.0	70.4	5.1	2.4	1.5	120	170
					2.0	9.4	4.1	2.8	14.4	2.8	3.8	44.6	5.8	4.2	65.6	5.5	3.2	2.0	120	175
					2.4	7.1	4.8	3.2	11.3	3.2	4.2	39.0	6.6	4.4	61.3	5.9	3.8	3.0	140	205
					2.8	5.7	5.4	3.6	8.8	3.6	4.6	33.4	7.4	4.6	57.3	6.4	6.0	4.0	145	205
					3.2	5.0	6.0	4.0	8.1	3.9	5.0	29.4	8.1	4.8	54.1	6.7	–	–	–	–
					3.6	3.6	6.6	4.4	6.2	4.3	5.4	25.5	8.9	5.0	51.3	7.2	–	–	–	–
					4.0	3.2	7.2	4.8	4.6	4.6	5.8	22.0	9.6	5.2	49.3	7.7	–	–	–	–
					4.4	2.2	7.8	5.2	3.2	4.9	6.0	20.6	9.9	5.4	46.5	8.2	–	–	–	–
					–	–	–	5.6	1.6	5.3	–	–	–	5.6	43.7	8.6	–	–	–	–
					–	–	–	5.8	0.8	5.4	–	–	–	5.8	41.3	8.9	–	–	–	–
					–	–	–	–	–	–	–	–	–	6.0	39.0	9.3	–	–	–	–
60°	136.425.xx.A2	●	●	0.5	0.8	6.5	1.2	1.4	9.4	1.7	2.4	13.2	2.5	2.4	16.1	2.5	1.2	0.7	155	195
					1.2	5.5	1.6	1.8	8.7	2.1	2.6	12.9	2.7	2.8	15.5	2.9	2.2	1.5	165	255
					1.6	4.7	1.9	2.2	7.9	2.4	3.0	12.3	3.0	3.2	15.0	3.2	3.0	2.0	170	265
					2.0	4.0	2.3	2.6	7.2	2.7	3.4	11.8	3.4	3.6	14.5	3.5	3.4	3.0	200	330
					2.4	3.2	2.6	3.0	6.4	3.1	3.8	11.1	3.7	4.0	13.9	3.8	5.6	4.0	200	330
					2.8	2.6	2.9	3.4	5.7	3.4	4.2	10.4	4.0	4.4	13.4	4.1	–	–	–	–
					3.0	2.2	3.1	3.8	5.1	3.7	4.6	9.8	4.3	4.8	12.8	4.5	–	–	–	–
					–	–	–	4.0	4.8	3.9	5.0	9.2	4.6	5.2	12.2	4.8	–	–	–	–
					–	–	–	4.4	4.2	4.2	5.4	8.6	5.0	5.6	11.7	5.1	–	–	–	–
					–	–	–	4.8	3.6	4.5	5.8	8.1	5.3	6.0	11.2	5.4	–	–	–	–
					–	–	–	5.2	2.8	4.8	6.0	7.8	5.4	–	–	–	–	–	–	–
					–	–	–	5.6	2.2	5.1	–	–	–	–	–	–	–	–	–	–
	–	–	–	6.0	1.6	5.5	–	–	–	–	–	–	–	–	–	–				
	136.452.xx.A2	●	●	1.5	1.0	18.8	3.9	1.8	31.0	5.3	3.2	50.1	7.7	3.8	70.7	8.2	1.0	0.7	130	185
					1.4	8.6	5.7	2.0	25.4	6.3	3.6	39.5	9.4	4.2	58.6	9.6	1.8	1.5	150	240
					1.8	7.4	7.0	2.2	20.1	7.2	4.0	31.3	11.2	4.6	48.6	11.2	2.6	2.0	155	245
					2.2	4.1	8.4	2.4	15.5	8.0	4.4	24.0	12.9	5.0	41.2	13.1	3.6	3.0	175	280
					2.6	1.0	9.8	2.6	12.4	8.9	4.8	17.7	14.5	5.4	33.6	14.8	5.0	4.0	180	285
					2.8	0.1	10.3	2.8	10.4	9.6	5.2	13.4	16.0	5.8	27.5	16.4	–	–	–	–
					–	–	–	–	–	–	5.6	10.6	17.5	6.0	24.4	17.2	–	–	–	–
–					–	–	–	–	–	6.0	8.6	18.8	–	–	–	–	–	–	–	
80°	136.433.xx.A2	●	●	0.4	1.0	11.6	2.0	1.8	18.3	2.8	3.0	31.0	3.7	3.8	37.5	4.4	1.4	0.7	150	210
					1.2	8.1	2.4	2.0	15.3	3.2	3.4	25.4	4.4	4.2	32.4	5.0	2.2	1.5	185	255
					1.4	5.3	2.8	2.2	12.2	3.6	3.8	20.6	5.1	4.6	27.7	5.7	3.0	2.0	205	300
					1.6	3.7	3.2	2.4	9.8	4.0	4.2	16.3	5.9	5.0	23.4	6.5	3.8	4.0	300	485
					–	–	–	2.6	7.6	4.3	4.6	12.5	6.6	5.4	19.4	7.2	5.2	4.0	260	395
					–	–	–	2.8	5.9	4.7	5.0	9.3	7.3	5.8	15.9	7.9	–	–	–	–

Ordering Type + Material no. = Ordering no.
 example: 136.462.xx.A2 + 1Y = 136.462.1Y.A2

Pneumatic atomizing nozzles, flat fan, siphon principle, internal mixing Series 136.5

Features:




- Particularly fine flat fan atomization
- Siphon principle
- Internal mixing

Applications:

- Humidification of goods
- Cooling
- Belt humidification



Series 136.5




Liquid connection G ₁	Air connection G ₂	Screw plug thread (size 11)	Weight [g] (Stainless steel 303 SS)
1/4 BSPP	1/4 BSPP	5/16-24 UNF-2A	220

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Air		V̇ water [l/h]								Spray dimensions			
	Type	Mat. no.					Water column [mm WS]				Aspiration height [mm WS]							
		1Y	16		p [bar]	V̇ _n [m³/h]	150	300	450	100	200	300	600	900	p air [bar]	Aspiration height [mm WS]	B ₁ [mm]	B ₂ [mm]
		Stainless steel 316L	Stainless steel 303															
60°	136.516.xx.A2			0.40														
1.20					2.20	1.89	2.13	2.19	1.80	1.77	1.68	1.41	1.16	3.00	300	150	200	
1.40					2.50	1.95	2.16	2.25	1.86	1.80	1.68	1.47	1.21	4.60	300	170	225	
1.80					2.90	1.98	2.22	2.34	1.89	1.86	1.77	1.53	1.26	6.00	300	180	240	
2.00					3.10	1.95	2.19	2.31	1.89	1.80	1.68	1.50	1.26	–	–	–	–	
2.40					3.50	1.89	2.25	2.25	1.83	1.71	1.68	1.47	1.22	–	–	–	–	
2.60					3.70	1.83	2.25	2.25	1.74	1.71	1.59	1.44	1.18	–	–	–	–	
3.00					4.20	1.74	2.01	2.22	1.71	1.62	1.56	1.44	1.28	–	–	–	–	
3.20					4.40	1.71	1.92	2.16	1.65	1.62	1.59	1.59	1.38	–	–	–	–	
3.60					4.80	1.74	1.83	2.10	1.80	1.77	1.74	1.68	1.47	–	–	–	–	
3.80					5.00	1.92	1.80	2.10	1.86	1.86	1.80	1.71	1.49	–	–	–	–	
4.20					5.50	1.98	2.04	2.19	1.92	1.83	1.83	1.68	1.70	–	–	–	–	
4.40					5.70	1.95	2.04	2.19	1.89	1.86	1.80	1.74	1.77	–	–	–	–	
4.80					6.10	2.01	2.04	2.16	2.01	2.01	2.04	2.04	1.98	–	–	–	–	
5.00					6.30	2.10	2.13	2.22	2.19	2.19	2.16	2.10	1.93	–	–	–	–	
5.40					6.80	2.31	2.34	2.28	2.25	2.22	2.16	2.04	1.86	–	–	–	–	
5.60					7.00	2.31	2.28	2.25	2.19	2.16	2.10	2.01	1.80	–	–	–	–	
									6.00	7.40	2.22	2.22	2.22	2.10	2.10	2.04	1.92	1.79

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Air		V̇ water [l/h]							Spray dimensions				
	Type	Mat. no.					Water column [mm WS]			Aspiration height [mm WS]								
		1Y	16		150	300	450	100	200	300	600	900	p air [bar]	Aspiration height [mm WS]	B ₁ [mm]	B ₂ [mm]		
		Stainless steel 316L	Stainless steel 303															
60°	136.525.xx.A2	●	●	0.50	p [bar]	V̇ _n [m³/h]	150	300	450	100	200	300	600	900	p air [bar]	Aspiration height [mm WS]	B ₁ [mm]	B ₂ [mm]
					0.60	1.60	–	–	–	2.00	–	–	–	–	1.00	300	155	240
					0.80	1.90	–	–	–	2.21	2.10	1.98	–	–	3.00	300	200	295
					1.20	2.30	2.75	2.84	–	2.53	2.39	2.33	2.04	1.69	4.60	300	215	325
					1.40	2.60	2.84	2.90	3.05	2.63	2.51	2.42	2.14	1.82	6.00	300	250	400
					1.80	3.00	2.96	3.01	3.16	2.78	2.64	2.56	2.20	1.88	–	–	–	–
					2.00	3.30	2.94	3.02	3.16	2.73	2.69	2.58	2.18	1.82	–	–	–	–
					2.40	3.70	2.87	2.97	3.10	2.59	2.50	2.38	2.01	1.68	–	–	–	–
					2.60	3.90	2.82	2.86	3.04	2.49	2.46	2.29	1.91	1.62	–	–	–	–
					3.00	4.40	2.59	2.71	2.85	2.23	2.11	2.04	1.73	1.72	–	–	–	–
					3.20	4.60	2.48	2.51	2.71	2.09	1.96	1.91	1.74	1.87	–	–	–	–
					3.60	5.10	2.37	2.31	2.51	2.25	2.18	2.19	1.98	1.90	–	–	–	–
					3.80	5.30	2.34	2.37	2.52	2.22	2.23	2.15	1.99	1.85	–	–	–	–
					4.20	5.70	2.35	2.35	2.43	2.20	2.13	2.11	1.94	1.82	–	–	–	–
					4.40	6.00	2.30	2.32	2.44	2.20	2.07	2.05	1.96	1.83	–	–	–	–
					4.80	6.40	2.25	2.24	2.41	2.12	2.03	2.08	1.90	2.12	–	–	–	–
					5.00	6.60	2.20	2.21	2.37	2.09	2.03	1.98	2.25	2.27	–	–	–	–
					5.40	7.10	2.52	2.23	2.36	2.60	2.55	2.49	2.26	2.08	–	–	–	–
					5.60	7.30	2.50	2.45	2.58	2.57	2.54	2.39	2.16	2.02	–	–	–	–
					6.00	7.80	2.57	2.61	2.76	2.37	2.40	2.18	1.94	1.80	–	–	–	–

Ordering Type + Material no. = Ordering no.
 example: 136.525.xx.A2 + 1Y = 136.525.1Y.A2

Pneumatic atomizing nozzles, flat fan, pressure principle, external mixing Series 136.6



Features:




- Fine flat fan atomization
- Liquid pressure principle
- External mixing

Applications:

- Humidification of goods
- Cooling
- Belt humidification
- Atomization of viscous liquids



Series 136.6



Liquid connection G ₁	Air connection G ₂	Screw plug thread (size 11)	Weight [g] (Stainless steel 303)
1/4 BSPP	1/4 BSPP	5/16-24 UNF-2A	220

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.			0.07				0.15			0.30			0.35		p air [bar]	p water [bar]	B ₁ [mm]	B ₂ [mm]
		1Y	16		p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]							
		Stainless steel 316L	Stainless steel 303																	
45°	136.616.xx.A2	●	●	0.40	0.80	1.68	2.50	0.80	2.43	2.40	0.80	3.42	2.50	1.00	3.69	2.80	1.40	0.07	80	115
1.20					1.80	3.10	1.00	2.46	2.90	1.20	3.48	3.10	1.40	3.81	3.40	2.20	0.15	90	130	
1.60					1.92	3.70	1.40	2.58	3.60	1.60	3.51	3.70	1.80	3.87	4.00	3.20	0.20	90	135	
2.00					2.10	4.30	1.80	2.61	4.20	2.00	3.63	4.30	2.20	3.84	4.60	4.00	0.30	95	145	
2.40					2.07	4.90	2.20	2.76	4.80	2.40	3.63	4.90	2.60	3.90	5.20	5.00	0.35	100	145	
2.80					2.19	5.50	2.60	2.73	5.40	2.80	3.63	5.50	3.00	3.93	5.80	–	–	–	–	
3.20					2.19	6.10	3.00	2.73	6.00	3.20	3.63	6.10	3.40	3.90	6.40	–	–	–	–	
3.60					2.22	6.70	3.60	2.76	6.70	3.60	3.66	6.70	3.80	3.93	7.00	–	–	–	–	
4.00					2.22	7.30	4.00	2.76	7.30	4.00	3.69	7.30	4.20	3.96	7.60	–	–	–	–	
4.40					2.22	7.90	4.40	2.76	7.90	4.40	3.69	7.90	4.60	3.93	8.20	–	–	–	–	
4.80					2.22	8.50	4.80	2.76	8.50	4.80	3.69	8.40	5.00	3.93	8.80	–	–	–	–	
5.20					2.22	9.10	5.20	2.76	9.10	5.20	3.66	9.10	5.40	3.93	9.40	–	–	–	–	
5.60					2.22	9.60	5.60	2.76	9.70	5.60	3.66	9.60	5.80	3.87	10.00	–	–	–	–	
6.00					2.22	10.20	6.00	2.73	10.20	6.00	3.66	10.20	6.00	3.87	10.20	–	–	–	–	

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.																		
		1Y	16																	
		Stainless steel 316L	Stainless steel 303		p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	p water [bar]	B1 [mm]	B2 [mm]
45°	136.635.xx.A2	●	●	0.50	0.80	2.37	2.50	0.80	3.45	2.40	0.80	4.80	2.40	1.00	5.34	2.80	1.40	0.07	85	120
1.20					2.61	3.10	1.20	3.54	3.10	1.20	5.10	3.10	1.40	5.37	3.40	2.20	0.15	95	130	
1.60					2.85	3.70	1.60	3.66	3.70	1.60	5.01	3.70	1.80	5.46	4.00	3.20	0.20	95	135	
2.00					3.03	4.30	2.00	3.72	4.30	2.10	5.10	4.30	2.20	5.46	4.60	4.00	0.30	100	140	
2.40					3.12	4.90	2.40	3.90	4.90	2.40	5.13	4.90	2.60	5.58	5.20	5.00	0.35	100	145	
2.80					3.15	5.50	2.80	3.87	5.50	2.80	5.16	5.50	3.00	5.58	5.80	-	-	-	-	
3.20					3.21	6.10	3.20	3.96	6.10	3.20	5.22	6.10	3.40	5.58	6.40	-	-	-	-	
3.60					3.18	6.70	3.60	3.96	6.70	3.60	5.25	6.70	3.80	5.58	7.00	-	-	-	-	
4.00					3.21	7.30	4.00	3.96	7.20	4.00	5.22	7.30	4.20	5.58	7.60	-	-	-	-	
4.40					3.21	7.90	4.40	3.96	7.90	4.40	5.22	7.90	4.60	5.58	8.10	-	-	-	-	
4.80					3.21	8.40	4.80	3.96	8.40	4.80	5.22	8.40	5.00	5.58	8.70	-	-	-	-	
5.20					3.21	9.00	5.20	3.96	9.00	5.20	5.22	9.00	5.40	5.58	9.30	-	-	-	-	
5.60					3.12	9.60	5.60	3.90	9.60	5.60	5.22	9.60	5.80	5.58	9.90	-	-	-	-	
6.00					3.18	10.20	6.00	3.84	10.20	6.00	5.16	10.20	6.00	5.58	10.20	-	-	-	-	
136.654.xx.A2	●	●	0.70	0.80	5.25	2.40	0.80	7.29	2.40	1.20	10.11	3.10	1.60	11.07	3.70	1.40	0.07	95	135	
				1.20	5.64	3.10	1.20	7.44	3.10	1.60	10.23	3.70	2.00	11.22	4.30	2.20	0.15	100	150	
				1.60	5.79	3.70	1.60	7.62	3.70	2.00	10.38	4.30	2.40	11.28	4.90	3.20	0.20	105	160	
				2.00	6.18	4.30	2.00	7.86	4.30	2.40	10.47	4.90	2.80	11.31	5.50	4.00	0.30	105	160	
				2.40	6.24	4.90	2.40	7.92	4.90	2.80	10.59	5.50	3.20	11.43	6.10	5.00	0.35	105	160	
				2.80	6.27	5.50	2.80	8.04	5.50	3.20	10.59	6.10	3.60	11.46	6.60	-	-	-	-	
				3.20	6.39	6.10	3.20	8.13	6.10	3.60	10.62	6.70	4.00	11.43	7.20	-	-	-	-	
				3.60	6.42	6.60	3.60	8.13	6.70	4.00	10.62	7.20	4.40	11.37	7.80	-	-	-	-	
				4.00	6.45	7.20	4.00	8.13	7.20	4.40	10.62	7.80	4.80	11.37	8.40	-	-	-	-	
				4.40	6.42	7.80	4.40	8.07	7.80	4.80	10.59	8.40	5.20	11.34	9.00	-	-	-	-	
				4.80	6.30	8.40	4.80	8.04	8.40	5.20	10.56	9.00	5.60	11.22	9.60	-	-	-	-	
				5.20	6.24	9.00	5.20	7.86	9.00	5.60	10.50	9.60	6.00	11.16	10.10	-	-	-	-	
				5.60	6.09	9.60	5.60	7.83	9.60	6.00	10.35	10.20	-	-	-	-	-	-	-	
				6.00	5.85	10.20	6.00	7.59	10.20	-	-	-	-	-	-	-	-	-	-	
60°	136.626.xx.A2	●	●	0.40	0.80	1.83	2.80	0.80	2.49	2.80	0.80	3.48	2.80	0.80	3.78	2.80	1.60	0.07	85	135
					1.20	1.98	3.60	1.20	2.58	3.50	1.20	3.60	3.50	1.20	3.87	3.60	2.40	0.15	90	140
					1.60	2.10	4.30	1.60	2.70	4.20	1.60	3.66	4.30	1.60	3.90	4.20	3.20	0.20	90	140
					2.00	2.16	4.90	2.00	2.82	4.90	2.00	3.69	4.90	2.00	3.96	4.90	4.00	0.30	100	145
					2.40	2.25	5.60	2.40	2.85	5.60	2.40	3.69	5.60	2.40	3.96	5.60	5.20	0.35	105	150
					2.80	2.34	6.30	2.80	2.88	6.30	2.80	3.72	6.30	2.80	4.02	6.30	-	-	-	-
					3.20	2.31	7.00	3.20	2.88	7.00	3.20	3.78	7.00	3.20	3.99	7.00	-	-	-	-
					3.60	2.34	7.60	3.60	2.88	7.70	3.60	3.78	7.60	3.60	4.02	7.70	-	-	-	-
					4.00	2.40	8.40	4.00	2.94	8.40	4.00	3.81	8.30	4.00	4.05	8.30	-	-	-	-
					4.40	2.40	9.00	4.40	2.91	9.00	4.40	3.81	9.00	4.40	4.02	9.00	-	-	-	-
					4.80	2.40	9.70	4.80	2.97	9.70	4.80	3.81	9.70	4.80	4.08	9.70	-	-	-	-
					5.20	2.43	10.40	5.20	2.97	10.40	5.20	3.81	10.40	5.20	4.05	10.40	-	-	-	-
					5.60	2.43	11.20	5.60	2.97	11.10	5.60	3.81	11.10	5.60	4.05	11.00	-	-	-	-
					6.00	2.43	11.80	6.00	2.97	11.80	6.00	3.81	11.80	6.00	4.05	11.80	-	-	-	-





Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.																		
		1Y	16		0.07			0.15			0.30			0.35			p air [bar]	p water [bar]	B ₁ [mm]	B ₂ [mm]
		Stainless steel 316L	Stainless steel 303		p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]				
60°	136.645.xx.A2	●	●	0.50	0.80	2.73	2.80	0.80	3.69	2.80	1.00	5.16	3.20	1.00	5.55	3.10	1.60	0.07	100	140
1.20					2.82	3.50	1.20	3.87	3.50	1.40	5.31	3.90	1.40	5.64	3.90	2.40	0.15	110	150	
1.60					3.09	4.20	1.60	3.99	4.20	1.80	5.37	4.60	1.80	5.67	4.60	3.20	0.20	115	155	
2.00					3.27	4.90	2.00	4.11	4.90	2.20	5.37	5.20	2.20	5.76	5.20	4.00	0.30	125	160	
2.40					3.36	5.60	2.40	4.17	5.60	2.60	5.43	5.90	2.60	5.82	5.90	5.20	0.35	130	165	
2.80					3.39	6.20	2.80	4.20	6.30	3.00	5.49	6.60	3.00	5.82	6.60	–	–	–	–	
3.20					3.45	7.00	3.20	4.26	7.00	3.40	5.49	7.20	3.40	5.88	7.30	–	–	–	–	
3.60					3.48	7.60	3.60	4.29	7.60	3.80	5.55	8.00	3.80	5.88	8.00	–	–	–	–	
4.00					3.51	8.30	4.00	4.32	8.30	4.20	5.55	8.60	4.20	5.88	8.70	–	–	–	–	
4.40					3.54	9.00	4.40	4.35	9.00	4.60	5.58	9.30	4.60	5.94	9.30	–	–	–	–	
4.80					3.57	9.70	4.80	4.38	9.70	5.00	5.55	10.00	5.00	5.94	10.10	–	–	–	–	
5.20					3.57	10.40	5.20	4.35	10.40	5.40	5.61	10.70	5.40	5.94	10.70	–	–	–	–	
5.60					3.60	11.00	5.60	4.35	11.10	5.80	5.61	11.40	5.80	5.94	11.40	–	–	–	–	
6.00					3.60	11.70	6.00	4.38	11.70	6.00	5.61	11.80	6.00	5.97	11.80	–	–	–	–	
136.664.xx.A2	●	●	0.70	0.80	5.46	2.80	1.00	7.68	3.20	1.00	10.50	3.20	1.00	11.28	3.20	1.60	0.07	110	140	
				1.20	5.91	3.50	1.40	7.95	3.90	1.40	10.71	3.90	1.40	11.52	3.90	2.40	0.15	130	160	
				1.60	6.15	4.20	1.80	8.13	4.60	1.80	10.83	4.60	1.80	11.58	4.50	3.20	0.20	140	170	
				2.00	6.42	4.90	2.20	8.34	5.30	2.20	11.01	5.30	2.20	11.70	5.20	4.00	0.30	150	180	
				2.40	6.63	5.60	2.60	8.46	5.90	2.60	11.07	5.90	2.60	11.79	5.90	5.20	0.35	155	200	
				2.80	6.75	6.30	3.00	8.58	6.60	3.00	11.16	6.60	3.00	11.88	6.60	–	–	–	–	
				3.20	6.93	6.90	3.40	8.67	7.30	3.40	11.19	7.30	3.40	11.94	7.30	–	–	–	–	
				3.60	6.99	7.60	3.80	8.73	8.00	3.80	11.25	8.00	3.80	12.00	8.00	–	–	–	–	
				4.00	7.05	8.30	4.20	8.76	8.70	4.20	11.28	8.60	4.20	12.03	8.70	–	–	–	–	
				4.40	7.11	9.00	4.60	8.82	9.30	4.60	11.34	9.40	4.60	12.06	9.40	–	–	–	–	
				4.80	7.11	9.70	5.00	8.82	10.10	5.00	11.37	10.00	5.00	12.06	10.10	–	–	–	–	
				5.20	7.17	10.40	5.40	8.82	10.70	5.40	11.37	10.70	5.40	12.09	10.70	–	–	–	–	
				5.60	7.11	11.10	5.80	8.85	11.40	5.80	11.40	11.40	5.80	12.12	11.40	–	–	–	–	
				6.00	7.20	11.80	6.00	8.85	11.80	6.00	11.40	11.70	6.00	12.15	11.80	–	–	–	–	
136.673.xx.A2	●	●	1.00	0.60	13.89	5.60	1.00	18.51	7.60	1.60	24.81	10.20	2.00	26.61	11.80	1.60	0.07	115	160	
				1.00	14.28	7.60	1.40	18.51	9.30	2.00	24.66	11.70	2.40	26.31	13.50	2.40	0.15	120	160	
				1.40	14.28	9.40	1.80	18.33	11.00	2.40	24.42	13.30	2.80	25.65	15.10	3.20	0.20	120	160	
				1.80	14.10	11.00	2.20	17.91	12.70	2.80	23.52	15.10	3.20	24.57	16.60	4.00	0.30	120	165	
				2.20	13.68	12.60	2.60	17.37	14.20	3.20	22.47	16.60	3.60	23.28	18.30	5.20	0.35	120	170	
				2.60	13.62	14.20	3.00	16.65	15.90	3.60	21.30	18.40	4.00	21.93	19.90	–	–	–	–	
				3.00	13.29	18.90	3.40	15.93	17.30	4.00	20.10	19.80	4.40	20.34	21.50	–	–	–	–	
				3.40	12.87	17.40	3.80	15.06	19.00	4.40	18.78	21.50	4.80	19.20	23.10	–	–	–	–	
				3.80	12.57	19.10	4.20	14.58	20.80	4.80	17.52	23.20	5.20	18.06	24.70	–	–	–	–	
				4.20	12.18	20.80	4.60	13.83	22.30	5.20	16.71	24.80	5.60	17.01	26.30	–	–	–	–	
				4.60	11.79	22.40	5.00	13.08	24.00	5.60	15.63	26.40	6.00	15.87	28.00	–	–	–	–	
				5.00	10.95	24.00	5.40	12.30	25.60	5.80	15.12	27.30	–	–	–	–	–	–	–	
				5.40	10.44	25.60	5.80	11.52	27.20	6.00	14.76	28.00	–	–	–	–	–	–	–	
				5.80	9.57	27.20	6.00	11.04	28.10	–	–	–	–	–	–	–	–	–	–	
				6.00	8.97	28.10	–	–	–	–	–	–	–	–	–	–	–	–	–	

Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.																		
		1Y	16		0.07			0.15			0.30			0.35						
		Stainless steel 316L	Stainless steel 303		p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	v̇ water [l/h]	v̇ _n air [m³/h]	p air [bar]	p water [bar]	B ₁ [mm]	B ₂ [mm]
60°	136.682.xx.A2	●	●	1.50	1.00	22.41	7.50	1.40	28.95	9.30	1.80	41.22	11.10	2.00	44.04	11.80	1.60	0.07	110	155
					1.40	20.19	9.30	1.80	26.07	10.90	2.20	34.92	12.60	2.40	39.09	13.40	2.40	0.15	120	155
					1.80	18.75	11.00	2.20	23.94	12.50	2.60	33.18	14.20	2.80	35.16	15.10	3.20	0.20	120	160
					2.20	17.88	12.50	2.60	22.23	14.30	3.00	30.45	15.90	3.20	32.22	16.70	4.00	0.30	120	165
					2.60	17.10	14.20	3.00	21.12	15.90	3.40	28.29	17.50	3.60	30.18	18.30	5.20	0.35	120	175
					3.00	16.47	15.90	3.40	20.10	17.50	3.80	26.64	19.10	4.00	28.32	19.90	–	–	–	–
					3.40	16.08	17.50	3.80	19.44	19.10	4.20	25.35	20.70	4.40	26.94	21.50	–	–	–	–
					3.80	15.90	19.10	4.20	18.99	20.70	4.60	24.24	22.30	4.80	25.59	23.10	–	–	–	–
					4.20	15.90	20.70	4.60	18.45	22.30	5.00	23.13	24.00	5.20	24.36	24.80	–	–	–	–
					4.60	15.81	22.30	5.00	18.18	24.00	5.40	22.14	25.50	5.60	23.28	26.40	–	–	–	–
					5.00	15.21	23.90	5.40	17.25	25.40	5.80	21.12	27.20	6.00	22.17	28.00	–	–	–	–
					5.40	13.92	25.50	5.80	15.72	27.20	6.00	20.67	28.00	–	–	–	–	–	–	–
					5.80	12.09	27.20	6.00	14.91	28.00	–	–	–	–	–	–	–	–	–	–
					6.00	11.07	28.00	–	–	–	–	–	–	–	–	–	–	–	–	–
	136.691.xx.A2	●	●	2.50	1.40	52.00	13.80	2.00	67.30	17.50	2.60	92.30	21.20	2.60	102.10	21.20	1.60	0.07	150	200
					1.80	50.00	16.30	2.40	64.60	20.10	3.00	87.70	23.60	3.00	97.20	23.70	2.40	0.15	160	205
					2.20	48.60	18.80	2.80	62.00	22.50	3.40	84.30	26.00	3.40	92.50	26.10	3.20	0.20	160	205
					2.60	47.50	21.30	3.20	60.40	24.90	3.80	80.70	28.50	3.80	88.40	28.50	4.00	0.30	160	210
					3.00	46.50	23.70	3.60	58.00	27.30	4.20	77.00	30.90	4.20	85.20	31.00	5.20	0.35	150	210
					3.40	45.40	26.10	4.00	56.20	29.80	4.60	74.40	33.40	4.60	81.30	33.40	–	–	–	–
					3.80	44.40	28.60	4.40	54.20	32.10	5.00	71.10	35.90	5.00	78.20	35.80	–	–	–	–
					4.20	42.90	31.00	4.80	52.40	34.70	5.40	68.10	38.30	5.40	74.30	38.20	–	–	–	–
					4.60	41.50	33.40	5.20	49.90	37.10	5.80	64.30	40.80	5.80	71.10	40.70	–	–	–	–
					5.00	39.90	35.80	5.60	48.10	39.50	6.00	63.20	42.00	6.00	68.90	41.90	–	–	–	–
					5.40	38.90	38.30	6.00	46.40	42.00	–	–	–	–	–	–	–	–	–	–
					5.60	38.50	39.40	–	–	–	–	–	–	–	–	–	–	–	–	–

Ordering Type + Material no. = Ordering no.
example: 136.682.xx.A2 + 1Y = 136.682.1Y.A2

Pneumatic atomizing nozzles, full cone, pressure principle, internal mixing Series 166.1

Features:


- Version with magnetic valve
- Fine full cone atomization
- Liquid pressure principle
- Internal mixing

Applications:

- Humidification of air
- Cooling

Technical data:

- Operating pressure: 0–6 bar
- Voltage: 24 V DC
- Power: 8 W
- Switching frequency: Approx. 500/min
- Protective system: IP 67
- Ambient temperature: +10 °C/+50 °C
- Cable length: 1,000 mm
- Material of gasket: EPDM



Series 166.1

Air connection G ₁	Water connection G ₂	Weight [g]
1/4 BSPP	1/4 BSPP	410

Spray angle	Ordering no.		Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.		0.7			1.5			3.0			4.0			p air [bar]	p water [bar]	Ø D ₁ [mm]	Ø D ₂ [mm]
		16		p air [bar]	ṽ water [l/h]	ṽ _n air [m³/h]	p air [bar]	ṽ water [l/h]	ṽ _n air [m³/h]	p air [bar]	ṽ water [l/h]	ṽ _n air [m³/h]	p air [bar]	ṽ water [l/h]	ṽ _n air [m³/h]				
20°	166.115.xx.A2	●	0.5	0.4	5.9	0.3	1.4	5.8	0.8	2.4	9.1	1.1	3.0	11.0	1.2	0.8	0.7	60	100
				0.8	3.8	0.6	1.8	4.1	1.0	2.8	7.5	1.2	3.4	9.6	1.4	1.8	1.5	60	95
				1.2	1.7	0.9	2.2	2.2	1.4	3.2	5.9	1.5	3.8	8.2	1.6	2.6	2.0	60	100
				-	-	-	2.6	1.2	1.7	3.6	4.4	1.8	4.2	6.8	1.9	3.2	3.0	55	95
				-	-	-	-	-	-	4.0	2.9	2.1	4.6	5.5	2.2	4.4	4.0	55	100
				-	-	-	-	-	-	4.4	2.0	2.5	5.0	4.1	2.5	-	-	-	-
				-	-	-	-	-	-	4.8	1.1	2.8	5.4	2.9	2.8	-	-	-	-
				-	-	-	-	-	-	5.2	0.4	3.0	5.8	2.1	3.1	-	-	-	-
	166.125.xx.A2	●	0.5	0.8	4.7	1.5	1.2	7.0	1.8	2.8	9.1	3.3	3.4	10.6	3.9	1.4	0.7	55	90
				1.2	4.4	1.9	1.6	6.6	2.2	3.2	8.7	3.7	3.8	10.3	4.3	2.2	1.5	55	95
				1.6	4.0	2.3	2.0	6.2	2.6	3.6	8.4	4.1	4.2	9.9	4.6	2.8	2.0	55	100
				2.0	3.5	2.6	2.4	5.8	3.0	4.0	8.0	4.5	4.6	9.6	5.0	3.4	3.0	60	100
				2.4	3.0	3.0	2.8	5.4	3.4	4.4	7.7	4.8	5.0	9.3	5.4	4.2	4.0	60	100
				2.8	2.7	3.2	3.2	4.9	3.7	4.8	7.3	5.2	5.4	8.9	5.8	-	-	-	-
				3.2	2.0	3.7	3.6	4.4	4.1	5.2	7.0	5.6	5.8	8.6	6.1	-	-	-	-
				3.6	1.6	4.1	4.0	3.9	4.5	5.6	6.6	5.9	-	-	-	-	-	-	-
				4.0	1.3	4.5	4.4	3.5	4.8	6.0	6.2	6.3	-	-	-	-	-	-	-
				4.4	1.0	4.9	4.8	3.1	5.2	-	-	-	-	-	-	-	-	-	-
				4.8	0.6	5.2	5.2	2.7	5.6	-	-	-	-	-	-	-	-	-	-
				-	-	-	5.6	2.3	5.9	-	-	-	-	-	-	-	-	-	-
				-	-	-	6.0	1.9	6.3	-	-	-	-	-	-	-	-	-	-

Spray angle	Ordering no.		Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.		0.7			1.5			3.0			4.0			p air [bar]	p water [bar]	Ø D ₁ [mm]	Ø D ₂ [mm]
		16		p air [bar]	ṽ water [l/h]	ṽ air [m³/h]	p air [bar]	ṽ water [l/h]	ṽ air [m³/h]	p air [bar]	ṽ water [l/h]	ṽ air [m³/h]	p air [bar]	ṽ water [l/h]	ṽ air [m³/h]				
20°	166.134.xx.A2	●	0.7	1.2	13.2	2.7	2.0	19.4	3.9	3.0	28.3	5.2	3.8	32.6	6.2	1.8	0.7	55	95
				1.6	12.4	3.3	2.4	18.1	4.4	3.4	27.5	5.7	4.2	32.0	6.8	2.8	1.5	60	105
				2.0	11.8	3.9	2.8	17.3	4.9	3.8	26.7	6.3	4.6	31.3	7.3	3.8	2.0	60	105
				2.4	11.4	4.4	3.2	16.7	5.5	4.2	25.9	6.8	5.0	30.6	7.8	5.2	3.0	65	110
				2.8	11.1	4.9	3.6	16.1	6.0	4.6	25.0	7.3	5.4	29.9	8.4	6.0	4.0	65	110
				3.2	10.8	5.5	4.0	15.6	6.5	5.0	24.2	7.8	5.8	29.3	8.9	—	—	—	—
				3.6	10.6	6.0	4.4	15.2	7.0	5.4	23.6	8.4	—	—	—	—	—	—	—
				4.0	10.4	6.5	4.8	15.0	7.6	5.8	23.1	8.9	—	—	—	—	—	—	—
				4.4	10.1	7.0	5.2	14.6	8.1	—	—	—	—	—	—	—	—	—	—
				4.8	9.9	7.6	5.6	14.1	8.6	—	—	—	—	—	—	—	—	—	—
				5.2	9.5	8.1	6.0	13.8	9.1	—	—	—	—	—	—	—	—	—	—
				5.6	9.0	8.6	—	—	—	—	—	—	—	—	—	—	—	—	—
				6.0	8.5	9.2	—	—	—	—	—	—	—	—	—	—	—	—	—
	166.142.xx.A2	●	2.5	1.4	24.2	5.1	1.6	53.4	4.7	3.2	70.8	8.0	3.8	93.2	9.2	0.8	0.7	60	100
				1.8	20.4	6.3	2.0	42.6	5.9	3.6	62.5	9.2	4.2	83.1	10.1	1.6	1.5	65	105
				2.2	20.0	7.2	2.4	35.3	7.2	4.0	55.7	10.6	4.6	75.3	11.3	3.0	2.0	60	105
				2.6	19.3	8.2	2.8	30.4	8.4	4.4	49.3	11.7	5.0	69.0	12.5	4.0	3.0	65	110
				3.0	17.6	9.3	3.2	28.6	9.5	4.8	44.6	12.9	5.4	63.4	13.7	6.0	4.0	65	110
				3.4	16.5	10.4	3.6	28.2	10.5	5.2	41.9	14.1	5.8	57.5	14.9	—	—	—	—
				3.8	17.0	11.4	4.0	27.3	11.5	5.6	40.4	15.1	—	—	—	—	—	—	—
				4.2	16.3	12.4	4.4	25.9	12.5	6.0	39.7	16.1	—	—	—	—	—	—	—
				4.6	15.1	13.3	4.8	24.3	13.5	—	—	—	—	—	—	—	—	—	—
				5.0	14.0	14.3	5.2	22.3	14.6	—	—	—	—	—	—	—	—	—	—
				5.4	13.1	15.3	5.6	21.8	15.7	—	—	—	—	—	—	—	—	—	—
				5.8	12.4	16.2	6.0	21.4	16.7	—	—	—	—	—	—	—	—	—	—

Ordering Type + Material no. = Ordering no.
 example: 166.134.xx.A2 + 16 = 166.134.16.A2

Pneumatic atomizing nozzles, full cone, pressure principle, internal mixing Series 166.2

Features:


- Version with magnetic valve
- Fine full cone atomization
- Pressure principle
- Internal mixing
- Especially wide spray angle of 60°

Applications:

- Humidification of air
- Cooling

Technical data:

- Operating pressure: 0–6 bar
- Voltage: 24 V DC
- Power: 8 W
- Switching frequency: Approx. 500/min
- Protective system: IP 67
- Ambient temperature: +10 °C / +50 °C
- Cable length: 1,000 mm
- Material of gasket: EPDM



Air connection G ₁	Water connection G ₂	Weight [g]
1/4 BSPP	1/4 BSPP	410

Spray angle	Ordering no.		Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.		0.7			1.5			3.0			4.0			p air [bar]	p water [bar]	Ø D ₁ [mm]	Ø D ₂ [mm]
		16		p air [bar]	v water [l/h]	v air [m³/h]	p air [bar]	v water [l/h]	v air [m³/h]	p air [bar]	v water [l/h]	v air [m³/h]	p air [bar]	v water [l/h]	v air [m³/h]				
60°	166.215.xx.A2	●	0.5	1.0	3.0	1.3	1.6	5.8	1.7	2.8	8.5	2.4	3.8	9.4	3.1	1.0	0.7	200	330
				1.2	1.8	1.5	1.8	4.9	1.9	3.2	7.2	2.8	4.2	8.2	3.5	1.6	1.5	230	380
				1.4	0.7	1.8	2.0	3.8	2.1	3.6	5.7	3.2	4.6	6.9	3.9	2.4	2.0	230	385
				–	–	–	2.2	2.8	2.3	4.0	4.0	3.6	5.0	5.4	4.2	3.2	3.0	245	390
				–	–	–	2.4	1.7	2.5	4.4	2.2	4.1	5.4	3.8	4.7	4.2	4.0	250	410
				–	–	–	2.6	0.8	2.8	4.8	0.8	4.5	5.8	2.3	5.2	–	–	–	–
				–	–	–	–	–	–	5.0	0.4	4.6	6.0	1.4	5.6	–	–	–	–
				0.8	17.5	2.8	1.6	25.9	4.0	3.0	40.4	5.8	3.8	54.9	6.4	0.8	0.7	250	450
	166.222.xx.A2	●	1.0	1.0	6.0	4.3	1.8	14.7	5.3	3.2	31.5	6.9	4.0	45.6	7.3	1.6	1.5	245	465
				–	–	–	2.0	6.7	6.7	3.4	22.2	8.2	4.2	37.6	8.5	2.3	2.0	245	465
				–	–	–	2.2	1.9	8.1	3.6	14.6	9.5	4.4	29.6	9.7	3.2	3.0	250	465
				–	–	–	–	–	–	3.8	8.5	11.0	4.6	21.6	11.2	4.2	4.0	245	465
				–	–	–	–	–	–	4.0	4.5	12.3	4.8	15.3	12.4	–	–	–	–
				–	–	–	–	–	–	–	–	–	5.0	9.7	13.8	–	–	–	–
				–	–	–	–	–	–	–	–	–	5.2	6.0	15.2	–	–	–	–
				–	–	–	–	–	–	–	–	–	5.4	2.9	16.5	–	–	–	–
	166.231.xx.A2	●	1.4	1.6	25.6	5.1	2.6	44.2	7.0	3.6	93.7	7.9	4.2	132.9	7.3	2.0	0.7	235	380
				2.0	17.8	6.2	3.0	33.0	8.2	4.0	78.3	9.3	4.6	117.2	9.0	2.6	1.5	245	415
				2.4	11.3	7.2	3.4	24.7	9.2	4.4	65.8	10.6	5.0	101.1	10.4	2.4	2.0	255	420
				2.8	6.9	8.1	3.8	18.1	10.2	4.8	54.9	11.9	5.4	87.9	11.8	3.6	3.0	255	425
				–	–	–	4.2	13.2	11.2	5.2	45.6	13.0	5.8	76.6	13.2	4.2	4.0	265	430
				–	–	–	4.6	9.3	12.0	5.6	38.0	14.1	6.0	71.2	13.8	–	–	–	–
				–	–	–	–	–	–	6.0	36.1	14.4	–	–	–	–	–	–	–
				–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–

Ordering Type + Material no. = Ordering no.
 example: 166.215.xx.A2 + 16 = 166.215.16.A2

Pneumatic atomizing nozzles, flat fan, pressure principle, internal mixing Series 166.4

Features:


- Version with magnetic valve
- Fine flat fan atomization
- Liquid pressure principle
- Internal mixing

Applications:

- Belt humidification
- Cooling
- Humidification of goods

Technical data:

- Operating pressure: 0–6 bar
- Voltage: 24 V DC
- Power: 8 W
- Switching frequency: Approx. 500/min
- Protective system: IP 67
- Ambient temperature: +10 °C /+50 °C
- Cable length: 1,000 mm
- Material of gasket: EPDM



Series 166.4

Air connection G ₁	Water connection G ₂	Weight [g]
1/4 BSPP	1/4 BSPP	410

Spray angle	Ordering no.		Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.		0.7			1.5			3.0			4.0			p air [bar]	p water [bar]	B ₁ [mm]	B ₂ [mm]
		16 Stainless steel 303		p air [bar]	v water [l/h]	v air [m³/h]	p air [bar]	v water [l/h]	v air [m³/h]	p air [bar]	v water [l/h]	v air [m³/h]	p air [bar]	v water [l/h]	v air [m³/h]				
45°	166.414.xx.A2	●	0.7	1.0	7.7	1.3	1.4	14.3	1.5	2.2	22.4	2.0	3.0	25.1	2.5	1.4	0.7	85	125
				1.2	6.0	1.5	1.6	13.0	1.6	2.6	20.0	2.3	3.4	23.0	2.8	2.4	1.5	100	145
				1.4	4.2	1.7	1.8	11.6	1.8	3.0	17.7	2.6	3.8	20.9	3.1	3.2	2.0	105	155
				1.6	2.7	1.9	2.0	10.2	2.0	3.4	15.5	3.0	4.2	18.9	3.5	3.8	3.0	120	170
				1.8	1.3	2.1	2.2	8.9	2.2	3.8	13.3	3.4	4.6	16.9	3.8	4.6	4.0	130	210
				–	–	–	2.4	7.4	2.4	4.2	11.0	3.7	5.0	14.9	4.2	–	–	–	–
				–	–	–	2.6	5.9	2.6	4.6	8.8	4.1	5.4	12.8	4.6	–	–	–	–
				–	–	–	2.8	4.6	2.8	5.0	6.6	4.5	5.8	10.8	5.0	–	–	–	–
				–	–	–	3.0	3.2	3.0	5.4	4.3	4.9	6.0	9.8	5.2	–	–	–	–
				–	–	–	3.2	2.1	3.2	5.8	2.5	5.3	–	–	–	–	–	–	–
				–	–	–	3.4	1.1	3.4	6.0	1.6	5.5	–	–	–	–	–	–	–
	166.462.xx.A2	●	1.5	1.2	19.0	2.6	2.0	22.0	2.0	3.0	61.8	4.0	3.8	76.1	4.6	1.2	0.7	120	140
				1.6	12.2	3.4	2.4	18.0	2.4	3.4	51.9	4.8	4.0	70.4	5.1	2.4	1.5	120	170
				2.0	9.4	4.1	2.8	14.4	2.8	3.8	44.6	5.8	4.2	65.6	5.5	3.2	2.0	120	175
				2.4	7.1	4.8	3.2	11.3	3.2	4.2	39.0	6.6	4.4	61.3	5.9	3.8	3.0	140	205
				2.8	5.7	5.4	3.6	8.8	3.6	4.6	33.4	7.4	4.6	57.3	6.4	6.0	4.0	145	205
				3.2	5.0	6.0	4.0	8.1	3.9	5.0	29.4	8.1	4.8	54.1	6.7	–	–	–	–
				3.6	3.6	6.6	4.4	6.2	4.3	5.4	25.5	8.9	5.0	51.3	7.2	–	–	–	–
				4.0	3.2	7.2	4.8	4.6	4.6	5.8	22.0	9.6	5.2	49.3	7.7	–	–	–	–
				4.4	2.2	7.8	5.2	3.2	4.9	6.0	20.6	9.9	5.4	46.5	8.2	–	–	–	–
				–	–	–	5.6	1.6	5.3	–	–	–	5.6	43.7	8.6	–	–	–	–
				–	–	–	5.8	0.8	5.4	–	–	–	5.8	41.3	8.9	–	–	–	–
				–	–	–	–	–	–	–	–	–	6.0	39.0	9.3	–	–	–	–



Spray angle	Ordering no.		Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.																	
		16																	
		Stainless steel 303																	
				0.7			1.5			3.0			4.0						
				p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇n air [m³/h]	p air [bar]	p water [bar]	B₁ [mm]	B₂ [mm]
60°	166.425.xx.A2	●	0.5	0.8	6.5	1.2	1.4	9.4	1.7	2.4	13.2	2.5	2.4	16.1	2.5	1.2	0.7	155	195
				1.2	5.5	1.6	1.8	8.7	2.1	2.6	12.9	2.7	2.8	15.5	2.9	2.2	1.5	165	255
				1.6	4.7	1.9	2.2	7.9	2.4	3.0	12.3	3.0	3.2	15.0	3.2	3.0	2.0	170	265
				2.0	4.0	2.3	2.6	7.2	2.7	3.4	11.8	3.4	3.6	14.5	3.5	3.4	3.0	200	330
				2.4	3.2	2.6	3.0	6.4	3.1	3.8	11.1	3.7	4.0	13.9	3.8	5.6	4.0	200	330
				2.8	2.6	2.9	3.4	5.7	3.4	4.2	10.4	4.0	4.4	13.4	4.1	–	–	–	–
				3.0	2.2	3.1	3.8	5.1	3.7	4.6	9.8	4.3	4.8	12.8	4.5	–	–	–	–
				–	–	–	4.0	4.8	3.9	5.0	9.2	4.6	5.2	12.2	4.8	–	–	–	–
				–	–	–	4.4	4.2	4.2	5.4	8.6	5.0	5.6	11.7	5.1	–	–	–	–
				–	–	–	4.8	3.6	4.5	5.8	8.1	5.3	6.0	11.2	5.4	–	–	–	–
				–	–	–	5.2	2.8	4.8	6.0	7.8	5.4	–	–	–	–	–	–	–
				–	–	–	5.6	2.2	5.1	–	–	–	–	–	–	–	–	–	–
				–	–	–	6.0	1.6	5.5	–	–	–	–	–	–	–	–	–	–
	166.452.xx.A2	●	1.5	1.0	18.8	3.9	1.8	31.0	5.3	3.2	50.1	7.7	3.8	70.7	8.2	1.0	0.7	130	185
				1.4	8.6	5.7	2.0	25.4	6.3	3.6	39.5	9.4	4.2	58.6	9.6	1.8	1.5	150	240
				1.8	7.4	7.0	2.2	20.1	7.2	4.0	31.3	11.2	4.6	48.6	11.2	2.6	2.0	155	245
				2.2	4.1	8.4	2.4	15.5	8.0	4.4	24.0	12.9	5.0	41.2	13.1	3.6	3.0	175	280
				2.6	1.0	9.8	2.6	12.4	8.9	4.8	17.7	14.5	5.4	33.6	14.8	5.0	4.0	180	285
				2.8	0.1	10.3	2.8	10.4	9.6	5.2	13.4	16.0	5.8	27.5	16.4	–	–	–	–
				–	–	–	–	–	–	5.6	10.6	17.5	6.0	24.4	17.2	–	–	–	–
				–	–	–	–	–	–	6.0	8.6	18.8	–	–	–	–	–	–	–
80°	166.433.xx.A2	●	0.4	1.0	11.6	2.0	1.8	18.3	2.8	3.0	31.0	3.7	3.8	37.5	4.4	1.4	0.7	150	210
				1.2	8.1	2.4	2.0	15.3	3.2	3.4	25.4	4.4	4.2	32.4	5.0	2.2	1.5	185	255
				1.4	5.3	2.8	2.2	12.2	3.6	3.8	20.6	5.1	4.6	27.7	5.7	3.0	2.0	205	300
				1.6	3.7	3.2	2.4	9.8	4.0	4.2	16.3	5.9	5.0	23.4	6.5	3.8	4.0	300	485
				–	–	–	2.6	7.6	4.3	4.6	12.5	6.6	5.4	19.4	7.2	5.2	4.0	260	395
				–	–	–	2.8	5.9	4.7	5.0	9.3	7.3	5.8	15.9	7.9	–	–	–	–
				–	–	–	3.0	4.4	5.0	5.4	6.5	8.0	6.0	14.2	8.3	–	–	–	–

Ordering Type + Material no. = Ordering no.
 example: 166.425.xx.A2 + 16 = 166.425.16.A2



Pneumatic atomizing nozzles, flat fan, pressure principle, external mixing

Series 166.6

Features:

- Version with magnetic valve
- Fine flat fan atomization
- Liquid pressure principle
- External mixing

Applications:




- Belt humidification
- Cooling
- Humidification of goods
- Atomization of viscous liquids

Technical data:

- Operating pressure: 0–6 bar
- Voltage: 24 V DC
- Power: 8 W
- Switching frequency: Approx. 500/min
- Protective system: IP 67
- Ambient temperature: +10 °C /+50 °C
- Cable length: 1,000 mm
- Material of gasket: EPDM



Series 166.6



Air connection G ₁	Water connection G ₂	Weight [g]
1/4 BSPP	1/4 BSPP	410

Spray angle	Ordering no.		Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions							
	Type	Mat. no.		0.07				0.15				0.30				0.35				p air [bar]	p water [bar]	B ₁ [mm]	B ₂ [mm]
		16		p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]	p air [bar]	V̇ water [l/h]	V̇ _n air [m³/h]								
		Stainless steel 303																					
45°	166.616.xx.A2	●	0.40	0.80	1.68	2.50	0.80	2.43	2.40	0.80	3.42	2.50	1.00	3.69	2.80	1.40	0.07	80	115				
				1.20	1.80	3.10	1.00	2.46	2.90	1.20	3.48	3.10	1.40	3.81	3.40	2.20	0.15	90	130				
				1.60	1.92	3.70	1.40	2.58	3.60	1.60	3.51	3.70	1.80	3.87	4.00	3.20	0.20	90	135				
				2.00	2.10	4.30	1.80	2.61	4.20	2.00	3.63	4.30	2.20	3.84	4.60	4.00	0.30	95	145				
				2.40	2.07	4.90	2.20	2.76	4.80	2.40	3.63	4.90	2.60	3.90	5.20	5.00	0.35	100	145				
				2.80	2.19	5.50	2.60	2.73	5.40	2.80	3.63	5.50	3.00	3.93	5.80	–	–	–	–				
				3.20	2.19	6.10	3.00	2.73	6.00	3.20	3.63	6.10	3.40	3.90	6.40	–	–	–	–				
				3.60	2.22	6.70	3.60	2.76	6.70	3.60	3.66	6.70	3.80	3.93	7.00	–	–	–	–				
				4.00	2.22	7.30	4.00	2.76	7.30	4.00	3.69	7.30	4.20	3.96	7.60	–	–	–	–				
				4.40	2.22	7.90	4.40	2.76	7.90	4.40	3.69	7.90	4.60	3.93	8.20	–	–	–	–				
				4.80	2.22	8.50	4.80	2.76	8.50	4.80	3.69	8.40	5.00	3.93	8.80	–	–	–	–				
				5.20	2.22	9.10	5.20	2.76	9.10	5.20	3.66	9.10	5.40	3.93	9.40	–	–	–	–				
				5.60	2.22	9.60	5.60	2.76	9.70	5.60	3.66	9.60	5.80	3.87	10.00	–	–	–	–				
				6.00	2.22	10.20	6.00	2.73	10.20	6.00	3.66	10.20	6.00	3.87	10.20	–	–	–	–				
				166.654.xx.A2	●	0.70	0.80	5.25	2.40	0.80	7.29	2.40	1.20	10.11	3.10	1.60	11.07	3.70	1.40	0.07	95	135	
							1.20	5.64	3.10	1.20	7.44	3.10	1.60	10.23	3.70	2.00	11.22	4.30	2.20	0.15	100	150	
	1.60	5.79	3.70				1.60	7.62	3.70	2.00	10.38	4.30	2.40	11.28	4.90	3.20	0.20	105	160				
	2.00	6.18	4.30				2.00	7.86	4.30	2.40	10.47	4.90	2.80	11.31	5.50	4.00	0.30	105	160				
	2.40	6.24	4.90				2.40	7.92	4.90	2.80	10.59	5.50	3.20	11.43	6.10	5.00	0.35	105	160				
	2.80	6.27	5.50				2.80	8.04	5.50	3.20	10.59	6.10	3.60	11.46	6.60	–	–	–	–				
	3.20	6.39	6.10				3.20	8.13	6.10	3.60	10.62	6.70	4.00	11.43	7.20	–	–	–	–				
	3.60	6.42	6.60				3.60	8.13	6.70	4.00	10.62	7.20	4.40	11.37	7.80	–	–	–	–				
	4.00	6.45	7.20				4.00	8.13	7.20	4.40	10.62	7.80	4.80	11.37	8.40	–	–	–	–				
	4.40	6.42	7.80				4.40	8.07	7.80	4.80	10.59	8.40	5.20	11.34	9.00	–	–	–	–				
	4.80	6.30	8.40				4.80	8.04	8.40	5.20	10.56	9.00	5.60	11.22	9.60	–	–	–	–				
	5.20	6.24	9.00				5.20	7.86	9.00	5.60	10.50	9.60	6.00	11.16	10.10	–	–	–	–				
	5.60	6.09	9.60				5.60	7.83	9.60	6.00	10.35	10.20	–	–	–	–	–	–	–				
	6.00	5.85	10.20				6.00	7.59	10.20	–	–	–	–	–	–	–	–	–	–				






Spray angle	Ordering no.		Narrowest free cross section Ø [mm]	Liquid pressure p [bar]												Spray dimensions			
	Type	Mat. no.		0.07			0.15			0.30			0.35			p air [bar]	p water [bar]	B ₁ [mm]	B ₂ [mm]
		16 Stainless steel 303		p air [bar]	V water [l/h]	V _n air [m³/h]	p air [bar]	V water [l/h]	V _n air [m³/h]	p air [bar]	V water [l/h]	V _n air [m³/h]	p air [bar]	V water [l/h]	V _n air [m³/h]				
60°	166.626.xx.A2	●	0.40	0.80	1.83	2.80	0.80	2.49	2.80	0.80	3.48	2.80	0.80	3.78	2.80	1.60	0.07	85	135
				1.20	1.98	3.60	1.20	2.58	3.50	1.20	3.60	3.50	1.20	3.87	3.60	2.40	0.15	90	140
				1.60	2.10	4.30	1.60	2.70	4.20	1.60	3.66	4.30	1.60	3.90	4.20	3.20	0.20	90	140
				2.00	2.16	4.90	2.00	2.82	4.90	2.00	3.69	4.90	2.00	3.96	4.90	4.00	0.30	100	145
				2.40	2.25	5.60	2.40	2.85	5.60	2.40	3.69	5.60	2.40	3.96	5.60	5.20	0.35	105	150
				2.80	2.34	6.30	2.80	2.88	6.30	2.80	3.72	6.30	2.80	4.02	6.30	-	-	-	-
				3.20	2.31	7.00	3.20	2.88	7.00	3.20	3.78	7.00	3.20	3.99	7.00	-	-	-	-
				3.60	2.34	7.60	3.60	2.88	7.70	3.60	3.78	7.60	3.60	4.02	7.70	-	-	-	-
				4.00	2.40	8.40	4.00	2.94	8.40	4.00	3.81	8.30	4.00	4.05	8.30	-	-	-	-
				4.40	2.40	9.00	4.40	2.91	9.00	4.40	3.81	9.00	4.40	4.02	9.00	-	-	-	-
				4.80	2.40	9.70	4.80	2.97	9.70	4.80	3.81	9.70	4.80	4.08	9.70	-	-	-	-
				5.20	2.43	10.40	5.20	2.97	10.40	5.20	3.81	10.40	5.20	4.05	10.40	-	-	-	-
				5.60	2.43	11.20	5.60	2.97	11.10	5.60	3.81	11.10	5.60	4.05	11.00	-	-	-	-
				6.00	2.43	11.80	6.00	2.97	11.80	6.00	3.81	11.80	6.00	4.05	11.80	-	-	-	-
	166.682.xx.A2	●	1.50	1.00	22.41	7.50	1.40	28.95	9.30	1.80	41.22	11.10	2.00	44.04	11.80	1.60	0.07	110	155
				1.40	20.19	9.30	1.80	26.07	10.90	2.20	34.92	12.60	2.40	39.09	13.40	2.40	0.15	120	155
				1.80	18.75	11.00	2.20	23.94	12.50	2.60	33.18	14.20	2.80	35.16	15.10	3.20	0.20	120	160
				2.20	17.88	12.50	2.60	22.23	14.30	3.00	30.45	15.90	3.20	32.22	16.70	4.00	0.30	120	165
				2.60	17.10	14.20	3.00	21.12	15.90	3.40	28.29	17.50	3.60	30.18	18.30	5.20	0.35	120	175
				3.00	16.47	15.90	3.40	20.10	17.50	3.80	26.64	19.10	4.00	28.32	19.90	-	-	-	-
				3.40	16.08	17.50	3.80	19.44	19.10	4.20	25.35	20.70	4.40	26.94	21.50	-	-	-	-
				3.80	15.90	19.10	4.20	18.99	20.70	4.60	24.24	22.30	4.80	25.59	23.10	-	-	-	-
				4.20	15.90	20.70	4.60	18.45	22.30	5.00	23.13	24.00	5.20	24.36	24.80	-	-	-	-
				4.60	15.81	22.30	5.00	18.18	24.00	5.40	22.14	25.50	5.60	23.28	26.40	-	-	-	-
				5.00	15.21	23.90	5.40	17.25	25.40	5.80	21.12	27.20	6.00	22.17	28.00	-	-	-	-
				5.40	13.92	25.50	5.80	15.72	27.20	6.00	20.67	28.00	-	-	-	-	-	-	-
				5.80	12.09	27.20	6.00	14.91	28.00	-	-	-	-	-	-	-	-	-	-
				6.00	11.07	28.00	-	-	-	-	-	-	-	-	-	-	-	-	-
	166.691.xx.A2	●	2.50	1.40	52.00	13.80	2.00	67.30	17.50	2.60	92.30	21.20	2.60	102.10	21.20	1.60	0.07	150	200
				1.80	50.00	16.30	2.40	64.60	20.10	3.00	87.70	23.60	3.00	97.20	23.70	2.40	0.15	160	205
				2.20	48.60	18.80	2.80	62.00	22.50	3.40	84.30	26.00	3.40	92.50	26.10	3.20	0.20	160	205
				2.60	47.50	21.30	3.20	60.40	24.90	3.80	80.70	28.50	3.80	88.40	28.50	4.00	0.30	160	210
				3.00	46.50	23.70	3.60	58.00	27.30	4.20	77.00	30.90	4.20	85.20	31.00	5.20	0.35	150	210
				3.40	45.40	26.10	4.00	56.20	29.80	4.60	74.40	33.40	4.60	81.30	33.40	-	-	-	-
				3.80	44.40	28.60	4.40	54.20	32.10	5.00	71.10	35.90	5.00	78.20	35.80	-	-	-	-
				4.20	42.90	31.00	4.80	52.40	34.70	5.40	68.10	38.30	5.40	74.30	38.20	-	-	-	-
				4.60	41.50	33.40	5.20	49.90	37.10	5.80	64.30	40.80	5.80	71.10	40.70	-	-	-	-
				5.00	39.90	35.80	5.60	48.10	39.50	6.00	63.20	42.00	6.00	68.90	41.90	-	-	-	-
				5.40	38.90	38.30	6.00	46.40	42.00	-	-	-	-	-	-	-	-	-	-
				5.60	38.50	39.40	-	-	-	-	-	-	-	-	-	-	-	-	-

Ordering Type + Material no. = Ordering no.
 example: 166.626.xx.A2 + 16 = 166.626.16.A2

Accessories for pneumatic atomizing nozzles

Series 136.1 to 136.6


Overview of accessories



Regulating device and shut-off needle

Enables manual regulation of the flow rate and closing of the nozzle.

Material: Stainless steel 303
Weight: 33 g



Ordering no.

Type


013.600.16

Suitable for
all nozzles of
series 136

Regulating device with quick-cleaning needle

Enables manual regulation of the flow rate and cleaning of the nozzle orifice.

Material: Stainless steel 303
Weight: 75 g



Ordering no.

Type

013.601.16.30

013.602.16.30

013.603.16.30

013.604.16.30

013.605.16.30

013.606.16.30

For nozzles

136.xx1

136.xx2

136.xx3

136.xx4

136.xx5

136.xx6

Needle diameter
D
[mm]

2.1

1.2

0.8

0.6

0.4

0.3






Pneumatically controlled valve. Opening pressure 2.1 bar, max. 180 cycles/min.

External control system via separate compressed air connection for switching the nozzle on and off.

Material: Stainless steel 303
Weight: 230 g



Ordering no.		
Type	For nozzles	Needle diameter D [mm]
013.601.16.10	136.xx1	2.1
013.602.16.10	136.xx2	1.2
013.603.16.10	136.xx3	0.8
013.604.16.10	136.xx4	0.6
013.605.16.10	136.xx5	0.4
013.606.16.10	136.xx6	0.3

Pneumatic atomizing nozzles, full cone, siphon principle, internal mixing Series 140

Features:


- Particularly fine full cone atomization
- Siphon principle
- Internal mixing
- Integrated regulating device
- Material: Brass

Applications:

- Lubrication
- Cooling
- Humidification of air




Series 140



Mat. no.	Weight [g]
30	70


Spray angle	Ordering no. Type	Narrowest free cross section Ø [mm]		Hs Aspiration height [mm WS]	Flow rate $\dot{V}_W$ = water $\dot{V}_n$ L = air p [bar] air pressure							
					0.5		1.0		2.0		3.0	
		Water	Air		$\dot{V}_W$ [l/h]	$\dot{V}_n$ L [m³/h]	$\dot{V}_W$ [l/h]	$\dot{V}_n$ L [m³/h]	$\dot{V}_W$ [l/h]	$\dot{V}_n$ L [m³/h]	$\dot{V}_W$ [l/h]	$\dot{V}_n$ L [m³/h]
20°–30°	140.252.30.01	0.50	0.75	500	–	–	4.50	4.00	8.00	6.00	10.50	8.00
		0.50	0.75	200	4.50	2.50	7.00	4.00	10.00	6.00	12.00	8.00

Assembly scheme/Accessories



Accessories:

- Gasket
014.040.72
 7.8 x 12 x 1 (EWP 210)
- Nipple
014.010.30.04
 (Material: Brass)
 Weight: 17 g



Pneumatic atomizing nozzles for atomizing viscous media Series 176 ViscoMist






The ViscoMist series enables the independent regulation of both atomizing air and fan air. Spray angle and droplet size can thus be individually adjusted.

The integrated, pneumatically controlled shut-off/clean-out needle opens and closes the liquid orifice and also cleans it during each closing procedure. This is of particular advantage when spraying viscous liquids. Thanks to their modular design, the nozzles of the ViscoMist series can be optimally adapted to the respective spraying process. To do this, it is simply enough to replace the nozzle components relevant for the flow rate and spray pattern. The housing stays the same.



Series 176 ViscoMist



External mixing nozzle for viscous liquids, e.g. for:

- Coating processes
- Moisturising
- Lubrication
- Glazing
- Disinfection

One nozzle – several spray characters:

- Spray characters
 - Solid stream
 - Full cone
 - Flat fan
- Independent regulation of liquid, atomizing air and fan air
- Fluid circulation possible (nozzle body with five connections)

Nozzle sizes:

- Ø 0.38 mm to 2.54 mm

Valve position:

- Normally closed, fail-safe with loss of air

Signal air pressure:

- Min. 2 bar, max. 3 bar

Cycles per minute:

- 180 cycles/min (short term)

Connection thread:

- 1/8 BSPP
- NPT thread available on request

Weight:

- 550 g

Material:

- 1Y (stainless steel 316L)

Flow rate range:


- Water: 7.8 to 307.0 l/h, at 2 bar
- Air 7.5 to 28.4 m³/h in normal condition, at 2 bar

Atomizing air/Signal air/Fan air:

- The atomizing air causes the liquid to atomize at the nozzle orifice. The fan air allows the spray characteristics to be adapted to the application. The nozzle is activated by the signal air.


Nozzle body configurations

Nozzle body configuration 2




Version with three connections

Nozzle body configuration 4



Version with four connections

Nozzle body configuration 5



Version with five connections

Ordering no.	Narrowest free cross section Ø [mm]	Liquid		Air			Spray dimensions [mm] at distance D ₁ , D ₂ and D ₃																	
Type		Liquid pressure p [bar]	V̇ water [l/h]	Air pressure p air [bar]	Atomizing air [m³/h]	Fan air [m³/h]	Atomizing air [bar]	Liquid pressure p [bar]	Fan air [bar]															
									0.00*			0.35			0.70			1.00			1.50			
									Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	
176.201.1Y.11.00 176.401.1Y.11.00 176.501.1Y.11.00	0.38	0.15	1.89	0.15	0.75	1.00	0.30	0.35	40	60	100	150	180	200	180	230	290	180	230	250	180	230	280	
		0.30	2.80	0.30	1.09	1.44		0.70	40	50	80	150	200	280	200	270	330	230	280	330	230	280	330	
		1.00	4.39	0.70	1.63	2.28		1.00	-	-	-	170	200	280	200	300	380	230	300	360	250	300	380	
		0.70	4.39	0.70	1.63	2.28	1.00	1.50	-	-	-	170	200	360	200	250	340	250	300	360	280	320	380	
		1.00	5.49	1.00	2.02	2.89		0.35	40	60	100	100	130	170	130	180	230	150	230	280	170	220	300	
		1.35	6.40	1.35	2.38	3.45		0.70	40	60	100	80	110	180	130	180	230	150	200	230	180	230	280	
		1.70	7.19	1.70	2.77	3.99	1.00	30	40	80	80	130	180	130	180	250	150	230	280	180	230	330		
		2.00	7.91	2.00	3.11	4.55	2.00	1.50	-	-	-	100	150	200	150	190	250	180	250	360	190	270	360	
		2.40	8.63	2.40	3.48	5.11		0.35	40	60	100	50	80	110	90	130	150	100	150	190	150	200	240	
		2.75	9.24	2.75	3.87	5.67		0.70	40	60	90	60	90	140	80	100	140	110	180	230	150	200	250	
		3.15	9.80	3.15	4.23	6.24	2.75	1.00	40	60	90	70	90	140	100	130	190	130	200	250	150	200	250	
		3.50	10.33	3.50	4.60	6.78		1.50	-	-	-	60	80	130	110	140	180	140	190	230	180	230	300	
4.00	11.17	4.00	5.22	7.70	0.35	40		60	90	50	60	90	50	90	110	80	130	180	170	150	180			
176.202.1Y.11.00 176.402.1Y.11.00 176.502.1Y.11.00	0.58	0.15	4.05	0.15	0.78	1.00	0.30	0.70	-	-	-	180	240	250	230	300	360	280	330	410	300	340	410	
		0.30	5.90	0.30	1.10	1.44		1.00	-	-	-	150	200	230	250	290	430	300	340	460	300	370	560	
		0.70	9.27	0.70	1.67	2.28		1.50	-	-	-	-	-	-	250	290	360	280	340	430	360	410	480	
		1.00	11.47	1.00	2.06	2.89	1.00	0.35	40	50	90	110	140	150	130	170	230	150	180	230	180	220	250	
		1.35	13.32	1.35	2.43	3.45		0.70	40	60	90	110	130	190	140	180	240	170	220	250	200	230	280	
		1.70	14.99	1.70	2.79	3.99		1.00	-	-	-	100	140	200	170	200	280	190	230	330	200	250	330	
		2.00	16.43	2.00	3.14	4.55	2.00	1.50	-	-	-	-	-	-	170	200	300	200	250	360	250	300	380	
		2.40	17.90	2.40	3.52	5.11		0.35	40	50	80	60	80	110	90	130	170	110	150	180	130	200	230	
		2.75	19.23	2.75	3.91	5.67		0.70	40	40	80	70	100	130	110	140	170	140	180	190	150	200	250	
		3.15	20.44	3.15	4.28	6.24	2.75	1.00	30	50	90	70	100	130	100	150	180	130	180	230	150	200	250	
		3.50	21.57	3.50	4.66	6.78		1.50	-	-	-	70	100	150	110	150	230	130	180	240	170	230	300	
		4.00	23.32	4.00	5.22	7.70		0.35	40	40	80	60	80	100	80	100	120	100	140	180	130	150	180	
176.203.1Y.11.00 176.403.1Y.11.00 176.503.1Y.11.00	0.79	0.15	8.36	0.15	0.48	1.00	0.30	0.70	-	-	-	230	300	410	330	410	480	330	410	510	300	380	460	
		0.30	12.38	0.30	0.71	1.44		1.00	-	-	-	230	280	330	300	360	510	410	480	610	430	580	740	
		0.70	19.19	0.70	1.16	2.28		1.50	-	-	-	-	-	-	330	410	530	410	460	640	460	530	710	
		1.00	23.77	1.00	1.46	2.89	1.00	0.35	40	60	100	150	200	270	170	230	280	230	300	380	280	360	410	
		1.35	27.59	1.35	1.65	3.45		0.70	-	-	-	150	200	250	230	300	380	300	360	460	330	380	430	
		1.70	31.04	1.70	1.89	3.99		1.00	-	-	-	-	-	-	230	280	410	300	380	510	300	410	480	
		1.50	-	-	-	-	1.50	-	-	-	-	-	-	230	280	380	280	380	510	330	430	530		

* A cone-shaped spray pattern is produced without fan air.





Ordering no.	Narrowest free cross section Ø [mm]	Liquid		Air			Spray dimensions [mm] at distance D ₁ , D ₂ and D ₃																
Type		Liquid pressure p [bar]	V water [l/h]	Air pressure p air [bar]	Atomizing air [m³/h]	Fan air [m³/h]	Atomizing air [bar]	Liquid pressure p [bar]	Fan air [bar]														
									0.00*			0.35			0.70			1.00			1.50		
									Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm
176.203.1Y.11.00 176.403.1Y.11.00 176.503.1Y.11.00	0.79	2.00	33.99	2.00	2.14	4.55	2.00	0.35	30	60	80	100	140	180	150	200	240	190	230	300	200	230	280
		0.70	-	-	-	130		150	200	170	230	330	230	300	380	250	300	360					
		1.00	-	-	-	130		180	200	180	230	330	230	300	410	250	320	410					
		1.50	-	-	-	-		-	-	180	230	330	240	300	430	250	330	430					
		3.15	41.98	3.15	2.94	6.24	2.75	0.35	40	60	90	100	130	180	140	180	230	170	200	280	190	230	300
		0.70	-	-	-	110		150	200	150	200	250	180	230	300	230	280	380					
		1.00	-	-	-	-		-	-	180	230	300	200	250	360	230	280	380					
1.50	-	-	-	-	-	-		180	230	330	230	280	380	230	290	410							
176.204.1Y.11.00 176.404.1Y.11.00 176.504.1Y.11.00	1.07	0.15	16.88	0.15	2.34	2.04	0.30	0.35	-	-	-	150	200	300	300	410	460	330	410	560	300	410	510
		0.70	-	-	-	-		-	-	300	380	1,040	360	430	530	410	480	640					
		1.00	-	-	-	-		-	-	250	380	510	360	460	580	410	510	690					
		1.50	-	-	-	-		-	-	250	380	480	330	380	530	410	510	660					
		1.00	45.80	1.00	7.32	5.81	1.00	0.35	40	60	80	110	140	190	150	200	250	200	250	330	250	300	430
		0.70	-	-	-	100		140	230	170	200	270	220	270	380	250	330	430					
		1.00	-	-	-	100		130	180	150	190	300	220	250	380	250	300	480					
		1.50	-	-	-	-		-	-	150	200	280	200	250	410	240	300	460					
		2.00	64.99	2.00	11.55	9.06	2.00	0.35	40	60	90	80	100	140	100	130	180	110	170	230	150	190	280
		0.70	-	-	-	80		100	150	100	130	200	130	170	230	150	200	280					
		1.00	-	-	-	70		100	150	100	140	200	130	180	250	150	200	280					
		1.50	-	-	-	70		100	150	110	140	230	130	170	250	150	200	300					
		3.15	80.28	3.15	15.63	12.27	2.75	0.35	50	70	100	70	90	140	90	120	180	110	140	200	140	180	250
		0.70	40	70	100	60		90	140	100	130	180	110	150	230	140	190	250					
		1.00	-	-	-	70		90	140	100	120	190	110	160	250	150	180	280					
		1.50	-	-	-	70		100	150	100	120	180	110	150	230	140	190	300					
176.205.1Y.11.00 176.405.1Y.11.00 176.505.1Y.11.00	1.32	0.15	24.60	0.15	2.17	2.04	0.30	0.35	-	-	-	230	330	460	360	460	530	410	530	640	460	530	660
		0.70	-	-	-	-		-	-	330	460	580	410	510	660	410	480	610					
		1.00	-	-	-	-		-	-	330	410	480	360	460	560	430	560	740					
		1.50	-	-	-	-		-	-	-	-	-	380	510	660	460	580	810					
		1.00	66.62	1.00	6.75	5.81	1.00	0.35	-	-	-	130	170	230	180	230	380	230	290	430	190	360	510
		0.70	-	-	-	110		170	230	180	230	330	220	290	410	190	360	510					
		1.00	-	-	-	-		-	-	190	240	360	230	300	430	270	340	480					
		1.50	-	-	-	-		-	-	170	220	300	220	300	410	250	330	480					
		2.00	94.81	2.00	10.35	9.06	2.00	0.35	40	60	90	80	100	150	110	140	200	140	180	250	170	220	330
		0.70	-	-	-	70		100	150	110	150	230	130	180	280	170	230	360					
		1.00	-	-	-	80		100	150	110	140	220	140	190	280	170	230	360					
		1.50	-	-	-	70		100	150	110	150	200	140	190	300	170	230	360					
		3.15	117.52	3.15	14.00	12.27	2.75	0.35	40	60	100	80	100	150	90	130	200	110	150	230	140	180	280
		0.70	-	-	-	60		90	140	100	130	200	110	170	250	150	200	300					
		1.00	-	-	-	60		90	130	100	130	200	120	170	240	150	200	300					
		1.50	-	-	-	60		90	150	100	130	200	110	180	250	150	200	300					

* A cone-shaped spray pattern is produced without fan air.

Ordering no.	Narrow- est free cross section Ø [mm]	Liquid		Air			Spray dimensions [mm] at distance D ₁ , D ₂ and D ₃																	
Type		Liquid pressure p [bar]	V water [l/h]	Air pressure p air [bar]	Atomizing air [m³/h]	Fan air [m³/h]	Atomizing air [bar]	Liquid pressure p [bar]	Fan air [bar]															
									0.70			1.00			1.40			1.75			2.00			
									Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	
176.206.1Y.11.00 176.406.1Y.11.00 176.506.1Y.11.00	1,70	0.15	41.71	0.15	1.53	2.04	1.00	0.35	220	330	510	280	410	610	360	460	660	-	-	-	-	-	-	
		0.30	59.54	0.30	2.24	2.94		0.70	240	360	530	330	430	660	360	510	760	-	-	-	-	-	-	
		0.70	90.88	0.70	3.47	4.60		1.00	250	360	510	300	430	610	360	510	690	-	-	-	-	-	-	
		1.00	111.73	1.00	4.35	5.81	2.00	0.35	150	230	330	200	280	410	230	300	460	230	330	460	250	330	430	
		1.35	128.99	1.35	5.15	6.90		0.70	180	230	300	200	250	380	230	300	460	250	360	480	280	360	510	
		1.70	144.21	1.70	5.95	7.99		1.00	150	230	330	180	250	380	230	300	430	250	330	480	280	360	530	
		2.00	157.91	2.00	6.71	9.06	2.75	0.35	140	180	280	180	230	300	180	250	360	200	280	410	200	280	430	
		2.40	170.48	2.40	7.53	10.13		0.70	150	200	300	180	230	330	180	250	380	200	280	410	230	300	410	
		2.75	182.25	2.75	8.27	11.21		1.00	140	180	280	180	230	330	190	230	380	200	280	410	230	300	430	
		3.15	193.26	3.15	9.07	12.27	4.00	0.35	130	180	250	150	200	300	170	230	330	180	230	360	180	230	360	
		3.50	203.52	3.50	9.91	13.32		0.70	130	170	250	150	200	300	180	230	330	180	230	360	180	250	380	
		4.00	218.85	4.00	11.13	15.12		1.00	130	180	280	150	200	300	150	230	330	180	250	360	200	250	410	
							1.50	-	-	-	150	200	300	150	230	360	180	250	380	200	280	430		
176.207.1Y.11.00 176.407.1Y.11.00 176.507.1Y.11.00	2.05	0.15	59.20	0.15	3.64	3.36	1.00	0.35	200	280	410	280	360	480	330	430	530	330	480	690	410	480	660	
		0.30	84.97	0.30	5.37	4.91		0.70	200	280	410	280	360	480	300	410	580	360	460	710	410	530	760	
		0.70	129.79	0.70	8.53	7.87		1.00	150	230	360	230	300	460	280	360	530	300	430	610	360	510	740	
		1.00	159.42	1.00	10.84	10.08		1.50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
		1.35	184.59	1.35	12.98	12.16	2.00	0.35	100	140	220	140	190	280	180	230	360	230	280	380	250	330	480	
		1.70	206.70	1.70	14.92	14.07		0.70	100	150	230	140	190	280	180	250	380	200	280	410	250	330	480	
		2.00	226.76	2.00	16.91	15.97		1.00	100	150	250	130	180	280	170	220	330	200	280	410	240	300	480	
		2.40	245.27	2.40	18.94	17.69	2.75	1.50	-	-	-	-	-	-	150	230	330	190	250	380	230	300	430	
		2.75	262.64	2.75	20.86	19.64		0.35	90	130	180	110	170	250	150	200	300	180	230	330	200	280	380	
		3.15	279.03	3.15	22.82	21.53		0.70	90	130	200	130	170	250	150	200	300	180	230	360	200	280	410	
		3.50	293.98	3.50	24.72	23.33	4.00	1.00	90	110	180	120	150	250	140	190	300	170	230	330	200	280	380	
		4.00	317.15	4.00	27.80	26.33		1.50	90	130	200	110	150	250	140	200	300	150	230	360	200	280	380	
									0.35	90	110	150	110	150	230	140	190	250	150	220	360	180	250	410
								0.70	90	110	180	100	140	220	130	190	290	150	200	330	180	250	360	
								1.00	80	110	190	110	150	230	130	180	280	150	230	330	170	250	380	
								1.50	-	-	-	100	150	230	130	180	250	150	200	330	170	240	360	






Ordering no.	Narrow- est free cross section Ø [mm]	Liquid		Air			Spray dimensions [mm] at distance D ₁ , D ₂ and D ₃																
Type		Liquid pressure p [bar]	V water [l/h]	Air pressure p air [bar]	Atomizing air [m³/h]	Fan air [m³/h]	Atomizing air [bar]	Liquid pressure p [bar]	Fan air [bar]														
									0.70			1.00			1.40			1.75			2.00		
									Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm	Ø D ₁ = 150 mm	Ø D ₂ = 230 mm	Ø D ₃ = 380 mm
176.208.1Y.11.00 176.408.1Y.11.00 176.508.1Y.11.00	2.36	0.15	97.20	0.15	3.84	4.40	1.00	0.35	190	280	430	280	360	610	300	460	710	-	-	-	-	-	-
		0.30	114.76	0.30	4.64	5.28		0.70	190	280	430	250	360	610	330	480	760	-	-	-	-	-	-
		0.70	162.98	0.70	6.80	7.87		1.00	-	-	-	230	330	560	300	430	690	-	-	-	-	-	-
		1.50	-	-	-	-		250	360	530	300	380	580	-	-	-	-	-	-	-	-	-	
		1.00	199.13	1.00	8.63	10.08	2.00	0.35	110	190	300	170	250	360	200	280	410	230	330	460	280	460	560
		1.35	229.60	1.35	10.21	12.16		0.70	110	180	250	170	230	360	220	280	410	230	360	510	270	380	530
		1.70	256.24	1.70	11.86	14.07		1.00	110	170	230	140	200	330	190	250	410	230	300	480	280	380	610
		1.50	-	-	-	-		150	200	330	200	280	380	220	300	460	270	380	560	-	-	-	-
		2.00	280.70	2.00	13.37	15.97	2.75	0.35	110	170	230	140	190	280	170	250	360	200	280	380	250	360	460
		2.40	302.99	2.40	14.99	17.69		0.70	100	150	230	140	200	300	170	240	360	200	280	430	230	330	480
		2.75	324.03	2.75	16.33	19.64		1.00	100	140	200	130	180	280	170	230	380	200	280	410	230	330	480
		1.50	90	130	200	130		180	280	150	220	360	190	280	460	230	320	460	-	-	-	-	-
3.15	343.22	3.15	17.99	21.53	4.00	0.35	90	110	180	110	150	220	140	190	300	150	220	300	190	300	410		
3.50	361.32	3.50	19.27	23.33		0.70	90	110	190	130	170	230	140	200	300	170	230	330	200	270	430		
4.00	388.72	4.00	21.73	26.33		1.00	90	110	170	110	150	220	130	200	300	150	230	360	180	280	430		
1.50	-	-	-	-		110	150	220	140	200	300	150	220	360	190	250	410	-	-	-	-	-	
176.209.1Y.11.00 176.409.1Y.11.00 176.509.1Y.11.00	2.54	0.15	82.06	0.15	1.87	3.36	1.00	0.35	200	300	460	280	380	610	330	460	710	410	530	760	460	660	810
		0.30	119.53	0.30	3.77	4.91		0.70	200	280	430	280	410	610	330	480	690	410	560	740	460	640	810
		0.69	180.05	0.69	6.58	7.87		1.00	-	-	-	-	-	-	300	460	690	410	510	690	430	580	810
		1.50	-	-	-	-		-	-	-	300	460	690	380	530	760	430	580	810	-	-	-	-
		1.03	221.23	1.03	8.50	10.08	2.00	0.35	130	200	300	180	250	380	200	280	460	250	330	510	280	360	560
		1.38	255.60	1.38	10.13	12.16		0.70	130	180	280	170	230	360	200	280	460	230	330	560	280	380	610
		1.72	285.50	1.72	11.57	14.07		1.00	100	170	280	170	230	360	200	280	430	230	330	510	280	380	560
		1.50	-	-	-	-		-	-	-	200	250	430	230	300	460	250	380	560	-	-	-	-
		2.07	312.94	2.07	13.13	15.97	2.75	0.35	100	150	230	150	200	330	170	230	410	200	280	460	240	360	510
		2.41	338.83	2.41	14.71	17.69		0.70	100	150	230	140	190	300	180	240	410	200	280	460	230	360	560
		2.76	362.49	2.76	16.26	19.64		1.00	90	140	230	140	190	300	180	250	410	200	280	460	250	360	560
		1.50	100	140	200	140		190	300	180	250	410	200	280	460	230	330	510	-	-	-	-	-
		3.10	384.75	3.10	17.75	21.53	4.00	0.35	100	140	200	130	180	250	140	190	280	180	250	360	190	250	410
		3.45	405.71	3.45	19.33	23.33		0.70	90	130	200	130	180	280	150	200	300	170	230	360	200	280	410
		4.00	436.86	4.00	21.83	26.33		1.00	90	130	180	110	150	250	140	200	300	180	230	410	200	280	460
		1.50	-	-	-	-		110	150	250	140	180	300	170	230	410	190	280	460	-	-	-	-

Notice:

The fourth digit in the order number (2, 4 or 5) stands for the housing variant (for details see Page 54).

Spare parts set for pneumatic atomizing nozzles Series 176 ViscoMist

Overview of the spare parts set and the power set



Spare parts set

Spare parts set for replacing the main wear parts of the nozzle, consisting of:

- Needle (stainless steel 316L)
- O-rings (Viton)
- Nozzle tip (stainless steel 316L)

Ordering no.	Narrowest free cross section Ø [mm]	For nozzles
Type		
017.601.1Y.01	0.38	176.xx1.1Y.11.00
017.602.1Y.01	0.58	176.xx2.1Y.11.00
017.603.1Y.01	0.79	176.xx3.1Y.11.00
017.604.1Y.01	1.07	176.xx4.1Y.11.00
017.605.1Y.01	1.32	176.xx5.1Y.11.00
017.606.1Y.01	1.70	176.xx6.1Y.11.00
017.607.1Y.01	2.05	176.xx7.1Y.11.00
017.608.1Y.01	2.36	176.xx8.1Y.11.00
017.609.1Y.01	2.54	176.xx9.1Y.11.00

Power set

Power set for replacing the main wear parts of the nozzle and the air hood, consisting of:

- Needle (stainless steel 316L)
- O-rings (Viton)
- Nozzle tip (stainless steel 316L)
- Air hood (stainless steel 316L)

Ordering no.	Narrowest free cross section Ø [mm]	For nozzles
Type		
017.601.1Y.00	0.38	176.xx1.1Y.11.00
017.602.1Y.00	0.58	176.xx2.1Y.11.00
017.603.1Y.00	0.79	176.xx3.1Y.11.00
017.604.1Y.00	1.07	176.xx4.1Y.11.00
017.605.1Y.00	1.32	176.xx5.1Y.11.00
017.606.1Y.00	1.70	176.xx6.1Y.11.00
017.607.1Y.00	2.05	176.xx7.1Y.11.00
017.608.1Y.00	2.36	176.xx8.1Y.11.00
017.609.1Y.00	2.54	176.xx9.1Y.11.00

Notice:

Instructions for replacing individual or all components of the nozzles are included in the scope of delivery of the spare parts sets and the power sets.

O-ring set


Ordering no.			Consisting of 4 O-rings, suitable for all nozzles of series 176
Type	Mat. no.		
	7A	6C	
	Viton	EPDM	
017.600.xx.01.03	●	●	

Viton (7A) is the standard O-ring material.
EPDM (6C) is optionally available.


Ordering Type + Material no. = Ordering no.
example: 017.600.xx.01.03 + 7A = 017.600.7A.01.03



HOLLOW CONE NOZZLES



HOLLOW CONE NOZZLES OVERVIEW OF TYPES



Hollow cone nozzles are used wherever fine droplets are required. A distinction is made between axial-flow hollow cone nozzles and tangential-flow hollow cone nozzles. Axial-flow hollow cone nozzles are mainly used for cooling, humidification and disinfecting, whilst tangential-flow hollow cone nozzles are traditionally used for humidification of air, dust control, sprinkling and foaming.

Axial-flow hollow cone nozzles



- High and controlled degree of atomization due to integrated swirl insert
- Narrow droplet spectrum
- Uniform atomization
- Large droplet surface area for mass transfer processes


Tangential-flow hollow cone nozzles



- Liquid rotation without swirl insert
- Maximum free passage making less susceptible to clogging
- Large free cross sections
- Operational reliability
- Coarse droplets that are larger than axial-flow hollow cone nozzles



HOLLOW CONE NOZZLES OVERVIEW OF SERIES




		Axial-flow hollow cone nozzles			
					
Series		220	226	214/216	2TR
Information on page		66	67	68	69
 Flow rate at p = 2 bar	Very low < 0.5 l/min	• (at p = 5 bar)	• (at p = 5 bar)	• (at p = 5 bar)	• (at p = 5 bar)
	Low 0.5 l/min–2.0 l/min			• (at p = 5 bar)	• (at p = 5 bar)
	Medium 2.0 l/min–10.0 l/min			• (at p = 5 bar)	
	High 10.0 l/min–50.0 l/min			• (at p = 5 bar)	
	Very high > 50.0 l/min				
 Spray angle	Small 45°				
	Medium 55°–95°	•	•	•	•
	Large 130°				
 Nozzle material	Stainless steel	•	•	•	
	Brass			•	
	Plastic				•
 Nozzle connection		1/4 BSPP	Assembly with retaining nut 3/8 BSPP	1/8 BSPP 3/8 BSPP	Assembly with retaining nut 3/8 BSPP

Tangential-flow hollow cone nozzles

					
302	302 with bayonet quick-release system	308	304/306/307	350	373 Ramp Bottom
70/71	73	74	75	76	77
•	•				
•	•	•		•	
•		•	•	•	
•			•		
					•
	•				
•	•	•	•		•
•	•		•	•	
•			•		•
•		•	•		
•	•			•	
3/8 BSPP	Assembly with bayonet quick-release system	3/8 BSPP	1/2 BSPP 3/4 BSPP	3/8 BSPP quick-release system	1 BSPP 1 1/4 BSPP 1 1/2 BSPP

➤ Axial-flow hollow cone nozzles Series 220



Features:


- Extremely fine, fog-like atomization

Applications:

- Humidification
- Cooling
- Disinfection
- Chemical engineering
- Adiabatic cooling



Series 220



Code	G	Dimensions [mm]				Weight [g]
		L ₁	L ₂	Ø D	Hex	
AC	1/4 BSPP	22.0	8.0	15.0	17	27.0

Spray angle	Ordering no.				Bore diameter B [mm]	Narrowest free cross section Ø [mm]	Strainer insert mesh size [mm]	V̇ water [l/min]									Spray diameter D [mm] (at p = 5 bar) 
	Type	Mat. no.		Code				p [bar]									
		1Y	11														
		Stainless steel 316L	Stainless steel 430F					2.0	3.0	5.0	7.0	10.0	20.0	50.0	100.0	H = 250 [mm]	
60°	220.004	●	●	AC	0.10	0.10	0.04	–	–	0.013	0.015	0.018	0.026	0.041	0.058	120	
	220.014	●	●	AC	0.15	0.15	0.04	–	0.015	0.019	0.022	0.027	0.038	0.060	0.085	140	
	220.054	●	●	AC	0.20	0.15	0.04	0.017	0.021	0.027	0.032	0.038	0.054	0.085	0.121	160	
80°	220.085	●	●	AC	0.25	0.25	0.10	0.025	0.031	0.040	0.047	0.057	0.080	0.126	0.179	190	
	220.125	●	●	AC	0.35	0.35	0.10	0.039	0.048	0.062	0.073	0.088	0.124	0.196	0.277	230	
	220.145	●	●	AC	0.40	0.40	0.10	0.052	0.064	0.082	0.097	0.116	0.164	0.259	0.367	250	
	220.165	●	●	AC	0.45	0.45	0.10	0.065	0.080	0.103	0.122	0.146	0.206	0.326	0.461	260	
	220.185	●	●	AC	0.55	0.35	0.20	0.082	0.101	0.130	0.154	0.184	0.260	0.411	0.581	270	
	220.205	●	●	AC	0.60	0.35	0.20	0.106	0.130	0.168	0.199	0.238	0.336	0.531	0.751	280	
	220.245	●	●	AC	0.70	0.50	0.20	0.165	0.202	0.261	0.309	0.369	0.522	0.825	1.167	290	
	220.285	●	●	AC	0.90	0.55	0.20	0.247	0.302	0.390	0.461	0.552	0.780	1.233	1.744	300	

Mat. no.	Housing	Nozzle insert	Strainer
1Y	Stainless steel 316L	Stainless steel 316L	Stainless steel 316L
11	Stainless steel 430F	Stainless steel 430F	Stainless steel 316L

The supplied and integrated strainer insert prevents clogging of the nozzle, thereby ensuring a long service life.


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. + Code = Ordering no.
example: 220.004 + 1Y + AC = 220.004.1Y.AC



Assembly accessories can be found in Chapter 9 "Accessories".

Axial-flow hollow cone nozzles Series 226




Features:

- Extremely fine, fog-like atomization
- Assembly with retaining nut

Applications:

- Humidification
- Cooling
- Disinfection
- Chemical engineering
- Adiabatic cooling



Series 226

Code	Dimensions [mm]				Weight [g]
	L ₁	L ₂	Ø D ₁	Ø D ₂	
Assembly with retaining nut 3/8 BSPP	18.00	2.00	14.80	12.65	20.00

Spray angle	Ordering no.		Bore diameter B [mm]	Narrowest free cross section Ø [mm]	Strainer insert mesh size [mm]	V̇ water [l/min]								Spray diameter D [mm] (at p = 5 bar)
	Type	Mat. no.				p [bar]								
		16												
		Stainless steel 303				2.0	3.0	5.0	7.0	10.0	20.0	50.0	100.0	
60°	226.004	●	0.10	0.10	0.04	–	–	0.013	0.015	0.018	0.026	0.041	0.058	120
	226.014	●	0.15	0.15	0.04	–	0.015	0.019	0.022	0.027	0.038	0.060	0.085	140
	226.054	●	0.20	0.15	0.04	0.017	0.021	0.027	0.032	0.038	0.054	0.085	0.121	160
80°	226.085	●	0.25	0.25	0.10	0.025	0.031	0.040	0.047	0.057	0.080	0.126	0.179	190
	226.125	●	0.35	0.35	0.10	0.039	0.048	0.062	0.073	0.088	0.124	0.196	0.277	230
	226.145	●	0.40	0.40	0.10	0.052	0.064	0.082	0.097	0.116	0.164	0.259	0.367	250
	226.165	●	0.45	0.45	0.10	0.065	0.080	0.103	0.122	0.146	0.206	0.326	0.461	260
	226.185	●	0.55	0.35	0.20	0.082	0.101	0.130	0.154	0.184	0.260	0.411	0.581	270
	226.205	●	0.60	0.35	0.20	0.106	0.130	0.168	0.199	0.238	0.336	0.531	0.751	280
	226.245	●	0.70	0.50	0.20	0.165	0.202	0.261	0.309	0.369	0.522	0.825	1.167	290
	226.285	●	0.90	0.55	0.20	0.247	0.302	0.390	0.461	0.552	0.780	1.233	1.744	300

Mat. no.	Housing	Nozzle insert	Strainer
16	Stainless steel 303	Stainless steel 430F	Stainless steel 316L

The supplied and integrated strainer insert prevents clogging of the nozzle, thereby ensuring a long service life.


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 226.004 + 16 = 226.004.16



Assembly accessories can be found in Chapter 9 "Accessories".

Axial-flow hollow cone nozzlesSeries 214/216




Features:

- Fine, uniform atomization

Applications:

- Cooling
- Gas washing
- Dust control
- Sprinkling
- Adiabatic cooling



Series 214/216

Series	G	Dimensions [mm]				Weight [g] (Brass)
		L ₁	L ₂	Ø D	Hex	
214	1/8 BSPP	18.0	6.0	16.0	17	27.0
216	3/8 BSPP	29.0	12.0	21.3	22	60.0

Spray angle	Ordering no.			Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray diameter D [mm] (at p = 5 bar) 
	Type	Mat. no.				p [bar]							
		17	30										
		Stainless steel 316Ti	Brass			0.5	1.0	2.0	3.0	5.0	10.0	20.0	H =250 [mm]
60°	214.184	●	●	0.50	0.50	–	–	0.08	0.10	0.13	0.18	0.25	120
	216.324	●	●	1.00	1.00	–	0.28	0.40	0.49	0.63	0.89	1.26	190
	216.364	●	●	1.40	1.40	–	0.45	0.63	0.77	1.00	1.41	1.99	220
	216.404	●	●	2.00	2.00	–	0.71	1.00	1.22	1.58	2.24	3.16	240
80°	214.245	●	●	1.00	0.50	–	–	0.16	0.20	0.25	0.36	0.51	240
	214.305	●	●	1.80	0.50	–	0.23	0.32	0.39	0.51	0.72	1.01	320
90°	216.496	●	●	3.00	2.00	–	1.20	1.70	2.08	2.69	3.80	5.38	430
	216.566	●	●	4.00	2.00	–	1.77	2.50	3.06	3.95	5.59	7.91	430
	216.646	●	●	3.50	2.00	2.00	2.83	4.00	4.90	6.32	8.94	12.65	440
	216.686	●	●	4.00	2.00	2.50	3.54	5.00	6.12	7.91	11.18	15.81	450
	216.726	●	●	5.00	2.00	3.15	4.45	6.30	7.72	9.96	14.09	19.92	460
	216.776	●	●	6.00	2.00	4.30	6.00	8.50	10.40	13.40	19.00	26.90	470


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 214.184 + 17 = 214.184.17



Assembly accessories can be found in Chapter 9 "Accessories".

➤ Axial-flow hollow cone nozzles Series 2TR




Features:

- Fine, uniform atomization
- Assembly with retaining nut

Applications:

- Sprinkling
- Adiabatic cooling
- Cooling
- Humidification of air




Series 2TR

Code	Dimensions [mm]					Weight [g]
	L ₁	L ₂	L ₃	Ø D ₁	Ø D ₂	
Assembly with retaining nut 3/8 BSPP	20.0	15.0	2.0	14.8	11.9	3.0

Spray angle	Ordering no.		Color	Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 5 bar) 
	Type	Mat. no.				p [bar]						
		C8										
		Housing: POM Insert: Ceramic				1.0	2.0	3.0	5.0	7.0	10.0	H = 250 [mm]
80°	2TR.245	●	Purple	0.65	0.55	–	0.16	0.20	0.25	0.30	0.36	220
	2TR.275	●	Black	0.80	0.70	0.16	0.22	0.27	0.35	0.41	0.49	260
	2TR.305	●	Orange	0.90	0.80	0.23	0.32	0.39	0.51	0.60	0.72	320
	2TR.345	●	Green	1.10	0.90	0.34	0.48	0.59	0.76	0.90	1.07	420
	2TR.365	●	Yellow	1.40	0.95	0.46	0.65	0.80	1.03	1.22	1.45	490
	2TR.405	●	Blue	1.70	1.10	0.69	0.97	1.19	1.53	1.81	2.17	530
	2TR.445	●	Red	2.00	1.20	0.89	1.26	1.55	2.02	2.37	2.83	550
	2TR.485	●	Brown	2.20	1.30	1.11	1.57	1.94	2.50	2.96	3.54	560

Assembly example




Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 2TR.245 + C8 = 2TR.245.C8



Assembly accessories can be found in Chapter 9 "Accessories".

>> Tangential-flow hollow cone nozzles, stainless steel/brass version Series 302



Features:



- Uniform atomization
- Non-clogging nozzle without swirl insert

Applications:

- Humidification of air
- Dust control
- Sprinkling
- Foam control
- Adiabatic cooling



Series 302



G	Dimensions [mm]							Weight [g] (Brass)
	C ₁	C ₂	H	L ₁	L ₂	L ₃	Hex	
3/8 BSPP	34.0	8.0	23.0	23.0	6.5	36.0	22	90.0

Spray angle	Ordering no.		Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]								Spray diameter D [mm] (at p = 2 bar)		
	Type	Mat. no.			p [bar]										
		1Y													30
		Stainless steel 316L													Brass
		0.5			1.0	2.0	3.0	5.0	7.0	10.0	H = 250 [mm]	H = 500 [mm]			
60°	302.364		●	1.50	1.50	0.32	0.45	0.63	0.77	1.00	1.18	1.41	280	420	
	302.464	●	●	2.00	2.00	0.70	0.99	1.40	1.71	2.21	2.62	3.13	280	460	
80°	302.545	●	●	4.90	2.30	1.12	1.58	2.24	2.74	3.54	4.19	5.01	360	660	
90°	302.606	●	●	4.60	4.00	1.58	2.23	3.15	3.86	4.98	5.89	7.04	470	810	
130°	302.368	●	●	3.00	1.00	0.32	0.45	0.63	0.77	1.00	1.18	1.41	660	1,080	
	302.468	●	●	5.00	1.70	0.70	0.99	1.40	1.71	2.21	2.62	3.13	810	1,370	
	302.548		●	5.00	2.50	1.12	1.58	2.24	2.74	3.54	4.19	5.01	960	1,640	
	302.608	●	●	5.00	3.50	1.58	2.23	3.15	3.86	4.98	5.89	7.04	1,060	1,800	
	302.668		●	7.50	3.60	2.25	3.18	4.50	5.51	7.12	8.42	10.06	1,120	1,950	
	302.748	●	●	7.50	4.80	3.55	5.02	7.10	8.70	11.23	13.28	15.88	1,160	2,150	


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
 example: 302.364 + 30 = 302.364.30



Assembly accessories can be found in Chapter 9
 "Accessories".

Tangential-flow hollow cone nozzles, plastic version Series 302



Features:


- Uniform atomization
- Non-clogging nozzle without swirl insert

Applications:


- Humidification of air
- Dust control
- Sprinkling
- Foam control
- Adiabatic cooling



Series 302



Type 302.32x-302.48x



Type 302.52x-302.96x

Type	G	Dimensions [mm]						Weight [g]	p _{max} [bar]
		H ₁	H ₂	L ₁	L ₂	Hex ₁	Hex ₂		
302.32x-302.48x	3/8 BSPP	27.5	16.5	43.5	10.0	22	22	13.0	5.0
302.52x-302.96x	3/8 BSPP	34.0	18.5	37.0	10.0	22	22	18.0	5.0

Spray angle	Ordering no.				Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]					Spray diameter D [mm] (at p = 2 bar)		
	Type	Mat. no.					p [bar]						H = 250 [mm]	H = 500 [mm]
		51	5E	53										
		PA	PVDF	PP			0.5	1.0	2.0	3.0	5.0			
60°	302.364	●		●	1.30	1.30	0.32	0.45	0.63	0.77	1.00	320	600	
	302.464	●		●	1.95	1.95	0.70	0.99	1.40	1.71	2.21	330	620	
90°	302.326	●	●		1.05	1.05	0.20	0.28	0.40	0.49	0.63	470	770	
	302.366	●	●		1.30	1.30	0.32	0.45	0.63	0.77	1.00	480	790	
	302.406	●	●	●	1.55	1.55	0.50	0.71	1.00	1.22	1.58	490	810	
	302.486	●		●	2.10	2.10	0.80	1.13	1.60	1.96	2.53	510	850	
	302.526	●		●	5.00	2.00	1.00	1.41	2.00	2.45	3.16	520	870	
	302.566	●		●	5.00	2.40	1.25	1.77	2.50	3.06	3.95	520	900	
	302.606	●		●	5.00	3.20	1.58	2.23	3.15	3.86	4.98	530	940	
	302.686	●			7.50	3.40	2.50	3.54	5.00	6.12	7.91	540	1,010	
	302.766	●			9.00	4.30	4.00	5.66	8.00	9.80	12.65	540	1,040	
	302.846	●		●	11.00	5.20	6.25	8.84	12.50	15.31	19.67	540	1,050	
	302.886	●	●	●	11.00	6.40	8.00	11.31	16.00	19.60	25.30	540	1,050	
	302.966	●			11.00	8.60	12.50	17.68	25.00	30.62	39.53	540	1,050	



Spray angle	Ordering no.				Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]					Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.					p [bar]						
		51	5E	53									
		PA	PVDF	PP			0.5	1.0	2.0	3.0	5.0		
130°	302.328		●		1.35	0.80	0.20	0.28	0.40	0.49	0.63	640	930
	302.368	●	●		1.85	1.10	0.32	0.45	0.63	0.77	1.00	660	1,010
	302.408	●	●		3.65	1.30	0.50	0.71	1.00	1.22	1.58	680	1,110
	302.488	●		●	5.20	1.60	0.80	1.13	1.60	1.96	2.53	720	1,250
	302.528	●			5.00	2.00	1.00	1.41	2.00	2.45	3.16	750	1,330
	302.568	●			5.00	2.40	1.25	1.77	2.50	3.06	3.95	780	1,410
	302.608	●	●	●	5.00	3.20	1.58	2.23	3.15	3.86	4.98	820	1,500
	302.648	●			7.50	3.00	2.00	2.83	4.00	4.90	6.32	860	1,590
	302.688	●			7.50	3.40	2.50	3.54	5.00	6.12	7.91	900	1,650
	302.728	●			7.50	4.10	3.15	4.45	6.30	7.72	9.96	920	1,700
	302.768	●			9.00	4.30	4.00	5.66	8.00	9.80	12.65	940	1,730
	302.848	●			11.00	5.20	6.25	8.84	12.50	15.31	19.76	960	1,760
	302.888	●		●	11.00	6.40	8.00	11.31	16.00	19.60	25.30	970	1,780
	302.968	●	●		11.00	8.60	12.50	17.68	25.00	30.62	39.53	1,000	1,800


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 302.328 + 5E = 302.328.5E



Assembly accessories can be found in Chapter 9 "Accessories".

Tangential-flow hollow cone nozzles, plastic version with bayonet quick-release system Series 302



Features:


- Uniform atomization
- Non-clogging nozzle without swirl insert
- Quick and secure assembly thanks to bayonet quick-release system
- Setting of spray direction

Applications:


- Humidification of air
- Dust control
- Sprinkling
- Foam control
- Adiabatic cooling



Series 302



Type 302.32x-302.54x



Type 302.6xx.51.KB

Type	Code	Dimensions [mm]				Weight [g]	P _{max} [bar]
		H ₁	H ₂	L	Hex		
302.32x-302.54x	KB	21.8	16.8	36.0	22	12.0	5.0
302.6xx.51.KB	KB	34.0	19.0	42.0	30	19.0	5.0

Spray angle	Ordering no.				Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]					Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.		Code			p [bar]					H = 250 [mm]	H = 500 [mm]
		51	56										
		PA	POM										
45°	302.503	●		KB	2.05	2.05	0.90	1.27	1.80	2.20	2.85	210	430
60°	302.464		●	KB	1.95	1.95	0.70	0.99	1.40	1.71	2.21	290	540
80°	302.545		●	KB	2.30	2.30	1.12	1.58	2.24	2.74	3.54	450	810
90°	302.326	●	●	KB	1.05	1.05	0.20	0.28	0.40	0.49	0.63	400	720
	302.406	●	●	KB	1.55	1.55	0.50	0.71	1.00	1.22	1.58	400	740
	302.486	●		KB	2.10	2.10	0.80	1.13	1.60	1.96	2.53	450	800
	302.606	●		KB	5.00	3.20	1.58	2.23	3.15	3.86	4.98	530	1,000
	302.686		●	KB	7.50	3.40	2.50	3.54	5.00	6.13	7.91	540	1,010
130°	302.368		●	KB	1.30	1.30	0.32	0.45	0.63	0.77	1.00	660	1,100
	302.408	●	●	KB	2.00	2.00	0.50	0.71	1.00	1.22	1.58	680	1,200
	302.468	●		KB	2.40	2.40	0.70	0.99	1.40	1.71	2.21	680	1,250
	302.488	●		KB	2.75	2.75	0.80	1.13	1.60	1.96	2.53	720	1,300


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{P_2}{P_1}}$

Ordering Type + Material no. + Code = Ordering no.
 example: 302.503 + 51 + KB = 302.503.51.KB



Assembly accessories can be found in Chapter 9 "Accessories".

Tangential-flow hollow cone nozzles Series 308



Features:


- Uniform atomization
- Non-clogging nozzle without swirl insert
- Adjustable flow rate

Applications:

- Humidification of air in air washers
- Dust control
- Spraying onto filters
- Foam control
- Cooling



Series 308



G	Dimensions [mm]						Weight [g]
	C ₁	C ₂	H	L ₁	L ₂	Hex	
3/8 BSPP	34.0	8.0	40.0	36.0	23.0	22	150.0

Spray angle	Ordering no.		Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V _{max} water [l/min]						Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.			p [bar]							
		30										
		Brass										
					0.3	0.5	1.0	2.0	5.0	10.0	H = 250 [mm]	H = 500 [mm]
90°	308.466	●	2.00	2.00	0.54	0.70	1.00	1.40	2.21	3.13	440	830
	308.606	●	4.00	4.00	1.22	1.58	2.23	3.15	4.98	7.04	460	850


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 308.466 + 30 = 308.466.30



Assembly accessories can be found in Chapter 9 "Accessories".

Tangential-flow hollow cone nozzles Series 304/306/307



Features:



- Uniform atomization
- Non-clogging nozzle without swirl insert

Applications:

- Storage tank cooling
- Foam control
- Dust control
- Surface spraying
- Absorption



Series 304/306/307



Series	G	Dimensions [mm]							Weight [g] (Brass)
		C ₁	C ₂	H	L ₁	L ₂	L ₃	Hex	
304	1/2 BSPP	43.0	11.0	33.0	46.0	30.0	11.0	27	205.0
306/307	3/4 BSPP	54.0	13.0	43.0	60.0	40.0	13.0	36	410.0

Spray angle	Ordering no.			Bore diameter B [mm]	Narrowest free cross section Ø [mm]	G ISO 228	V̇ water [l/min]							Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.					p [bar]							H = 250 [mm]	H = 500 [mm]
		1Y	30												
		Stainless steel 316L	Brass				0.5	1.0	2.0	3.0	5.0	7.0	10.0		
90°	304.706	●	●	5.10	5.10	1/2	2.80	3.96	5.60	6.86	8.85	10.48	12.52	500	1,000
	304.796	●	●	8.90	6.00	1/2	4.75	6.72	9.50	11.64	15.02	17.77	21.24	500	1,000
	306.906	●	●	9.00	9.00	3/4	9.00	12.73	18.00	22.05	28.46	33.67	40.25	550	1,050
	306.976	●	●	13.50	10.00	3/4	13.25	18.74	26.50	32.46	41.90	49.58	59.26	550	1,050
130°	304.818		●	12.00	5.00	1/2	5.30	7.50	10.60	12.98	16.76	19.83	23.70	1,200	2,100
	304.898	●	●	12.00	7.00	1/2	8.50	12.02	17.00	20.82	26.88	31.80	38.01	1,250	2,200
	306.978		●	19.00	7.30	3/4	13.25	18.74	26.50	32.46	41.90	49.58	59.26	1,300	2,350
	307.018	●	●	19.00	8.60	3/4	16.75	23.69	33.50	41.03	52.97	62.67	74.91	1,300	2,350


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 304.706 + 1Y = 307.706.1Y




Assembly accessories can be found in Chapter 9 "Accessories".

Tangential-flow hollow cone nozzles Series 350



Features:

- High performance nozzle for humidification of air
- Very narrow droplet spectrum
- Extremely uniform liquid distribution over the entire spray pattern
- Quick-release clamp unit available for pipe mounting



Applications:


- Foam control
- Dust control
- Surface spraying
- Absorption

Series 350

G	Dimensions [mm]				Weight [g]	P _{max} [bar]
	H ₁	H ₂	L	Ø D		
3/8 BSPP	24.0	20.0	14.0	37.0	37.0	20.0

Spray angle	Ordering no.		Bore diameter B [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.			p [bar]								
		56											
		POM											
					0.5	1.0	2.0	3.0	5.0	7.0	10.0	H = 250 [mm]	H = 500 [mm]
130°	350.368	●	1.55	0.70	0.32	0.45	0.63	0.77	1.00	1.18	1.41	950	1,250
	350.608	●	5.00	1.40	1.58	2.23	3.15	3.86	4.98	5.89	7.04	990	1,950

Accessories:



Recommended bore diameter 18 mm.

Quick-release clamp unit: Ordering no. 035.030.15.05.00.

Consisting of: Stainless steel clamp, polyurethane gasket.


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 350.368 + 56 = 350.368.56



Assembly accessories can be found in Chapter 9 "Accessories".

Eccentric hollow cone nozzles Series 373 Ramp Bottom



Features:



- Fine, uniform atomization even at low pressure
- Patented swirl chamber with built-in ramp extends service life

Applications:

- Gas cooling
- Water recooling
- Dust control



Series 373



Code	G	Dimensions [mm]					Weight [g]
		H	L ₁	L ₂	E	Hex	
AN	1 BSPP	52.0	67.0	45.0	6.3	41	285.0
AQ	1 1/4 BSPP	65.0	77.0	51.0	7.9	48	570.0
AS	1 1/2 BSPP	81.0	97.0	65.0	7.9	58	900.0

Spray angle	Ordering no.					Bore diameter B [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar)		
	Type	Mat. no.	Code				p [bar]							H = 500 [mm]	H = 1,000 [mm]
		17	1 BSPP	1 1/4 BSPP	1 1/2 BSPP		0.3	0.5	1.0	2.0	5.0	10.0			
70°	373.115	●	AN			11.40	24.40	31.50	44.55	63.00	99.61	140.87	670	1,200	
80°	373.175	●	AN			12.90	30.98	40.00	56.57	80.00	126.49	178.89	800	1,450	
	373.235	●		AQ		16.20	45.70	59.00	83.44	118.00	186.57	263.86	750	1,300	
	373.285	●		AQ		20.50	61.97	80.00	113.14	160.00	252.98	357.77	800	1,350	
	373.325	●			AS	22.20	77.46	100.00	141.42	200.00	316.23	447.21	900	1,500	
	373.365	●			AS	23.60	87.92	113.50	160.51	227.00	358.92	507.59	830	1,400	

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. + Code = Ordering no.
 example: 373.115 + 17 + AN = 373.115.17.AN




Assembly accessories can be found in Chapter 9 "Accessories".



FULL CONE NOZZLES



FULL CONE NOZZLES OVERVIEW OF TYPES



Lechler full cone nozzles are characterised by uniform liquid distribution over the entire circular impact area and are used, among other things, for surface spraying, in cleaning and washing processes and also in chemical process engineering. Full cone nozzles come in a variety of sizes and are made available as an axial full cone or a tangential full cone design. For special applications, unique types are made available, e.g. cluster head nozzles and deflector-plate nozzles.

Axial-flow full cone nozzles



- Axial flow
- Uniform liquid distribution
- Full surface impact
- Extensive flow rate range
- Extensive range of spray angles
- Standard materials:
Stainless steel 316Ti/316L, Brass, PVDF (special material available on request)

Tangential-flow full cone nozzles



- Tangential flow
- Uniform liquid distribution
- Full surface impact
- Maximum free passage making less susceptible to clogging
- Stable spray angle
- Standard materials:
Stainless steel 316L, Brass, PVDF (special material available on request)

Cluster head nozzles




- Axial flow
- Multi-nozzle spray head
- Full surface impact
- Atomized spray – very fine droplets
- Small droplet sizes
- Enlarged droplet surface area
- Standard materials:
Stainless steel 316Ti/316L, Brass
(special material available on request)

Deflector-plate nozzles



- Axial flow
- Large impact area
- Large free cross sections
- Standard materials:
Stainless steel 316Ti/316L, Brass
(special material available on request)


FULL CONE NOZZLES OVERVIEW OF SERIES



		Axial-flow full cone nozzles				
						
Series		490/491	460/461	405	403	419
Information on page		84	87	89	90	91
 Flow rate at p = 2 bar	Very low < 5 l/min	•	•			
	Low 5 l/min–25 l/min	•	•			
	Medium 25 l/min–80 l/min	•	•			
	High 80 l/min–400 l/min			•		• (at p = 1 bar)
	Very high > 400 l/min				•	• (at p = 1 bar)
 Spray angle	Small 45°	•				
	Medium 60°–90°	•	•	•	•	•
	Large ≥ 120°	•	•	•	•	•
 Nozzle material	Stainless steel	•		•	•	•
	Brass	•		•		
	Plastic		•			
 Nozzle connection		1/8 BSPT 1/4 BSPT 3/8 BSPT 1/2 BSPT 3/4 BSPP 1 BSPP	1/8 BSPT 1/4 BSPT 3/8 BSPT 1/2 BSPT 3/4 BSPT 3/4 BSPP 1 BSPP	1 1/4 BSPP 1 1/2 BSPP 2 BSPP	2 1/2 BSPP 3 BSPP 3 1/2 BSPP 4 BSPP	2 BSPP 2 1/2 BSPP 3 BSPP

		Tangential-flow full cone nozzles		Bündeldüsen	Pralltellerdüsen
					
468/494	4Fx	422/423	422 with bayonet quick-release system	502/503	524/525
92	93	95/97	99	100	101
•		•	•	•	
•		•		•	•
		•		•	•
	•	•			•
	•				
•	•	•	•	•	
•	•	•	•	•	•
•	•	•		•	•
•		•		•	•
•		•	•		
Assembly with retaining nut 3/8 BSPP	1/2 BSPP 3/4 BSPP 1 BSPP 1 1/2 BSPP 2 BSPP	1/4 BSPT 3/8 BSPT 1/2 BSPT 3/4 BSPT 1 BSPT	Assembly with bayonet quick-release system	1/2 BSPP 3/4 BSPP	1/2 BSPP

➤ Axial-flow full cone nozzles Series 490/491



Features:

- Extremely uniform liquid distribution
- Very stable spray angle
- Non clogging due to large free cross sections

Applications:

- Cleaning and washing processes
- Surface spraying
- Chemical process engineering
- Foam control



Series 490/491




Figure 1




Figure 2

Code	Figure	G	Dimensions [mm]				Weight [g] (brass)
			L ₁	L ₂	Ø D	Hex/Flats	
CA	1	1/8 BSPT	18.0	6.5	10.2	11	13.0
CC	1	1/4 BSPT	22.0	10.2	13.2	14	16.0
CE	1	3/8 BSPT	24.5	10.1	16.2	17	30.0
CG	1	1/2 BSPT	32.5	13.2	21.2	22	60.0
CG	1	1/2 BSPT	42.0	13.2	21.2	22	85.0
AK	2	3/4 BSPP	42.0	15.0	31.5	27	190.0
AM	2	1 BSPP	56.0	17.0	39.5	36	350.0

Spray angle	Ordering no.									Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]							Spray diameter D [mm] (at p = 2 bar) 	
	Type	Mat. no.		Code								p [bar]								
		1Y	30	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPP	1 BSPP			0.5	1.0	2.0	3.0	5.0	7.0	10.0		
		Stainless steel 316L	Brass																	
45°	490.403	●	●	CA						1.25	1.25	0.57	0.76	1.00	1.18	1.44	1.65	1.90	200	400
	490.523	●	●	CA						1.70	1.70	1.15	1.52	2.00	2.35	2.89	3.30	3.81	200	410
	490.603	●	●		CC	CE¹				2.00	2.00	1.81	2.39	3.15	3.70	4.54	5.20	6.00	200	410
	490.643	●	●		CC	CE¹				2.45	2.45	2.30	3.03	4.00	4.70	5.77	6.60	7.61	200	410
	490.683		●			CE				2.55	2.55	2.87	3.79	5.00	5.88	7.21	8.25	9.52	210	410
	490.703		●			CE				2.65	2.65	3.22	4.24	5.60	6.59	8.08	9.24	10.66	210	420
	490.723	●	●			CE				2.85	2.85	3.62	4.77	6.30	7.41	9.09	10.40	11.99	210	420
	490.783		●				CG			3.45	3.45	5.17	6.82	9.00	10.58	12.98	14.85	17.13	210	430
	490.843		●				CG			3.80	3.80	7.18	9.47	12.50	14.70	18.03	20.63	23.80	220	430

¹ Only available in material 30.

Spray angle	Ordering no.									Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]							Spray diameter D [mm] (at p = 2 bar) 	
	Type	Mat. no.		Code								p [bar]								
		1Y	30	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPP	1 BSPP			0.5	1.0	2.0	3.0	5.0	7.0	10.0	H = 250 [mm]	H = 500 [mm]
		Stainless steel 316L	Brass																	
60°	490.404	●	●	CA						1.15	1.15	0.57	0.76	1.00	1.18	1.44	1.65	1.90	260	520
	490.444	●		CA						1.25	1.25	0.72	0.95	1.25	1.47	1.80	2.06	2.38	260	520
	490.484	●	●	CA						1.45	1.45	0.92	1.21	1.60	1.88	2.31	2.64	3.05	260	520
	490.524	●	●	CA						1.60	1.60	1.15	1.52	2.00	2.35	2.89	3.30	3.81	270	530
	490.564	●	●	CA						1.80	1.80	1.44	1.89	2.50	2.94	3.61	4.13	4.76	270	530
	490.604	●	●	CA	CC	CE				2.05	2.05	1.81	2.39	3.15	3.70	4.54	5.20	6.00	270	540
	490.644	●	●		CC	CE				2.30	2.30	2.30	3.03	4.00	4.70	5.77	6.60	7.61	270	540
	490.684	●	●		CC	CE				2.60	2.60	2.87	3.79	5.00	5.88	7.21	8.25	9.52	280	550
	490.724	●	●		CC	CE				2.95	2.80	3.62	4.77	6.30	7.41	9.09	10.40	11.99	280	560
	490.764	●	●			CE				3.25	3.25	4.59	6.06	8.00	9.41	11.54	13.20	15.23	290	560
	490.804	●	●			CE				3.70	3.70	5.74	7.58	10.00	11.76	14.43	16.51	19.04	290	570
	490.844	●	●				CG			4.05	4.05	7.18	9.47	12.50	14.70	18.03	20.63	23.80	290	570
	490.884	●	●				CG			4.65	4.65	9.19	12.13	16.00	18.82	23.08	26.41	30.46	300	580
	490.924	●	●					AK		5.20	5.20	11.49	15.16	20.00	23.52	28.85	33.01	38.07	300	590
	490.964	●	●					AK		5.80	5.80	14.36	18.95	25.00	29.40	36.07	41.26	47.59	300	590
	491.044	●	●						AM	7.25	7.25	22.97	30.31	40.00	47.04	57.71	66.02	76.15	300	600
	491.084	●	●						AM	8.15	8.15	28.72	37.89	50.00	58.80	72.13	82.53	95.18	300	600
90°	490.406	●	●	CA						1.20	1.20	0.57	0.76	1.00	1.18	1.44	1.65	1.90	490	880
	490.446		●	CA						1.30	1.30	0.72	0.95	1.25	1.47	1.80	2.06	2.38	490	900
	490.486	●	●	CA						1.45	1.45	0.92	1.21	1.60	1.88	2.31	2.64	3.05	500	900
	490.526	●	●	CA						1.70	1.55	1.15	1.52	2.00	2.35	2.89	3.30	3.81	500	910
	490.566	●	●	CA						1.90	1.90	1.44	1.89	2.50	2.94	3.61	4.13	4.76	510	920
	490.606	●	●	CA			CE			2.10	2.05	1.81	2.39	3.15	3.70	4.54	5.20	6.00	510	930
	490.646	●	●		CC	CE				2.40	2.40	2.30	3.03	4.00	4.70	5.77	6.60	7.61	520	950
	490.686	●	●		CC	CE				2.70	2.70	2.87	3.79	5.00	5.88	7.21	8.25	9.52	520	960
	490.726	●	●		CC	CE				3.20	2.80	3.62	4.77	6.30	7.41	9.09	10.40	11.99	530	970
	490.746	●	●			CE				3.15	3.15	4.08	5.38	7.10	8.35	10.24	11.72	13.52	530	980
	490.766	●	●			CE				3.40	3.40	4.59	6.06	8.00	9.41	11.54	13.20	15.23	540	980
	490.806	●	●			CE				3.90	3.90	5.74	7.58	10.00	11.76	14.43	16.51	19.04	550	990
	490.846	●	●			CE				4.65	4.00	7.18	9.47	12.50	14.70	18.03	20.63	23.80	550	1,000
	490.886	●	●				CG			5.45	4.50	9.19	12.13	16.00	18.82	23.08	26.41	30.46	550	1,010
	490.926	●	●				CG			5.90	4.50	11.49	15.16	20.00	23.52	28.85	33.01	38.07	560	1,010
	490.966	●	●				CG	AK		6.55	4.85	14.36	18.95	25.00	29.40	36.07	41.26	47.59	560	1,020
	491.006	●	●					AK		7.55	5.50	18.09	23.87	31.50	37.05	45.45	51.99	59.97	560	1,030
	491.046	●	●					AK		8.60	6.60	22.97	30.31	40.00	47.04	57.71	66.02	76.15	560	1,040
	491.086	●	●						AM	9.45	7.25	28.72	37.89	50.00	58.80	72.13	82.53	95.18	560	1,040
	491.126	●	●						AM	10.40	8.00	36.18	47.75	63.00	74.09	90.89	103.98	119.93	560	1,040
491.146	●							AM	11.00	7.50	40.78	53.81	71.00	83.50	102.43	117.19	135.16	560	1,040	
120°	490.368	●	●	CA						0.85	0.65	0.36	0.48	0.63	0.74	0.91	1.04	1.20	700	1,240
	490.408	●	●	CA						1.20	1.20	0.57	0.76	1.00	1.18	1.44	1.65	1.90	720	1,260
	490.448	●	●	CA						1.30	1.30	0.72	0.95	1.25	1.47	1.80	2.06	2.38	740	1,280
	490.488	●	●	CA						1.45	1.45	0.92	1.21	1.60	1.88	2.31	2.64	3.05	760	1,300
	490.528	●	●	CA						1.70	1.70	1.15	1.52	2.00	2.35	2.89	3.30	3.81	780	1,320
	490.568	●	●	CA						1.90	1.90	1.44	1.89	2.50	2.94	3.61	4.13	4.76	800	1,340





Spray angle	Ordering no.									Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]							Spray diameter D [mm] (at p = 2 bar) 	
	Type	Mat. no.		Code								p [bar]								
		1Y	30	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT	1 BSPT											
		Stainless steel 316L	Brass																	
												0.5	1.0	2.0	3.0	5.0	7.0	10.0	H = 250 [mm]	H = 500 [mm]
120°	490.608	●	●	CA						2.10	2.05	1.81	2.39	3.15	3.70	4.54	5.20	6.00	820	1,370
	490.648	●	●		CC	CE				2.40	2.40	2.30	3.03	4.00	4.70	5.77	6.60	7.61	840	1,400
	490.688	●	●		CC	CE				2.75	2.75	2.87	3.79	5.00	5.88	7.21	8.25	9.52	850	1,430
	490.728	●	●		CC	CE				3.20	2.80	3.62	4.77	6.30	7.41	9.09	10.40	11.99	860	1,470
	490.748	●	●			CE				3.20	3.20	4.08	5.38	7.10	8.35	10.24	11.72	13.52	870	1,500
	490.768	●	●			CE				3.45	3.45	4.59	6.06	8.00	9.41	11.54	13.20	15.23	880	1,530
	490.808	●	●			CE				3.90	3.90	5.74	7.58	10.00	11.76	14.43	16.51	19.04	900	1,580
	490.848	●	●			CE				4.70	4.00	7.18	9.47	12.50	14.70	18.03	20.63	23.80	910	1,630
	490.888	●	●				CG			5.10	4.50	9.19	12.13	16.00	18.82	23.08	26.41	30.46	920	1,680
	490.928	●	●				CG			5.80	4.75	11.49	15.16	20.00	23.52	28.85	33.01	38.07	930	1,700
	490.968	●	●				CG	AK		6.65	4.85	14.36	18.95	25.00	29.40	36.07	41.26	47.59	930	1,710
	491.048	●	●					AK		9.10	5.85	22.97	30.31	40.00	47.04	57.71	66.02	76.15	930	1,730
	491.128	●	●						AM	10.80	7.75	36.18	47.75	63.00	74.09	90.89	103.98	119.93	930	1,740
	491.148	●							AM	11.40	7.65	40.78	53.81	71.00	83.50	102.43	117.19	135.16	930	1,750


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \left(\frac{p_2}{p_1}\right)^{0.4}$
(≤ 10 bar)

Ordering Type + Material no. + Code = Ordering no.
example: 490.608 + 1Y + CA = 490.608.1Y.CA



Assembly accessories can be found in Chapter 9 "Accessories".

Axial-flow full cone nozzles Series 460/461



Features:

- Extremely uniform liquid distribution

Applications:

- Cleaning and washing processes
- Cooling
- Surface spraying
- Chemical process engineering



Series 460/461




Figure 1




Figure 2




Figure 3

Code	Figure	G	Dimensions [mm]					Weight [g]
			L ₁	L ₂	Ø D ₁	Ø D ₂	Hex/Flats	
CA	1	1/8 BSPT	22.0	6.5	13.0	–	14	2.7
CC	1	1/4 BSPT	22.0	9.7	13.0	–	14	3.3
CE	1	3/8 BSPT	30.0	10.0	17.0	–	17	6.4
CG	1	1/2 BSPT	43.5	13.2	22.0	–	22	14.5
CK	2	3/4 BSPT	42.0	15.0	31.5	–	27	19.9
AK	2	3/4 BSPP	42.0	15.0	31.5	–	27	24.3
AM	3	1 BSPP	52.5	15.0	27.0	34.5	27	34.4

Spray angle	Ordering no.									Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]							Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.	Code									p [bar]							H = 250 [mm]	H = 500 [mm]
		5E	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT	3/4 BSPP	1 BSPP			0.5	1.0	2.0	3.0	5.0	7.0	10.0		
		PVDF																		
60°	460.524	●	CA							1.60	1.60	1.15	1.52	2.00	2.35	2.89	3.30	3.81	210	380
	460.644	●		CC						2.40	1.90	2.30	3.03	4.00	4.70	5.77	6.60	7.61	240	420
	460.724	●		CC						2,80	2,10	3,62	4,77	6,30	7,41	9,09	10,40	11,99	260	450
	460.964	●						AK		5,80	4,90	14,36	18,95	25,00	29,40	36,07	41,26	47,59	310	560





Spray angle	Ordering no.									Bore diameter B [mm]	Narrow-est free cross sections Ø [mm]	V̇ water [l/min]							Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.	Code									p [bar]								
		5E	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT	3/4 BSPP	1 BSPP			0.5	1.0	2.0	3.0	5.0	7.0	10.0		
90°	460.326	●	CA							0.80	0.55	0.23	0.30	0.40	0.47	0.58	0.66	0.76	430	750
	460.406	●	CA							1.20	0.85	0.57	0.76	1.00	1.18	1.44	1.65	1.90	440	780
	460.486	●	CA							1.45	1.20	0.92	1.21	1.60	1.88	2.31	2.64	3.05	450	800
	460.526	●	CA							1.65	1.30	1.15	1.52	2.00	2.35	2.89	3.30	3.81	450	820
	460.606	●	CA		CE					2.05	1.45	1.81	2.39	3.15	3.70	4.54	5.20	6.00	470	850
	460.646	●		CC						2.30	1.80	2.30	3.03	4.00	4.70	5.77	6.60	7.61	480	870
	460.726	●			CE					2.95	2.00	3.62	4.77	6.30	7.41	9.09	10.40	11.99	500	900
	460.746	●			CE					3.30	1.90	4.08	5.38	7.10	8.35	10.24	11.72	13.52	510	910
	460.766	●			CE					3.30	2.40	4.59	6.06	8.00	9.41	11.54	13.20	15.23	510	910
	460.806	●			CE					3.70	2.70	5.74	7.58	10.00	11.76	14.43	16.51	19.04	520	920
	460.846	●			CE					4.05	3.20	7.18	9.47	12.50	14.70	18.03	20.63	23.80	520	930
	460.886	●			CE	CG				4.70	3.10	9.19	12.13	16.00	18.82	23.08	26.41	30.46	520	930
	460.926	●				CG				5.10	2.80	11.49	15.16	20.00	23.52	28.85	33.01	38.07	520	940
	460.966	●				CG				5.80	3.80	14.36	18.95	25.00	29.40	36.07	41.26	47.59	520	940
	461.006	●				CG				6.40	3.80	18.09	23.87	31.50	37.05	45.45	51.99	59.97	520	940
	461.046	●					CK			7.20	5.30	22.97	30.31	40.00	47.04	57.71	66.02	76.15	520	950
	461.086	●						AM		8.40	5.00	25.00	35.36	50.00	61.24	70.71	79.06	111.80	530	950
120°	460.368	●	CA							0.95	0.65	0.32	0.45	0.63	0.77	0.89	1.00	1.41	650	1,030
	460.408	●	CA							1.20	0.85	0.57	0.76	1.00	1.18	1.44	1.65	1.90	680	1,100
	460.488	●	CA							1.50	1.00	0.92	1.21	1.60	1.88	2.31	2.64	3.05	700	1,160
	460.528	●	CA							1.65	1.20	1.15	1.52	2.00	2.35	2.89	3.30	3.81	710	1,200
	460.608	●	CA							2.10	1.40	1.81	2.39	3.15	3.70	4.54	5.20	6.00	730	1,270
	460.648	●		CC						2.45	1.60	2.30	3.03	4.00	4.70	5.77	6.60	7.61	750	1,310
	460.728	●			CE					3.10	1.90	3.62	4.77	6.30	7.41	9.09	10.40	11.99	780	1,380
	460.748	●			CE					3.30	1.90	4.08	5.38	7.10	8.35	10.24	11.72	13.52	790	1,400
	460.768	●			CE					3.50	1.90	4.59	6.06	8.00	9.41	11.54	13.20	15.23	790	1,410
	460.808	●			CE					3.80	2.40	5.74	7.58	10.00	11.76	14.43	16.51	19.04	810	1,430
	460.848	●			CE					4.20	2.70	7.18	9.47	12.50	14.70	18.03	20.63	23.80	820	1,450
	460.888	●				CG				4.60	3.10	9.19	12.13	16.00	18.82	23.08	26.41	30.46	830	1,470
	460.968	●				CG				5.90	4.10	14.36	18.95	25.00	29.40	36.07	41.26	47.59	850	1,500
	461.048	● ¹					CK			7.60	4.90	22.97	30.31	40.00	47.04	57.71	66.02	76.15	870	1,530

¹ Material PP (mat. no. 53).

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \left(\frac{p_2}{p_1}\right)^{0.4}$
(≤ 10 bar)


Ordering Type + Material no. + Code = Ordering no.
example: 460.326 + 5E + CA = 460.326.5E.CA



Assembly accessories can be found in Chapter 9 "Accessories".

Axial-flow full cone nozzles

Series 405



Features:


- Extremely uniform liquid distribution

Applications:

- Surface spraying
- Chemical process engineering
- Cleaning and washing processes
- Water treatment



Series 405



Code	G	Dimensions [mm]				Weight [kg] (brass)
		L ₁	L ₂	Ø D	Flats	
AP	1 1/4 BSPP	50.0	19.0	49.0	41	0.5
AR	1 1/2 BSPP	60.0	19.0	59.0	50	0.9
AV	2 BSPP	78.0	24.0	68.0	60	1.6

Spray angle	Ordering no.						Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar) 	
	Type	Mat. no.		Code					p [bar]							
		1Y	30	1 1/4 BSPP	1 1/2 BSPP	2 BSPP										
		Stainless steel 316L	Brass													
0.3	0.5	1.0	2.0				3.0	5.0	H = 500 [mm]	H = 1,000 [mm]						
60°	405.204	●	●	AP			11.2	5.8	47	57	76	100	118	144	600	1,140
	405.284	●	●		AR		14.3	7.0	75	92	121	160	188	231	630	1,210
	405.324	●	●			AV	16.4	7.5	94	115	152	200	235	289	650	1,250
	405.364	●	●			AV	18.4	8.5	117	144	189	250	294	361	650	1,250
	405.404	●				AV	20.0	7.0	147	181	239	315	370	454	650	1,250
90°	405.206	●	●	AP			12.0	5.0	47	57	76	100	118	144	1,120	2,100
	405.286	●	●		AR		15.2	6.2	75	92	121	160	188	231	1,120	2,100
	405.326	●				AV	17.2	7.7	94	115	152	200	235	289	1,120	2,100
	405.366	●				AV	19.5	8.7	117	144	189	250	294	361	1,120	2,100
	405.406	●	●			AV	22.0	9.5	147	181	239	315	370	454	1,120	2,100
120°	405.208	●	●	AP			12.7	5.0	47	57	76	100	118	144	1,850	3,050
	405.288	●	●		AR		16.0	6.6	75	92	121	160	188	231	1,900	3,150
	405.328	●				AV	17.8	7.9	94	115	152	200	235	289	1,900	3,200
	405.368	●	●			AV	20.1	8.8	117	144	189	250	294	361	1,900	3,200
	405.408	●	●			AV	22.4	9.1	147	181	239	315	370	454	1,900	3,200

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \left(\frac{p_2}{p_1}\right)^{0.4}$
(≤ 10 bar)


Ordering Type + Material no. + Code = Ordering no.
example: 405.204 + 1Y + AP = 405.204.1Y.AP



Assembly accessories can be found in Chapter 9 "Accessories".

➤ Axial-flow full cone nozzles

Series 403



Features:


- Extremely uniform liquid distribution

Applications:


- Surface spraying
- Spraying over packings
- Chemical process engineering
- Cleaning and washing processes
- Cooling



Series 403



90° version



120° version

90° version

Type	G	Dimensions [mm]				Weight [kg]
		L ₁	L ₂	Ø D	Flats	
403.446/403.486	2 1/2 BSPP	52.0	27.0	83.0	75	1.3
403.526	3 BSPP	60.0	30.0	98.0	85	2.0
403.606	3 1/2 BSPP	70.0	32.0	118.0	105	3.6

120° version

Type	G	Dimensions [mm]				Weight [kg]
		L ₁	L ₂	Ø D	Flats	
403.448/403.488	2 1/2 BSPP	124.0	27.0	83.0	75	3.2
403.528	3 BSPP	153.0	30.0	98.0	85	5.4
403.608	3 1/2 BSPP	156.0	32.0	118.0	105	8.3
403.628	4 BSPP	165.0	36.0	128.0	110	9.6

Spray angle	Ordering no.		Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]							Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.											
		1Y											
		Stainless steel 316L			p [bar]								
					0.3	0.5	1.0	2.0	3.0	5.0	7.0	H = 500 [mm]	H = 1,000 [mm]
90°	403.446	●	25.0	12.0	187	230	303	400	470	577	660	1,000	1,780
	403.486	●	29.5	12.0	234	287	379	500	588	721	825	1,000	1,780
	403.526	●	32.0	13.8	295	362	477	630	741	909	1,040	1,000	1,780
	403.606	●	40.0	15.0	468	574	758	1,000	1,176	1,443	1,651	1,000	1,780
120°	403.448	●	25.5	10.0	187	230	303	400	470	577	660	1,700	2,930
	403.488	●	29.5	11.0	234	287	379	500	588	721	825	1,700	2,930
	403.528	●	32.0	15.0	295	362	477	630	741	909	1,040	1,700	2,930
	403.608	●	42.0	12.0	468	574	758	1,000	1,176	1,443	1,651	1,700	2,930
	403.628	●	45.0	15.0	585	718	947	1,250	1,470	1,803	2,063	1,700	2,930

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \left(\frac{p_2}{p_1}\right)^{0.4}$
(≤ 10 bar)


Ordering Type + Material no. = Ordering no.
example: 403.446 + 1Y = 403.446.1Y



Assembly accessories can be found in Chapter 9 "Accessories".

➤ Axial-flow full cone nozzles

Series 419 FreeFlow



Features:


- High resistance to clogging due to large free cross-sections
- Very stable spray angle
- Uniform liquid distribution

Applications:

- Cleaning and washing processes
- Dust control
- Absorption
- Distillation



Series 419



Type	Code	G	Dimensions [mm]				Weight [kg]
			L ₁	L ₂	Ø D	Flats	
419.3xx	AV	2 BSPP	133.0	24.0	70.0	65	1.8
419.4xx	AV	2 BSPP	177.0	24.0	80.0	75	2.3
419.51x	AV	2 BSPP	217.0	27.0	102.0	95	4.0
419.51x	AY	2 1/2 BSPP	220.0	27.0	102.0	95	4.4
419.54x	AY	2 1/2 BSPP	220.0	27.0	102.0	95	4.3
419.57x	AY	2 1/2 BSPP	256.0	27.0	115.0	105	6.0
419.57x	LA	3 BSPP	259.0	30.0	115.0	105	6.4
419.608	LA	3 BSPP	266.0	30.0	122.0	115	6.1
419.6xx	LA	3 BSPP	276.0	30.0	122.0	115	6.3

Spray angle ¹	Ordering no.					Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]					Spray diameter D [mm] (at p = 1 bar)	
	Type	Mat. no.	Code					p [bar]						
		H1												
		Stainless steel 1.4408						2 BSPP	2 1/2 BSPP	3 BSPP	0.3	0.5		
90°	419.366	●	AV			18.40	18.40	117	143	189	249	360	1,200	2,200
	419.396	●	AV			22.60	20.75	140	172	227	300	432	1,200	2,200
	419.446	●	AV			23.10	23.10	187	230	303	400	577	1,200	2,200
	419.486	●	AV			28.00	26.40	234	287	379	500	721	1,200	2,200
	419.516	●	AV	AY		26.70	26.70	281	345	455	600	866	1,200	2,200
	419.546	●		AY		31.20	31.20	332	408	538	710	1,024	1,200	2,200
	419.576	●		AY	LA	32.50	32.50	398	488	644	850	1,226	1,200	2,200
	419.606	●			LA	37.10	37.10	468	574	758	1,000	1,443	1,200	2,200
419.626	●			LA	41.30	41.30	585	718	947	1,250	1,803	1,200	2,200	
120°	419.368	●	AV			18.50	18.50	117	143	189	249	360	1,660	2,900
	419.398	●	AV			23.00	20.75	140	172	227	300	432	1,660	2,900
	419.448	●	AV			23.80	23.80	187	230	303	400	577	1,660	2,900
	419.488	●	AV			29.50	26.40	234	287	379	500	721	1,660	2,900
	419.518	●	AV	AY		28.50	28.50	281	345	455	600	866	1,660	2,900
	419.548	●		AY		32.20	32.00	332	408	538	710	1,024	1,660	2,900
	419.578	●		AY	LA	34.90	34.90	398	488	644	850	1,226	1,660	2,900
	419.608	●			LA	37.10	37.10	468	574	758	1,000	1,443	1,660	2,900
	419.628	●			LA	45.00	41.50	585	718	947	1,250	1,803	1,660	2,900

¹ Spray angle at 1 bar.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \left(\frac{p_2}{p_1}\right)^{0.4}$
(≤ 10 bar)


Ordering Type + Material no. + Code = Ordering no.
example: 419.366 + H1 + AV = 419.366.H1.AV



Assembly accessories can be found in Chapter 9 "Accessories".

➤ Axial-flow full cone nozzles

Series 468/494



Features:

- Extremely uniform liquid distribution
- Assembly with retaining nut

Applications:

- Surface spraying
- Chemical process engineering
- Cleaning and washing processes
- Water treatment



Series 468/494




Figure 1
(468)




Figure 2
(494)

Code	Figure	Dimensions [mm]			Weight [g] (brass)
		L ₂	Ø D ₁	Ø D ₂	
Assembly with retaining nut 3/8 BSPP	1	2.00	14.80	12.65	18.00
	2	2.00	14.80	12.65	18.00

Spray angle	Ordering no.				Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	L ₁ [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.						p [bar]						H = 250 [mm]	H = 500 [mm]
		1Y	30	5E											
		Stainless steel 316L	Brass	PVDF				0.5	1.0	2.0	3.0	5.0	10.0		
60°	494.604	●	●		2.05	2.05	18.00	1.81	2.39	3.15	3.70	4.54	6.00	270	540
	468.644			●	2.32	2.80	24.50	2.30	3.03	4.00	4.70	5.77	7.61	290	570
	494.644		●		2.32	2.80	24.50	2.30	3.03	4.00	4.70	5.77	7.61	270	540
	494.684		●		2.63	2.80	24.50	2.87	3.79	5.00	5.88	7.21	9.52	280	550
	494.724	●	●		2.96	2.80	24.50	3.62	4.77	6.30	7.41	9.09	11.99	280	560
90°	468.526			●	1.71	1.55	18.00	1.15	1.52	2.00	2.35	2.89	3.81	460	780
	494.526	●	●		1.71	1.55	18.00	1.15	1.52	2.00	2.35	2.89	3.81	500	910
	494.846	●	●		4.95	3.20	24.50	7.18	9.47	12.50	14.70	18.03	23.80	550	1,000
120°	494.368		●		0.85	0.65	18,00	0.36	0.48	0.63	0.74	0.91	1.20	700	1,240
	494.408	●	●		1.20	1.20	18,00	0.57	0.76	1.00	1.18	1.44	1.90	720	1,260
	494.488	●	●		1.49	1.55	18,00	0.92	1.21	1.60	1.88	2.31	3.05	760	1,300
	494.528	●	●		1.70	1.75	18,00	1.15	1.52	2.00	2.35	2.89	3.81	780	1,320

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \left(\frac{p_2}{p_1}\right)^{0.4}$
(≤ 10 bar)

Ordering Type + Material no. = Ordering no.
example: 494.604 + 1Y = 494.604.1Y



Assembly accessories can be found in Chapter 9 "Accessories".

Full cone nozzles

Series 4Fx




Features:

- Fine droplet sizes
- Low weight
- Robust design
- Maintenance free

Applications:

- General Industry
- Flue gas desulphurization
- (special material)
- General cooling
- General gas humidification



Series 4Fx

Spray angle	Ordering no.						Bore diameter B [mm]]	V̇ water [l/min]						L1 [mm]	L2 [mm]	Hex	Weight [g]	Spray diameter D [mm] (at p = 2 bar)			
	Type	Mat. no.	Code																		
		1Y	1/2 BSPP	3/4 BSPP	1BSPP	1 1/2 BSPP		2 BSPP													
		Stainless steel 316L																			
								0,3	0,5	1,0	2,0	5,0	10,0					H = 500 [mm]	H = 1.000 [mm]		
60°	4F5.254	●		AK				6.0	51	66	93	132	209	295	94.0	11.8	27	106.0	600	800	
	4F5.334	●			AM			7.0	82	106	150	212	335	474	123.0	12.6	34	218.0	600	1,000	
	4F5.354	●			AM			7.0	91	118	167	236	373	528	123.0	12.6	34	214.0	600	1,000	
	4F5.394	●			AM			7.0	116	150	212	300	474	671	123.0	12.6	34	187.0	600	1,000	
	4F5.454	●					AR	9.0	165	213	301	425	672	950	153.0	16.6	50	573.0	800	1,200	
	4F5.504	●					AR	10.0	217	280	396	560	885	1,252	153.0	16.6	50	529.0	600	1,000	
	4F5.524	●					AR	11.0	244	315	445	630	996	1,409	153.0	16.6	50	518.0	800	1,200	
	4F5.584	●						AV	20.0	349	450	636	900	1,423	2,012	203.0	18.6	60	959.0	800	1,200
	4F5.614	●						AV	24.0	434	560	792	1,120	1,771	2,504	203.0	18.6	60	892.0	800	1,200
90°	4F5.166	●	AG					4.5	31	40	57	80	126	179	69.0	9.8	22	78.0	900	1,400	
	4F5.216	●	AG					4.5	41	53	75	106	168	237	69.0	9.8	22	75.0	800	1,600	
	4F5.256	●		AK				7.0	51	66	93	132	209	295	79.0	11.8	27	106.0	900	1,800	
	4F5.336	●				AM		7.0	82	106	150	212	335	474	110.0	12.6	34	237.0	1,000	2,000	
	4F5.396	●				AM		8.0	116	150	212	300	474	671	110.0	12.6	34	220.0	1,000	2,000	
	4F5.456	●					AR	11.0	165	213	301	425	672	950	125.0	16.6	50	478.0	900	1,800	
	4F5.506	●					AR	12.0	217	280	396	560	885	1,252	125.0	16.6	50	442.0	1,000	1,600	
	4F5.526	●					AR	12.0	244	315	445	630	996	1,409	125.0	16.6	50	423.0	800	1,400	
	4F5.586	●						AV	15.0	349	450	636	900	1,423	2,012	176.0	18.6	60	978.0	1,200	2,200
	4F5.616	●						AV	15.0	434	560	792	1,120	1,771	2,504	176.0	18.6	60	900.0	1,200	2,000





Spray angle	Ordering no.							Bore diameter B [mm]	V̇ water [l/min]						L1 [mm]	L2 [mm]	Hex	Weight [g]	Spray diameter D [mm] (at p = 2 bar)		
	Type	Mat.-Nr.	Code																		
		1Y	1/2 BSPP	3/4 BSPP	1BSPP	1 1/2 BSPP	2 BSPP														
		Stainless steel 316L																			
									0.3	0.5	1.0	2.0	5.0	10.0						H = 500 [mm]	H = 1,000 [mm]
120°	4F5.218	●	AG					5.0	41	53	75	106	168	237	69.0	9.8	22	50.0	1,400	2,400	
	4F5.258	●		AK				6.0	51	66	93	132	209	295	79.0	11.8	27	109.0	1,600	2,600	
	4F5.338	●			AM			7.0	82	106	150	212	335	474	110.0	12.6	34	248.0	1,600	3,200	
	4F5.398	●			AM			9.0	116	150	212	300	474	671	110.0	12.6	34	227.0	1,800	2,600	
	4F5.458	●				AR		12.0	165	213	301	425	672	950	130.0	16.6	50	561.0	1,400	2,400	
	4F5.508	●				AR		12.0	217	280	396	560	885	1.252	130.0	16.6	50	530.0	2,000	3,000	
	4F5.528	●				AR		12.0	244	315	445	630	996	1.409	130.0	16.6	50	510.0	1,600	2,600	
	4F7.588	●					AV	12.0	349	450	636	900	1.423	2.012	191.0	18.6	60	1.058.0	1,600	2,800	
	4F7.618	●					AV	13.0	434	560	792	1,120	1.771	2.504	191.0	18.6	60	986.0	1,800	2,800	
150°	4F7.339	●			AM			8.0	82	106	150	212	335	474	119.0	12.6	34	258.0	2,200	4,200	
	4F7.399	●			AM			8.0	116	150	212	300	474	671	119.0	12.6	34	237.0	2,200	4,200	
170°	4F7.250	●		AK				6.0	51	66	93	132	209	295	94.0	11.8	27	120.0	3,000	5,400	
	4F7.330	●			AM			8.0	82	106	150	212	335	474	119.0	12.6	34	272.0	4,000	6,000	
	4F7.390	●			AM			8.0	116	150	212	300	474	671	119.0	12.6	34	253.0	4,000	6,000	
	4F7.450	●				AR		10.0	165	213	301	425	672	950	156.0	16.6	50	642.0	2,800	4,400	
	4F7.500	●				AR		10.0	217	280	396	560	885	1.252	156.0	16.6	50	604.0	3,400	4,800	
	4F7.520	●				AR		10.0	244	315	445	630	996	1.409	156.0	16.6	50	585.0	3,400	4,400	

Manufacture in other materials and with external threads according to EN 10226 or NPT threads available on request.


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. + Code = Ordering no.
example: 4F5.218 + 1Y + AG = 4F5.218.1Y.AG



Assembly accessories can be found in Chapter 9 "Accessories".

Tangential-flow full cone nozzles stainless steel/brass version Series 422/423



Features:

- Tangentially arranged supply of liquid
- Without swirl inserts
- Non-clogging
- Stable spray angle
- Uniform liquid distribution

Applications:

- Surface spraying
- Cooling
- Cleaning and washing processes
- Foam control



Series 422/423





Figure 1




Figure 2

Code	Figure	G	Dimensions [mm]								Weight [g] (stainless steel 316L)
			H ₁	H ₂	L ₁	L ₂	L ₃	W ₁	W ₂	Hex	
CC	1	1/4 BSPT	21.0	8.0	28.0	20.0	9.7	15.6	16.0	–	44.0
CE	1	3/8 BSPT	26.7	11.0	36.0	25.0	10.1	23.2	22.0	–	101.0
CG	2	1/2 BSPT	40.0	20.0	56.0	33.5	13.2	32.0	48.0	19	370.0
CK	2	3/4 BSPT	57.0	23.5	65.5	38.5	14.5	40.0	63.0	27	830.0
CM	2	1 BSPT	66.0	27.3	85.0	48.5	16.8	55.0	78.0	36	1,581.0

Spray angle	Ordering no.								Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.		Code							p [bar]						H = 250 [mm]	H = 500 [mm]
		1Y	30															
		Stainless steel 316L	Brass															
				1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT	1 BSPT			0.5	1.0	2.0	3.0	5.0	10.0		
60°	422.644	●	●		CE				3.00	3.00	2.00	2.83	4.00	4.90	6.32	8.94	300	580
90°	422.406	●	●	CC					1.40	1.40	0.50	0.71	1.00	1.22	1.58	2.24	430	800
	422.486	●		CC					1.85	1.85	0.80	1.13	1.60	1.96	2.53	3.58	450	820
	422.566	●	●	CC					2.25	2.25	1.25	1.77	2.50	3.06	3.95	5.59	470	840
	422.606	●	●		CE				2.55	2.55	1.57	2.23	3.15	3.86	4.98	7.04	480	860
	422.646	●	●		CE				2.90	2.90	2.00	2.83	4.00	4.90	6.32	8.94	500	880
	422.726		●		CE				3.70	3.70	3.15	4.45	6.30	7.72	9.96	14.09	520	910
	422.766	●			CE				4.15	4.15	4.00	5.66	8.00	9.80	12.65	17.89	520	910
	422.806		●		CE				4.65	4.65	5.00	7.07	10.00	12.25	15.81	22.36	520	910
	422.846	●	●		CE				5.10	5.10	6.25	8.84	12.50	15.31	19.76	27.95	520	910
	422.886	●	●		CE				5.85	5.85	8.00	11.31	16.00	19.60	25.30	35.78	520	910
	422.966	●				CG			8.00	8.00	12.50	17.68	25.00	30.62	39.53	55.90	520	910





Spray angle	Ordering no.								Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.		Code							p [bar]						H = 250 [mm]	H = 500 [mm]
		1Y	30	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT	1 BSPT			0.5	1.0	2.0	3.0	5.0	10.0		
		Stainless steel 316L	Brass															
60°	422.644	●	●		CE				3.00	3.00	2.00	2.83	4.00	4.90	6.32	8.94	300	580
90°	422.406	●	●	CC					1.40	1.40	0.50	0.71	1.00	1.22	1.58	2.24	430	800
	422.486	●		CC					1.85	1.85	0.80	1.13	1.60	1.96	2.53	3.58	450	820
	422.566	●	●	CC					2.25	2.25	1.25	1.77	2.50	3.06	3.95	5.59	470	840
	422.606	●	●		CE				2.55	2.55	1.57	2.23	3.15	3.86	4.98	7.04	480	860
	422.646	●	●		CE				2.90	2.90	2.00	2.83	4.00	4.90	6.32	8.94	500	880
	422.726		●		CE				3.70	3.70	3.15	4.45	6.30	7.72	9.96	14.09	520	910
	422.766	●			CE				4.15	4.15	4.00	5.66	8.00	9.80	12.65	17.89	520	910
	422.806		●		CE				4.65	4.65	5.00	7.07	10.00	12.25	15.81	22.36	520	910
	422.846	●	●		CE				5.10	5.10	6.25	8.84	12.50	15.31	19.76	27.95	520	910
	422.886	●	●		CE				5.85	5.85	8.00	11.31	16.00	19.60	25.30	35.78	520	910
422.966	●				CG			8.00	8.00	12.50	17.68	25.00	30.62	39.53	55.90	520	910	
120°	422.488		●	CC					1.90	1.90	0.80	1.13	1.60	1.96	2.53	3.58	670	1,200
	422.568	●	●	CC					2.45	2.40	1.25	1.77	2.50	3.06	3.95	5.59	700	1,230
	422.608		●		CE				2.70	2.70	1.57	2.23	3.15	3.86	4.98	7.04	710	1,250
	422.728	●	●		CE				4.00	3.90	3.15	4.45	6.30	7.72	9.96	14.09	770	1,360
	422.808	●			CE				4.90	4.90	5.00	7.07	10.00	12.25	15.81	22.36	830	1,490
	422.848	●	●		CE				5.30	5.30	6.25	8.84	12.50	15.31	19.76	27.95	860	1,550
	422.888	●	●		CE				6.60	6.00	8.00	11.31	16.00	19.60	25.30	35.78	880	1,570
	422.928	●				CG			7.30	7.30	10.00	14.14	20.00	24.49	31.62	44.72	890	1,580
	422.968	●	●			CG			8.00	8.00	12.50	17.68	25.00	30.62	39.53	55.90	890	1,590
	423.008	●				CG			8.70	8.70	15.75	22.27	31.50	38.58	49.81	70.44	890	1,590
	423.128	●					CK		12.70	12.30	31.50	44.55	63.00	77.16	99.61	140.87	890	1,590
	423.208	●						CM	17.00	16.00	50.00	70.71	100.00	122.47	158.11	223.61	890	1,590


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. + Code = Ordering no.
example: 422.488 + 30 + CC = 422.488.30.CC



Assembly accessories can be found in Chapter 9 "Accessories".

Tangential-flow full cone nozzles, plastic version Series 422/423



Features:



- Tangentially arranged supply of liquid
- Without swirl inserts
- Non-clogging
- Stable spray angle
- Uniform liquid distribution
- High chemical resistance



Applications:

- Surface spraying
- Cooling
- Cleaning and washing processes
- Foam control

Series 422/423



Code	G	Dimensions [mm]						Weight [g]
		H ₁	H ₂	L ₁	L ₂	L ₃	Flats	
CC	1/4 BSPT	16.0	8.0	28.0	20.0	9.8	16.0	7.0
CE	3/8 BSPT	23.0	11.2	36.0	25.0	10.1	22.0	16.0
CG	1/2 BSPT	38.0	19.2	49.5	33.5	13.2	32.0	40.0
CK	3/4 BSPT	50.0	24.5	58.5	38.5	18.5	41.0	50.0

Spray angle	Ordering no.						Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar) 	
	Type	Mat. no.	Code						p [bar]							
		5E	1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT			0.5	1.0	2.0	3.0	5.0	10.0	H = 250 [mm]	H = 500 [mm]
		PVDF														
60°	422.724	●						CE								
90°	422.406	●	CC				1.50	1.45	0.50	0.71	1.00	1.22	1.58	2.24	530	900
	422.566	●	CC				2.30	2.20	1.25	1.77	2.50	3.06	3.95	5.59	530	920
	422.606	●		CE			2.60	2.50	1.58	2.23	3.15	3.86	4.98	7.04	540	920
	422.646	●		CE			3.00	2.90	2.00	2.83	4.00	4.90	6.32	8.94	540	930
	422.726	●		CE			3.70	3.60	3.15	4.45	6.30	7.72	9.96	14.09	550	950
	422.806	●		CE			4.65	4.60	5.00	7.07	10.00	12.25	15.81	22.36	560	980
	422.846	●		CE			5.10	5.10	6.25	8.84	12.50	15.31	19.76	27.95	560	990
	422.886	●		CE			5.80	5.80	8.00	11.31	16.00	19.60	25.30	35.78	570	1,010
	422.926	●			CG		7.30	7.30	10.00	14.14	20.00	24.49	31.62	44.72	570	1,030
	422.966	●			CG		8.00	8.00	12.50	17.68	25.00	30.62	39.53	55.90	580	1,040
	423.006	●			CG		8.70	8.70	15.75	22.27	31.50	38.58	49.81	70.44	580	1,040
	423.126	●				CK	12.00	12.00	31.50	44.55	63.00	77.16	99.61	140.87	580	1,050





Spray angle	Ordering no.						Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar) 	
	Type	Mat. no.	Code						p [bar]							
		5E														
		PVDF							1/4 BSPT	3/8 BSPT	1/2 BSPT	3/4 BSPT	0.5	1.0	2.0	3.0
120°	422.408	●	CC				1.50	1.45	0.50	0.71	1.00	1.22	1.58	2.24	670	1,200
	422.448	●	CC				1.65	1.60	0.63	0.88	1.25	1.53	1.98	2.80	680	1,210
	422.488	●	CC				1.90	1.90	0.80	1.13	1.60	1.96	2.53	3.58	680	1,230
	422.568	●	CC				2.40	2.40	1.25	1.77	2.50	3.06	3.95	5.59	700	1,260
	422.728	●		CE			4.00	3.90	3.15	4.45	6.30	7.72	9.96	14.09	770	1,400
	422.888	●		CE			6.60	6.00	8.00	11.31	16.00	19.60	25.30	35.78	850	1,560
	422.968	●			CG		8.00	8.00	12.50	17.68	25.00	30.62	39.53	55.90	960	1,620
	423.008	●			CG		8.70	8.70	15.75	22.27	31.50	38.58	49.81	70.44	970	1,630
423.128	●				CK	12.70	12.30	31.50	44.55	63.00	77.16	99.61	140.87	990	1,660	


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. + Code = Ordering no.
example: 422.408 + 5E + CC = 422.408.5E.CC



Assembly accessories can be found in Chapter 9 "Accessories".

Tangential-flow full cone nozzles, plastic version with bayonet quick-release system Series 422



Features:

- Without swirl inserts
- Non-clogging
- Stable spray angle
- Simple and quick assembly
- Uniform liquid distribution
- High chemical resistance

Applications:

- Surface spraying
- Cooling
- Cleaning and washing processes
- Foam control



Series 422




Figure 1




Figure 2

Type	Code	Figure	Dimensions [mm]					Weight [g] (PVDF)
			H ₁	H ₂	L ₁	L ₂	Ø D	
422.644/422.606/422.608	KB	1	23.0	14.0	40.0	29.0	29.5	20.0
422.406/422.408/422.528	KB	2	17.5	3.5	48.0	40.0	29.5	14.0

Spray angle	Ordering no.				Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar)		
	Type	Mat. no.		Code			p [bar]							H = 250 [mm]	H = 500 [mm]
		5E	53												
		PVDF	PP				Bayonet quick-release system								
60°	422.644		●	KB	2.90	2.90	2.00	2.83	4.00	4.90	6.32	8.94	250	490	
90°	422.406	●		KB	1.50	1.45	0.50	0.71	1.00	1.22	1.58	2.24	530	900	
	422.606	●		KB	2.60	2.50	1.58	2.23	3.15	3.86	4.98	7.04	540	920	
120°	422.408	●		KB	1.50	1.45	0.50	0.71	1.00	1.22	1.58	2.24	670	1,140	
	422.528	●		KB	2.10	2.00	1.00	1.41	2.00	2.45	3.16	4.47	690	1,220	
	422.608	●		KB	2.60	2.50	1.58	2.23	3.15	3.86	4.98	7.04	710	1,260	

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. + Code = Ordering no.
 example: 422.644 + 53 + KB = 422.644.53.KB



Assembly accessories can be found in Chapter 9 "Accessories".

Cluster head nozzles

Series 502/503



Features:


- Fine, uniform atomization
- Stable spray angle
- Space-saving installation
- Maintenance-friendly design
- High temperature and chemical resistance

Applications:


- Chlorine precipitation
- Absorption
- Dust suppression
- Degassing of liquids
- Desuperheating



Series 502/503



70° version



130° version

70° version

G	Dimensions [mm]				Weight [g] (brass)
	H	Ø D	Flats ₁	Flats ₂	
1/2 BSPP	25.0	50.0	46	38	250.0
3/4 BSPP	46.0	75.0	65	55	870.0

130° version

G	Dimensions [mm]				Weight [g] (brass)
	H	Ø D	Flats ₁	Flats ₂	
1/2 BSPP	28.0	40.0	27	36	150.0
3/4 BSPP	53.0	60.0	50	55	410.0

Spray angle	Ordering no.			BSPP	Bore diameter B [mm]	Narrowest free cross sections Ø [mm]	V̇ water [l/min]					Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.					p [bar]					H = 500 [mm]	H = 1,000 [mm]
		17 ¹	30										
		Stainless steel 316Ti/ Stainless steel 316L	Brass				0.5	1.0	2.0	5.0	10.0		
70°	502.445		●	1/2	0.90	0.50	–	–	1.25	1.98	2.80	270	360
	502.985	●		3/4	3.30	2.00	14.00	19.80	28.00	44.27	62.61	610	1,000
	503.065	●		3/4	4.90	2.00	22.50	31.82	45.00	71.15	100.62	920	1,520
130°	502.448	●	●	1/2	0.90	0.50	–	–	1.25	1.98	2.80	310	370
	502.548	●	●	1/2	1.80	0.50	–	1.58	2.24	3.54	5.01	450	570
	502.748	●	●	3/4	1.90	1.90	3.55	5.02	7.10	11.23	15.88	1,110	1,400
	502.838	●	●	3/4	2.90	2.00	5.90	8.34	11.80	18.66	26.39	1,500	2,060
	502.908	●	●	3/4	4.00	2.00	9.00	12.73	18.00	28.46	40.25	1,770	2,650
	503.028	●	●	3/4	4.20	2.00	17.75	25.10	35.50	56.13	79.38	2,050	3,150
	503.118	●	●	3/4	6.50	2.00	30.00	42.43	60.00	94.87	134.16	2,300	3,550

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 502.445 + 30 = 502.445.30



Assembly accessories can be found in Chapter 9 "Accessories".

Deflector-plate nozzles

Series 524/525




Features:

- Full cone atomization
- Large impact area
- Non-clogging

Applications:

- Fire fighting
- Sprinkling
- Dust suppression



Series 524/525

G	Dimensions [mm]					Weight [g] (brass)
	L ₁	L ₂	L ₃	Ø D	Hex	
1/2 BSPP	53.5	11.0	14.5	56.0	24	68.0

Spray angle	Ordering no.			Bore diameter B [mm]	V̇ water [l/min]						Spray diameter D [mm] (at p = 2 bar)	
	Type	Mat. no.			p [bar]							
		17¹	30									
		Stainless steel 316Ti/ Stainless steel 316L	Brass									
					0.5	1.0	2.0	3.0	5.0	10.0	H = 1,000 [mm]	H = 3,000 [mm]
180°	524.809	●	●	4.00	5.00	7.07	10.00	12.25	15.81	22.36	3,800	4,300
	525.049	●	●	8.00	20.00	28.28	40.00	48.99	63.25	89.44	10,000	11,500
	525.109	●	●	9.30	28.00	39.60	56.00	89.59	88.54	125.22	10,500	12,750
	525.169	●	●	10.90	40.00	56.57	80.00	97.98	126.49	178.89	10,500	14,500
	525.229	●	●	12.20	56.00	79.20	112.00	137.17	177.09	250.44	7,500	11,500
	525.269	●	●	12.30	70.00	98.99	140.00	171.46	221.36	313.05	7,000	12,000

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 524.809 + 17 = 524.809.17




Assembly accessories can be found in Chapter 9 "Accessories".



FLAT FAN NOZZLES



FLAT FAN NOZZLES OVERVIEW OF TYPES



Lechler flat fan nozzles produce intensive, uniform water jet. Flat fan nozzles are generally used in cleaning processes and throughout many areas of surface treatment. Numerous designs – including tongue-type nozzles for special applications – and extensive assembly accessories enable easy installation as well as quick nozzle changeovers.

Standard flat fan nozzles



- Particularly high-energy spray with spray angles of up to 60°
- Parabolic liquid distribution
- Unaffected by transient pressures
- Simple and cost-saving assembling options

Tongue-type nozzles



- Special design in which a solid stream is diverted by a deflector plate
- Powerful, sharply delimited spray
- Shape of the deflector plate determines the spray angle
- Clog resistant due to large free cross-sections

International nozzle code

Flat fan nozzles designations are governed by international standards. The first two digits specify the spray angle in degrees, the others the flow rate in US gallons per minute at 40 psi. Our high pressure flat fan nozzles (series 602/608/652/6FH) are specified with this international nozzle code.

Spray angle
in degrees




Flow rate in US gal/min at 40 psi

Conversion: $\text{Value} \cdot 3.22 = \text{flow rate in l/min at 2 bar}$
example: 0.2 gal/min at 40 psi = 0.644 l/min at 2 bar

Good to know

Information on the arrangement of several flat fan nozzles can be found in Chapter “Planning Aids” on Page 266.

FLAT FAN NOZZLES OVERVIEW OF SERIES



		Standard flat fan nozzles				
						
Series		632/633	610	612	616/617	652
Information on page		110	113	115	118	120
Pressure range	Low pressure	•	•	•	•	•
	High pressure					
 Flow rate at p = 5 bar	Low < 4 l/min	•	•	•		•
	Medium 4 l/min–16 l/min	•	•	•	•	•
	High 16 l/min–50 l/min	•		•	•	•
	Very high > 50 l/min				•	
 Spray angle	Small 20°–45°	•	•	•	•	•
	Medium 60°–90°	•	•	•	•	•
	Large 120°–140°	•	•	•	•	•
 Nozzle material	Stainless steel	•	•	•	•	•
	Brass	•	•	•	•	•
	Plastic	•				•
 Nozzle connection		1/8 BSPT 1/4 BSPT 3/8 BSPT 1/2 BSPT	1/8 BSPP	1/4 BSPP	3/4 BSPP	Assembly with retaining nut 3/8 BSPP



		Standard flat fan nozzles			
					
Series		652 Belt lubrication nozzle	612.xxx.5E.03 Press-in nozzle	656/657	660
Information on page		123	124	125	127
 Pressure range	Low pressure	•	•	•	•
	High pressure				
 Flow rate at p = 5 bar	Low < 4 l/min	• (at p = 3 bar)	• (at p = 2 bar)		•
	Medium 4 l/min–16 l/min			•	•
	High 16 l/min–50 l/min			•	
	Very high > 50 l/min			•	
 Spray angle	Small 20°–45°			•	•
	Medium 60°–90°	•	•	•	•
	Large 120°–140°	•	•	•	•
 Nozzle material	Stainless steel	•		•	•
	Brass			•	•
	Plastic	•	•		
 Nozzle connection		Assembly with retaining nut 3/8 BSPP	For pressing into pipes	Assembly with retaining nut 3/4 BSPP	Assembly with retaining nut 3/8 BSPP and dovetail guide

		Tongue-type nozzles		
				
664/665	646	688/689	686	684
129	131	133	134	136
•	•	•	•	•
	•		• (at p = 2 bar)	• (at p = 2 bar)
•	•	• (at p = 2 bar)	• (at p = 2 bar)	• (at p = 2 bar)
•		• (at p = 2 bar)	• (at p = 2 bar)	
•				
•	•	•		
•	•		•	
•	•		•	•
•		•	•	
•			•	
	•	•	•	•
Assembly with retaining nut 3/4 BSPP and dovetail guide	Assembly with bayonet quick-release system	3/8 BSPT 3/4 BSPP	1/8 BSPT 1/4 BSPT 3/8 BSPT 1/2 BSPT	Assembly with retaining nut 3/8 BSPP





		Standard flat fan nozzles			
					
Series		602	608	652	6FH with spray stabiliser
Information on page		137	138	139	140
Pressure range	Low pressure				
	High pressure	•	•	•	•
 Flow rate at p = 5 bar	Low < 4 l/min				
	Medium 4 l/min–16 l/min	• (at p = 80 bar)	• (at p = 80 bar)	• (at p = 80 bar)	• (at p = 80 bar)
	High 16 l/min–50 l/min	• (at p = 80 bar)	• (at p = 80 bar)	• (at p = 80 bar)	• (at p = 80 bar)
	Very high > 50 l/min	• (at p = 80 bar)		• (at p = 80 bar)	• (at p = 80 bar)
 Spray angle	Small 20°–45°	•	•	•	•
	Medium 60°–90°	•	•	•	•
	Large 120°–140°				
 Nozzle material	Stainless steel	•	•	•	•
	Brass				
	Plastic				
 Nozzle connection		1/4 BSPT 1/4 NPT	1/8 BSPT 1/8 NPT	Assembly with retaining nut 3/8 BSPP	1/8 BSPT 1/8 NPT 1/4 BSPT 1/4 NPT Assembly with retaining nut 3/8 BSPP

Swivelling nozzles	Nozzle systems for surface treatment		Descaling nozzles
			
676	676/677 MEMOSPRAY	676 Easy-Clip	SCALEMASTER
142	144	148	Upon request
•	•	•	
•			
•	• (at p = 2 bar)	• (at p = 2 bar)	
	• (at p = 2 bar)	• (at p = 2 bar)	
•	•		
•	•	•	
•	•		
•	•		
•			
	•	•	
Assembly with retaining nut Welded nipple Threaded nipple Threaded socket	Eyelet clamps for following pipe sizes: 1" 1 1/4" 1 1/2" 2"	Eyelet clamps for following pipe sizes: 1" 1 1/4" 1 1/2" 2"	

Low pressure flat fan nozzles

Series 632/633

Features:

- Uniform, parabolic liquid distribution
- Stable spray angle
- Tapered, self-sealing thread

Applications:

- Spray cleaning
- Surface cleaning
- Strainer insert cleaning
- Coating processes
- Belt cleaning
- Lubrication processes



Series 632/633




Figure 1




Figure 2

Code	Figure	G	Dimensions [mm]				Weight [g] (Brass)
			L ₁	L ₂	Hex	Flats	
CA	1	1/8 BSPT	22.0	6.5	14	10	17.0
CC	1	1/4 BSPT	22.0	9.7	14	10	20.0
CE	2	3/8 BSPT	22.0	10.1	17	–	30.0
CG	2	1/2 BSPT	27.0	13.2	22	–	40.0

Spray angle	Ordering no.									Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.				Code						p [bar]							H = 250 [mm]	H = 500 [mm]
		16 ¹	17 ²	30	5E															
		Stainless steel 303/ Stainless steel 304	Stainless steel 316 Ti/ Stainless steel 316L	Brass	PVDF													1/8 BSPT		
20°	632.301	●	●	●	●	CA	CC			0.70	0.60	0.16*	0.23*	0.32	0.39	0.51	0.60	0.72	85	160
	632.361	●	●	●	●	CA	CC			1.00	0.80	0.31*	0.44*	0.63	0.77	1.00	1.18	1.40	85	160
	632.441	●	●	●	●	CA	CC			1.35	1.10	0.62*	0.88	1.25	1.53	1.98	2.34	2.80	85	160
	632.481	●	●	●	●	CA	CC			1.50	1.20	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	85	160
30°	632.302	●	●	●	●	CA	CC			0.60	0.50	0.16*	0.23*	0.32	0.39	0.51	0.60	0.72	120	220
	632.362	●	●	●	●	CA	CC			1.00	0.70	0.31*	0.44*	0.63	0.77	1.00	1.18	1.40	120	220
	632.402	●	●	●	●	CA	CC			1.20	0.90	0.50*	0.71	1.00	1.23	1.58	1.87	2.24	120	230
	632.482	●	●	●	●	CA	CC			1.50	1.10	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	130	230
	632.562	●	●	●	●	CA	CC			2.00	1.50	1.25	1.77	2.50	3.06	3.95	4.68	5.59	130	240
	632.642	●	●	●			CC			2.50	1.80	2.00	2.83	4.00	4.90	6.33	7.48	8.94	140	250
	632.722	●	●	●			CC			3.00	2.40	3.15	4.46	6.30	7.72	9.96	11.79	14.09	140	260
	632.762	●	●	●			CC			3.50	2.70	4.00	5.66	8.00	9.80	12.65	14.97	17.89	140	260
	632.802	●	●	●			CC			4.00	3.10	5.00	7.07	10.00	12.25	15.81	18.71	22.36	140	260

Spray angle	Ordering no.									Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.				Code						p [bar]							H = 250 [mm]	H = 500 [mm]
		16 ¹	17 ²	30	5E															
		Stainless steel 303/ Stainless steel 304	Stainless steel 316Ti/ Stainless steel 316L	Brass	PVDF	1/8 BSPT	1/4 BSPT	3/8 BSPT	1/2 BSPT			0.5	1.0	2.0	3.0	5.0	7.0	10.0		
45°	632.303	●	●	●		CA	CC			0.70	0.50	0.16*	0.23*	0.32	0.39	0.51	0.60	0.72	170	330
	632.363	●	●	●	●	CA	CC			1.00	0.60	0.31*	0.44*	0.63	0.77	1.00	1.18	1.40	190	350
	632.403	●	●	●	●	CA	CC			1.20	0.90	0.50*	0.71	1.00	1.23	1.58	1.87	2.24	200	370
	632.483	●	●	●	●	CA	CC			1.50	1.10	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	200	390
	632.563	●	●	●	●	CA	CC			2.00	1.40	1.25	1.77	2.50	3.06	3.95	4.68	5.59	210	410
	632.643	●	●	●	●	CA	CC			2.50	1.80	2.00	2.83	4.00	4.90	6.33	7.48	8.94	220	410
	632.673	●	●	●			CC	CE		2.70	2.00	2.37	3.36	4.75	5.82	7.51	8.89	10.62	220	420
	632.723	●	●	●			CC	CE		3.00	2.40	3.15	4.46	6.30	7.72	9.96	11.79	14.09	220	420
	632.763	●	●	●			CC	CE		3.50	2.60	4.00	5.66	8.00	9.80	12.65	14.97	17.89	220	420
	632.803	●	●	●			CC	CE	CG	4.00	3.00	5.00	7.07	10.00	12.25	15.81	18.71	22.36	220	420
	632.843	●	● ³	●			CC		CG	4.50	3.40	6.25	8.84	12.50	15.31	19.76	23.38	27.94	220	420
	632.883	●	●	●					CG	5.00	3.80	8.00	11.31	16.00	19.60	25.30	29.94	35.78	220	420
	632.923	●	●	●					CG	5.50	4.20	10.00	14.14	20.00	24.49	31.62	37.41	44.72	220	430
632.963	●	●	●					CG	6.00	4.40	12.50	17.68	25.00	30.62	39.53	46.77	55.90	220	430	
60°	632.304	●	●	●	●	CA	CC			0.70	0.40	0.16*	0.23*	0.32	0.39	0.51	0.60	0.72	260	480
	632.334	●	●	●	●	CA	CC			0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	260	490
	632.364	●	●	●	●	CA	CC			1.00	0.60	0.31*	0.44*	0.63	0.77	1.00	1.18	1.40	260	500
	632.404	●	●	●	●	CA	CC			1.20	0.80	0.50*	0.71	1.00	1.23	1.58	1.87	2.24	260	510
	632.444	●	●	●	●	CA	CC			1.35	0.90	0.62*	0.88	1.25	1.53	1.98	2.34	2.80	260	510
	632.484	●	●	●	●	CA	CC			1.50	1.00	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	260	520
	632.514	●	●	●	●	CA	CC			1.65	1.10	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	270	520
	632.564	●	●	●	●	CA	CC			2.00	1.30	1.25	1.77	2.50	3.06	3.95	4.68	5.59	270	530
	632.604	●	●	●	●	CA	CC			2.20	1.50	1.57	2.23	3.15	3.86	4.98	5.89	7.04	270	540
	632.644	●	●	●	● ⁴		CC	CE		2.50	1.60	2.00	2.83	4.00	4.90	6.33	7.48	8.94	270	540
	632.674	●	●	●	● ⁴		CC	CE		2.70	1.80	2.37	3.36	4.75	5.82	7.51	8.89	10.62	270	550
	632.724	●	●	●	● ⁴		CC	CE		3.00	2.10	3.15	4.46	6.30	7.72	9.96	11.79	14.09	280	560
	632.764	●	●	●			CC	CE		3.50	2.30	4.00	5.66	8.00	9.80	12.65	14.97	17.89	280	570
	632.804	●	● ³	●	● ⁴		CC		CG	4.00	2.60	5.00	7.07	10.00	12.25	15.81	18.71	22.36	290	580
	632.844	●	● ³	●	● ⁴		CC		CG	4.50	3.00	6.25	8.84	12.50	15.31	19.76	23.38	27.94	290	580
	632.884	●	● ³	●	● ⁴		CC		CG	5.00	3.40	8.00	11.31	16.00	19.60	25.30	29.94	35.78	290	580
	632.924	●	●	●					CG	5.50	4.10	10.00	14.14	20.00	24.49	31.62	37.41	44.72	290	580
	632.964	●	●	●					CG	6.00	4.20	12.50	17.68	25.00	30.62	39.53	46.77	55.90	290	580
	633.004	●	●						CG	7.00	4.80	15.75	22.27	31.50	38.57	49.80	58.92	70.43	290	580
	633.044	●	●	●					CG	8.00	5.50	20.00	28.29	40.00	48.99	63.25	74.84	89.45	290	580
	633.084	●	●	●					CG	9.00	6.80	25.00	35.36	50.00	61.24	79.06	93.55	111.81	290	580
75°	632.145	●		●		CA	CC			0.20	0.12	–	0.04*	0.05	0.06	0.08	0.09	0.11	380	690
	632.165	●		●		CA	CC			0.20	0.14	–	0.04*	0.06	0.08	0.10	0.12	0.14	380	690
	632.185	●		●		CA	CC			0.20	0.16	–	0.06*	0.08	0.10	0.13	0.15	0.18	380	690
	632.215	●		●		CA	CC			0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	380	690
	632.245	●		●		CA	CC			0.50	0.30	–	0.12*	0.16	0.20	0.26	0.31	0.37	380	690
	632.275	●		●		CA	CC			0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.41	0.49	380	690





Spray angle	Ordering no.								Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)		
	Type	Mat. no.				Code					p [bar]									
		16 ¹	17 ²	30	5E															
		Stainless steel 303/ Stainless steel 304	Stainless steel 316Ti/ Stainless steel 316L	Brass	PVDF	1/8 BSPT	1/4 BSPT	3/8 BSPT			1/2 BSPT	0.5	1.0	2.0	3.0	5.0	7.0		10.0	H = 250 [mm]
90°	632.216	●		●		CA	CC			0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	420	780
	632.276	●		●		CA	CC			0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.41	0.49	430	790
	632.306	●	●	●	●	CA	CC			0.70	0.40	0.16*	0.23*	0.32	0.39	0.51	0.60	0.72	440	800
	632.336	●	●	●	●	CA	CC			0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	440	820
	632.366	●	●	●	●	CA	CC			1.00	0.50	0.31*	0.44*	0.63	0.77	1.00	1.18	1.40	450	830
	632.406	●	●	●	●	CA	CC			1.20	0.70	0.50*	0.71	1.00	1.23	1.58	1.87	2.24	450	840
	632.446	●	●	●	●	CA	CC			1.35	0.80	0.62*	0.88	1.25	1.53	1.98	2.34	2.80	460	860
	632.486	●	●	●	●	CA	CC			1.50	0.80	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	470	870
	632.516	●	●	●	●	CA	CC			1.65	0.90	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	480	880
	632.566	●	●	●	●	CA	CC			2.00	1.10	1.25	1.77	2.50	3.06	3.95	4.68	5.59	490	900
	632.606	●	●	●	●	CA	CC			2.20	1.20	1.57	2.23	3.15	3.86	4.98	5.89	7.04	500	910
	632.646	●	●	●	● ⁴		CC	CE		2.50	1.30	2.00	2.83	4.00	4.90	6.33	7.48	8.94	510	930
	632.676	●	●	●	● ⁴		CC	CE		2.70	1.40	2.37	3.36	4.75	5.82	7.51	8.89	10.62	510	950
	632.726	●	●	●	● ⁴		CC	CE		3.00	1.70	3.15	4.46	6.30	7.72	9.96	11.79	14.09	520	980
	632.766	●	●	●	● ⁴		CC	CE		3.50	1.90	4.00	5.66	8.00	9.80	12.65	14.97	17.89	530	1,000
	632.806	●	● ³	●	● ⁴		CC		CG	4.00	2.40	5.00	7.07	10.00	12.25	15.81	18.71	22.36	530	1,030
	632.846	●	● ³	●	● ⁴		CC		CG	4.50	2.40	6.25	8.84	12.50	15.31	19.76	23.38	27.94	540	1,050
	632.886	●	● ³	●	● ⁴		CC		CG	5.00	3.10	8.00	11.31	16.00	19.60	25.30	29.94	35.78	540	1,060
632.926	●	●	●					CG	5.50	3.60	10.00	14.14	20.00	24.49	31.62	37.41	44.72	540	1,070	
632.966	●	●	●					CG	6.00	3.90	12.50	17.68	25.00	30.62	39.53	46.77	55.90	540	1,070	
120°	632.187	●		●		CA	CC			0.35	0.20	–	0.06*	0.08	0.10	0.13	0.15	0.18	630	1,060
	632.217	●		●		CA	CC			0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	650	1,080
	632.247	●		●		CA	CC			0.50	0.20	–	0.12*	0.16	0.20	0.26	0.31	0.37	660	1,100
	632.277	●		●		CA	CC			0.60	0.30	–	0.16*	0.22	0.27	0.35	0.41	0.49	670	1,150
	632.307	●	●	●	●	CA	CC			0.70	0.30	0.16*	0.23*	0.32	0.39	0.51	0.60	0.72	710	1,240
	632.337	●	●	●	●	CA	CC			0.90	0.40	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	740	1,350
	632.367	●	●	●	●	CA	CC			1.00	0.50	0.31*	0.44*	0.63	0.77	1.00	1.18	1.40	800	1,430
	632.407	●	●	●	●	CA	CC			1.20	0.60	0.50*	0.71	1.00	1.23	1.58	1.87	2.24	830	1,480
	632.447	●	●	●	●	CA	CC			1.35	0.60	0.62*	0.88	1.25	1.53	1.98	2.34	2.80	840	1,520
	632.487	●	●	●	●	CA	CC			1.50	0.60	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	850	1,540
	632.517	●	●	●	●	CA	CC			1.65	0.90	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	850	1,560
	632.567	●	●	●	●	CA	CC			2.00	0.90	1.25	1.77	2.50	3.06	3.95	4.68	5.59	870	1,590
	632.607	●	●	●	●	CA	CC			2.20	1.10	1.57	2.23	3.15	3.86	4.98	5.89	7.04	870	1,620
	632.647	●	●	●			CC	CE		2.50	1.30	2.00	2.83	4.00	4.90	6.33	7.48	8.94	880	1,640
	632.677	●	●	●	● ⁴		CC	CE		2.70	1.40	2.37	3.36	4.75	5.82	7.51	8.89	10.62	890	1,660
	632.727	●	●	●	● ⁴		CC	CE		3.00	1.60	3.15	4.46	6.30	7.72	9.96	11.79	14.09	890	1,680
	632.767	●	●	●	● ⁴		CC	CE		3.50	1.70	4.00	5.66	8.00	9.80	12.65	14.97	17.89	900	1,700
	632.807	●	● ³	●			CC		CG	4.00	2.00	5.00	7.07	10.00	12.25	15.81	18.71	22.36	900	1,710
	632.847	● ³	● ³	● ³	● ⁴		CC		CG	4.50	2.30	6.25	8.84	12.50	15.31	19.76	23.38	27.94	900	1,710
	632.887	●	●	●					CG	5.00	2.60	8.00	11.31	16.00	19.60	25.30	29.94	35.78	910	1,710
632.927	●	●	●					CG	5.50	2.90	10.00	14.14	20.00	24.49	31.62	37.41	44.72	910	1,710	

* Differing spray pattern.

¹ We reserve the right to supply material 303 or 304 under material no. 16.

² We reserve the right to supply material 316Ti or 316L under material no. 17.

³ Only available with Code CG.

⁴ Only available with Code CC.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. + Code = Ordering no.
example: 632.216 + 16 + CA = 632.216.16.CA



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles

Series 610




Features:

- Uniform, parabolic liquid distribution
- Stable spray angle
- Compact design for narrow installation conditions

Applications:

- Spray cleaning
- Surface cleaning
- Strainer insert cleaning
- Coating processes
- Belt cleaning
- Lubrication processes



Series 610

G	Dimensions [mm]			Weight [g] Brass
	L ₁	L ₂	Hex	
1/8 BSPP	11.0	7.0	14	10.0

Spray angle	Ordering no.			Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.				p [bar]							H = 250 [mm]	H = 500 [mm]
		16	30											
		Stainless steel 303	Brass											
20°	610.301	●	●	0.70	0.60	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	85	160
	610.361	●	●	1.00	0.80	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	85	160
	610.441	●	●	1.35	1.10	0.63*	0.89	1.25	1.53	1.98	2.34	2.80	85	160
	610.481	●	●	1.50	1.20	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	85	160
30°	610.302	●	●	0.70	0.50	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	120	220
	610.362	●	●	1.00	0.70	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	120	220
	610.402	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	120	230
	610.482	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	130	230
	610.562	●	●	2.00	1.50	1.25	1.77	2.50	3.06	3.95	4.67	5.59	130	240
45°	610.303	●	●	0.70	0.50	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	170	330
	610.363	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	190	350
	610.403	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	200	370
	610.483	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	200	390
	610.563	●	●	2.00	1.40	1.25	1.77	2.50	3.06	3.95	4.67	5.59	210	410
	610.643	●	●	2.20	1.80	2.00	2.83	4.00	4.90	6.33	7.49	8.95	220	410





Spray angle	Ordering no.			Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.				p [bar]							H = 250 [mm]	H = 500 [mm]
		16	30											
		Stainless steel 303	Brass											
60°	610.304	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	260	480
	610.334	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	260	490
	610.364	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	260	500
	610.404	●	●	1.20	0.80	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	260	510
	610.444	●	●	1.35	0.90	0.63*	0.89	1.25	1.53	1.98	2.34	2.80	260	510
	610.484	●	●	1.50	1.00	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	260	520
	610.514	●	●	1.65	1.10	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	270	520
	610.564	●	●	2.00	1.30	1.25	1.77	2.50	3.06	3.95	4.67	5.59	270	530
610.604	●	●	2.20	1.50	1.57	2.23	3.15	3.86	4.98	5.89	7.04	270	540	
75°	610.145	●	●	0.20	0.12	–	0.04*	0.05	0.06	0.08	0.09	0.11	380	690
	610.165	●	●	0.20	0.14	–	0.05*	0.06	0.08	0.10	0.12	0.14	380	690
	610.185	●	●	0.20	0.16	–	0.06*	0.08	0.10	0.13	0.15	0.18	380	690
	610.215	●	●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	380	690
	610.245	●	●	0.50	0.30	–	0.12*	0.16	0.20	0.26	0.31	0.37	380	690
	610.275	●	●	0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.41	0.49	380	690
90°	610.216	●	●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	420	780
	610.276	●	●	0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.41	0.49	430	790
	610.306	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	440	800
	610.336	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	440	820
	610.366	●	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	450	830
	610.406	●	●	1.20	0.70	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	450	840
	610.446	●	●	1.35	0.80	0.63*	0.89	1.25	1.53	1.98	2.34	2.80	460	860
	610.486	●	●	1.50	0.80	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	470	870
	610.516	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	480	880
	610.566	●	●	2.00	1.10	1.25	1.77	2.50	3.06	3.95	4.67	5.59	490	900
	610.606	●	●	2.20	1.20	1.57	2.23	3.15	3.86	4.98	5.89	7.04	500	910
120°	610.187	●	●	0.35	0.20	–	0.06*	0.08	0.10	0.13	0.15	0.18	630	1,060
	610.217	●	●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	650	1,080
	610.247	●	●	0.50	0.20	–	0.12*	0.16	0.20	0.26	0.31	0.37	660	1,100
	610.277	●	●	0.60	0.30	–	0.16*	0.22	0.27	0.35	0.41	0.49	670	1,150
	610.307	●	●	0.70	0.30	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	710	1,240
	610.337	●	●	0.90	0.40	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	740	1,350
	610.367	●	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	800	1,430
	610.407	●	●	1.20	0.60	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	830	1,480
	610.447	●	●	1.35	0.60	0.63*	0.89	1.25	1.53	1.98	2.34	2.80	840	1,520
	610.487	●	●	1.50	0.60	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	850	1,540
	610.517	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	850	1,560
	610.567	●	●	2.00	0.90	1.25	1.77	2.50	3.06	3.95	4.67	5.59	870	1,590
	610.607	●	●	2.20	1.10	1.57	2.23	3.15	3.86	4.98	5.89	7.04	870	1,620

* Differing spray pattern.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 610.304 + 16 = 610.304.16



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles

Series 612



Features:


- Uniform, parabolic liquid distribution
- Stable spray angle
- Compact design for narrow installation conditions

Applications:

- Spray cleaning
- Surface cleaning
- Strainer insert cleaning
- Coating processes
- Belt cleaning
- Lubrication processes



Series 612



G	Dimensions [mm]			Weight [g] Brass
	L ₁	L ₂	Hex	
1/4 BSPP	13.0	8.0	17	14.0

Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)		
	Type	Mat. no.					p [bar]								H = 250 [mm]	H = 500 [mm]
		16	17 ¹	30												
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass												
20°	612.301	●	●	●	0.70	0.60	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	85	160	
	612.361	●	●	●	1.00	0.80	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	85	160	
	612.441	●	●	●	1.30	1.10	0.63*	0.89	1.25	1.53	1.98	2.34	2.80	85	160	
	612.481	●	●	●	1.50	1.20	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	85	160	
30°	612.302	●	●	●	0.60	0.50	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	120	220	
	612.362	●	●	●	1.00	0.70	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	120	220	
	612.402	●	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	120	230	
	612.482	●	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	130	230	
	612.562	●	●	●	2.00	1.50	1.25	1.77	2.50	3.06	3.95	4.67	5.59	130	240	
	612.642	●	●	●	2.50	1.80	2.00	2.83	4.00	4.90	6.33	7.49	8.95	140	250	
	612.722	●	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	11.78	14.09	140	260	
	612.762	●	●	●	3.50	2.70	4.00	5.66	8.00	9.80	12.65	14.97	17.89	140	260	
612.802	●	●	●	4.00	3.10	5.00	7.07	10.00	12.25	15.81	18.71	22.36	140	260		
45°	612.303	●	●	●	0.70	0.50	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	170	330	
	612.363	●	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	190	350	
	612.403	●	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	200	370	
	612.483	●	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	200	390	
	612.563	●	●	●	2.00	1.40	1.25	1.77	2.50	3.06	3.95	4.67	5.59	210	410	
	612.643	●	●	●	2.50	1.80	2.00	2.83	4.00	4.90	6.33	7.49	8.95	220	410	
	612.723	●	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	11.78	14.09	220	420	
	612.763	●	●	●	3.50	2.60	4.00	5.66	8.00	9.80	12.65	14.97	17.89	220	420	
612.803	●	●	●	4.00	3.00	5.00	7.07	10.00	12.25	15.81	18.71	22.36	220	420		





Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]								
		16	17¹	30											
		Stainless steel 303	Stainless steel 316Ti Stainless steel 316L	Brass			0.5	1.0	2.0	3.0	5.0	7.0	10.0		H = 250 [mm]
60°	612.304	●	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	260	480
	612.334	●	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	260	490
	612.364	●	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	260	500
	612.404	●	●	●	1.20	0.80	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	260	510
	612.444	●	●	●	1.35	0.90	0.63*	0.89	1.25	1.53	1.98	2.34	2.80	260	510
	612.484	●	●	●	1.50	1.00	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	260	520
	612.514	●	●	●	1.65	1.10	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	270	520
	612.564	●	●	●	2.00	1.30	1.25	1.77	2.50	3.06	3.95	4.67	5.59	270	530
	612.604	●	●	●	2.20	1.50	1.57	2.23	3.15	3.86	4.98	5.89	7.04	270	540
	612.644	●	●	●	2.50	1.60	2.00	2.83	4.00	4.90	6.33	7.49	8.95	270	540
	612.674	●	●	●	2.70	1.80	2.37	3.36	4.75	5.82	7.51	8.89	10.62	270	550
	612.724	●	●	●	3.00	2.10	3.15	4.45	6.30	7.71	9.96	11.78	14.09	280	560
	612.764	●	●	●	3.50	2.30	4.00	5.66	8.00	9.80	12.65	14.97	17.89	280	570
	612.804	●	●	●	4.00	2.60	5.00	7.07	10.00	12.25	15.81	18.71	22.36	290	580
612.884	●		●	5.00	3.40	8.00	11.31	16.00	19.60	25.30	29.94	35.78	290	580	
75°	612.145	●		●	0.20	0.12	–	0.04*	0.05	0.06	0.08	0.09	0.11	380	690
	612.165	●		●	0.20	0.14	–	0.05*	0.07	0.08	0.10	0.12	0.15	380	690
	612.185	●		●	0.20	0.16	–	0.06*	0.08	0.10	0.13	0.15	0.18	380	690
	612.215	●		●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	380	690
	612.245	●		●	0.50	0.30	–	0.12*	0.16	0.20	0.26	0.31	0.37	380	690
	612.275	●		●	0.60	0.30	0.11*	0.16	0.22	0.27	0.35	0.41	0.49	380	690
90°	612.216	●		●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	420	780
	612.276	●		●	0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.41	0.49	430	790
	612.306	●	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	440	800
	612.336	●	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	440	820
	612.366	●	●	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	450	830
	612.406	●	●	●	1.20	0.70	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	450	840
	612.446	●	●	●	1.35	0.80	0.63*	0.89	1.25	1.53	1.98	2.34	2.80	460	860
	612.486	●	●	●	1.50	0.80	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	470	870
	612.516	●	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	480	880
	612.566	●	●	●	2.00	1.10	1.25	1.77	2.50	3.06	3.95	4.67	5.59	490	900
	612.606	●	●	●	2.20	1.20	1.57	2.23	3.15	3.86	4.98	5.89	7.04	500	910
	612.646	●	●	●	2.50	1.30	2.00	2.83	4.00	4.90	6.33	7.49	8.95	510	930
	612.676	●	●	●	2.70	1.40	2.37	3.36	4.75	5.82	7.51	8.89	10.62	510	950
	612.726	●	●	●	3.00	1.70	3.15	4.45	6.30	7.71	9.96	11.78	14.09	520	980
	612.766	●	●	●	3.50	1.90	4.00	5.66	8.00	9.80	12.65	14.97	17.89	530	1,000
	612.806	●		●	4.00	2.40	5.00	7.07	10.00	12.25	15.81	18.71	22.36	530	1,030

Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]								
		16	17 ¹	30											
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass											
							0.5	1.0	2.0	3.0	5.0	7.0	10.0	H = 250 [mm]	H = 500 [mm]
120°	612.187	●		●	0.35	0.20	–	0.06*	0.08	0.10	0.13	0.15	0.18	630	1,060
	612.217	●		●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.21	0.25	650	1,080
	612.247	●		●	0.50	0.20	–	0.12*	0.16	0.20	0.26	0.31	0.37	660	1,100
	612.277	●		●	0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.41	0.49	670	1,150
	612.307	●		●	0.70	0.30	0.16*	0.23*	0.32	0.40	0.51	0.60	0.72	710	1,240
	612.337	●	●	●	0.90	0.40	0.22*	0.32*	0.45	0.55	0.71	0.84	1.00	740	1,350
	612.367	●	●	●	1.00	0.40	0.32*	0.45*	0.63	0.77	1.00	1.18	1.41	800	1,430
	612.407	●	●	●	1.20	0.60	0.50*	0.71	1.00	1.22	1.58	1.87	2.23	830	1,480
	612.447	●	●	●	1.35	0.60	0.63*	0.89	1.25	1.53	1.98	2.34	2.80	840	1,520
	612.487	●	●	●	1.50	0.60	0.80*	1.13	1.60	1.96	2.53	2.99	3.58	850	1,540
	612.517	●	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	3.55	4.24	850	1,560
	612.567	●	●	●	2.00	0.90	1.25	1.77	2.50	3.06	3.95	4.67	5.59	870	1,590
	612.607	●	●	●	2.20	1.10	1.57	2.23	3.15	3.86	4.98	5.89	7.04	870	1,620
	612.647	●	●	●	2.50	1.30	2.00	2.83	4.00	4.90	6.33	7.49	8.95	880	1,640
	612.677	●	●	●	2.70	1.40	2.37	3.36	4.75	5.82	7.51	8.89	10.62	890	1,660
	612.727	●	●	●	3.00	1.60	3.15	4.45	6.30	7.71	9.96	11.78	14.09	890	1,680
	612.767	●	●	●	3.50	1.70	4.00	5.66	8.00	9.80	12.65	14.97	17.89	900	1,700
	612.807	●		●	4.00	2.00	5.00	7.07	10.00	12.25	15.81	18.71	22.36	900	1,710

* Differing spray pattern.

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 612.187 + 16 = 612.187.16



Assembly accessories can be found in Chapter 9 "Accessories".


Low pressure flat fan nozzles

Series 616/617



Features:

- Uniform, parabolic liquid distribution
- Stable spray angle
- Compact design for narrow installation conditions



Applications:

- Spray cleaning
- Surface cleaning
- Filter cleaning
- Coating processes
- Belt cleaning
- Lubrication processes

Series 616/617

G	Dimensions [mm]			Weight [g] Brass
	L ₁	L ₂	Hex	
3/4 BSPP	19.0	12.0	32	75.0

Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]								Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]								H = 250 [mm]	H = 500 [mm]
		16	17 ¹	30												
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass			0.5	1.0	2.0	3.0	5.0	7.0	10.0			
20°	616.721	●	●	●	3.00	2.50	3.15	4.45	6.30	7.71	9.96	11.78	14.09	100	180	
	616.801	●	●	●	4.00	3.20	5.00	7.07	10.00	12.25	15.81	18.71	22.36	100	180	
	616.881	●	●	●	5.00	4.00	8.00	11.31	16.00	19.60	25.30	29.94	35.78	100	180	
	616.921	●	●	●	5.50	4.40	10.00	14.14	20.00	24.49	31.62	37.41	44.72	100	180	
	616.961	●	●	●	6.00	5.10	12.50	17.68	25.00	30.62	39.53	46.77	55.90	100	180	
30°	616.722	●	●	●	3.00	2.50	3.15	4.45	6.30	7.71	9.96	11.78	14.09	140	260	
	616.762	●	●	●	3.50	2.80	4.00	5.66	8.00	9.80	12.65	14.97	17.89	140	260	
	616.802	●	●	●	4.00	3.10	5.00	7.07	10.00	12.25	15.81	18.71	22.36	140	260	
	616.882	●	●	●	5.00	4.00	8.00	11.31	16.00	19.60	25.30	29.94	35.78	140	270	
	616.922	●	●	●	5.50	4.40	10.00	14.14	20.00	24.49	31.62	37.41	44.72	140	270	
	616.962	●	●	●	6.00	5.00	12.50	17.68	25.00	30.62	39.53	46.77	55.90	140	270	
45°	616.723	●	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	11.78	14.09	220	420	
	616.763	●	●	●	3.50	2.60	4.00	5.66	8.00	9.80	12.65	14.97	17.89	220	420	
	616.803	●	●	●	4.00	3.00	5.00	7.07	10.00	12.25	15.81	18.71	22.36	220	420	
	616.843	●	●	●	4.50	3.40	6.25	8.84	12.50	15.31	19.76	23.38	27.94	220	420	
	616.883	●	●	●	5.00	3.80	8.00	11.31	16.00	19.60	25.30	29.94	35.78	220	420	
	616.923	●	●	●	5.50	4.20	10.00	14.14	20.00	24.49	31.62	37.41	44.72	220	430	
	616.963	●	●	●	6.00	4.40	12.50	17.68	25.00	30.62	39.53	46.77	55.90	220	430	

Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]							Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]								
		16	17¹	30											
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass			0.5	1.0	2.0	3.0	5.0	7.0	10.0		
60°	616.724	●	●	●	3.00	2.10	3.15	4.45	6.30	7.71	9.96	11.78	14.09	280	560
	616.764	●	●	●	3.50	2.30	4.00	5.66	8.00	9.80	12.65	14.97	17.89	280	570
	616.804	●	●	●	4.00	2.60	5.00	7.07	10.00	12.25	15.81	18.71	22.36	290	580
	616.844	●	●	●	4.50	3.00	6.25	8.84	12.50	15.31	19.76	23.38	27.94	290	580
	616.884	●	●	●	5.00	3.40	8.00	11.31	16.00	19.60	25.30	29.94	35.78	290	580
	616.924	●	●	●	5.50	4.10	10.00	14.14	20.00	24.49	31.62	37.41	44.72	290	580
	616.964	●	●	●	6.00	4.20	12.50	17.68	25.00	30.62	39.53	46.77	55.90	290	580
	617.044	●		●	8.00	5.50	20.00	28.26	39.97	48.95	63.20	74.78	89.38	290	580
617.124			●	10.00	7.40	31.50	44.54	62.99	77.15	99.60	117.85	140.86	290	580	
90°	616.726	●	●	●	3.00	1.80	3.15	4.45	6.30	7.71	9.96	11.78	14.09	520	980
	616.766	●	●	●	3.50	1.90	4.00	5.66	8.00	9.80	12.65	14.97	17.89	530	1,000
	616.806	●	●	●	4.00	2.40	5.00	7.07	10.00	12.25	15.81	18.71	22.36	530	1,030
	616.846	●	●	●	4.50	2.40	6.25	8.84	12.50	15.31	19.76	23.38	27.94	540	1,050
	616.886	●	●	●	5.00	3.10	8.00	11.31	16.00	19.60	25.30	29.94	35.78	540	1,060
	616.926	●	●	●	5.50	3.60	10.00	14.14	20.00	24.49	31.62	37.41	44.72	540	1,070
	616.966	●	●	●	6.00	3.90	12.50	17.68	25.00	30.62	39.53	46.77	55.90	540	1,070
120°	616.727	●	●	●	3.00	1.60	3.15	4.45	6.30	7.71	9.96	11.78	14.09	890	1,680
	616.767	●	●	●	3.50	1.70	4.00	5.66	8.00	9.80	12.65	14.97	17.89	900	1,700
	616.807	●	●	●	4.00	2.00	5.00	7.07	10.00	12.25	15.81	18.71	22.36	900	1,710
	616.887	●	●	●	5.00	2.60	8.00	11.31	16.00	19.60	25.30	29.94	35.78	910	1,710
	616.927	●	●	●	5.50	2.90	10.00	14.14	20.00	24.49	31.62	37.41	44.72	910	1,710
	616.967			●	6.00	3.20	12.50	17.68	25.00	30.62	39.53	46.77	55.90	910	1,710
	617.047			●	8.00	4.40	20.00	28.26	39.97	48.95	63.20	74.78	89.38	910	1,710

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 616.724 + 16 = 616.724.16



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles for retaining nut Series 652



Features:


- Uniform, parabolic liquid distribution
- Stable spray angle
- Assembly with retaining nut

Applications:

- Spray cleaning
- Surface cleaning
- Filter cleaning
- Coating processes
- Belt cleaning
- Lubrication processes



Series 652



Code	Dimensions [mm]				Weight [g] Brass
	L ₁	L ₂	Ø D	Flats	
Assembly with retaining nut 3/8 BSPP	11.0	2.0	14.8	10	9.0

Spray angle	Ordering no.					Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.						p [bar]						H = 250 [mm]	H = 500 [mm]
		16	17 ¹	30	5E										
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass	PVDF			0.5	1.0	2.0	3.0	5.0	10.0		
20°	652.301	●	●	●	●	0.70	0.60	0.16*	0.23*	0.32	0.40	0.51	0.72	85	160
	652.361	●	●	●	●	1.00	0.80	0.32*	0.45*	0.63	0.77	1.00	1.41	85	160
	652.441	●	●	●	●	1.35	1.10	0.63*	0.89	1.25	1.53	1.98	2.80	85	160
	652.481	●	●	●	●	1.50	1.20	0.80*	1.13	1.60	1.96	2.53	3.58	85	160
30°	652.302	●	●	●	●	0.60	0.50	0.16*	0.23*	0.32	0.40	0.51	0.72	120	220
	652.362	●	●	●	●	1.00	0.70	0.32*	0.45*	0.63	0.77	1.00	1.41	120	220
	652.402	●	●	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	2.23	120	230
	652.482	●	●	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	3.58	130	230
	652.562	●	●	●	●	2.00	1.50	1.25	1.77	2.50	3.06	3.95	5.59	130	240
	652.642	●	●	●		2.50	1.80	2.00	2.83	4.00	4.90	6.33	8.95	140	250
	652.722	●	●	●		3.00	2.40	3.15	4.45	6.30	7.71	9.96	14.09	140	260
	652.762	●	●	●		3.50	2.70	4.00	5.66	8.00	9.80	12.65	17.89	140	260
652.802	●	●	●		4.00	3.10	5.00	7.07	10.00	12.25	15.81	22.36	140	260	
45°	652.303	●	●	●		0.70	0.50	0.16*	0.23*	0.32	0.40	0.51	0.72	170	330
	652.363	●	●	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.41	190	350
	652.403	●	●	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	2.23	200	370
	652.483	●	●	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	3.58	200	390
	652.563	●	●	●	●	2.00	1.40	1.25	1.77	2.50	3.06	3.95	5.59	210	410
	652.643	●	●	●	●	2.50	1.80	2.00	2.83	4.00	4.90	6.33	8.95	220	410
	652.723	●	●	●		3.00	2.40	3.15	4.45	6.30	7.71	9.96	14.09	220	420
	652.763	●	●	●		3.50	2.60	4.00	5.66	8.00	9.80	12.65	17.89	220	420
652.803	●	●	●		4.00	3.00	5.00	7.07	10.00	12.25	15.81	22.36	220	420	

Spray angle	Ordering no.					Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.						p [bar]							
		16	17¹	30	5E										
		Stainless steel 303	Stainless steel 316Ti Stainless steel 316L	Brass	PVDF			0.5	1.0	2.0	3.0	5.0	10.0		
60°	652.304	●	●	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.72	260	480
	652.334	●	●	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	1.00	260	490
	652.364	●	●	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.41	260	500
	652.404	●	●	●	●	1.20	0.80	0.50*	0.71	1.00	1.22	1.58	2.23	260	510
	652.444	●	●	●	●	1.35	0.90	0.63*	0.89	1.25	1.53	1.98	2.80	260	510
	652.484	●	●	●	●	1.50	1.00	0.80*	1.13	1.60	1.96	2.53	3.58	260	520
	652.514	●	●	●	●	1.65	1.10	0.95*	1.34	1.90	2.32	3.00	4.24	270	520
	652.564	●	●	●	●	2.00	1.30	1.25	1.77	2.50	3.06	3.95	5.59	270	530
	652.604	●	●	●	●	2.20	1.50	1.57	2.23	3.15	3.86	4.98	7.04	270	540
	652.644	●	●	●	●	2.50	1.60	2.00	2.83	4.00	4.90	6.33	8.95	270	540
	652.674	●	●	●	●	2.70	1.80	2.37	3.36	4.75	5.82	7.51	10.62	270	550
	652.724	●	●	●	●	3.00	2.10	3.15	4.45	6.30	7.71	9.96	14.09	280	560
	652.764	●	●	●		3.50	2.30	4.00	5.66	8.00	9.80	12.65	17.89	280	570
	652.804	●	●	●	●	4.00	2.60	5.00	7.07	10.00	12.25	15.81	22.36	290	580
	652.844	●			●	4.50	3.00	6.25	8.84	12.50	15.31	19.76	27.94	290	580
	652.884	●		●		5.00	3.40	8.00	11.31	16.00	19.60	25.30	35.78	290	580
75°	652.145	●		●		0.20	0.12	–	0.04*	0.05	0.06	0.08	0.11	380	690
	652.165	●		●		0.20	0.14	–	0.05*	0.07	0.08	0.10	0.14	380	690
	652.185	●		●		0.20	0.16	–	0.06*	0.08	0.10	0.13	0.18	380	690
	652.215	●		●		0.40	0.20	–	0.08*	0.11	0.14	0.18	0.25	380	690
	652.245	●		●		0.50	0.30	–	0.12*	0.16	0.20	0.26	0.37	380	690
	652.275	●		●		0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.49	380	690
90°	652.216	●		●		0.40	0.20	0.06*	0.08*	0.11	0.14	0.18	0.25	420	780
	652.246	●		●		0.50	0.30	0.08*	0.12*	0.16	0.20	0.26	0.37	420	780
	652.276	●		●		0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.49	430	790
	652.306	●	●	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.72	440	800
	652.336	●	●	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	1.00	440	820
	652.366	●	●	●	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.41	450	830
	652.406	●	●	●	●	1.20	0.70	0.50*	0.71	1.00	1.22	1.58	2.23	450	840
	652.446	●	●	●	●	1.35	0.80	0.63*	0.89	1.25	1.53	1.98	2.80	460	860
	652.486	●	●	●	●	1.50	0.80	0.80*	1.13	1.60	1.96	2.53	3.58	470	870
	652.516	●	●	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	4.24	480	880
	652.566	●	●	●	●	2.00	1.10	1.25	1.77	2.50	3.06	3.95	5.59	490	900
	652.606	●	●	●	●	2.20	1.20	1.57	2.23	3.15	3.86	4.98	7.04	500	910
	652.646	●	●	●	●	2.50	1.30	2.00	2.83	4.00	4.90	6.33	8.95	510	930
	652.676	●	●	●	●	2.70	1.40	2.37	3.36	4.75	5.82	7.51	10.62	510	950
	652.726	●	●	●	●	3.00	1.70	3.15	4.45	6.30	7.71	9.96	14.09	520	980
	652.766	●	●	●	●	3.50	1.90	4.00	5.66	8.00	9.80	12.65	17.89	530	1,000
	652.806	●	●	●	●	4.00	2.40	5.00	7.07	10.00	12.25	15.81	22.36	530	1,030
	652.846	●		●	●	4.50	2.40	6.25	8.84	12.50	15.31	19.76	27.94	540	1,050
	652.886	●		●	●	5.00	3.10	8.00	11.31	16.00	19.60	25.30	35.78	540	1,060






Spray angle	Ordering no.					Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar) 	
	Type	Mat. no.													
		16	17¹	30	5E			p [bar]							
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass	PVDF										
								0.5	1.0	2.0	3.0	5.0	10.0	H = 250 [mm]	H = 500 [mm]
120°	652.187	●		●		0.35	0.20	–	0.06*	0.08	0.10	0.13	0.18	630	1,060
	652.217	●		●		0.40	0.20	–	0.08*	0.11	0.14	0.18	0.25	650	1,080
	652.247	●		●		0.50	0.20	–	0.12*	0.16	0.20	0.26	0.37	660	1,100
	652.277	●		●		0.60	0.30	–	0.16*	0.22	0.27	0.35	0.49	670	1,150
	652.307	●		●	●	0.70	0.30	0.16*	0.23*	0.32	0.40	0.51	0.72	710	1,240
	652.337	●	●	●	●	0.90	0.40	0.22*	0.32*	0.45	0.55	0.71	1.00	740	1,350
	652.367	●	●	●	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.41	800	1,430
	652.407	●	●	●	●	1.20	0.60	0.50*	0.71	1.00	1.22	1.58	2.23	830	1,480
	652.447	●	●	●	●	1.35	0.60	0.63*	0.89	1.25	1.53	1.98	2.80	840	1,520
	652.487	●	●	●	●	1.50	0.60	0.80*	1.13	1.60	1.96	2.53	3.58	850	1,540
	652.517	●	●	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	4.24	850	1,560
	652.567	●	●	●	●	2.00	0.90	1.25	1.77	2.50	3.06	3.95	5.59	870	1,590
	652.607	●	●	●	●	2.20	1.10	1.57	2.23	3.15	3.86	4.98	7.04	870	1,620
	652.647	●	●	●		2.50	1.30	2.00	2.83	4.00	4.90	6.33	8.95	880	1,640
	652.677	●	●	●		2.70	1.40	2.37	3.36	4.75	5.82	7.51	10.62	890	1,660
	652.727	●	●	●	●	3.00	1.60	3.15	4.45	6.30	7.71	9.96	14.09	890	1,680
	652.767	●	●	●		3.50	1.70	4.00	5.66	8.00	9.80	12.65	17.89	900	1,700
	652.807	●		●		4.00	2.00	5.00	7.07	10.00	12.25	15.81	22.36	900	1,710
	652.847				●	4.50	2.30	6.25	8.84	12.50	15.31	19.76	27.94	900	1,710
	652.887				●	5.00	2.60	8.00	11.31	16.00	19.60	25.30	35.78	910	1,710

* Differing spray pattern.

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.



Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 652.187 + 16 = 652.187.16

Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles

Belt lubrication

Series 652



Features:


- Particularly low flow rate
- Parabolic liquid distribution
- Assembly with retaining nut

Applications:

- Belt lubrication
- Spraying on food products
- Moistening of rollers
- Oiling of metal sheets



Series 652.xxx.56.03



Code	Material	Dimensions [mm]				Weight [g]
		L ₁	L ₂	Ø D	Flats	
Assembly with retaining nut 3/8 BSPP	Stainless steel 303	11.0	2.0	14.8	10	10.0
	POM/Stainless steel	12.0	2.0	14.8	8	3.0
	POM	11.0	2.0	15.0	8	2.0

Spray angle	Ordering no.				Color	Narrowest free cross section Ø [mm]	V̇ water [l/min]			
	Type	Mat. no.					p [bar]			
		16	8H.03	56.03						
		Stainless steel 303	Housing: POM Insert: 303 SS	POM			1.0	2.0	3.0	5.0
75°	652.145	●	●	●	Green	0.12	0.04*	0.05	0.06	0.08
	652.165	●	●		Black	0.14	0.05*	0.07	0.08	0.10
	652.185	●	●	●	Red	0.16	0.06*	0.08	0.10	0.13
	652.215	●	●	●	Blue	0.20	0.08*	0.11	0.14	0.18
	652.245	●	●	●	Orange	0.30	0.12*	0.16	0.20	0.26
	652.275	●	●		Brown	0.30	0.16*	0.22	0.27	0.35
120°	652.187	●	●		Grey	0.20	0.06*	0.08	0.10	0.13
	652.247	●	●		Black	0.20	0.12*	0.16	0.20	0.26
	652.277	●	●		Black	0.30	0.16*	0.22	0.27	0.35

* Differing spray pattern.

Accessories:

	Designation	Ordering no.	Material	Color	Pressure [bar]		G BSPP	Dimensions [mm]						Mesh size [mm]
					Opening	Closing		H ₁	H ₂	Ø D	Ø D ₁	Ø D ₂	Hex	
	Filter with non-return valve	095.016.53.11.00	PP	Blue	0.50	0.30	–	21.00	1.60	–	15.00	11.00	–	0.08
		095.016.53.14.63	PP	Green	2.80	1.60	–	21.00	1.50	–	15.00	11.00	–	0.08
	Flat gas-ket	065.240.55	PTFE	–	–	–	–	–	–	–	–	–	–	–
		065.240.72	EWP 210	–	–	–	–	–	–	–	–	–	–	–
	Retaining nut	065.200.16	Stainless steel 303	–	–	–	3/8	13.00	10.00	12.80	–	–	22	–
		065.200.56	POM	Black	–	–	3/8	14.50	11.50	13.00	–	–	22	–

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 652.145 + 16 = 652.145.16




Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles

Press-in nozzle

Series 612.xxx.5E.03




Features:

- Uniform, parabolic liquid distribution
- For pressing into pipes

Applications:

- Cleaning and rinsing procedures
- Industrial dish washers




Series 612.xxx.5E.03

Dimensions [mm]				Weight [g]
L ₁	L ₂	Ø D	Flats	
12.5	5.5	14.0	12	2.0

Spray angle	Ordering no.		Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 2 bar)	
	Type	Mat. no.			p [bar]							
		5E.03										
		PVDF			0.3	0.5	0.7	1.0	1.5	2.0		H = 250 [mm]
90°	612.366	●	1.00	0.50	0.24	0.31	0.37	0.44	0.55	0.63	360	730
	612.486	●	1.50	0.60	0.62	0.80	0.95	1.13	1.39	1.60	360	730
120°	612.487	●	1.50	0.60	0.62	0.80	0.95	1.13	1.39	1.60	720	1,280
	612.647	●	2.50	1.20	1.55	2.00	2.37	2.83	3.46	4.00	720	1,280

Assembly :



Drill pipe (Ø 10 mm), ream to Ø 10.5 H11 (+0.09) mm, adjust nozzle, place press-in pipe (inner diameter 12.2 mm) on nozzle and tap in using a rubber mallet. Max. flow velocity in the pipe 2–3 m/s.


Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. = Ordering no.
example: 612.366 + 5E.03 = 612.366.5E.03




Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles for retaining nut Series 656/657



Features:

- Uniform, parabolic liquid distribution
- Stable spray angle
- High spray energy
- Assembly with retaining nut
- Non-clogging



Applications:

- Cleaning installations
- Gravel washing
- Roll cooling
- Cooling of rolled stock
- Cooling pipes

Series 656/657

Code	Dimensions [mm]				Weight [g] Brass
	L ₁	L ₂	Ø D	Flats	
Assembly with retaining nut 3/4 BSPP	11.0	2.0	24.0	17	23.0

Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]								Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]									
		16	17 ¹	30												
		Stainless steel 303	Stainless steel 316Ti Stainless steel 316L	Brass			0.5	1.0	2.0	3.0	5.0	7.0	10.0	H = 250 [mm]	H = 500 [mm]	
20°	656.721	●	●	●	3.00	2.50	3.15	4.45	6.30	7.71	9.96	11.78	14.09	100	180	
	656.801	●	●	●	4.00	3.20	5.00	7.07	10.00	12.25	15.81	18.71	22.36	100	180	
	656.881	●	●	●	5.00	4.00	8.00	11.31	16.00	19.60	25.30	29.94	35.78	100	180	
	656.921	●	●	●	5.50	4.40	10.00	14.14	20.00	24.49	31.62	37.41	44.72	100	180	
	656.961	●	●	●	6.00	5.30	12.50	17.68	25.00	30.62	39.53	46.77	55.90	100	180	
30°	656.722	●	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	11.78	14.09	140	260	
	656.762	●	●	●	3.50	2.70	4.00	5.66	8.00	9.80	12.65	14.97	17.89	140	260	
	656.802	●	●	●	4.00	3.10	5.00	7.07	10.00	12.25	15.81	18.71	22.36	140	260	
	656.882	●	●	●	5.00	4.00	8.00	11.31	16.00	19.60	25.30	29.94	35.78	140	270	
	656.922	●	●	●	5.50	4.40	10.00	14.14	20.00	24.49	31.62	37.41	44.72	140	270	
	656.962	●	●	●	6.00	5.00	12.50	17.68	25.00	30.62	39.53	46.77	55.90	140	270	
45°	656.723	●	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	11.78	14.09	220	420	
	656.763	●	●	●	3.50	2.60	4.00	5.66	8.00	9.80	12.65	14.97	17.89	220	420	
	656.803	●	●	●	4.00	3.00	5.00	7.07	10.00	12.25	15.81	18.71	22.36	220	420	
	656.843	●	●	●	4.50	3.40	6.25	8.84	12.50	15.31	19.76	23.38	27.94	220	420	
	656.883	●	●	●	5.00	3.80	8.00	11.31	16.00	19.60	25.30	29.94	35.78	220	420	
	656.923	●	●	●	5.50	4.20	10.00	14.14	20.00	24.49	31.62	37.41	44.72	220	430	
	656.963	●	●	●	6.00	4.40	12.50	17.68	25.00	30.62	39.53	46.77	55.90	220	430	





Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]								Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]								H = 250 [mm]	H = 500 [mm]
		16	17 ¹	30												
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass			0.5	1.0	2.0	3.0	5.0	7.0	10.0			
60°	656.724	●	●	●	3.00	2.10	3.15	4.45	6.30	7.71	9.96	11.78	14.09	280	560	
	656.764	●	●	●	3.50	2.30	4.00	5.66	8.00	9.80	12.65	14.97	17.89	280	570	
	656.804	●	●	●	4.00	2.60	5.00	7.07	10.00	12.25	15.81	18.71	22.36	290	580	
	656.844	●	●	●	4.50	3.00	6.25	8.84	12.50	15.31	19.76	23.38	27.94	290	580	
	656.884	●	●	●	5.00	3.40	8.00	11.31	16.00	19.60	25.30	29.94	35.78	290	580	
	656.924	●	●	●	5.50	4.10	10.00	14.14	20.00	24.49	31.62	37.41	44.72	290	580	
	656.964	●	●	●	6.00	4.20	12.50	17.68	25.00	30.62	39.53	46.77	55.90	290	580	
	657.044		●	●	8.00	5.50	20.00	28.29	40.00	48.99	63.25	74.84	89.45	290	580	
90°	656.726	●	●	●	3.00	1.70	3.15	4.45	6.30	7.71	9.96	11.78	14.09	520	980	
	656.766	●	●	●	3.50	1.90	4.00	5.66	8.00	9.80	12.65	14.97	17.89	530	1,000	
	656.806	●	●	●	4.00	2.40	5.00	7.07	10.00	12.25	15.81	18.71	22.36	530	1,030	
	656.846	●	●	●	4.50	2.40	6.25	8.84	12.50	15.31	19.76	23.38	27.94	540	1,050	
	656.886	●	●	●	5.00	3.10	8.00	11.31	16.00	19.60	25.30	29.94	35.78	540	1,060	
	656.926	●	●	●	5.50	3.60	10.00	14.14	20.00	24.49	31.62	37.41	44.72	540	1,070	
	656.966	●	●	●	6.00	3.90	12.50	17.68	25.00	30.62	39.53	46.77	55.90	540	1,070	
	657.046			●	8.00	4.90	20.00	28.29	40.00	48.99	63.25	74.84	89.45	540	1,070	
120°	656.727	●	●	●	3.00	1.60	3.15	4.45	6.30	7.71	9.96	11.78	14.09	890	1,680	
	656.767	●	●	●	3.50	1.70	4.00	5.66	8.00	9.80	12.65	14.97	17.89	900	1,700	
	656.807	●	●	●	4.00	2.00	5.00	7.07	10.00	12.25	15.81	18.71	22.36	900	1,710	
	656.887	●	●	●	5.00	2.60	8.00	11.31	16.00	19.60	25.30	29.94	35.78	910	1,710	
	656.927	●	●	●	5.50	2.90	10.00	14.14	20.00	24.49	31.62	37.41	44.72	910	1,710	

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 656.724 + 16 = 656.724.16



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles with dovetail guide

Series 660




Features:

- Uniform, parabolic liquid distribution
- Stable spray angle
- Spray automatically aligned approx. 5° to the longitudinal axis of the pipe due to dovetail guide
- Assembly with retaining nut
- Non-clogging
- High spray energy



Series 660



Applications:

- Cleaning installations
- Spray pipes
- Cooling pipes

Code	Dimensions [mm]				Weight [g] Brass
	L ₁	L ₂	Ø D ₁	Ø D ₂	
Assembly with retaining nut 3/8 BSPP and dovetail guide	12.0	7.0	14.8	12.0	10.0

Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]						H = 250 [mm]	H = 500 [mm]
		16	17 ¹	30										
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass			0.5	1.0	2.0	3.0	5.0	10.0		
20°	660.301	●	●	●	0.70	0.60	0.16*	0.23*	0.32	0.40	0.51	0.72	85	160
	660.361	●	●	●	1.00	0.80	0.32*	0.45*	0.63	0.77	1.00	1.41	85	160
	660.441	●	●	●	1.35	1.10	0.63*	0.89	1.25	1.53	1.98	2.80	85	160
	660.481	●	●	●	1.50	1.20	0.80*	1.13	1.60	1.96	2.53	3.58	85	160
30°	660.302	●	●	●	0.60	0.50	0.16*	0.23*	0.32	0.40	0.51	0.72	120	220
	660.362	●	●	●	1.00	0.70	0.32*	0.45*	0.63	0.77	1.00	1.41	120	220
	660.402	●	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	2.23	120	230
	660.482	●	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	3.58	130	230
	660.562	●	●	●	2.00	1.50	1.25	1.77	2.50	3.06	3.95	5.59	130	240
45°	660.303	●	●	●	0.70	0.50	0.16*	0.23*	0.32	0.40	0.51	0.72	170	330
	660.363	●	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.41	190	350
	660.403	●	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	2.23	200	370
	660.483	●	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	3.58	200	390
	660.563	●	●	●	2.00	1.40	1.25	1.77	2.50	3.06	3.95	5.59	210	410
	660.643	●	●	●	2.50	1.80	2.00	2.83	4.00	4.90	6.33	8.95	220	410
60°	660.304	●	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.72	260	480
	660.334	●	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	1.00	260	490
	660.364	●	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.41	260	500
	660.404	●	●	●	1.20	0.80	0.50*	0.71	1.00	1.22	1.58	2.23	260	510
	660.444	●	●	●	1.35	0.90	0.63*	0.89	1.25	1.53	1.98	2.80	260	510





Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]							
		16	17 ¹	30										
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass			0.5	1.0	2.0	3.0	5.0	10.0		H = 250 [mm]
60°	660.484	●	●	●	1.50	1.00	0.80*	1.13	1.60	1.96	2.53	3.58	260	520
	660.514	●	●	●	1.65	1.10	0.95*	1.34	1.90	2.32	3.00	4.24	270	520
	660.564	●	●	●	2.00	1.30	1.25	1.77	2.50	3.06	3.95	5.59	270	530
	660.604	●	●	●	2.20	1.50	1.57	2.23	3.15	3.86	4.98	7.04	270	540
	660.644	●	●	●	2.50	1.60	2.00	2.83	4.00	4.90	6.33	8.95	270	540
	660.724	●	●	●	3.00	2.10	3.15	4.45	6.30	7.71	9.96	14.09	280	560
	660.804	●		●	4.00	2.60	5.00	7.07	10.00	12.25	15.81	22.36	290	580
75°	660.145	●		●	0.20	0.14	–	0.04*	0.05	0.06	0.08	0.11	380	690
	660.165	●		●	0.20	0.14	–	0.05*	0.07	0.08	0.10	0.15	380	690
	660.185	●		●	0.20	0.16	–	0.06*	0.08	0.10	0.13	0.18	380	690
	660.215	●		●	0.50	0.20	–	0.08*	0.11	0.14	0.18	0.25	380	690
	660.245	●		●	0.50	0.30	–	0.12*	0.16	0.20	0.26	0.37	380	690
	660.275	●		●	0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.49	380	690
90°	660.216	●		●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.25	420	780
	660.276	●		●	0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.49	430	790
	660.306	●	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.72	440	800
	660.336	●	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	1.00	440	820
	660.366	●	●	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.41	450	830
	660.406	●	●	●	1.20	0.70	0.50*	0.71	1.00	1.22	1.58	2.23	450	840
	660.446	●	●	●	1.35	0.80	0.63*	0.89	1.25	1.53	1.98	2.80	460	860
	660.486	●	●	●	1.50	0.80	0.80*	1.13	1.60	1.96	2.53	3.58	470	870
	660.516	●	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	4.24	480	880
	660.566	●	●	●	2.00	1.10	1.25	1.77	2.50	3.06	3.95	5.59	490	900
	660.606	●	●	●	2.20	1.20	1.57	2.23	3.15	3.86	4.98	7.04	500	910
	660.646	●	●	●	2.50	1.30	2.00	2.83	4.00	4.90	6.33	8.95	510	930
	660.676	●	●	●	2.70	1.40	2.37	3.36	4.75	5.82	7.51	10.62	510	950
	660.726	●	●	●	3.00	1.70	3.15	4.45	6.30	7.71	9.96	14.09	520	980
	660.806		●	●	4.00	2.40	5.00	7.07	10.00	12.25	15.81	22.36	530	1,030
120°	660.187	●		●	0.35	0.20	–	0.06*	0.08	0.10	0.13	0.18	630	1,060
	660.217	●		●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.25	650	1,080
	660.247	●		●	0.50	0.30	–	0.12*	0.16	0.20	0.26	0.37	660	1,100
	660.277	●		●	0.60	0.30	–	0.16*	0.22	0.27	0.35	0.49	670	1,150
	660.307	●		●	0.70	0.30	0.16*	0.23*	0.32	0.40	0.51	0.72	710	1,240
	660.337	●	●	●	0.90	0.40	0.22*	0.32*	0.45	0.55	0.71	1.00	740	1,350
	660.367	●	●	●	1.00	0.40	0.32*	0.45*	0.63	0.77	1.00	1.41	800	1,430
	660.407	●	●	●	1.20	0.60	0.50*	0.71	1.00	1.22	1.58	2.23	830	1,480
	660.447	●	●	●	1.35	0.60	0.63*	0.88	1.25	1.53	1.98	2.80	840	1,520
	660.487	●	●	●	1.50	0.60	0.80*	1.13	1.60	1.96	2.53	3.58	850	1,540
	660.517	●	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	4.24	850	1,560
	660.567	●	●	●	2.00	0.90	1.25	1.77	2.50	3.06	3.95	5.59	870	1,590
	660.607	●	●	●	2.20	1.10	1.57	2.23	3.15	3.86	4.98	7.04	870	1,620
	660.647	●	●	●	2.50	1.30	2.00	2.83	4.00	4.90	6.33	8.95	880	1,640
	660.727	●	●	●	3.00	1.60	3.15	4.45	6.30	7.71	9.96	14.09	890	1,680
	660.807	●		●	4.00	2.00	5.00	7.07	10.00	12.25	15.81	22.36	900	1,710

* Differing spray pattern.

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 660.484 + 16 = 660.484.16



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles with dovetail guide

Series 664/665




Features:

- Uniform, parabolic liquid distribution
- Stable spray angle
- Spray automatically aligned approx. 15° to the longitudinal axis of the pipe via dovetail guide
- Assembly with retaining nut
- Non-clogging
- High spray energy



Series 664/665



Applications:

- Cleaning installations
- Spray pipes
- Roll cooling
- Cooling pipes
- Cooling of rolled stock

Code	Dimensions [mm]				Weight [g]
	L ₁	L ₂	Ø D ₁	Ø D ₂	
Assembly with retaining nut 3/4 BSPP and dovetail guide	14.0	8.0	24.0	20.0	35.0

Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]							
		16	17¹	30										
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass										
						0.5	1.0	2.0	3.0	5.0	10.0	H = 250 [mm]	H = 500 [mm]	
20°	664.721	●	●	●	3.00	2.50	3.15	4.45	6.30	7.71	9.96	14.09	100	180
	664.801	●	●	●	4.00	3.20	5.00	7.07	10.00	12.25	15.81	22.36	100	180
	664.881	●	●	●	5.00	4.00	8.00	11.31	16.00	19.60	25.30	35.78	100	180
	664.921	●	●	●	5.50	4.40	10.00	14.14	20.00	24.49	31.62	44.72	100	180
	664.961	●	●	●	6.00	5.10	12.50	17.68	25.00	30.62	39.53	55.90	100	180
30°	664.722	●	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	14.09	140	260
	664.762	●	●	●	3.50	2.70	4.00	5.66	8.00	9.80	12.65	17.89	140	260
	664.802	●	●	●	4.00	3.10	5.00	7.07	10.00	12.25	15.81	22.36	140	260
	664.882	●	●	●	5.00	4.00	8.00	11.31	16.00	19.60	25.30	35.78	140	270
	664.922	●	●	●	5.50	4.40	10.00	14.14	20.00	24.49	31.62	44.72	140	270
	664.962	●	●	●	6.00	5.00	12.50	17.68	25.00	30.62	39.53	55.90	140	270
	665.042	●		●	8.00	6.40	20.00	28.29	40.00	48.99	63.25	89.45	140	270
	665.122			●	10.00	8.20	31.50	44.55	63.00	77.16	99.61	140.87	140	270





Spray angle	Ordering no.				Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.					p [bar]						H = 250 [mm]	H = 500 [mm]
		16	17 ¹	30										
		Stainless steel 303	Stainless steel 316Ti/ Stainless steel 316L	Brass			0.5	1.0	2.0	3.0	5.0	10.0		
45°	664.723	●	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	14.09	220	420
	664.763	●	●	●	3.50	2.60	4.00	5.66	8.00	9.80	12.65	17.89	220	420
	664.803	●	●	●	4.00	3.00	5.00	7.07	10.00	12.25	15.81	22.36	220	420
	664.843	●	●	●	4.50	3.40	6.25	8.84	12.50	15.31	19.76	27.94	220	420
	664.883	●	●	●	5.00	3.80	8.00	11.31	16.00	19.60	25.30	35.78	220	420
	664.923	●	●	●	5.50	4.20	10.00	14.14	20.00	24.49	31.62	44.72	220	430
	664.963	●	●	●	6.00	4.40	12.50	17.68	25.00	30.62	39.53	55.90	220	430
	665.043			●	8.00	5.90	20.00	28.29	40.00	48.99	63.25	89.45	220	430
60°	664.724	●	●	●	3.00	2.10	3.15	4.45	6.30	7.71	9.96	14.09	280	560
	664.764	●	●	●	3.50	2.30	4.00	5.66	8.00	9.80	12.65	17.89	280	570
	664.804	●	●	●	4.00	2.60	5.00	7.07	10.00	12.25	15.81	22.36	290	580
	664.844	●	●	●	4.50	3.00	6.25	8.84	12.50	15.31	19.76	27.94	290	580
	664.884	●	●	●	5.00	3.40	8.00	11.31	16.00	19.60	25.30	35.78	290	580
	664.924	●	●	●	5.50	4.10	10.00	14.14	20.00	24.49	31.62	44.72	290	580
	664.964	●	●	●	6.00	4.20	12.50	17.68	25.00	30.62	39.53	55.90	290	580
	665.044	●	●	●	8.00	5.50	20.00	28.29	40.00	48.99	63.25	89.45	290	580
	665.084		●	●	9.00	6.20	25.00	35.36	50.00	61.24	79.06	111.81	290	580
	665.124			●	10.00	7.40	31.50	44.55	63.00	77.16	99.61	140.87	290	580
90°	664.726	●	●	●	3.00	1.70	3.15	4.45	6.30	7.71	9.96	14.09	520	980
	664.766	●	●	●	3.50	1.90	4.00	5.66	8.00	9.80	12.65	17.89	530	1,000
	664.806	●	●	●	4.00	2.40	5.00	7.07	10.00	12.25	15.81	22.36	530	1,030
	664.846	●	●	●	4.50	2.40	6.25	8.84	12.50	15.31	19.76	27.94	540	1,050
	664.886	●	●	●	5.00	3.10	8.00	11.31	16.00	19.60	25.30	35.78	540	1,060
	664.926	●	●	●	5.50	3.60	10.00	14.14	20.00	24.49	31.62	44.72	540	1,070
	664.966	●	●	●	6.00	3.90	12.50	17.68	25.00	30.62	39.53	55.90	540	1,070
	665.046			●	8.00	4.90	20.00	28.29	40.00	48.99	63.25	89.45	540	1,070
	665.126			●	10.00	6.40	31.50	44.55	63.00	77.16	99.61	140.87	540	1,070
120°	664.727	●	●	●	3.00	1.60	3.15	4.45	6.30	7.71	9.96	14.09	890	1,680
	664.767	●	●	●	3.50	1.70	4.00	5.66	8.00	9.80	12.65	17.89	900	1,700
	664.807	●	●	●	4.00	2.00	5.00	7.07	10.00	12.25	15.81	22.36	900	1,710
	664.887	●	●	●	5.00	2.60	8.00	11.31	16.00	19.60	25.30	35.78	910	1,710
	664.927	●	●	●	5.50	2.90	10.00	14.14	20.00	24.49	31.62	44.72	910	1,710
	664.967			●	6.00	3.20	12.50	17.68	25.00	30.62	39.53	55.90	910	1,710
	665.047			●	8.00	4.40	20.00	28.29	40.00	48.99	63.25	89.45	910	1,710

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 664.723 + 16 = 664.723.16



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure flat fan nozzles

Series 646





Features:

- Uniform, parabolic liquid distribution
- Adjusted spray direction
- Simple, fast manual assembly due to bayonet quick-release system

Applications:

- Belt cleaning
- Surface treatment
- Spray cleaning
- Coating processes



Series 646

Dimensions [mm]		Weight [g]
H	L	
15.0	44.0	12.0


Spray angle	Ordering no.		Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.			p [bar]						H = 250 [mm]	H = 500 [mm]
		5E										
		PVDF			0.5	1.0	2.0	3.0	5.0	10.0		
20°	646.301	●	0.70	0.60	0.16*	0.23*	0.32	0.39	0.51	0.72	85	160
	646.361	●	1.00	0.80	0.31*	0.44*	0.63	0.77	1.00	1.41	85	160
	646.441	●	1.35	1.10	0.63*	0.88	1.25	1.53	1.98	2.80	85	160
	646.481	●	1.50	1.20	0.80*	1.13	1.60	1.96	2.53	3.58	85	160
30°	646.302	●	0.70	0.50	0.16*	0.23*	0.32	0.39	0.51	0.72	120	220
	646.362	●	1.00	0.70	0.31*	0.44*	0.63	0.77	1.00	1.40	120	220
	646.402	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	2.24	120	230
	646.482	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	3.58	130	230
	646.562	●	2.00	1.50	1.25	1.77	2.50	3.06	3.95	5.59	130	240
45°	646.363	●	1.00	0.60	0.31*	0.44*	0.63	0.77	1.00	1.40	190	350
	646.403	●	1.20	0.90	0.50*	0.71	1.00	1.23	1.58	2.24	200	370
	646.483	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	3.58	200	390
	646.563	●	2.00	1.40	1.20	1.77	2.50	3.06	3.95	5.59	210	410
	646.643	●	2.50	1.80	2.00	2.83	4.00	4.90	6.32	8.94	210	410
60°	646.304	●	0.70	0.40	0.16*	0.23*	0.32	0.39	0.51	0.72	260	480
	646.334	●	0.90	0.50	0.23*	0.32*	0.45	0.55	0.71	1.01	260	490
	646.364	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.41	260	500
	646.404	●	1.20	0.80	0.50*	0.71	1.00	1.22	1.58	2.24	260	510
	646.444	●	1.35	0.90	0.63*	0.88	1.25	1.53	1.98	2.80	260	510
	646.484	●	1.50	1.00	0.80*	1.13	1.60	1.96	2.53	3.58	260	520
	646.514	●	1.65	1.10	0.95*	1.34	1.90	2.33	3.00	4.25	270	520
	646.564	●	2.00	1.30	1.25	1.77	2.50	3.06	3.95	5.59	270	530
	646.604	●	2.20	1.50	1.58	2.23	3.15	3.86	4.98	7.04	270	540





Spray angle	Ordering no.		Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.			p [bar]						H = 250 [mm]	H = 500 [mm]
		5E										
		PVDF										
90°	646.306	●	0.70	0.40	0.16*	0.23*	0.32	0.39	0.51	0.72	440	800
	646.336	●	0.90	0.50	0.23*	0.32*	0.45	0.55	0.71	1.01	440	820
	646.366	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.41	450	830
	646.406	●	1.20	0.70	0.50*	0.71	1.00	1.22	1.58	2.24	450	840
	646.446	●	1.35	0.80	0.63*	0.88	1.25	1.53	1.98	2.80	460	860
	646.486	●	1.50	0.80	0.80*	1.13	1.60	1.96	2.53	3.58	470	870
	646.516	●	1.65	0.90	0.95*	1.34	1.90	2.33	3.00	4.25	480	880
	646.566	●	2.00	1.10	1.25	1.77	2.50	3.06	3.95	5.59	490	900
646.606	●	2.20	1.20	1.58	2.23	3.15	3.86	4.98	7.04	500	910	
120°	646.307	●	0.70	0.30	0.16*	0.23*	0.32	0.39	0.51	0.72	710	1,240
	646.337	●	0.90	0.40	0.23*	0.32*	0.45	0.55	0.71	1.01	740	1,310
	646.367	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.41	800	1,350
	646.407	●	1.20	0.60	0.50*	0.71	1.00	1.22	1.58	2.24	830	1,390
	646.447	●	1.35	0.60	0.63*	0.88	1.25	1.53	1.98	2.80	840	1,410
	646.487	●	1.50	0.60	0.80*	1.13	1.60	1.96	2.53	3.58	850	1,420
	646.517	●	1.65	0.90	0.95*	1.34	1.90	2.33	3.00	4.25	850	1,430
	646.567	●	2.00	0.90	1.25	1.77	2.50	3.06	3.95	5.59	870	1,440
646.607	●	2.20	1.10	1.58	2.23	3.15	3.86	4.98	7.04	870	1,450	

* Differing spray pattern.



Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 646.306 + 5E = 646.306*



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure tongue-type nozzles

Series 688/689



Features:


- Narrowly delimited, powerful flat fan spray
- Non-clogging

Applications:

- Cleaning processes
- Washing processes
- Degreasing installations
- Phosphating installations
- Preparation techniques



Series 688/689



Type	Code	G	Dimensions [mm]		Weight [g]
			L	Hex	
688.763	CE	3/8 BSPT	43.0	19	53.0 (Stainless steel 303)
688.843	CE	3/8 BSPT	50.0	19	133.0 (Stainless steel 303)
688.923	CE	3/8 BSPT	59.0	22	247.0 (Stainless steel 303)
689.003	90	3/4 BSPP	80.0	32/24	306.0/33.0 (Stainless steel 303/PVDF)

Spray angle	η	Ordering no.				Bore diameter B [mm]	V̇ water [l/min]				Spray width B [mm] (at p = 2 bar)		
		Type	Mat. no.		Code		p [bar]				H = 250 [mm]	H = 500 [mm]	
			16	5E	3/8 BSPT								3/4 BSPP
			Stainless steel 303	PVDF									
45°	35°	688.763	●		CE		3.00	4.00	5.66	8.00	12.65	220	420
	30°	688.843	●		CE		3.80	6.25	8.84	12.50	19.76	220	420
	29°	688.923	●		CE		4.80	10.00	14.14	20.00	31.62	220	430
	35°	689.003	●	●		90	6.00	15.75	22.27	31.50	49.81	220	430

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. + Code = Ordering no.
example: 688.763 + 16 + CE = 688.763.16.CE



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure tongue-type nozzles

Series 686



Features:


- Sharply delimited, powerful flat fan spray
- Large spray angle
- Non-clogging

Applications:

- Foam control
- Cleaning processes
- Washing processes



Series 686



Type	BSPP BSPT	Code	Dimensions [mm]			Weight [g] Brass
			L ₁	L ₂	Hex	
686.366	1/8	CA	23.0	6.5	11	13.0
686.406	1/8	CA	23.0	6.5	11	13.0
686.686	1/4	CC	29.5	9.7	14	23.0
686.726	1/8	CA	25.0	6.5	11	13.0
686.806	1/4	CC	33.0	9.7	14	24.0
686.886	1/4	CC	35.0	9.7	17	30.0
686.926	3/8	CE	38.5	10.1	17	32.0
686.368	1/8	CA	20.0	6.5	11	13.0
686.408	1/8	CA	23.0	6.5	11	13.0
686.448	1/4	CC	24.0	9.7	14	21.0
686.488	1/8	CA	23.0	6.5	11	13.0
686.488	1/4	CC	24.0	9.7	14	21.0
686.528	1/8	CA	23.0	6.5	11	13.0
686.528	1/4	CC	24.0	9.7	14	21.0
686.568	1/8	CA	23.0	6.5	11	13.0
686.568	1/4	CC	24.0	9.7	14	21.0
686.608	1/8	CA	23.0	6.5	11	13.0
686.608	1/4	CC	24.0	9.7	14	21.0
686.648	1/4	CC	24.0	9.7	14	21.0
686.688	1/8	CA	23.0	6.5	11	13.0
686.688	1/4	CC	27.0	9.7	14	22.0
686.728	1/8	CA	23.0	6.5	11	13.0
686.728	1/4	CC	27.0	9.7	14	22.0
686.768	1/4	CC	27.0	9.7	14	22.0
686.808	1/8	CA	23.0	6.5	11	13.0
686.808	1/4	CC	27.0	9.7	14	22.0
686.828	1/4	CC	27.0	9.7	14	22.0
686.848	1/4	CC	27.0	9.7	14	22.0
686.868	1/4	CC	28.0	9.7	14	23.0
686.888	1/4	CC	28.0	9.7	14	23.0
686.908	1/4	CC	28.0	9.7	14	23.0
686.928	3/8	CE	30.0	10.1	17	32.0
686.968	1/2	CG	37.0	13.2	22	60.0
686.988	3/8	CE	32.0	10.1	17	32.0
686.988	1/2	CG	37.0	13.2	22	60.0

Also suitable for air or saturated steam
(see Page 172).

Spray angle	η	Ordering no.							Bore diameter B [mm]	V̇ water [l/min]			Spray width B [mm] (at p = 2 bar)	
		Type	Mat. no.			Code				p [bar]				
			16	30	5E	1/8 BSPT	1/4 BSPT	3/8 BSPT						1/2 BSPT
			Stainless steel 303	Brass	PVDF									
										1.0	2.0	5.0	H = 250 [mm]	
90°	75°	686.366		●		CA			0.80	0.45	0.63	1.00	450	
		686.406	●	●		CA			1.00	0.71	1.00	1.58	450	
	40°	686.686	●	●			CC			2.40	3.54	5.00	7.91	510
		686.726		●		CA			2.70	4.45	6.30	9.96	530	
		686.806	●	●			CC			3.40	7.07	10.00	15.81	540
		686.886	●				CC			4.20	11.31	16.00	25.30	540
686.926	●					CE		4.70	14.14	20.00	31.62	540		
140°	75°	686.368	●	●		CA			0.80	0.45	0.63	1.00	1,250	
		686.408	●	●		CA			1.00	0.71	1.00	1.58	1,260	
		686.448	●	●			CC			1.20	0.88	1.25	1.98	1,260
		686.488	●	●		CA	CC			1.30	1.13	1.60	2.53	1,270
		686.528	●	●		CA	CC			1.50	1.41	2.00	3.16	1,280
		686.568	●	●	● ¹	CA	CC			1.70	1.77	2.50	3.95	1,290
		686.608	●	●		CA	CC			1.90	2.23	3.15	4.98	1,300
		686.648	●	●			CC			2.20	2.83	4.00	6.32	1,320
		686.688	●	●		CA	CC			2.40	3.54	5.00	7.91	1,330
		686.728	●	●		CA	CC			2.70	4.45	6.30	9.96	1,340
		686.768	●	●			CC			3.00	5.66	8.00	12.65	1,350
		686.808	●	●		CA	CC			3.40	7.07	10.00	15.81	1,360
		686.828	●	●			CC			3.60	7.92	11.20	17.71	1,360
		686.848	●	●			CC			3.80	8.84	12.50	19.76	1,360
		686.868	●	●			CC			4.00	9.90	14.00	22.14	1,360
		686.888	●	●			CC			4.20	11.31	16.00	25.30	1,360
		686.908	●	●			CC			4.50	12.73	18.00	28.46	1,360
		686.928	●					CE		4.70	14.14	20.00	31.62	1,360
		686.968		●					CG	5.30	17.68	25.00	39.53	1,360
		686.988	●					CE	CG	5.60	19.80	28.00	44.27	1,360

¹ Only available with code CA.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. + Code = Ordering no.
example: 686.366 + 30 + CA = 686.366.30.CA



Assembly accessories can be found in Chapter 9 "Accessories".

Low pressure tongue-type nozzles

Series 684



Features:


- Sharply delimited, powerful flat fan spray
- Large spray angle
- Assembly with retaining nut
- Non-clogging

Applications:

- Foam control
- Cleaning processes
- Washing processes



Series 684




G	Dimensions [mm]			Weight [g]
	L ₂	Ø D ₁	Ø D ₂	
Assembly with retaining nut 3/8 BSPP	2.00	14.80	12.65	3.00

Spray angle	η	Ordering no.			Color ¹	Bore diameter B [mm]	L ₁ [mm]	V̇ water [l/min]			Spray width B [mm] (at p = 2 bar)
		Type	Mat. no.					p [bar]			
			56	5E							
			POM	PVDF				1.0	2.0	5.0	
140°	75°	684.348	●		Green	0.70	20.00	0.35*	0.50	0.79	1,240
		684.368	●	●	Yellow	0.80	20.00	0.45*	0.63	1.00	1,250
		684.408	●		Blue	1.00	20.00	0.71	1.00	1.58	1,260
		684.448	●		Red	1.20	20.00	0.88	1.25	1.98	1,260
		684.488	●	●	Brown	1.30	20.00	1.13	1.60	2.53	1,270
		684.528	●		Grey	1.50	20.00	1.41	2.00	3.16	1,280
		684.568	●	●	White	1.70	19.00	1.77	2.50	3.95	1,290
		684.608	●		Light blue	1.90	19.00	2.23	3.15	4.98	1,300
		684.688	●		Green	2.40	17.00	3.54	5.00	7.91	1,330
		684.728	●	●	Black	2.70	17.00	4.45	6.30	9.96	1,340
		684.808	●		Beige	3.40	16.00	7.07	10.00	15.81	1,340

* Differing spray pattern.

¹ PVDF material is always blue.

Assembly example



Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
example: 684.348 + 56 = 684.348.56



Assembly accessories can be found in Chapter 9 "Accessories".

High pressure flat fan nozzles

Series 602



Features:


- Sharp, uniform flat fan spray
- Extremely narrow spray depth
- Housing: Stainless steel 303,
Insert: Hardened stainless steel 420F

Applications:

- High pressure cleaning



Series 602



G	Dimensions [mm]					Weight [g]	p _{max} ¹ [bar]
	L ₁	L ₂	Ø D	Hex	Flats		
1/4 BSPT	22.0	10.0	13.0	14	10	18.0	approx. 700
1/4 NPT	22.0	10.2	13.0	14	10	18.0	approx. 700

¹ Applies only to operation at constant pressure.

US gal/min at 40 psi	Ordering no.								Equivalent bore diameter A [mm]	V̇ water [l/min]						
	Series	Flow rate code				Mat. no.	Code			p [bar]						
		Spray angle				A3	1/4 BSPT	1/4 NPT								
		20°	30°	45°	60°	Stainless steel 303/420F										
40	60	80	100	120	150	200										
02	602	361	362	363	364	●	00	07	1.00	2.88	3.53	4.08	4.56	5.00	5.58	6.45
021	602	371	372	373	374	●	00	07	1.02	3.03	3.71	4.28	4.79	5.25	5.87	6.77
025	602	381	382	383	384	●	00	07	1.10	3.60	4.42	5.10	5.70	6.24	6.98	8.06
028	602	391	392	393	394	●	00	07	1.16	4.04	4.94	5.71	6.38	6.99	7.81	9.02
03	602	401	402	403	404	●	00	07	1.18	4.32	5.29	6.11	6.83	7.48	8.37	9.66
034	602	411	412	413	414	●	00	07	1.30	4.90	6.00	6.93	7.75	8.49	9.49	10.96
038	602	441	442	443		●	00	07	1.33	5.48	6.72	7.75	8.67	9.50	10.62	12.26
04	602	451	452	453	454	●	00	07	1.35	5.77	7.06	8.16	9.12	9.99	11.17	12.90
043	602	461	462			●	00	07	1.38	6.20	7.59	8.77	9.80	10.74	12.00	13.86
045	602	471	472	473	474	●	00	07	1.40	6.49	7.95	9.18	10.26	11.24	12.57	14.51
05	602	481	482	483	484	●	00	07	1.55	7.21	8.83	10.20	11.40	12.49	13.96	16.12
055	602	501	502	503	504	●	00	07	1.60	7.93	9.71	11.22	12.54	13.74	15.36	17.73
06	602	521	522	523	524	●	00	07	1.72	8.65	10.60	12.24	13.68	14.99	16.75	19.35
065	602	531	532	533	534	●	00	07	1.75	9.37	11.48	13.26	14.82	16.23	18.15	20.96
07	602	541	542	543	544	●	00	07	1.80	10.09	12.36	14.28	15.96	17.48	19.55	22.57
075	602	551	552	553	554	●	00	07	1.90	10.81	13.25	15.29	17.10	18.73	20.94	24.18
08	602	571	572	573	574	●	00	07	2.05	11.54	14.13	16.31	18.24	19.98	22.34	25.80
087	602	581	582	583	584	●	00	07	2.06	12.54	15.36	17.74	19.83	21.72	24.29	28.04
09	602	591	592	593	594	●	00	07	2.10	12.98	15.89	18.35	20.52	22.48	25.13	29.02
10	602	601	602	603	604	●	00	07	2.30	14.41	17.65	20.38	22.79	24.97	27.91	32.23
11	602	621	622	623	624	●	00	07	2.40	15.86	19.42	22.42	25.07	27.46	30.70	35.45
125	602	641	642	643	644	●	00	07	2.50	18.02	22.07	25.48	28.49	31.21	34.89	40.29
131	602	651	652	653	654	●	00	07	2.55	18.89	23.13	26.71	29.86	32.71	36.57	42.23
139	602	661	662	663	664	●	00	07	2.65	20.04	24.54	28.34	31.68	34.70	38.80	44.80
15	602	671	672	673	674	●	00	07	2.70	21.62	26.48	30.58	34.19	37.45	41.87	48.35
175	602	701	702	703	704	●	00	07	3.00	25.23	30.90	35.68	39.89	43.70	48.86	56.41
20	602			723	724	●	00	07	3.05	28.83	35.31	40.78	45.59	49.94	55.84	64.47
25	602			763	764	●	00	07	3.50	36.04	44.14	50.97	56.99	62.43	69.80	80.60
30	602			793		●	00	07	3.90	43.25	52.97	61.16	68.38	74.91	83.75	96.70

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{P_2}{P_1}}$




Assembly accessories can be found in Chapter 9 "Accessories".

Ordering Series + Flow rate code + Material no. + Code = Ordering no.
example: 602 + 361 + A3 + 00 = 602.361.A3.00

High pressure flat fan nozzles

Series 608



Features:


- Sharp, uniform flat fan spray
- Extremely narrow spray depth
- Housing: Stainless steel 303,
Insert: Hardened stainless steel 420F

Applications:

- High pressure cleaning



Series 608



G	Dimensions [mm]					Weight [g]	p _{max} ¹ [bar]
	L ₁	L ₂	Ø D	Hex	Flats		
1/8 BSPT	22.0	6.5	13.0	14	10	13.0	approx. 700
1/8 NPT	22.0	6.7	13.0	14	10	13.0	approx. 700

¹ Applies only to operation at constant pressure.

US gal/min at 40 psi	Ordering no.								Equivalent bore diameter A [mm]	V̇ water [l/min]						
	Series	Flow rate code				Mat. no.	Code			p [bar]						
		Spray angle				A3										
		20°	30°	45°	60°	Stainless steel 303/420F				1/8 BSPT	1/8 NPT					
02	608	361	362	363	364	●	00	07	1.00	2.88	3.53	4.08	4.56	5.00	5.58	6.45
021	608	371	372	373	374	●	00	07	1.02	3.03	3.71	4.28	4.79	5.25	5.87	6.77
025	608	381	382	383	384	●	00	07	1.10	3.60	4.42	5.10	5.70	6.24	6.98	8.06
028	608	391	392	393	394	●	00	07	1.16	4.04	4.94	5.71	6.38	6.99	7.81	9.02
03	608	401	402	403	404	●	00	07	1.18	4.32	5.29	6.11	6.83	7.48	8.37	9.66
034	608	411	412	413	414	●	00	07	1.30	4.90	6.00	6.93	7.75	8.49	9.49	10.96
038	608	441	442	443		●	00	07	1.33	5.48	6.72	7.75	8.67	9.50	10.62	12.26
04	608	451	452	453	454	●	00	07	1.35	5.77	7.06	8.16	9.12	9.99	11.17	12.90
043	608	461	462			●	00	07	1.38	6.20	7.59	8.77	9.80	10.74	12.00	13.86
045	608	471	472	473	474	●	00	07	1.40	6.49	7.95	9.18	10.26	11.24	12.57	14.51
05	608	481	482	483	484	●	00	07	1.55	7.21	8.83	10.20	11.40	12.49	13.96	16.12
055	608	501	502	503	504	●	00	07	1.60	7.93	9.71	11.22	12.54	13.74	15.36	17.73
06	608	521	522	523	524	●	00	07	1.72	8.65	10.60	12.24	13.68	14.99	16.75	19.35
065	608	531	532	533	534	●	00	07	1.75	9.37	11.48	13.26	14.82	16.23	18.15	20.96
07	608	541	542	543	544	●	00	07	1.80	10.09	12.36	14.28	15.96	17.48	19.55	22.57
075	608	551	552	553	554	●	00	07	1.90	10.81	13.25	15.29	17.10	18.73	20.94	24.18
08	608	571	572	573	574	●	00	07	2.05	11.54	14.13	16.31	18.24	19.98	22.34	25.80
087	608	581	582	583	584	●	00	07	2.06	12.54	15.36	17.74	19.83	21.72	24.29	28.04
09	608	591	592	593	594	●	00	07	2.10	12.98	15.89	18.35	20.52	22.48	25.13	29.02
10	608	601	602	603	604	●	00	07	2.30	14.41	17.65	20.38	22.79	24.97	27.91	32.23

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$



Assembly accessories can be found in Chapter 9 "Accessories".


Ordering Series + Flow rate code + Material no. + Code = Ordering no.
example: 608 + 361 + A3 + 00 = 608.361.A3.00

High pressure flat fan nozzles

Series 652

Features:

- Sharp, uniform flat fan spray
- Extremely narrow spray depth
- Assembly with retaining nut
- Housing: Stainless steel 303,
Insert: Hardened stainless steel 420F



Applications:

- High pressure cleaning

Series 652

G	Dimensions [mm]					Weight [g]	p _{max} ¹ [bar]
	L ₁	L ₂	Ø D ₁	Ø D ₂	Flats		
Assembly with retaining nut 3/8 BSPP	16.00	14.00	14.80	12.65	10	13.00	approx. 300

¹ Applies only to operation at constant pressure.

US gal/min at 40 psi	Ordering no.							Equivalent bore diameter A [mm]	V̇ water [l/min]						
	Series	Flow rate code				Mat. no.	Code		p [bar]						
		Spray angle				A3									
		20°	30°	45°	60°	Stainless steel 303/420F			For retaining nut						
02	652	361	362	363	364	●	29	1.00	2.88	3.53	4.08	4.56	5.00	5.58	6.45
021	652	371	372	373	374	●	29	1.02	3.03	3.71	4.28	4.79	5.25	5.87	6.77
025	652	381	382	383	384	●	29	1.10	3.60	4.42	5.10	5.70	6.24	6.98	8.06
028	652	391	392	393	394	●	29	1.16	4.04	4.94	5.71	6.38	6.99	7.81	9.02
03	652	401	402	403	404	●	29	1.18	4.32	5.29	6.11	6.83	7.48	8.37	9.66
034	652	411	412	413	414	●	29	1.30	4.90	6.00	6.93	7.75	8.49	9.49	10.96
038	652	441	442	443		●	29	1.33	5.48	6.72	7.75	8.67	9.50	10.62	12.26
04	652	451	452	453	454	●	29	1.35	5.77	7.06	8.16	9.12	9.99	11.17	12.90
043	652	461	462			●	29	1.38	6.20	7.59	8.77	9.80	10.74	12.00	13.86
045	652	471	472	473	474	●	29	1.40	6.49	7.95	9.18	10.26	11.24	12.57	14.51
05	652	481	482	483	484	●	29	1.55	7.21	8.83	10.20	11.40	12.49	13.96	16.12
055	652	501	502	503	504	●	29	1.60	7.93	9.71	11.22	12.54	13.74	15.36	17.73
06	652	521	522	523	524	●	29	1.72	8.65	10.60	12.24	13.68	14.99	16.75	19.35
065	652	531	532	533	534	●	29	1.75	9.37	11.48	13.26	14.82	16.23	18.15	20.96
07	652	541	542	543	544	●	29	1.80	10.09	12.36	14.28	15.96	17.48	19.55	22.57
075	652	551	552	553	554	●	29	1.90	10.81	13.25	15.29	17.10	18.73	20.94	24.18
08	652	571	572	573	574	●	29	2.05	11.54	14.13	16.31	18.24	19.98	22.34	25.80
087	652	581	582	583	584	●	29	2.06	12.54	15.36	17.74	19.83	21.72	24.29	28.04
09	652	591	592	593	594	●	29	2.10	12.98	15.89	18.35	20.52	22.48	25.13	29.02
10	652	601	602	603	604	●	29	2.30	14.41	17.65	20.38	22.79	24.97	27.91	32.23
11	652	621	622	623	624	●	29	2.40	15.86	19.42	22.42	25.07	27.46	30.70	35.45
125	652	641	642	643	644	●	29	2.50	18.02	22.07	25.48	28.49	31.21	34.89	40.29
131	652	651	652	653	654	●	29	2.55	18.89	23.13	26.71	29.86	32.71	36.57	42.23
139	652	661	662	663	664	●	29	2.65	20.04	24.54	28.34	31.68	34.70	38.80	44.80
15	652	671	672	673	674	●	29	2.70	21.62	26.48	30.58	34.19	37.45	41.87	48.35
175	652	701	702	703	704	●	29	3.00	25.23	30.90	35.68	39.89	43.70	48.86	56.41
20	652			723	724	●	29	3.05	28.83	35.31	40.78	45.59	49.94	55.84	64.47
25	652			763	764	●	29	3.50	36.04	44.14	50.97	56.99	62.43	69.80	80.60
30	652			793		●	29	3.90	43.25	52.97	61.16	68.38	74.91	83.75	96.70

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$



Assembly accessories can be found in Chapter 9 "Accessories".

Ordering Series + Flow rate code + Material no. + Code = Ordering no.
example: 652 + 361 + A3 + 29 = 652.361.A3.29

High pressure flat fan nozzles

Series 6FH with spray stabiliser

Features:

- Sharp, uniform flat fan spray
- Extremely narrow spray depth
- Nozzle with spray stabilizer
- Housing: Stainless steel 303,
Insert: Hardened stainless steel 420F,
spray stabiliser: Stainless steel 301

Applications:

- High pressure cleaning



Series 6FH




Figure 1




Figure 2

Code	Figure	G	Dimensions [mm]							Weight [g]	p _{max} ¹ [bar]
			L ₁	L ₂	Ø D	Ø D ₁	Ø D ₂	Hex	Flats		
CA	1	1/8 BSPT	22.00	6.50	13.00	–	–	14	10	13.00	approx. 700
BA	1	1/8 NPT	22.00	6.70	13.00	–	–	14	10	13.00	approx. 700
CC	1	1/4 BSPT	22.00	10.00	13.00	–	–	14	10	18.00	approx. 700
BC	1	1/4 NPT	22.00	10.20	13.00	–	–	14	10	18.00	approx. 700
Assembly with retaining nut 3/8 BSPP	2	–	16.00	14.00	–	14.80	12.65	–	10	13.00	approx. 300

¹ Applies only to operation at constant pressure.

US gal/min at 40 psi	Ordering no.						Equivalent bore diameter A [mm]	V̇ water [l/min]						
	Series	Flow rate code				Mat. no.								
		Spray angle				A3								
		20°	30°	45°	60°	Stainless steel 303/420F/301								
								p [bar]						
		20°	30°	45°	60°			40	60	80	100	120	150	200
02	6FH	361	362	363	364	●	1.00	2.88	3.53	4.08	4.56	5.00	5.58	6.45
021	6FH	371	372	373	374	●	1.02	3.03	3.71	4.28	4.79	5.25	5.87	6.77
025	6FH	381	382	383	384	●	1.10	3.60	4.42	5.10	5.70	6.24	6.98	8.06
028	6FH	391	392	393	394	●	1.16	4.04	4.94	5.71	6.38	6.99	7.81	9.02
03	6FH	401	402	403	404	●	1.18	4.32	5.29	6.11	6.83	7.48	8.37	9.66
034	6FH	411	412	413	414	●	1.30	4.90	6.00	6.93	7.75	8.49	9.49	10.96
038	6FH	441	442	443		●	1.33	5.48	6.72	7.75	8.67	9.50	10.62	12.26
04	6FH	451	452	453	454	●	1.35	5.77	7.06	8.16	9.12	9.99	11.17	12.90
043	6FH	461	462			●	1.38	6.20	7.59	8.77	9.80	10.74	12.00	13.86
045	6FH	471	472	473	474	●	1.40	6.49	7.95	9.18	10.26	11.24	12.57	14.51
05	6FH	481	482	483	484	●	1.55	7.21	8.83	10.20	11.40	12.49	13.96	16.12
055	6FH	501	502	503	504	●	1.60	7.93	9.71	11.22	12.54	13.74	15.36	17.73
06	6FH	521	522	523	524	●	1.72	8.65	10.60	12.24	13.68	14.99	16.75	19.35
065	6FH	531	532	533	534	●	1.75	9.37	11.48	13.26	14.82	16.23	18.15	20.96

US gal/min at 40 psi	Ordering no.						Equivalent bore diameter A [mm]	V̇ water [l/min]						
	Series	Flow rate code				Mat. no.								
		Spray angle				A3								
						Stainless steel 303/420F/301		p [bar]						
		20°	30°	45°	60°			40	60	80	100	120	150	200
07	6FH	541	542	543	544	●	1.80	10.09	12.36	14.28	15.96	17.48	19.55	22.57
075	6FH	551	552	553	554	●	1.90	10.81	13.25	15.29	17.10	18.73	20.94	24.18
08	6FH	571	572	573	574	●	2.05	11.54	14.13	16.31	18.24	19.98	22.34	25.80
087	6FH	581	582	583	584	●	2.06	12.54	15.36	17.74	19.83	21.72	24.29	28.04
09	6FH	591	592	593	594	●	2.10	12.98	15.89	18.35	20.52	22.48	25.13	29.02
10	6FH	601	602	603	604	●	2.30	14.41	17.65	20.38	22.79	24.97	27.91	32.23
11	6FH	621*	622*	623*	624*	●	2.40	15.86	19.42	22.42	25.07	27.46	30.70	35.45
125	6FH	641*	642*	643*	644*	●	2.50	18.02	22.07	25.48	28.49	31.21	34.89	40.29
131	6FH	651*	652*	653*	654*	●	2.55	18.89	23.13	26.71	29.86	32.71	36.57	42.23
139	6FH	661*	662*	663*	664*	●	2.65	20.04	24.54	28.34	31.68	34.70	38.80	44.80
15	6FH	671*	672*	673*	674*	●	2.70	21.62	26.48	30.58	34.19	37.45	41.87	48.35
175	6FH	701*	702*	703*	704*	●	3.00	25.23	30.9	35.68	39.89	43.70	48.86	56.41
20	6FH			723*	724*	●	3.05	28.83	35.31	40.78	45.59	49.94	55.84	64.47
25	6FH			763*	764*	●	3.50	36.04	44.14	50.97	56.99	62.43	69.80	80.60
30	6FH			793*		●	3.90	43.25	52.97	61.16	68.38	74.91	83.75	96.70

* Only available with code CC, BC or 29.

Code	Type of connection
CA	1/8 BSPT
BA	1/8 NPT
CC	1/4 BSPT
BC	1/4 NPT
29	Assembly with retaining nut 3/8 BSPP

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$




Assembly accessories can be found in Chapter 9
"Accessories".

Ordering Series + Flow rate code + Material no. + Code = Ordering no.
example: 6FH + 541 + A3 + CA = 6FH.541.A3.CA

Low pressure flat fan nozzles with ball joint

Series 676



Features:


- Swivelling nozzle
- Precise spray alignment according to requirements
- Assembly with retaining nut, threaded socket, threaded nipple, welded nipple

Applications:

- Cleaning
- Cooling
- Lubrication



Series 676



Dimensions [mm]			Weight [g] Brass	P _{max} [bar]
L	Ø D ₁	Ø D ₂		
25.0	22.0	11.0	45.0	30.0

Spray angle	Ordering no.			Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.				p [bar]						H = 250 [mm]	H = 500 [mm]
		16	30										
		Stainless steel 303	Brass										
20°	676.301	●	●	0.70	0.60	0.16*	0.23*	0.32	0.40	0.51	0.72	85	160
	676.361	●	●	1.00	0.80	0.32*	0.45*	0.63	0.77	1.00	1.41	85	160
	676.441	●	●	1.35	1.10	0.63*	0.89	1.25	1.53	1.98	2.80	85	160
	676.481	●	●	1.50	1.30	0.80*	1.13	1.60	1.96	2.53	3.58	85	160
30°	676.302	●	●	0.70	0.50	0.16*	0.23*	0.32	0.40	0.51	0.72	120	220
	676.362	●	●	1.00	0.80	0.32*	0.45*	0.63	0.77	1.00	1.41	120	220
	676.402	●	●	1.20	1.00	0.50*	0.71	1.00	1.22	1.58	2.23	120	230
	676.482	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	3.58	130	230
	676.562	●	●	2.00	1.50	1.25	1.77	2.50	3.06	3.95	5.59	130	240
	676.642	●	●	2.50	1.80	2.00	2.83	4.00	4.90	6.33	8.95	140	250
	676.722	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	14.09	140	260
	676.762	●	●	3.50	2.70	4.00	5.66	8.00	9.80	12.65	17.89	140	260
	676.802	●	●	4.00	3.10	5.00	7.07	10.00	12.25	15.81	22.36	140	260
45°	676.303	●	●	0.70	0.50	0.16*	0.23*	0.32	0.40	0.51	0.72	170	330
	676.363	●	●	1.00	0.70	0.32*	0.45*	0.63	0.77	1.00	1.41	190	350
	676.403	●	●	1.20	0.90	0.50*	0.71	1.00	1.22	1.58	2.23	200	370
	676.483	●	●	1.50	1.10	0.80*	1.13	1.60	1.96	2.53	3.58	200	390
	676.563	●	●	2.00	1.40	1.25	1.77	2.50	3.06	3.95	5.59	210	410
	676.643	●	●	2.50	1.80	2.00	2.83	4.00	4.90	6.33	8.95	220	410
	676.723	●	●	3.00	2.40	3.15	4.45	6.30	7.71	9.96	14.09	220	420
	676.763	●	●	3.50	2.70	4.00	5.66	8.00	9.80	12.65	17.89	220	420
	676.803	●	●	4.00	3.00	5.00	7.07	10.00	12.25	15.81	22.36	220	420
60°	676.304	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.72	260	480
	676.334	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	1.00	260	490
	676.364	●	●	1.00	0.60	0.32*	0.45*	0.63	0.77	1.00	1.41	260	500
	676.404	●	●	1.20	0.80	0.50*	0.71	1.00	1.22	1.58	2.23	260	510
	676.444	●	●	1.35	1.00	0.63*	0.89	1.25	1.53	1.98	2.80	260	510
	676.484	●	●	1.50	1.00	0.80*	1.13	1.60	1.96	2.53	3.58	260	520

Spray angle	Ordering no.			Equivalent bore diameter A [mm]	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Spray width B [mm] (at p = 5 bar)	
	Type	Mat. no.				p [bar]						H = 250 [mm]	H = 500 [mm]
		16	30										
		Stainless steel 303	Brass										
						0.5	1.0	2.0	3.0	5.0	10.0		
60°	676.514	●	●	1.65	1.10	0.95*	1.34	1.90	2.32	3.00	4.24	270	520
	676.564	●	●	2.00	1.30	1.25	1.77	2.50	3.06	3.95	5.59	270	530
	676.604	●	●	2.20	1.50	1.57	2.23	3.15	3.86	4.98	7.04	270	540
	676.644	●	●	2.50	1.60	2.00	2.83	4.00	4.90	6.33	8.95	270	540
	676.674	●	●	2.70	1.80	2.37	3.36	4.75	5.82	7.51	10.62	270	550
	676.724	●	●	3.00	2.10	3.15	4.45	6.30	7.71	9.96	14.09	280	560
	676.764	●	●	3.50	2.30	4.00	5.66	8.00	9.80	12.65	17.89	280	570
75°	676.145	●	●	0.20	0.12	–	0.04*	0.05	0.06	0.08	0.11	380	690
	676.165	●	●	0.20	0.08	–	0.05*	0.06	0.08	0.10	0.14	380	690
	676.185	●	●	0.20	0.15	–	0.06*	0.08	0.09	0.12	0.17	380	690
	676.215	●	●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.25	380	690
	676.245	●	●	0.50	0.30	–	0.12*	0.16	0.20	0.26	0.37	380	690
	676.275	●	●	0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.49	380	690
90°	676.216	●	●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.25	420	780
	676.276	●	●	0.60	0.30	0.11*	0.16*	0.22	0.27	0.35	0.49	430	790
	676.306	●	●	0.70	0.40	0.16*	0.23*	0.32	0.40	0.51	0.72	440	800
	676.336	●	●	0.90	0.50	0.22*	0.32*	0.45	0.55	0.71	1.00	440	820
	676.366	●	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.41	450	830
	676.406	●	●	1.20	0.70	0.50*	0.71	1.00	1.22	1.58	2.23	450	840
	676.446	●	●	1.35	0.80	0.63*	0.89	1.25	1.53	1.98	2.80	460	860
	676.486	●	●	1.50	0.80	0.80*	1.13	1.60	1.96	2.53	3.58	470	870
	676.516	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	4.24	480	880
	676.566	●	●	2.00	1.10	1.25	1.77	2.50	3.06	3.95	5.59	490	900
	676.606	●	●	2.20	1.20	1.57	2.23	3.15	3.86	4.98	7.04	500	910
	676.646	●	●	2.50	1.30	2.00	2.83	4.00	4.90	6.33	8.95	510	930
	676.676	●	●	2.70	1.40	2.37	3.36	4.75	5.82	7.51	10.62	510	950
	676.726	●	●	3.00	1.70	3.15	4.45	6.30	7.71	9.96	14.09	520	980
120°	676.187	●	●	0.35	0.20	–	0.06*	0.08	0.10	0.13	0.18	630	1,060
	676.217	●	●	0.40	0.20	–	0.08*	0.11	0.14	0.18	0.25	650	1,080
	676.247	●	●	0.50	0.20	–	0.12*	0.16	0.20	0.26	0.37	660	1,100
	676.277	●	●	0.60	0.30	–	0.16*	0.22	0.27	0.35	0.49	670	1,150
	676.307	●	●	0.70	0.30	0.16*	0.23*	0.32	0.40	0.51	0.72	710	1,240
	676.337	●	●	0.90	0.40	0.22*	0.32*	0.45	0.55	0.71	1.00	740	1,350
	676.367	●	●	1.00	0.50	0.32*	0.45*	0.63	0.77	1.00	1.41	800	1,430
	676.407	●	●	1.20	0.60	0.50*	0.71	1.00	1.22	1.58	2.23	830	1,480
	676.447	●	●	1.35	0.70	0.63*	0.89	1.25	1.53	1.98	2.80	840	1,520
	676.487	●	●	1.50	0.60	0.80*	1.13	1.60	1.96	2.53	3.58	850	1,540
	676.517	●	●	1.65	0.90	0.95*	1.34	1.90	2.32	3.00	4.24	850	1,560
	676.567	●	●	2.00	0.90	1.25	1.77	2.50	3.06	3.95	5.59	870	1,590
	676.607	●	●	2.20	1.10	1.57	2.23	3.15	3.86	4.98	7.04	870	1,620
	676.647	●	●	2.50	1.30	2.00	2.83	4.00	4.90	6.33	8.95	880	1,640
	676.677	●	●	2.70	1.40	2.37	3.36	4.75	5.82	7.51	10.62	890	1,660
	676.727	●	●	3.00	1.60	3.15	4.45	6.30	7.71	9.96	14.09	890	1,680
	676.767	●	●	3.50	1.70	4.00	5.66	8.00	9.80	12.65	17.89	900	1,700

* Differing spray pattern.

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Material no. = Ordering no.
 example: 676.514 + 16 = 676.514.16



Assembly accessories can be found in Chapter 9 "Accessories".

➤ Nozzle systems for surface treatment

Series 676/677 MEMOSPRAY



Features:

- Retention of the adjusted spray direction when changing nozzles
- Simple, quick nozzle assembly without the need for tools
- Many combination options
- Large range of flow rates, spray angles and materials



Applications:


- Degreasing
- Phosphating in surface treatment
- Industrial cleaning
- Container washers

Assembly example



a Flat fan nozzle

Incl. gasket 095.015.7A.05.65
(Material: Viton)




Designation	Spray angle	Ordering no.				Narrowest free cross section Ø [mm]	V̇ [l/min]					Weight [g]				
		Type	Mat. no.				p [bar]					PP/Stainless steel 303	PP/Stainless steel 316L	PP/Ceramic	Polypropylene (PP)	
			8F	8R	E8											53
			Housing: PP Insert: 303 SS	Housing: PP Insert: 316L SS	Housing: PP Insert: Ceramic		Polypropylene (PP)									
① a Flat fan nozzle	30°	676.642.xx.40	●	●			1.60	2.83	3.46	4.00	4.47	6.33	15.00	15.00	–	–
		676.722.xx.40	●	●			2.10	4.46	5.46	6.30	7.04	9.96	15.00	15.00	–	–
		676.762.xx.40	●	●			2.30	5.66	6.93	8.00	8.94	12.65	15.00	15.00	–	–
		676.802.xx.40	●	●			2.60	7.07	8.66	10.00	11.18	15.81	15.00	15.00	–	–
		676.842.xx.40	●	●			3.00	8.84	10.82	12.50	13.97	19.76	15.00	15.00	–	–
		676.882.xx.40	●	●			3.40	11.31	13.86	16.00	17.89	25.30	15.00	15.00	–	–
		676.922.xx.40	●	●			4.10	14.14	17.32	20.00	22.36	31.62	15.00	15.00	–	–
		676.962.xx.40	●	●			4.20	17.68	21.65	25.00	27.95	39.53	15.00	15.00	–	–
	677.002.xx.40	●				4.70	22.27	27.28	31.50	35.22	49.81	15.00	–	–	–	
	60°	676.644.xx.40	●	●			1.60	2.83	3.46	4.00	4.47	6.33	15.00	15.00	–	–
		676.724.xx.40	●	●			2.10	4.46	5.46	6.30	7.04	9.96	15.00	15.00	–	–
		676.764.xx.40	●	●			2.30	5.66	6.93	8.00	8.94	12.65	15.00	15.00	–	–
		676.804.xx.40	●	●			2.60	7.07	8.66	10.00	11.18	15.81	15.00	15.00	–	–
		676.844.xx.40	●	●			3.00	8.84	10.82	12.50	13.97	19.76	15.00	15.00	–	–
		676.884.xx.40	●	●	●	●	3.40	11.31	13.86	16.00	17.89	25.30	15.00	15.00	10.00	8.00
		676.924.xx.40	●	●	●	●	4.10	14.14	17.32	20.00	22.36	31.62	15.00	15.00	10.00	8.00
		676.964.xx.40	●	●	●	●	4.20	17.68	21.65	25.00	27.95	39.53	15.00	15.00	10.00	8.00
		677.004.xx.40	●	●	●	●	4.70	22.27	27.28	31.50	35.22	49.81	15.00	15.00	10.00	8.00
		677.044.xx.40	●	●			5.50	28.28	34.64	40.00	44.72	63.25	15.00	15.00	–	–
		677.084.xx.40	●	●			6.20	35.36	43.30	50.00	55.90	79.06	15.00	15.00	–	–

Designation	Spray angle	Ordering no.					Narrowest free cross section Ø [mm]	V̇ [l/min]					Weight [g]			
		Type	Mat. no.					p [bar]					PP/Stainless steel 303	PP/Stainless steel 316L	PP/Ceramic	Polypropylene (PP)
			8F	8R	E8	53										
			Housing: PP Insert: 303 SS	Housing: PP Insert: 316L SS	Housing: PP Insert: Ceramic	Polypropylene (PP)		1.0	1.5	2.0	2.5	5.0				
① a Flat fan nozzle	90°	676.646.xx.40	●	●			1.60	2.83	3.46	4.00	4.47	6.33	15.00	15.00	–	–
		676.726.xx.40	●	●			2.10	4.46	5.46	6.30	7.04	9.96	15.00	15.00	–	–
		676.766.xx.40	●	●			2.30	5.66	6.93	8.00	8.94	12.65	15.00	15.00	–	–
		676.806.xx.40	●	●			2.60	7.07	8.66	10.00	11.18	15.81	15.00	15.00	–	–
		676.846.xx.40	●	●			3.00	8.84	10.82	12.50	13.97	19.76	15.00	15.00	–	–
		676.886.xx.40	●	●			3.40	11.31	13.86	16.00	17.89	25.30	15.00	15.00	–	–
		676.926.xx.40	●	●			4.10	14.14	17.32	20.00	22.36	31.62	15.00	15.00	–	–
		676.966.xx.40	●	●			4.20	17.68	21.65	25.00	27.95	39.53	15.00	15.00	–	–
	120°	676.647.xx.40	●	●			1.60	2.83	3.46	4.00	4.47	6.33	15.00	15.00	–	–
		676.727.xx.40	●	●			2.10	4.46	5.46	6.30	7.04	9.96	15.00	15.00	–	–
		676.767.xx.40	●	●			2.30	5.66	6.93	8.00	8.94	12.65	15.00	15.00	–	–
		676.807.xx.40	●	●			2.60	7.07	8.66	10.00	11.18	15.81	15.00	15.00	–	–
		676.847.xx.40	●	●			3.00	8.84	10.82	12.50	13.97	19.76	15.00	15.00	–	–
		676.887.xx.40	●	●			3.40	11.31	13.86	16.00	17.89	25.30	15.00	15.00	–	–
676.927.xx.40	●	●			4.10	14.14	17.32	20.00	22.36	31.62	15.00	15.00	–	–		
Blind nozzle	–	067.630.8F.40.01	●				–	–	–	–	–	15.00	–	–	–	

① b Tongue-type nozzle

Incl. gasket 095.015.7A.05.65
(Material: Viton)



Designation	Spray angle	η	Ordering no.			Narrowest free cross section Ø [mm]	V̇ [l/min]					Weight [g]	
			Type	Mat. no.			p [bar]					PP/Stainless steel 316L	PVDF
				8R	5E								
				Housing: PP Insert:316L SS	PVDF								
	1.0	1.5	2.0	2.5	5.0								
① b Tongue-type nozzle	45°	35°	676.803.xx.41	●		3.40	7.07	8.66	10.00	11.18	15.81	25.00	–
	60°	35°	676.874.xx.41	●		4.20	10.61	12.99	15.00	16.77	23.72	25.00	–
	60°	35°	676.924.xx.41	●		4.70	14.14	17.32	20.00	22.36	31.62	25.00	–
	70°	40°	677.005.xx.41	●	●	6.00	22.27	27.28	31.50	35.22	49.81	25.00	11.00





Ordering Type + Material no. = Ordering no.
example: 676.646.xx.40 + 8F = 676.646.8F.40

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$




② a Retaining nut

092.080.xx.00.02




② b Retaining nut

067.600.xx.40



③ Ball bayonet base


067.630.xx.40



④ a Ball seat

067.631.xx.40.x2


For eyelet clamp
067.631.xx.40.00



④ b Ball seat

067.631.xx.50.x2

For eyelet clamp
067.631.xx.50.00




Designation	Ordering no.		Mat. no.	Ø B _R ¹ [mm]	Recommended bore diameter [mm]	Pipe Ø [mm]	Weight [g]
	Type	53	6M				
		Polypropylene (PP)	PP reinforced				Polypropylene (PP)
② a Retaining nut	092.080.xx.00.02	●		–	–	–	18.0
② b Retaining nut	067.600.xx.40	●		–	–	–	18.0
③ Ball bayonet base	067.630.xx.40	●		–	–	–	12.0
④ a Ball seat for eyelet clamp no. 067.631.xx.40.00	067.631.xx.40.22		●	13.8	14.0–14.3	1 1/4" (40.0–43.0)	9.0
	067.631.xx.40.02		●	16.0	16.5–17.0	1 1/4" (40.0–43.0)	11.0
	067.631.xx.40.12		●	19.8	20.3–20.8	1 1/4" (40.0–43.0)	13.0
④ b Ball seat for eyelet clamp no. 067.631.xx.50.00	067.631.xx.50.22		●	13.8	14.0–14.3	1 1/2" (46.0–49.0)	9.0
	067.631.xx.50.02		●	16.0	16.5–17.0	1 1/2" (46.0–49.0)	11.0
	067.631.xx.50.12		●	19.8	20.3–20.8	1 1/2" (46.0–49.0)	13.0

¹ Ø B_R = spigot diameter.


⑤ a Eyelet clamp

067.631.xx.x0.00




⑤ b Eyelet clamp

090.0x3.xx.4x.10



⑤ c Single clamp

092.08x.xx.00



Designation	Ordering no.		Dimensions [mm]						Ø B _R ¹ [mm]	Recommend- ed bore diameter [mm]	Pipe Ø (Ø D) [mm]	Weight [g]
	Type	Mat. no.	B ₁	B ₂	H ₁	H ₂	Ø D ₁	Ø D ₂				Polypropylene (PP)
		53										
⑤ a Eyelet clamp	067.631.xx.40.00	●	–	–	47.7	22.0	43.0	–	–	–	1 1/4" (40.0–43.0)	31.0
	067.631.xx.50.00	●	–	–	51.5	22.0	50.6	–	–	–	1 1/2" (46.0–49.0)	33.0
⑤ b Eyelet clamp	090.023.xx.44.10	●	30.0	32.0	44.5	23.0	–	34.0	13.8	14.0–14.3	1" (32.0–34.5)	48.0
	090.023.xx.43.10	●	30.0	32.0	44.5	23.0	–	34.0	16.0	16.5–17.0	1" (32.0–34.5)	48.0
	090.033.xx.44.10	●	33.0	36.0	48.0	27.0	–	34.0	13.8	14.0–14.3	1 1/4" (40.0–43.0)	50.0
	090.033.xx.43.10	●	33.0	36.0	48.0	27.0	–	34.0	16.0	16.5–17.0	1 1/4" (40.0–43.0)	50.0
	090.033.xx.40.10	●	33.0	36.0	48.0	27.0	–	34.0	20.0	20.5–21.0	1 1/4" (40.0–43.0)	50.0
	090.043.xx.44.10	●	36.0	35.0	52.0	30.0	–	34.0	13.8	14.0–14.3	1 1/2" (46.0–49.0)	52.0
	090.043.xx.43.10	●	36.0	35.0	52.0	30.0	–	34.0	16.0	16.5–17.0	1 1/2" (46.0–49.0)	52.0
	090.043.xx.40.10	●	36.0	35.0	52.0	30.0	–	34.0	20.0	20.5–21.0	1 1/2" (46.0–49.0)	52.0
⑤ c Single clamp	092.080.xx.00	●	–	–	–	–	–	–	16.3*	16.5–17.0	1" (32.0–34.5)	36.0
	092.081.xx.00	●	–	–	–	–	–	–	16.3*	16.5–17.0	1 1/4" (40.0–43.0)	38.0
	092.082.xx.00	●	–	–	–	–	–	–	16.3*	16.5–17.0	1 1/2" (46.0–49.0)	40.0
	092.083.xx.00	●	–	–	–	–	–	–	16.3*	16.5–17.0	2" (58.0–62.0)	42.0


* Other spigot diameters available on request.

¹ Ø B_R = spigot diameter.

Ordering Type + Material no. = Ordering no.
example: 067.631.xx.40.00 + 53 = 067.631.53.40.00

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{P_2}{P_1}}$

Nozzle systems for surface treatment Series 676 Easy-Clip



Features:


- Simple, quick nozzle assembly without the need for tools
- All-round 30° swivelling
- Easy adjustment and cleaning

Applications:


- Degreasing
- Phosphating in surface treatment
- Industrial cleaning
- Container washers

Materials:

- Clamp: Stainless steel 301
- Gasket: EPDM
- Cylinder pin, screw, screw unit: Stainless steel 316L
- Body, retaining nut: Polypropylene, glass fibre reinforced
- Ball nozzle, ball joint: Polypropylene



Assembly example




Sets – series 676 Easy-Clip

Designation	Spray angle	Ordering no.	Nozzle Color	V̇ [l/min]				
		Type		p [bar]				
				0.5	1.0	1.5	2.0	2.5
Set 1 consisting of: Ball nozzle Single clamp for 1 1/4" pipe Retaining nut	60°	676.724.53.31	Grey	3.15	4.45	5.45	6.30	7.04
		676.764.53.31	Brown	4.00	5.66	6.93	8.00	8.94
		676.804.53.31	Purple	5.00	7.07	8.66	10.00	11.18
		676.844.53.31	Yellow	6.25	8.84	10.83	12.50	13.98
		676.884.53.31	Red	8.00	11.31	13.85	16.00	17.89
		676.904.53.31	Blue	9.10	12.87	15.76	18.20	20.35
		676.924.53.31	Green	10.00	14.14	17.32	20.00	22.36

Designation	Ordering no.	Ball Color	BSPP	Matches series
	Type			
Set 2 consisting of: Ball joint Single clamp for 1 1/4" pipe Retaining nut	092.081.53.AD	Beige	1/4	422, 460, 490, 544, 612, 632, 686
	092.081.53.AF	Beige	3/8	422, 460, 490, 632, 686, 688
	092.081.53.AH	Beige	1/2	422, 460, 490, 632, 686

Individual parts – series 676 Easy-Clip


① Ball nozzle



Dimensions [mm]				
L ₁	L ₂	Ø D ₁	Ø D ₂	Flats
41.5	31.5	34.0	15.0	16.0


Designation	Spray angle	Ordering no.	Nozzle Color	V̇ [l/min]				
		Type		p [bar]				
				0.5	1.0	1.5	2.0	2.5
① Ball nozzle	60°	676.724.53.30.01	Grey	3.15	4.45	5.45	6.30	7.04
		676.764.53.30.01	Brown	4.00	5.66	6.93	8.00	8.94
		676.804.53.30.01	Purple	5.00	7.07	8.66	10.00	11.18
		676.844.53.30.01	Yellow	6.25	8.84	10.83	12.50	13.98
		676.884.53.30.01	Red	8.00	11.31	13.85	16.00	17.89
		676.904.53.30.01	Blue	9.10	12.87	15.67	18.20	20.35
		676.924.53.30.01	Green	10.00	14.14	17.32	20.00	22.36
Blind nozzle	–	092.080.53.00.01	Grey	–	–	–	–	–

③ Ball joint



Designation	Ordering no.	Ball Color	BSPP	L [mm]	Matches series
	Type				
② Ball joint	092.080.53.AD.01	Beige	1/4	32.4	422, 460, 490, 544, 612, 632, 686
	092.080.53.AF.01	Beige	3/8	31.4	422, 460, 490, 632, 686, 688
	092.080.53.AH.01	Beige	1/2	33.0	422, 460, 490, 632, 686

③ Retaining nut



Designation	Ordering no.
	Type
③ Retaining nut	092.080.53.00.02




Nozzle systems for surface treatment

Series 676 Easy-Clip


④ a Single clamp

092.08x.53.00




④ b Double clamp

092.09x.53.00



④ c Eyelet clamp

090.0x3.53.43.10



Designation	Ordering no.	Dimensions [mm]					$\varnothing B_R^1$ [mm]	Recommend- ed bore diameter [mm]	Pipe $\varnothing$ ($\varnothing D$) [mm]	Weight [g]
	Type	B_1	B_2	H_1	H_2	$\varnothing D_1$				Polypropylene (PP)
④ a Single clamp	092.080.53.00	–	–	–	–	–	16.3*	16.5–17.0	1" (32.0–34.5)	36.0
	092.081.53.00	–	–	–	–	–	16.3*	16.5–17.0	1 1/4" (40.0–43.0)	38.0
	092.082.53.00	–	–	–	–	–	16.3*	16.5–17.0	1 1/2" (46.0–49.0)	40.0
	092.083.53.00	–	–	–	–	–	16.3*	16.5–17.0	2" (58.0–62.0)	42.0
④ b Double clamp	092.090.53.00	–	–	–	–	–	16.3*	16.5–17.0	1" (32.0–34.5)	46.0
	092.091.53.00	–	–	–	–	–	16.3*	16.5–17.0	1 1/4" (40.0–43.0)	48.0
	092.092.53.00	–	–	–	–	–	16.3*	16.5–17.0	1 1/2" (46.0–49.0)	50.0
	092.093.53.00	–	–	–	–	–	16.3*	16.5–17.0	2" (58.0–62.0)	52.0
④ c Eyelet clamp	090.023.53.43.10	30.0	32.0	44.5	23.0	34.0	16.3**	16.5–17.0	1" (32.0–34.5)	48.0
	090.033.53.43.10	33.0	36.0	48.0	27.0	34.0	16.3**	16.5–17.0	1 1/4" (40.0–43.0)	50.0
	090.043.53.43.10	36.0	35.0	52.0	30.0	34.0	16.3**	16.5–17.0	1 1/2" (46.0–49.0)	52.0

* Other spigot diameters (13.8/19.0 mm) available on request.


** Other spigot diameters (13.8/20.0 mm) available on request.

¹ $\varnothing B_R$ = spigot diameter.





SOLID STREAM NOZZLES



SOLID STREAM NOZZLES

OVERVIEW OF TYPES

Lechler solid stream nozzles are characterized by a stable and powerful jet stream, with low pressure and high pressure variants available. When concentrated spray power is required, e.g. in cleaning processes, the precision of Lechler solid stream nozzles enhances the productivity and performance for every installation.

Low pressure and high pressure solid stream nozzles



- Concentrated solid jet stream, minimal atomization
- High impact
- Suitable for cleaning and washing processes
- Injection
- Targeted cooling
- Pasteurization

International nozzle code

High pressure solid stream nozzle designations are governed by international standards. The two digits specify the flow rate in US gallons per minute at 40 psi. Our high pressure solid stream nozzles (series 546/548/550) are specified with this international nozzle code.

02

Flow rate in US gal/min at 40 psi

Conversion: Value · 3.22 = flow rate in l/min at 2 bar

example: 0.2 gal/min at 40 psi = 0.644 l/min at 2 bar

SOLID STREAM NOZZLES OVERVIEW OF SERIES

		Solid stream nozzles			
					
Series		544	546	548	550
Information on page		156	157	158	159
Pressure range	Low pressure	•			
	High pressure		•	•	•
 Flow rate	Low ≤ 20 l/min	• (at p = 5 bar)	• (at p = 80 bar)	• (at p = 80 bar)	• (at p = 80 bar)
	High > 20 l/min		• (at p = 80 bar)	• (at p = 80 bar)	• (at p = 80 bar)
 Nozzle material	Stainless steel	•	•	•	•
	Brass	•			
 Nozzle connection		1/8 BSPT 1/4 BSPT	1/4 BSPT 1/4 NPT	Assembly with retaining nut 3/8 BSPP	1/8 BSPT 1/8 NPT

Low pressure solid stream nozzles

Series 544

Properties:


- Concentrated solid stream jet
- High impact

Applications:

- Cleaning and washing processes
- Injection
- Targeted cooling
- Pasteurization



Series 544



Code	G	Dimensions [mm]					Weight [g] (Brass)
		L ₁	L ₂	Ø D	Hex	Flats	
CA	1/8 BSPT	22.0	6.5	13.0	14	10	14.0
CC	1/4 BSPT	22.0	10.0	13.0	14	10	16.0

Ordering no.					Bore diameter B [mm]	V̇ water [l/min]								
Type	Mat. no.		Code											
	16	30	1/8 BSPT	1/4 BSPT		p [bar]								
	Stainless steel 303	Brass												
						0.5	1.0	2.0	3.0	5.0	10.0	15.0	20.0	30.0
544.110	●	●	CA	CC	0.23	0.02	0.03	0.04	0.05	0.06	0.08	0.10	0.12	0.15
544.160	●		CA	CC	0.33	0.03	0.04	0.06	0.07	0.09	0.13	0.16	0.18	0.22
544.200	●	●	CA	CC	0.39	0.05	0.07	0.10	0.12	0.16	0.23	0.28	0.32	0.39
544.240	●		CA	CC	0.50	0.08	0.11	0.16	0.19	0.25	0.35	0.43	0.50	0.61
544.280	●		CA	CC	0.63	0.13	0.18	0.25	0.31	0.40	0.57	0.69	0.80	0.98
544.320	●	●	CA	CC	0.80	0.20	0.28	0.40	0.49	0.63	0.89	1.09	1.26	1.54
544.360	●	●	CA	CC	1.05	0.32	0.45	0.63	0.77	1.00	1.41	1.73	2.00	2.45
544.400	●	●	CA	CC	1.30	0.50	0.71	1.00	1.22	1.58	2.23	2.74	3.16	3.87
544.480	●	●	CA	CC	1.33	0.80	1.13	1.60	1.96	2.53	3.58	4.38	5.06	6.20
544.560	●	●	CA	CC	1.65	1.25	1.77	2.50	3.06	3.95	5.59	6.84	7.90	9.68
544.640	●	●	CA	CC	2.09	2.00	2.83	4.00	4.90	6.32	8.94	10.95	12.64	15.48
544.720	●	●	CA	CC	2.66	3.15	4.45	6.30	7.71	9.96	14.09	17.25	19.92	24.40
544.800	●	●	CA	CC	3.30	5.00	7.07	10.00	12.25	15.81	22.36	27.38	31.62	38.73

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Material no. + Code = Ordering no.
example: 544.110 + 16 + CA = 544.110.16.CA



Assembly accessories can be found in Chapter 9 "Accessories".

High pressure solid stream nozzles

Series 546

Properties:


- Concentrated solid stream jet
- High impact
- Housing 303 SS, insert:
Hardened stainless steel 420F

Applications:

- Cleaning and washing processes



Series 546



G	Dimensions [mm]					Weight [g]	p _{max} ¹ [bar]
	L ₁	L ₂	Ø D	Hex	Flats		
1/4 BSPT	22.0	10.0	13.0	14	10	18.0	approx. 700
1/4 NPT	22.0	10.0	13.0	14	10	18.0	approx. 700

¹ Applies only to operation at constant pressure.

US gal/min at 40 psi	Ordering no.			Bore diameter B [mm]	V̇ water [l/min]							
	Type	Code			p [bar]							
		1/4 BSPT	1/4 NPT		40	60	80	100	120	150	200	300
01	546.300.A3	00	07	0.60	1.44	1.77	2.04	2.28	2.50	2.79	3.22	3.95
02	546.360.A3	00	07	0.84	2.88	3.53	4.08	4.56	5.00	5.58	6.45	7.90
025	546.380.A3	00	07	0.94	3.60	4.42	5.10	5.70	6.24	6.98	8.06	9.87
027	546.390.A3	00	07	0.99	3.89	4.76	5.50	6.15	6.74	7.53	8.70	10.65
03	546.400.A3	00	07	1.03	4.33	5.30	6.12	6.84	7.49	8.38	9.67	11.85
034	546.410.A3	00	07	1.07	4.90	6.00	6.93	7.75	8.49	9.49	10.96	13.42
035	546.420.A3	00	07	1.11	5.05	6.18	7.14	7.98	8.74	9.77	11.29	13.82
038	546.440.A3	00	07	1.15	5.48	6.71	7.75	8.66	9.49	10.61	12.25	15.00
04	546.450.A3	00	07	1.19	5.77	7.06	8.16	9.12	9.99	11.17	12.90	15.80
045	546.470.A3	00	07	1.26	6.49	7.95	9.18	10.26	11.24	12.57	14.51	17.77
05	546.480.A3	00	07	1.33	7.21	8.83	10.20	11.40	12.49	13.96	16.12	19.75
055	546.500.A3	00	07	1.39	7.93	9.71	11.22	12.54	13.74	15.36	17.73	21.72
06	546.520.A3	00	07	1.46	8.65	10.60	12.24	13.68	14.99	16.75	19.35	23.69
065	546.530.A3	00	07	1.51	9.37	11.48	13.26	14.82	16.23	18.15	20.96	25.67
070	546.540.A3	00	07	1.58	10.09	12.36	14.28	15.96	17.48	19.55	22.57	27.64
074	546.550.A3	00	07	1.62	10.67	13.07	15.09	16.87	18.48	20.66	23.86	29.22
08	546.570.A3	00	07	1.69	11.54	14.13	16.31	18.24	19.98	22.34	25.80	31.59
087	546.580.A3	00	07	1.76	12.54	15.36	17.74	19.83	21.72	24.29	28.04	34.35
089	546.590.A3	00	07	1.78	12.83	15.72	18.15	20.29	22.23	24.85	28.69	35.14
10	546.600.A3	00	07	1.88	14.41	17.65	20.38	22.79	24.97	27.91	32.23	39.47
11	546.620.A3	00	07	1.97	15.86	19.42	22.42	25.07	27.46	30.70	35.45	43.42
124	546.640.A3	00	07	2.09	17.87	21.89	25.28	28.26	30.96	34.61	39.97	48.95
131	546.650.A3	00	07	2.15	18.89	23.13	26.71	29.86	32.71	36.57	42.23	51.72
139	546.660.A3	00	07	2.22	20.04	24.54	28.34	31.68	34.70	38.80	44.80	54.87
15	546.670.A3	00	07	2.30	21.62	26.48	30.58	34.19	37.45	41.87	48.35	59.22
165	546.690.A3	00	07	2.41	23.79	29.13	33.64	37.61	41.20	46.06	53.19	65.14
174	546.700.A3	00	07	2.48	25.08	30.72	35.47	39.66	43.45	48.57	56.09	68.69
183	546.710.A3	00	07	2.55	26.38	32.31	37.31	41.71	45.69	51.08	58.99	72.24
20	546.720.A3	00	07	2.66	28.83	35.31	40.78	45.59	49.94	55.84	64.47	78.96
218	546.740.A3	00	07	2.77	31.43	38.49	44.44	49.69	54.43	60.86	70.27	86.07
25	546.760.A3	00	07	2.96	36.04	44.14	50.97	56.99	62.43	69.80	80.60	98.71
294	546.790.A3	00	07	3.22	42.38	51.91	59.94	67.01	73.41	82.07	94.77	116.06
310	546.800.A3	00	07	3.30	44.69	54.73	63.20	70.66	77.40	86.54	99.93	122.39

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$

Ordering Type + Code = Ordering no.
example: 546.300.A3 + 00 = 546.300.A3.00




Assembly accessories can be found in Chapter 9 "Accessories".

High pressure solid stream nozzles

Series 548

Properties:

- Concentrated solid stream jet
- High impact
- Housing 303 SS, insert:
Hardened stainless steel 420F
- Assembly with retaining nut



Applications:

- Cleaning and washing processes

Series 548

Code	Dimensions [mm]					Weight [g]	p _{max} ¹ [bar]
	L ₁	L ₂	Ø D ₁	Ø D ₂	Flats		
Assembly with retaining nut 3/8 BSPP	16.00	14.00	14.80	12.65	10	13.00	approx. 300

¹ Applies only to operation at constant pressure.

US gal/min at 40 psi	Ordering no. Type	Bore diameter B [mm]	V̇ water [l/min]							
			p [bar]							
			40	60	80	100	120	150	200	300
01	548.300.A3.29	0.60	1.44	1.77	2.04	2.28	2.50	2.79	3.22	3.95
02	548.360.A3.29	0.84	2.88	3.53	4.08	4.56	5.00	5.58	6.45	7.90
025	548.380.A3.29	0.94	3.60	4.42	5.10	5.70	6.24	6.98	8.06	9.87
027	548.390.A3.29	0.99	3.89	4.76	5.50	6.15	6.74	7.53	8.70	10.65
03	548.400.A3.29	1.03	4.33	5.30	6.12	6.84	7.49	8.38	9.67	11.85
034	548.410.A3.29	1.07	4.90	6.00	6.93	7.75	8.49	9.49	10.96	13.42
035	548.420.A3.29	1.11	5.05	6.18	7.14	7.98	8.74	9.77	11.29	13.82
038	548.440.A3.29	1.15	5.48	6.71	7.75	8.66	9.49	10.61	12.25	15.00
04	548.450.A3.29	1.19	5.77	7.06	8.16	9.12	9.99	11.17	12.90	15.80
045	548.470.A3.29	1.26	6.49	7.95	9.18	10.26	11.24	12.57	14.51	17.77
05	548.480.A3.29	1.33	7.21	8.83	10.20	11.40	12.49	13.96	16.12	19.75
055	548.500.A3.29	1.39	7.93	9.71	11.22	12.54	13.74	15.36	17.73	21.72
06	548.520.A3.29	1.46	8.65	10.60	12.24	13.68	14.99	16.75	19.35	23.69
065	548.530.A3.29	1.51	9.37	11.48	13.26	14.82	16.23	18.15	20.96	25.67
070	548.540.A3.29	1.58	10.09	12.36	14.28	15.96	17.48	19.55	22.57	27.64
074	548.550.A3.29	1.62	10.67	13.07	15.09	16.87	18.48	20.66	23.86	29.22
08	548.570.A3.29	1.69	11.54	14.13	16.31	18.24	19.98	22.34	25.80	31.59
087	548.580.A3.29	1.76	12.54	15.36	17.74	19.83	21.72	24.29	28.04	34.35
089	548.590.A3.29	1.78	12.83	15.72	18.15	20.29	22.23	24.85	28.69	35.14
10	548.600.A3.29	1.88	14.41	17.65	20.38	22.79	24.97	27.91	32.23	39.47
11	548.620.A3.29	1.97	15.86	19.42	22.42	25.07	27.46	30.70	35.45	43.42
124	548.640.A3.29	2.09	17.87	21.89	25.28	28.26	30.96	34.61	39.97	48.95
131	548.650.A3.29	2.15	18.89	23.13	26.71	29.86	32.71	36.57	42.23	51.72
139	548.660.A3.29	2.22	20.04	24.54	28.34	31.68	34.70	38.80	44.80	54.87
15	548.670.A3.29	2.30	21.62	26.48	30.58	34.19	37.45	41.87	48.35	59.22
165	548.690.A3.29	2.41	23.79	29.13	33.64	37.61	41.20	46.06	53.19	65.14
174	548.700.A3.29	2.48	25.08	30.72	35.47	39.66	43.45	48.57	56.09	68.69
183	548.710.A3.29	2.55	26.38	32.31	37.31	41.71	45.69	51.08	58.99	72.24
20	548.720.A3.29	2.66	28.83	35.31	40.78	45.59	49.94	55.84	64.47	78.96
218	548.740.A3.29	2.77	31.43	38.49	44.44	49.69	54.43	60.86	70.27	86.07
25	548.760.A3.29	2.96	36.04	44.14	50.97	56.99	62.43	69.80	80.60	98.71
294	548.790.A3.29	3.22	42.38	51.91	59.94	67.01	73.41	82.07	94.77	116.06
310	548.800.A3.29	3.30	44.69	54.73	63.20	70.66	77.40	86.54	99.93	122.39

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$



Assembly accessories can be found in Chapter 9 "Accessories".

High pressure solid stream nozzles

Series 550

Properties:


- Concentrated solid stream jet
- High impact
- Housing 303, insert:
Hardened stainless steel 1.4034 S

Applications:

- Cleaning and washing processes



Series 550



G	Dimensions [mm]					Weight [g]	p _{max} ¹ [bar]
	L ₁	L ₂	Ø D	Hex	Flats		
1/8 BSPT	22.0	6.5	13.0	14	10	13.0	approx. 700
1/8 NPT	22.0	6.5	13.0	14	10	13.0	approx. 700

¹ Applies only to operation at constant pressure.

US gal/min at 40 psi	Ordering no.			Bore diameter B [mm]	V̇ water [l/min]							
	Type	Code			p [bar]							
		1/8 BSPT	1/8 NPT									
					40	60	80	100	120	150	200	300
01	550.300.A3	00	07	0.60	1.44	1.77	2.04	2.28	2.50	2.79	3.22	3.95
02	550.360.A3	00	07	0.84	2.88	3.53	4.08	4.56	5.00	5.58	6.45	7.90
025	550.380.A3	00	07	0.94	3.60	4.42	5.10	5.70	6.24	6.98	8.06	9.87
027	550.390.A3	00	07	0.99	3.89	4.76	5.50	6.15	6.74	7.53	8.70	10.65
03	550.400.A3	00	07	1.03	4.33	5.30	6.12	6.84	7.49	8.38	9.67	11.85
034	550.410.A3	00	07	1.07	4.90	6.00	6.93	7.75	8.49	9.49	10.96	13.42
035	550.420.A3	00	07	1.11	5.05	6.18	7.14	7.98	8.74	9.77	11.29	13.82
038	550.440.A3	00	07	1.15	5.48	6.71	7.75	8.66	9.49	10.61	12.25	15.00
04	550.450.A3	00	07	1.19	5.77	7.06	8.16	9.12	9.99	11.17	12.90	15.80
045	550.470.A3	00	07	1.26	6.49	7.95	9.18	10.26	11.24	12.57	14.51	17.77
05	550.480.A3	00	07	1.33	7.21	8.83	10.20	11.40	12.49	13.96	16.12	19.75
055	550.500.A3	00	07	1.39	7.93	9.71	11.22	12.54	13.74	15.36	17.73	21.72
06	550.520.A3	00	07	1.46	8.65	10.60	12.24	13.68	14.99	16.75	19.35	23.69
065	550.530.A3	00	07	1.51	9.37	11.48	13.26	14.82	16.23	18.15	20.96	25.67
070	550.540.A3	00	07	1.58	10.09	12.36	14.28	15.96	17.48	19.55	22.57	27.64
074	550.550.A3	00	07	1.62	10.67	13.07	15.09	16.87	18.48	20.66	23.86	29.22
08	550.570.A3	00	07	1.69	11.54	14.13	16.31	18.24	19.98	22.34	25.80	31.59
087	550.580.A3	00	07	1.76	12.54	15.36	17.74	19.83	21.72	24.29	28.04	34.35
089	550.590.A3	00	07	1.78	12.83	15.72	18.15	20.29	22.23	24.85	28.69	35.14
10	550.600.A3	00	07	1.88	14.41	17.65	20.38	22.79	24.97	27.91	32.23	39.47
11	550.620.A3	00	07	1.97	15.86	19.42	22.42	25.07	27.46	30.70	35.45	43.42
124	550.640.A3	00	07	2.09	17.87	21.89	25.28	28.26	30.96	34.61	39.97	48.95
131	550.650.A3	00	07	2.15	18.89	23.13	26.71	29.86	32.71	36.57	42.23	51.72
139	550.660.A3	00	07	2.22	20.04	24.54	28.34	31.68	34.70	38.80	44.80	54.87
15	550.670.A3	00	07	2.30	21.62	26.48	30.58	34.19	37.45	41.87	48.35	59.22
165	550.690.A3	00	07	2.41	23.79	29.13	33.64	37.61	41.20	46.06	53.19	65.14
174	550.700.A3	00	07	2.48	25.08	30.72	35.47	39.66	43.45	48.57	56.09	68.69
183	550.710.A3	00	07	2.55	26.38	32.31	37.31	41.71	45.69	51.08	58.99	72.24
20	550.720.A3	00	07	2.66	28.83	35.31	40.78	45.59	49.94	55.84	64.47	78.96
218	550.740.A3	00	07	2.77	31.43	38.49	44.44	49.69	54.43	60.86	70.27	86.07
25	550.760.A3	00	07	2.96	36.04	44.14	50.97	56.99	62.43	69.80	80.60	98.71
294	550.790.A3	00	07	3.22	42.38	51.91	59.94	67.01	73.41	82.07	94.77	116.06
310	550.800.A3	00	07	3.30	44.69	54.73	63.20	70.66	77.40	86.54	99.93	122.39

Conversion formula for this series: $\dot{V}_2 = \dot{V}_1 \cdot \sqrt{\frac{p_2}{p_1}}$


Ordering Type + Code = Ordering no.
example: 550.300.A3 + 00 = 550.300.A3.00



Assembly accessories can be found in Chapter 9 "Accessories".




AIR NOZZLES




AIR NOZZLES

GENERAL INFORMATION



Compressed air is an indispensable tool in many areas for drying, cooling, cleaning, conveying, blowing off and much more. Lechler air nozzles make all this possible – with the highest level of precision at extraordinarily favourable conditions.



The three advantages of Lechler air nozzles for you



Cost efficiency

Lechler nozzles make it possible to reduce compressed air consumption by up to 45% compared to open pipes. In view of increasing energy costs and the growing range of compressed air applications, it is not surprising that there are extremely high potential savings in this area. An advantage that will have direct positive impact on your business.

Employee safety

The unique design of our nozzles allows noise levels to be verifiably reduced by up to 25% compared to conventional solutions – thus also reducing noise-related stress for your employees. Noise levels have been confirmed to reduce concentration resulting in increased levels of stress. The use of low-noise nozzles has a positive effect on production quality.

Service offering


A perfect solution must be optimally tailored to the local requirements. We will, therefore, gladly advise you in person about the use of air nozzles and introduce you to new possibilities. Contact us and let us come up with the best possible solution together for improved quality and optimized process reliability.

Good to know

Detailed information can be found in our brochure "Air nozzles" as well as at www.lechler.com/de-en/airnozzles.

MODERN NOZZLE TECHNOLOGY FOR MORE EFFICIENCY AND LESS NOISE


Air consumption



Lower measurable air consumption

The generation of compressed air requires energy. Since the energy costs account for an increasingly large share of the overall costs of manufacturing a product, considerable savings can be achieved through the right nozzle selection. Nozzles from Lechler are designed so that they need less compressed air than conventional nozzles, without the need to compromise on performance. As a result, our products help to make production processes more efficient and more environmentally friendly.


Blowing force



Higher measurable blowing force

In practice, the available blowing force is critical. Our measurements show that Lechler multi-channel nozzles achieve a high blowing force even at large distances. Thanks to this benefit, our nozzle technology opens up new applications for use with compressed air. Compared with conventional solutions, the competitive advantage that can be realized with Lechler nozzles is evident again.


Noise level



Less measurable noise

Conventional air nozzles simply blow air through a hole. The resulting turbulence generates unpleasant, loud hissing noises. Such noises can trigger stress reactions among employees even at relatively low sound pressure levels, thereby impairing both concentration and performance. Regulations such as those on determination of occupational noise exposure (DIN EN ISO 9612) are designed to protect employees. Testing of our compressed air nozzles in accordance with this standard is one reason why the German Employers' Liability Insurance Associations recommend Lechler air nozzles as a valuable aid to combat noise.

Jet pattern measurement




Larger measurable jet pattern

For the jet pattern measurement, the nozzles are clamped in a fixture specially designed for this purpose. An anemometer (windmeter) moves through the air jet at right angles to the jet direction at previously defined distances and at different pressures. The wind speeds measured here define the jet (as specified on the product pages). An air speed of 2.5 m/s was defined as the limit value on the basis of experience and flow calculations (CFD).



WHAT YOU SHOULD KEEP IN MIND WHEN PLANNING



- The difference between standard volume flow and operating volume flow
- Difference between blowers and compressors
- Jet pattern of air nozzles
- Innovative nozzle design
- Materials and connections
- Gases
- Operating medium steam
- Cost savings and noise reduction in comparison to an open pipe

The difference between standard volume flow and operating volume flow

The term „standard volume flow“ refers to a unit quantity of a gas based on a standard reference. These standard conditions are used in nozzle technology, process engineering and other areas to compare gases on the basis of quantity information. If reference is made to standard volume flows in relation to nozzle technology, Lechler always bases its values on DIN EN ISO 1343. **DIN EN ISO 1343** is a standard that is commonly used in pneumatics. This standard specifies a unit of measure, the so-called standard volume, to describe a quantity of gas on the basis of reference conditions (pressure and temperature).

The standard conditions for pressure and temperature are as follows:

Absolute pressure: $p_n = 101325 \text{ Pa} // [1.01325 \text{ bar(a)}]$

Temperatur: $T_n = 273.15 \text{ K} // [0^\circ \text{C}]$

In contrast, the term „operating volume flow“ describes the volume of the corresponding gas under the actual operating/application conditions. Since these normally differ from the standard conditions, pressure and temperature must always be clearly defined. If an operating volume is delivered in a certain time, this results in the operating volume flow.

In order to avoid mistakes or misunderstandings, mass flows are used in practice and for calculation since the mass of a substance is independent of pressure and temperature.

Figure 1 shows the relationship between standard and operating volume flows at different pressures with constant temperature. Since the influence of temperature on the volume of a substance is comparatively small, this diagram can be used for approximate determination of the respective volume.

The following formula can be used for exact calculation:

$$\dot{V}_{\text{Operating}} = \frac{T}{p} \cdot 0.00371 \times \dot{V}_{\text{Standard}}$$

Diagram Operating and standard flow rate at 298 K (+25°C)




Figure 1: Relationship between standard volume flow and operating volume flow

Jet pattern of air nozzles

Air nozzles are used for concentrated, targeted delivery of air or other gases. The nozzles used are normally flat jet or round jet nozzles. Air is also discharged at a specific angle. However, this is not comparable with that of liquids (which, however, is not comparable to that of liquids) which leads to expansion of the jet. The spray angle is normally approx. 20°.




Figure 2: Jet expansion of an air nozzle

Materials and connections

Lechler nozzles meet many different requirements of international organizations – including food grade compatibility and occupational safety.



The FDA, the U.S. Food & Drug Administration, is a federal agency which oversees those two industries. Materials used in making Lechler products are compliant with the requirements of FDA regulation 21 CFR for use in food applications.




The regulation (EC) No. 1935/ 2004 of the European Parliament regulates general safety requirements to all food and beverage contact materials. Within this regulation, it is additionally stipulated that plastics must comply with (EU) 10/2011.



The Occupational Safety and Health Administration (OSHA) is a US federal authority for prevention of accidents at work.

The respective logo on the product pages indicates which requirements are met.





Gases

The output of gases (e.g. air) is fundamentally different to the output of liquids. Gases are compressible fluids, whereas liquids are considered as incompressible fluids.

Gases can be supplied with practically all nozzles that can also be used for atomizing liquids. However, due to the compressibility and lower density of gases, gas jets cannot be formed in the same way as with liquids. Gases tend to generate a significantly increased noise level under certain conditions (pressure and nozzle design).

The development of multi-channel nozzles with specially shaped nozzle orifices makes it possible to considerably reduce the turbulence in the nozzle that causes noise. In addition, this nozzle design increases blowing force while at the same time reducing air consumption.

The speeds of gases can be very high under certain conditions. If a specific pressure difference is applied to a nozzle, speeds of approx. 320 m/s can often occur in the smallest cross section. This speed can even increase shortly after the gas leaves the nozzle. The illustration below shows the speed characteristic in a flow simulation.




Figure 3: Compressibility behavior: Left water / right air





Figure 4: Representation of the speed curve of outflowing air





Cost savings and noise reduction in comparison to an open pipe

The use of compressed air has long been standard in companies. Whether for blowing off debris, sorting out defective parts or simply for drying products after washing. Companies frequently use simple pipes for this purpose. These are often purchased inexpensively and then individually shaped and aligned for the specific application.


However, this seemingly inexpensive solution is usually very uneconomical in the long run. Thanks to their individual design, the air consumption and noise level of Lechler air nozzles are significantly lower than for comparable open pipes with equivalent bore diameter. The use of Lechler air nozzles is not only a cost savings but it also protects the health and safety of your employees.

AIR NOZZLES

OVERVIEW OF SERIES

						
Series		6WB	6WB (OSHA)	600.484.56	600.130.1Y	600.283.42
Information on page		172	174	177	178	179
Spray pattern		Multi-channel flat fan	Multi-channel flat fan	Multi-channel flat fan	Multi-channel flat fan	Multi-channel flat fan
						
 Nozzle material	Plastic	•	•	•		
	Stainless steel				•	
	Galvanized steel					
	Brass					
	Zinc					
	Aluminium					•
 Air consumption	At 2 bar	16.5 m³/h	16.5 m³/h	8 m³/h	12 m³/h	18 m³/h
 Nozzle connection		1/4 BSPP 1/4 NPT	1/4 BSPP 1/4 NPT	1/4 BSPP 1/4 NPT M12 x 1.25 Quick-release coupling size 5	1/4 BSPP 1/4 NPT	1/4 BSPP 1/4 NPT
 Maximum pressure		6 bar	6 bar	6 bar	10 bar	10 bar
 Maximum temperature		50 °C	50 °C	50 °C	550 °C	200 °C
 Noise level	At 2 bar	72 dB(A)	72 dB(A)	65 dB(A)	70 dB(A)	76 dB(A)
 Blowing force	At 2 bar	2,4 N	2,4 N	0.8 N	2 N	2.4 N


Flat fan nozzles

					
600.606.42	600.493.1Y	600.562.1Y	600.382.35	600.383.35	600.386.01
179	180	181	182	183	184
Multi-channel flat fan	Multi-channel flat fan	Multi-channel flat fan	Mini multi-channel flat fan	Intensive multi-channel flat fan	Compact multi-channel flat fan
					
	•	•			•
•			•	•	
12 m³/h	30 m³/h	9 m³/h	15 m³/h	31 m³/h	27 m³/h
1/4 BSPP 1/4 NPT	1/4 BSPP 1/4 NPT	1/8 BSPP 1/8 NPT	3/8 BSPP	3/8 BSPP	3/8 BSPP
10 bar	30 bar	30 bar	10 bar	10 bar	10 bar
200 °C	550 °C	550 °C	50 °C	50 °C	50 °C
68.5 dB(A)	78 dB(A)	71 dB(A)	77.5 dB(A)	86 dB(A)	83.5 dB(A)
1.4 N	4.2 N	1.2 N	2.3 N	4.3 N	3.7 N






		Flat fan nozzles			
					
Series		600.385.35	679	686	600.326.5K
Information on page		185	186	188	189
Spray pattern		Maxi multi-channel flat fan	Flat fan slotted nozzle	Flat fan tongue-type nozzle	Multi-channel round jet
					
 Nozzle material	Plastic				•
	Stainless steel		•	•	
	Galvanized steel				
	Brass	•	•	•	
	Zinc				
	Aluminium				
 Air consumption	at 2 bar	100 m³/h	3–31 m³/h	2–16 m³/h	15 m³/h
 Nozzle connection		3/4 BSPP	Assembly with retaining nut	1/8 BSPT	1/8 BSPP 1/4 BSPP 1/8 NPT 1/4 NPT M12 x 1.25
 Maximum pressure		10 bar	10 bar	30 bar	6 bar
 Maximum temperature		50 °C	550 °C (stainless steel) 240 °C (brass)	550 °C (stainless steel) 240 °C (brass)	50 °C
 Noise level	at 2 bar	91.5 dB(A)	67–92 dB(A)	73–84 dB(A)	74 dB(A)
 Blowing force	at 2 bar	11.5 N			2.2 N

Round jet nozzles					Solid stream nozzle/Multiple solid stream nozzle	
						
600.725.5K	600.326.3W	600.388.30	600.625.1Y	600.387.35	544	540/541
189	190	191	192	193	194	195
Multi-channel round jet	Multi-channel round jet	Multi-channel round jet	Multi-channel round jet	Maxi multi-channel round jet	Solid stream	Multiple solid stream
						
•		•	•		•	•
		•		•		
	•					
32 m³/h	15 m³/h	8 m³/h	2–4 m³/h	105 m³/h	1–16 m³/h	34–251 m³/h
1/4 BSPP 1/4 NPT	1/4 BSPP 1/4 NPT M12 x 1.25	1/8 BSPP 1/8 NPT M12 x 1.25	M4 x 0.5 M5 x 0.5	G 1/2 ISO 228	1/8 BSPT 1/4 BSPT	1/2 BSPP
6 bar	10 bar	10 bar	5 bar	6 bar	30 bar	10 bar
50 °C	90 °C	50 °C	550 °C	50 °C	550 °C	550 °C
96 dB(A)	79 dB(A)	77 dB(A)	63–70 dB(A)	92 dB(A)	65–90 dB(A)	
3.9 N	2.1 N	1.1 N	0.4–0.7 N	17.0 N	0.25–2.9 N	

Multi-channel flat fan nozzles for air “Whisperblast”, plastic version Series 6WB.800.56/6WB.800.S2



Features:

- Laminar, powerful air stream
- Low noise level
(also at higher levels of pressure)

Applications:

- Blowing off and out
- Cleaning
- Drying
- Cooling
- Transporting




Figure 1
With mounting bracket

Series 6WB.800.56/6WB.800.S2




Figure 2
Without mounting bracket

¹ Meets OSHA specifications
in terms of noise level.

Cost savings and noise reduction



Cost saving




21 %



Noise
reduction

24 %

Technical data



**Maximum
pressure**
6 bar



**Maximum
temperature**
50 °C

Code	Figure	G	Dimensions [mm]								Weight [g]
			A	C	D	L ₁	L ₂	L ₃	L ₄	Ø B	
AC	1	1/4 BSPP	25.0	14.2	47.0	90.0	61.0	10.5	39.0	5.0	23.0
BC	1	1/4 NPT	25.0	14.2	47.0	90.0	61.0	10.5	39.0	5.0	23.0
20	2	1/4 BSPP	–	14.2	47.0	90.0	61.0	10.5	39.0	5.0	23.0
21	2	1/4 NPT	–	14.2	47.0	90.0	61.0	10.5	39.0	5.0	23.0






Figure 3



Pressure		1 bar	3 bar	5 bar
6WB.800	Length Z [mm]	600	900	900
	X [mm]	140	240	260
	Y [mm]	130	185	220


Ordering no.					Figure
Type	Mat.-no.		Code		
	56	S2	1/4 BSPP	1/4 NPT	
	POM	Natural PP			
6WB.800	●	●	AC	BC	1
6WB.800	●	●	20	21	2
6WB.800 (with cover strip)	●		02		3
6WB.800 (Düse mit Rohr)	●		01		3

Ordering Type + Material no. + Code = Ordering no.
example: 6WB.800 + 56 + AC = 6WB.800.56.AC



Assembly accessories can be found in Chapter 9 "Accessories".

Multi-channel flat fan nozzles for air “Whisperblast”, plastic version Series 6WB.800.56 OSHA



Features:

- Laminar, powerful air stream
- Low noise level
(also at higher levels of pressure)

Applications:

- Blowing off and out
- Cleaning
- Drying
- Cooling
- Transporting



OSHA®

FDA




Figure 1
With mounting bracket

Series 6WB.800.56 OSHA



OSHA®

FDA




Figure 2
Without mounting bracket

Cost savings and noise reduction



Cost saving




26 %



Noise reduction

21 %

Technical data





Maximum pressure
6 bar



Maximum temperature
50 °C

Code	Figure	G	Dimensions [mm]								Weight [g]
			A	C	D	L ₁	L ₂	L ₃	L ₄	Ø B	
10	1	1/4 BSPP	25.0	14.2	47.0	92.0	63.0	10.5	41.0	5.0	23.0
11	1	1/4 NPT	25.0	14.2	47.0	92.0	63.0	10.5	41.0	5.0	23.0
30	2	1/4 BSPP	–	14.2	47.0	92.0	63.0	10.5	41.0	5.0	23.0
31	2	1/4 NPT	–	14.2	47.0	92.0	63.0	10.5	41.0	5.0	23.0



Pressure		1 bar	3 bar	5 bar
6WB.800 (OSHA)	Length Z [mm]	625	900	900
	X [mm]	125	200	230
	Y [mm]	125	200	230

Ordering no.				Figure
Type	Mat.-no.	Code		
	56	1/4 BSPP	1/4 NPT	
	POM			
6WB.800	●	10	11	1
6WB.800	●	30	31	2

Ordering Type + Material no. + Code = Ordering no.
 example: 6WB.800 + 56 + 10 = 6WB.800.56.10



Assembly accessories can be found in Chapter 9 "Accessories".



Multi-channel flat fan nozzles for air “Whisperblast”, plastic version Series 600.484.56

Features:


- Compact, powerful air stream
- Low noise level
(also at higher levels of pressure)
- Narrow design

Applications:

- Blowing off and out
- Cleaning
- Drying
- Cooling
- Transporting



Series 600.484.56



¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




22 %



Noise reduction

22 %

Technical data




Maximum pressure
6 bar



Maximum temperature
50 °C

Code	G	Dimensions [mm]								Weight [g]
		A	C	D	L ₁	L ₂	L ₃	L ₄	Ø B	
AC	1/4 BSPP	25.0	14.2	25.0	90.0	61.0	13.5	9.0	5.0	16.0
BC	1/4 NPT	25.0	14.2	25.0	90.0	61.0	13.5	9.0	5.0	16.0
HG	M12 x 1.25	25.0	14.2	25.0	90.0	61.0	13.5	9.0	5.0	16.0
00	Quick-release coupling size 5	25.0	14.2	25.0	90.0	61.0	13.5	–	5.0	16.0



Jet pattern of series 6WB.484.56

Pressure		1 bar	3 bar	5 bar
600.484	Length Z [mm]	350	600	850
	X [mm]	110	170	220
	Y [mm]	80	120	170

Ordering no.					
Type	Mat.-no.	Code			
	56				
	POM	1/4 BSPP	1/4 NPT	M12 x 1.25	Quick-release coupling size 5
600.484	●	AC	BC	HG	00

Ordering Type + Material no. + Code = Ordering no.
example: 600.484 + 56 + AC = 600.484.56.AC



Assembly accessories can be found in Chapter 9
“Accessories”.




Multi-channel flat fan nozzles for air “Whisperblast”, stainless steel version Series 600.130.1Y

Features:

- Laminar, powerful air stream
- Low noise level
(also at higher levels of pressure)
- For the highest demands

Applications:

- Blowing off and out
- Cleaning
- Drying
- Cooling
- Transporting



Series 600.130.1Y

¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




24 %



Noise reduction

22 %

Technical data




Maximum pressure
10 bar



Maximum temperature
550 °C

Code	G	Dimensions [mm]							Weight [g]
		A	C	D	L ₁	L ₂	L ₃	Ø B	
AC	1/4 BSPP	22.0	13.0	42.0	81.0	53.0	10.5	4.0	100.0
BC	1/4 NPT	22.0	13.0	42.0	81.0	53.0	10.5	4.0	100.0



Pressure		1 bar	3 bar	5 bar
600.130	Length Z [mm]	300	425	600
	X [mm]	100	140	170
	Y [mm]	56	80	110

Ordering no.			
Type	Mat.-no.	Code	
	1Y		
	Stainless steel 316L	1/4 BSPP	1/4 NPT
600.130	●	AC	BC

Ordering Type + Material no. + Code = Ordering no.
example: 600.130 + 1Y + AC = 600.130.1Y.AC



Assembly accessories can be found in Chapter 9
“Accessories”.


Multi-channel flat fan nozzles for air “Whisperblast”, metal version Series 600.283.42/600.606.42

Features:

- Laminar, powerful air stream
- Low noise level
(also at higher levels of pressure)
- For the highest demands

Applications:

- Blowing off and out
- Cleaning
- Drying
- Cooling
- Transporting



Series 600.283.42/600.606.42


¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction

Series 600.283/
Series 600.606






Cost saving



Noise reduction



Technical data




Maximum pressure
10 bar



Maximum temperature
200 °C

— 600.283.42
— 600.606.42

Code	G	Dimensions [mm]							Weight [g]
		A	B	C	D	L ₁	L ₂	L ₃	
AC	1/4 BSPP	41.0	5.1	17.0	51.0	86.5	55.0	10.5	60.0
BC	1/4 NPT	41.0	5.1	17.0	51.0	86.5	55.0	10.2	60.0



Pressure		1 bar	3 bar	5 bar
600.283	Length Z [mm]	675	900	900
	X [mm]	160	300	460
	Y [mm]	215	215	215
600.606	Length Z [mm]	900	900	900
	X [mm]	200	425	510
	Y [mm]	230	230	230

Ordering no.			
Type	Mat.-no.	Code	
	42 Aluminium 3.2582	1/4 BSPP	1/4 NPT
600.283	•	AC	BC
600.606	•	AC	

Ordering Type + Material no. + Code = Ordering no.
example: 600.283 + 42 + AC = 600.283.42.AC



Assembly accessories can be found in Chapter 9
“Accessories”.


Multi-channel flat fan nozzles for air “Whisperblast”, stainless steel version Series 600.493.1Y

Features:

- Extremely wide, powerful air stream
- For the highest thermal requirements
- Protecting tips prevent air penetrating your skin

Applications:

- Blowing off and out
- Cleaning
- Drying



Series 600.493.1Y

¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




34 %



Noise reduction

21 %

Technical data




Maximum pressure
30 bar



Maximum temperature
550 °C

Code	G	Dimensions [mm]							Weight [g]
		A	C	D	L ₁	L ₂	L ₃	Ø B	
AC	1/4 BSPP	30.0	16.5	70.0	79.7	53.7	12.0	4.2	130.0
BC	1/4 NPT	30.0	16.5	70.0	79.7	53.7	12.0	4.2	130.0



Pressure		1 bar	3 bar	5 bar
600.493	Length Z [mm]	900	900	900
	X [mm]	210	240	270
	Y [mm]	210	210	280

Ordering no.			
Type	Mat.-no.	Code	
	1Y		
	Stainless steel 316L	1/4 BSPP	1/4 NPT
600.493	●	AC	BC

Ordering Type + Material no. + Code = Ordering no.
example: 600.493 + 1Y + AC = 600.493.1Y.AC



Assembly accessories can be found in Chapter 9
“Accessories”.

Multi-channel flat fan nozzles for air “Whisperblast”, stainless steel version Series 600.562.1Y

Features:

- Compact, powerful air stream
- Angled design for applications with restricted installation conditions
- Resistant to higher pressures and temperatures
- Protecting tips prevent air penetrating your skin


Applications:

- Blowing off and out
- Cleaning
- Drying



Series 600.562.1Y

¹ Meets OSHA specification in terms of noise level.



Cost savings and noise reduction



Cost saving




8 %



Noise reduction

14 %

Technical data




Maximum pressure
30 bar



Maximum temperature
550 °C

Code	G	Dimensions [mm]				Weight [g]
		D ₁	D ₂	L ₁	L ₂	
10	1/8 BSPP	25.0	14.7	19.5	8.0	17.0
20	1/8 NPT	25.0	14.7	19.5	6.7	17.0



Pressure		1 bar	3 bar	5 bar
600.562	Length Z [mm]	750	900	900
	X [mm]	170	210	240
	Y [mm]	150	180	210

Ordering no.			
Type	Mat.-no.	Code	
	1Y		
	Stainless steel 316L	1/8 BSPP	1/8 NPT
600.562	●	10	20

Ordering Type + Material no. + Code = Ordering no.
example: 600.562 + 1Y + 10 = 600.562.1Y.10



Assembly accessories can be found in Chapter 9 “Accessories”.

Mini-multi-channel flat fan nozzles for air Series 600.382.35

Features:


- Narrow, powerful air jet
- Smaller nozzle for precise alignment
- Accurate and economical operation possible thanks to the narrow orifice

Applications:

- Blowing off and out
- Cleaning
- Drying



OSHA¹



Series 600.382.35

¹ Meets OSHA specifications in terms of noise level.

Cost savings and noise reduction



Cost saving




15%



Noise reduction

12%

Technical data




Maximum pressure
10 bar



Maximum temperature
50 °C

Code	G	Dimensions [mm]					Weight [g]
		C	D	L ₁	L ₂	Hex	
AE	3/8 BSPP	4.5	21.5	100.0	10.0	17	48.0



Jet pattern of series 600.382.35

Pressure		1 bar	3 bar	5 bar
600.382	Length Z [mm]	475	825	900
	X [mm]	110	170	200
	Y [mm]	85	140	180

Ordering no.		
Type	Mat.-no.	Code
	35	
	Brass nickel-plated/PVC	3/8 BSPP
600.382	●	AE

Ordering Type + Material no. + Code = Ordering no.
example: 600.382 + 35 + AE 600.382.35.AE



Assembly accessories can be found in Chapter 9 "Accessories".

Intensive-multi-channel flat fan nozzles for air


Series 600.383.35

Features:

- Concentrated, powerful air jet
- Constant jet depth thanks to flattened design
- Precise work under changing conditions

Applications:

- Blowing off and out
- Cleaning
- Drying



Series 600.383.35

¹ Meets OSHA specifications in terms of noise level.

Cost savings and noise reduction



Cost saving




8%



Noise reduction

10%

Technical data




Maximum pressure
10 bar



Maximum temperature
50 °C

Code	G	Dimensions [mm]				Hex	Weight [g]
		C	D	L ₁	L ₂		
AE	3/8 BSPP	6.0	21.0	100.0	10.0	17	60.0



Jet pattern of series 600.383.35

Pressure		1 bar	3 bar	5 bar
600.383	length Z [mm]	900	900	900
	X [mm]	200	425	510
	Y [mm]	230	230	230

Ordering no.		
Type	Mat.-no.	Code
	35	
	Brass nickel-plated/PVC	3/8 BSPP
600.383	●	AE


Ordering Type + Material no. + Code = Ordering no.
example: 600.383 + 35 + AE 600.383.35.AE



Assembly accessories can be found in Chapter 9 "Accessories".

Compact-multi-channel flat fan nozzles for air

Series 600.386.01





Features:

- Concentrated, powerful air jet
- Compact design suitable for use in hard-to-reach areas
- Precise work in very small spaces

Applications:

- Blowing off and out
- Cleaning
- Drying



Series 600.386.01

¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




45%



Noise reduction

15%

Technical data




Maximum pressure
10 bar



Maximum temperature
50 °C

Code	G	Dimensions [mm]				Weight [g]
		C	D	L ₁	L ₂	
AE	3/8 BSPP	8.6	16.5	50.0	10.0	58.0



Pressure		1 bar	3 bar	5 bar
600.386	Length Z [mm]	825	900	900
	X [mm]	160	300	460
	Y [mm]	216	216	216

Ordering no.		
Type	Mat.-no.	Code
	01	3/8 BSPP
	Galvanized steel//PVC	
600.386	●	AE

Ordering Type + Material no. + Code = Ordering no.
example: 600.386 + 01 + AE 600.386.01.AE



Assembly accessories can be found in Chapter 9 "Accessories".

Maxi-multi-channel flat fan nozzles for air Series 600.385.35

Features:


- Very powerful air jet
- Large volume of air in a concentrated jet due to large nozzle cross-section
- Effective over long distances Low noise level

Applications:

- Blowing off and out
- Cleaning
- Drying



OSHA¹



Series 600.385.35

Innengewinde (15 mm)

Cost savings and noise reduction



Cost saving




28 %



Noise reduction

15 %

Technical data




Maximum pressure
10 bar



Maximum temperature
50 °C

Code	G	Dimensions [mm]				Weight [g]
		C	D	L ₁	Hex	
AL	3/4 BSPP	9.0	43.0	120.0	32	200.0



Pressure		1 bar	3 bar	5 bar
600.383	Length Z [mm]	775	775	775
	X [mm]	205	255	270
	Y [mm]	200	245	270


Ordering no.		
Type	Mat.-no.	Code
	35	3/4 BSPP
	Brass nickel-plated/PVC	
600.385	●	AL

Ordering Type + Material no. + Code = Ordering no.
example: 600.385 + 35 + AL 600.385.35.AL



Assembly accessories can be found in Chapter 9 "Accessories".

Flat fan nozzles for air or saturated steam Series 679



Features:

- Wide, powerful air stream
- Assembly with retaining nut
- Easy nozzle changing
- Simple jet alignment


Applications:

- Blowing off liquids
- Cooling
- Heating
- Drying



OSHA¹


FDA²



Series 679

¹ Meets OSHA specification in terms of noise level.

² Only applies to the stainless variant.




Jet pattern of series 679



Maximum pressure
10 bar



Maximum temperature
550 °C (Stainless steel)
240 °C (Brass)




Pressure		1 bar	3 bar	5 bar
679.037	Length Z [mm]	50	100	150
	X [mm]	110	260	380
	Y [mm]	25	35	45
679.117	Length Z [mm]	50	125	150
	X [mm]	100	250	310
	Y [mm]	25	30	35
679.255	Length Z [mm]	375	500	500
	X [mm]	90	190	280
	Y [mm]	90	90	90

Pressure		1 bar	3 bar	5 bar
679.415	Length Z [mm]	675	900	900
	X [mm]	160	300	460
	Y [mm]	215	215	215
679.495	Length Z [mm]	900	900	900
	X [mm]	200	425	510
	Y [mm]	230	230	230

Code	Dimensions [mm]					Weight [g] (Brass)
	L ₁	L ₂	Ø D ₁	Ø D ₂	Hex	
Assembly with retaining nut 3/8 BSPP	13.0	2.0	14.8	12.0	10	8.0

Strahl- winkel	Ordering no.			Equivalent bore diameter B [mm]	V̇ _n Air [m³/h]				Ṁ Saturated steam [kg/h]			
	Type	Mat.-no.			p [bar]				p [bar]			
		17	30									
		Stainless steel 316L	Brass 2.0401									
					0.5	2.0	5.0	10.0	0.5	2.0	5.0	10.0
Circa 70°–90°	679.037		●	1.2	1.5	3.0	6.0	11.0	1.2	2.3	4.6	8.3
	679.085	●	●	1.3	2.0	4.0	8.0	14.7	1.6	3.1	6.1	11.1
	679.117	●	●	1.5	2.1	4.2	8.4	15.4	1.7	3.3	6.5	11.7
	679.165	●	●	1.8	2.6	5.1	10.3	18.8	2.0	4.1	8.0	14.3
	679.255	●	●	2.1	3.6	7.3	14.5	26.6	2.8	5.7	11.2	20.2
	679.365	●	●	2.8	6.3	12.7	25.4	46.5	5.0	10.0	19.6	35.3
	679.415	●	●	3.6	10.2	20.3	40.7	74.6	8.0	16.0	31.4	56.7
	679.495	●	●	4.3	15.6	31.1	62.2	114.0	12.4	24.8	48.5	87.6

Assembly example




Ordering Type + Material no. = Ordering no.
 example: 679.037 + 30 = 679.037.30



Assembly accessories can be found in Chapter 9
 "Accessories".

Flat fan tongue-type nozzles for air or saturated steam

Series 686



Features:

- Wide, powerful air stream
- Compact design
- Large spray width, also for short blowing distances
- Brass and stainless steel versions available for high ambient temperatures



Applications:

- Blowing off liquids
- Cooling
- Heating
- Drying



OSHA¹

FDA²



Series 686

¹ Meets OSHA specifications in terms of noise level.


² Only applies to the stainless variant.



Maximum pressure
30 bar



Maximum temperature
550 °C (Stainless steel)
240 °C (Brass)



Jet pattern of series 686

G	Dimensions [mm]			Weight [g] (Brass)
	L ₁	L ₂	Hex	
1/8 BSPT	23.0	6.5	11	13.0

Pressure		1 bar	3 bar	5 bar
686.408	Length Z [mm]	40	80	125
	X [mm]	35	50	60
	Y [mm]	15	40	50
686.528	Length Z [mm]	60	100	150
	X [mm]	75	140	210
	Y [mm]	20	40	50
686.608	Length Z [mm]	90	175	250
	X [mm]	145	230	350
	Y [mm]	25	45	55
686.688	Length Z [mm]	150	400	525
	X [mm]	230	560	740
	Y [mm]	40	80	100
686.728	Length Z [mm]	180	230	375
	X [mm]	170	360	530
	Y [mm]	50	50	70

Strahl- winkel	η	Ordering no.				Bore diameter B [mm]	V̇ _n Air [m³/h]				Ṁ Saturated steam [kg/h]			
		Type	Mat.-no.		Code									
			16	30										
			Stainless steel 316L	Brass 2.0401			1/8 BSPT	1.0	2.0	5.0	10.0	0.5	2.0	5.0
Circa 27°–47°	75°	686.408	●	●	CA	1.00	1.07	1.60	3.20	5.86	0.88	1.31	2.57	4.64
	75°	686.488	●	●	CA	1.30	1.76	2.64	5.29	9.69	1.46	2.17	4.25	7.67
Circa 70°	75°	686.528	●	●	CA	1.50	2.2	3.31	6.61	12.13	1.83	2.71	5.31	9.59
	75°	686.568	●	●	CA	1.70	2.73	4.09	8.19	15.01	2.27	3.36	6.57	11.87
	75°	686.608	●	●	CA	1.90	3.35	5.02	10.04	18.40	2.78	4.11	8.06	14.55
	75°	686.688	●	●	CA	2.40	5.45	8.18	16.36	30.00	4.53	6.71	13.14	23.72
	75°	686.728	●	●	CA	2.70	6.88	10.33	20.65	37.86	5.71	8.46	16.58	29.94
	75°	686.808	●	●	CA	3.40	10.89	16.33	32.66	59.87	9.04	13.28	26.22	47.35

Ordering Type + Material no. + Code = Ordering no.
example: 686.408 + 16 + CA = 686.408.16.CA



Assembly accessories can be found in Chapter 9
"Accessories".

Multi-channel round jet nozzles for air, plastic version


Series 600.326.5K/600.725.5K

Features:

- Powerful, circular air stream
- Low noise level
- Reduced air consumption

Applications:

- Targeted blowing off and blowing out (e.g. in connection with a compressed air gun)



Series 600.326.5K/600.725.5K

¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




9%



Noise reduction

17%

Technical data




Maximum pressure
6 bar



Maximum temperature
50 °C

— 600.326.5K
— 600.725.5K

Code	G	Dimensions [mm]					Weight [g]
		L ₁	L ₂	L ₃	Ø D ₁	Ø D ₂	
AA	1/8 BSPP	54.0	9.5	6.2	19.0	23.0	7.0
AC	1/4 BSPP	55.0	10.2	8.0	19.0	23.0	7.0
BA	1/8 NPT	54.0	9.5	6.7	19.0	23.0	7.0
BC	1/4 NPT	55.0	10.2	9.7	19.0	23.0	7.0
HG	M12 x 1.25	55.0	10.2	8.0	19.0	23.0	7.0



Pressure		1 bar	3 bar	5 bar
600.386	Length Z [mm]	700	900	900
	X [mm]	180	220	260
	Y [mm]	180	220	260

Ordering no.						
Type	Mat.-no.	Code				
	ABS	1/8 BSPP	1/4 BSPP	1/8 NPT	1/4 NPT	M12 x 1.25
600.326.5K	●	AA	AC	BA	BC	HG
600.725.5K	●		AC		BC	

Ordering Type + Material no. + Code = Ordering no.
example: 686.408 + 16 + CA = 686.408.16.CA



Assembly accessories can be found in Chapter 9 "Accessories".

Multi-channel round jet nozzles for air, zinc version


Series 600.326.3W

Features:

- Powerful, circular air stream
- Low noise level
- Reduced air consumption
- Zinc version: Use at high pressure and temperature levels

Applications:

- Targeted blowing off and blowing out (e.g. in connection with a compressed air gun)



Series 600.326.3W

¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




8 %



Noise reduction

17 %

Technical data




Maximum pressure
10 bar



Maximum temperature
90 °C

Code	G	Dimensions [mm]						Weight [g]
		L ₁	L ₂	L ₃	Ø D ₁	Ø D ₂	Hex	
AC	1/4 BSPP	47.0	12.0	9.0	19.0	23.0	19	50.0
BC	1/4 NPT	47.0	12.0	10.2	19.0	23.0	19	50.0
HG	M12 x 1.25	47.0	12.0	9.5	19.0	23.0	19	50.0



Jet pattern of series 600.326.3W

Pressure		1 bar	3 bar	5 bar
600.326	Length Z [mm]	700	900	900
	X [mm]	180	220	260
	Y [mm]	180	220	260

Ordering no.				
Type	Mat.-no.	Code		
	Zinc	1/4 BSPP	1/4 NPT	M12 x 1.25
600.326.3W	●	AC	BC	HG

Ordering Type + Code = Ordering no.
example: 600.326.3W + AC = 600.326.3W.AC



Assembly accessories can be found in Chapter 9 "Accessories".


Mini multi-channel round jet nozzles for air Series 600.388.30

Features:

- Powerful, punctiform air stream for large distances
- Compact design
- Low noise level
- Reduced air consumption
- Particularly suitable for difficult-to-reach locations

Applications:

- Targeted blowing off and blowing out (e.g. in connection with a compressed air gun)



Series 600.388.30

¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




7 %



Noise reduction

8 %

Technical data




Maximum pressure
10 bar



Maximum temperature
50 °C

Code	G	Dimensions [mm]				Weight [g]
		L ₁	L ₂	Ø D	Hex	
AA	1/8 BSPP	43.5	8.0	8.0	12	12.0
BA	1/8 NPT	44.0	6.7	8.0	12	12.0
HG	M12 x 1.25	43.5	8.0	8.0	17	20.0



Pressure		1 bar	3 bar	5 bar
600.388	Length Z [mm]	500	750	900
	X [mm]	130	185	260
	Y [mm]	130	185	260

Ordering no.				
Type	Mat.-no.	Code		
	Brass, POM	1/8 BSPP	1/8 NPT	M12 x 1.25
600.388.30	●	AA	BA	HG

Ordering Type + Code = Ordering no.
example: 600.388.30 + AA = 600.388.30.AA




Assembly accessories can be found in Chapter 9 "Accessories".

Micro multi-channel round jet nozzles for air

Series 600.625.1Y

Features:

- Powerful, punctiform air stream
- Ultra-compact design for difficult-to-reach locations
- Low noise level
- Reduced air consumption
- For the highest thermal requirements



Applications:

- Targeted blowing off and blowing out

Series 600.625.1Y

¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




10%



Noise reduction

6%

Technical data




Maximum pressure
5 bar



Maximum temperature
550 °C

— 600.625.1Y.00
— 600.625.1Y.10

Code	G	Dimensions [mm]			Weight [g]
		L ₁	L ₂	Ø D	
00	M4 x 0.5	16.5	5.5	4.0	1.0
10	M5 x 0.5	16.5	5.5	5.0	1.0



Pressure		1 bar	3 bar	5 bar
600.625.1Y.00	Length Z [mm]	225	400	500
	X [mm]	60	85	110
	Y [mm]	60	85	110
600.625.1Y.10	Length Z [mm]	350	600	825
	X [mm]	80	110	155
	Y [mm]	80	110	155
Ordering no.				
Type	Mat.-no.		Code	
	1Y Stainless steel 316L		M4 x 0.5	M5 x 0.5
600.625	●		00	10

Ordering Type + Material no. + Code = Ordering no.
example: 600.625 + 1Y + 00 = 600.625.1Y.00



Assembly accessories can be found in Chapter 9 "Accessories".


Maxi multi-channel round jet nozzles for air Series 600.387.35

Features:

- Circular, very powerful air jet
- Large volume of air in a concentrated jet due to large nozzle cross-section
- Effective over long distances

Applications:

- Blowing off and out
- Cleaning
- Drying



Series 600.387.35

¹ Meets OSHA specification in terms of noise level.

Cost savings and noise reduction



Cost saving




15%



Noise reduction

16%

Technical data




Maximum pressure
6 bar



Maximum temperature
50 °C

Code	G	Dimensions [mm]			Weight [g]
		L	Ø D	Hex	
AH	G 1/2 ISO 228	85.0	25.0	27	200.0



Pressure		1 bar	3 bar	5 bar
600.388	Length Z [mm]	800	800	800
	X [mm]	220	255	310
	Y [mm]	220	255	310

Ordering no.		
Type	Mat.-no.	Code
	35	1/2 BSPP
	Brass nickel-plated/ PVC	
600.387	●	AH

Ordering Type + Material no. + Code = Ordering no.
example: 600.387.35 + 35 + AH = 600.387.35.AH



Assembly accessories can be found in Chapter 9 "Accessories".

➤ Solid stream nozzles for air or saturated steam

Series 544

Features:

- Powerful, punctiform air stream
- Stainless steel version for higher ambient temperatures


Applications:

- Targeted blowing off and blowing out



OSHA¹

FDA




Series 544

¹ Meets OSHA specification in terms of noise level.

Code	G	Dimensions [mm]					Weight [g]
		L ₁	L ₂	Ø D	Hex	Flats	
CA	1/8 BSPT	22.0	6.5	13.0	14	10	14.0
CC	1/4 BSPT	22.0	10.0	13.0	14	10	16.0

Ordering no.				Bore diameter B [mm]	V _n Air [m³/h]				M Saturated steam [kg/h]			
Type	Mat.-no.	Code			p [bar]				p [bar]			
	16											
	Stainless steel 316L				1/8 BSPT	1/4 BSPT	1.0	2.0	3.0	5.0	1.0	2.0
544.360	●	CA	CC	1.05	0.93	1.40	1.92	2.88	0.77	1.14	1.64	2.42
544.400	●	CA	CC	1.30	1.43	2.14	2.94	4.41	1.18	1.75	2.51	3.71
544.480	●	CA	CC	1.33	1.67	2.51	3.42	5.13	1.39	2.06	2.92	4.23
544.560	●	CA	CC	1.69	2.58	3.87	5.27	7.90	2.14	3.18	4.50	6.66
544.640	●	CA	CC	2.09	4.33	6.50	8.81	13.22	3.60	5.33	7.52	11.13
544.720	●	CA	CC	2.66	6.85	10.27	14.00	21.02	5.68	8.42	11.96	17.70
544.800	●	CA	CC	3.30	10.75	16.12	21.87	32.81	8.92	13.21	18.66	27.63



Pressure		1 bar	3 bar	5 bar
544.360	Length Z [mm]	175	325	400
	X [mm]	50	75	100
	Y [mm]	50	75	100
544.480	Length Z [mm]	250	400	475
	X [mm]	70	120	150
	Y [mm]	70	120	150
544.640	Length Z [mm]	400	650	825
	X [mm]	105	175	225
	Y [mm]	105	175	225
544.800	Length Z [mm]	750	900	900
	X [mm]	180	260	280
	Y [mm]	180	260	280


Ordering Type + Material no. + Code = Ordering no.
example: 544.360 + 16 + CA = 544.360.16.CA



Assembly accessories can be found in Chapter 9 "Accessories".

Cluster solid stream nozzles for air or saturated steam

Series 540/541




Features:

- Powerful round jet through 40 individual bore holes
- Delivery of media at an angle of approx. 240°
- Suitable for use in difficult conditions
- Suitable for immersion in liquid media

Applications:


- Injection of steam into liquids
- Injection of compressed air into bulk goods
- Injection of gas (acid and neutralization baths)



Series 540/541

G	Dimensions [mm]				Weight [g]
	L ₁	L ₂	Ø D	Hex	
1/2 BSPP	45.0	15.0	26.0	27	100.0

Strahl- winkel	Ordering no.		Bore diameter B [mm]	V̇ _n Air [m³/h]				Ṁ Saturated steam [kg/h]			
	Type	Mat.-no.		p [bar]				p [bar]			
		16									
		Stainless steel 1.4305		1.0	2.0	3.0	5.0	1.0	2.0	3.0	5.0
Circa 240°	540.909	●	0.80	22.80	34.20	45.50	68.30	18.10	26.90	35.50	52.70
	540.989	●	1.00	35.50	53.30	71.00	106.50	28.20	41.70	55.10	81.70
	541.109	●	1.50	83.30	124.90	166.50	249.80	66.00	97.70	129.20	191.60
	541.189	●	2.00	129.70	194.50	259.30	389.00	103.00	152.60	201.70	299.10
	541.239	●	2.30	167.20	250.80	334.30	501.50	133.20	197.30	260.80	386.60



Pressure		1 bar	3 bar	5 bar
540.909	Length Z [mm]	375	725	850
	X [mm]	80	160	170
	Y [mm]	80	160	170
541.109	Length Z [mm]	800	800	800
	X [mm]	195	290	325
	Y [mm]	195	290	325
541.239	Length Z [mm]	800	800	800
	X [mm]	220	225	260
	Y [mm]	220	225	260


Ordering Type + Material no. = Ordering no.
example: 540.909 + 16 = 540.909.16




Assembly accessories can be found in Chapter 9 "Accessories".



TANK CLEANING NOZZLES



TANK CLEANING NOZZLES **GENERAL INFORMATION**



Static

Static spray balls do not rotate and therefore require considerably more liquid for cleaning processes. They are used primarily for rinsing tanks. Spray balls are a very robust and cost effective solution used in many processes.



Free-spinning

Free spinning devices utilize spray nozzles that are engineered in a specific position to allow the fluid to drive/rotate the spray head. The repeated impacts of the spray remove the soil and rinse it from the tank surface. This results in optimum cleaning efficiency at low pressures in small to medium-sized tanks.



Controlled rotation

The rotating head is driven by the fluid. A turbine wheel with an internal gear is used to control the rotation. This ensures that the speed remains in the optimum range even at higher pressures. The generated droplets are larger and impact the tank wall at higher speed. These rotating cleaning nozzles thus achieve an even higher impact which is especially important for large tanks.



Controlled rotation about two axes

The cleaning fluid drives an internal gear by means of a turbine wheel so that the spray head rotates around two axes. The solid jet nozzles mounted on the spray head produces powerful solid stream like jets. These solid jets sweep the entire tank surface in a pre-programmed, model-specific pattern during a spray cycle. This requires a certain minimum time. These models generate the highest impact and are ideal for very large tanks and the toughest cleaning tasks.



Perfect add

Various add-ons are available to cope with special tasks and installation situations. Retractable, wall-flush cleaning nozzles can be found here, as well as sensors and adapters.

Materials



Lechler tank cleaning nozzles are made of high quality materials such as Stainless steel 316L, PVDF, PEEK or PTFE. In addition to the requirements for material resistance and wear, the materials must

also be food grade for use in the beverage, food and pharmaceutical industries.

A large number of the materials used for Lechler tank cleaning nozzles comply with the requirements of the FDA or conform to regulation (EC) 1935/2004.

Hygienic requirements



All Lechler precision nozzles for tank cleaning are designed to meet hygiene requirements. In addition, Lechler also offers special nozzles for particularly stringent hygienic applications, certified to 3-A.

ATEX



Lechler offers several nozzle series designed especially for use in explosive atmospheres.

The respective logo on the product pages indicates which requirements are met.

Good to know

Detailed information can be found in our brochure "Tank and Equipment Cleaning" as well as at www.lechler.com/de-en/tankcleaningnozzles.

Cleaning efficiency classes 1 to 5



Cleaning efficiency classes

Lechler precision nozzles for tank and equipment cleaning are divided into five different cleaning efficiency classes. This is intended to help users find the right nozzle for the respective application quickly.

Every nozzle from Lechler is assigned to a class. The respective class is suitable for specific cleaning tasks.

Dependant upon the application, several cleaning classes can be suitable to the task of removing soils from your application. Generally, it is not possible to quantify and/or differentiate between soil types. The information should be seen as a guide intended to make it easier in the selection to finding the right nozzle.

The first step is to find a cleaning efficiency class suitable for the task. If your application is to clean a non-adhering pow-

der material from a tank surface the cleaning task can be defined as "rinsing". The nozzle series in cleaning efficiency class 1, e.g. static spray ball, or class 2, e.g. MicroWhirly or MiniSpinner, would be suitable for rinsing/washing cycle.

Taking into account the maximum possible tank diameter and the flow rate range, the tables on the following pages can be used to quickly narrow down the suitable nozzles. If the focus is on a low purchase price in the above referenced example, a spray ball should be chosen. If you want to save on your cost-intensive cleaning media, the MicroWhirly or MiniSpinner would be recommended.

If there is no recommended series for the tank diameter, several nozzles can be positioned in the tank to ensure that the distance between nozzle and tank is within the required dimensions.

Simulation software

Various inserts, such as agitators or mixing blades, can cause spray shadows. To find the ideal nozzle for such complex challenges, we have developed TankClean. The software simulates the use of various tank cleaning nozzles. The tank geometry is freely definable. As a result, subsequent cleaning can already be optimized in the planning phase.

TankClean




Function video

www.lechler.com/de-en/tankclean

Or scan the QR code.

TANK CLEANING NOZZLES

OVERVIEW OF SERIES



		Cleaning efficiency class 1				
						
Series		540/541	5B2/5B3	500.234	566	500.186
Information on page		206	207	209	210	212
Type		Static spray ball	Static spray ball	Rotating cleaning nozzle	Rotating cleaning nozzle	Rotating cleaning nozzle
Operating principle	Static	•	•			
	Free-spinning			•	•	•
	Controlled rotation					
	Controlled rotation about two axes					
 Max. tank diameter	Very small (up to ≈ 1 m)	•	•	•	•	•
	Small (up to ≈ 2 m)	•	•		•	
	Medium (up to ≈ 3 m)	•	•			
	Large (up to ≈ 8 m)	•	•			
	Very large (> 8 m)	•				
 Flow rate	Very low (up to ≈ 25 l/min)	•	•	•	•	•
	Low (up to ≈ 50 l/min)	•	•			
	Medium (up to ≈ 100 l/min)	•	•			
	High (up to ≈ 400 l/min)		•			
	Very high (up to ≈ 700 l/min)		•			
 Nozzle material	Stainless steel	•	•	•	•	
	Plastic					•
 Nozzle connection	Thread	•		•	•	•
	Slip-on connection		•			
ATEX available					•	

Cleaning efficiency class 2

					
500.191	5M1	5M2	5M3	5M4	573/583
213	214	216	218	220	222
Rotating cleaning nozzle	Rotating cleaning nozzle	Rotating cleaning nozzle	Rotating cleaning nozzle	Rotating cleaning nozzle	Rotating cleaning nozzle
•	•	•	•	•	•
•	•	•	•	•	•
		•	•	•	•
			•	•	•
				•	
•	•	•			
		•	•		•
			•	•	•
				•	
	•	•	•	•	
•					•
•	•	•	•	•	•
		•	•	•	•
	•	•	•	•	





		Cleaning efficiency class 3			Cleaning
					
Series		594/595	5W9	577	5S6/5S7
Information on page		224	226	228	230
Type		Rotating cleaning nozzle	Rotating cleaning nozzle	Rotating cleaning nozzle	Rotating cleaning nozzle
Operating principle	Static				
	Free-spinning	•	•	•	
	Controlled rotation				•
	Controlled rotation about two axes				
 Max. tank diameter	Very small (up to ≈ 1 m)	•	•		
	Small (up to ≈ 2 m)	•	•	•	•
	Medium (up to ≈ 3 m)	•	•	•	•
	Large (up to ≈ 8 m)			•	•
	Very large (> 8 m)				
 Flow rate	Very low (up to ≈ 25 l/min)	•			
	Low (up to ≈ 50 l/min)	•	•		•
	Medium (up to ≈ 100 l/min)	•	•		•
	High (up to ≈ 400 l/min)			•	•
	Very high (up to ≈ 700 l/min)			•	
 Nozzle material	Stainless steel	•	•	•	•
	Plastic				
 Nozzle connection	Thread	•	•	•	•
	Slip-on connection	•	•		•
ATEX available			•		•

efficiency class 4	Cleaning efficiency class 5			
				
5S5	5T2/5T3	5T5	5TM	5TP
232	234	236	238	240
Rotating cleaning nozzle	High impact cleaner	High impact cleaner	High impact cleaner	High impact tank cleaning machine
•				
	•	•	•	•
				•
•	•	•	•	•
•	•	•	•	
•	•	•	•	
•	•	•	•	
	•			•
	•			•
•	•	•	•	
•		•	•	
•	•	•	•	•
•	•	•	•	•
•	•			
	•	•	•	




		Extendable cleaning nozzles		
				
Series		5P2/5P3	5P8/5P9 Horizontal Duct	5P8/5P9 Vertical Duct & Tower
Information on page		242	244	246
Type		Extendable rotating cleaning nozzle	Extendable rotating cleaning nozzle	Extendable rotating cleaning nozzle
Operating principle	Static			
	Free-spinning	•	•	•
	Controlled rotation			
	Controlled rotation about two axes			
 Max. tank diameter	Very small (up to ≈ 1 m)			
	Small (up to ≈ 2 m)			
	Medium (up to ≈ 3 m)			
	Large (up to ≈ 8 m)			
	Very large (> 8 m)			
 Flow rate	Very low (up to ≈ 25 l/min)	•	•	•
	Low (up to ≈ 50 l/min)	•	•	•
	Medium (up to ≈ 100 l/min)			
	High (up to ≈ 400 l/min)			
	Very high (up to ≈ 700 l/min)			
 Nozzle material	Stainless steel	•	•	•
	Plastic			
 Nozzle connection	Thread	•		
	Slip-on connection			
	Tri-Clamp	•	•	•
ATEX available		•	•	•

		Perfect add	
			
5P7	5P5	05C	050
248	250	252	253
Extendable rotating cleaning nozzle	Extendable static cleaning nozzle	Adapter	Rotation monitoring sensor
	•		
•			
	•		
•	•	•	•
	•		
•	•		
	•		


Static spray balls

Series 540/541



Features:

- Robust and especially compact design
- Threaded connection
- Suitable for very high temperatures
- Also suitable for steam and air operation



Series 540/541

Female thread

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
1



Max. temperature
200 °C



Installation
Operation in every direction is possible



Material
Stainless steel 303



Recommended operating pressure
3 bar

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.




Spray angle	Ordering no.	Narrowest free cross section Ø [mm]	V̇ water [l/min]						Max. tank diameter [m]
	Type		p [bar] (p _{max} = 10 bar)						
			0.5	1.0	2.0	3.0	5.0	at 40 psi [US gal/min]	
240° 	540.909.16	0.8	9	13	18	22	28	6	6.5
	540.989.16	1.0	14	20	28	34	44	9	7.0
	541.109.16	1.5	29	40	57	70	90	18	7.5
	541.189.16	2.0	45	64	90	110	142	28	8.3
	541.239.16	2.3	59	83	118	145	187	37	9.5

NPT thread available on request.


The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Static spray balls RinseClean Series 5B2/5B3



Features:

- No moving parts
- Self-draining
- Proven use in many applications
- Suitable for very high temperatures and hygienic requirements




Series 5B2/5B3

Dimension of the slip-on connection according to DIN 10357, Series B

With the slip-on connection, the spray ball is pushed onto the customer's connection pipe and secured with the supplied Pin.



Pin 1



Pin 2-5

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
1



Max. temperature
200 °C



Installation
Operation in every direction is possible



Material
Stainless steel 316L,
pin stainless steel 316L



Recommended operating pressure
2 bar

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.





Spray angle	Ordering no.	Narrowest free cross section Ø [mm]	V̇ water [l/min]					Abmessungen [mm]					Pin	Max. tank diameter [m]
	Type		p [bar] (p _{max} = 5 bar)					L ₁	L ₂	Ø D ₁	Ø D ₂	Ø D ₃		
			0.5	1.0	2.0	3.0	at 40 psi [US gal/min]							
	5B3.083.1Y.D1.80	1.2	25	35	50	61	16	42.0	9.0	18.2	2,2	28.0	1	2.2
	5B3.253.1Y.D2.20	1.8	65	92	130	159	40	84.0	18.0	22.2	2,2	64.0	2	3.0
	5B3.323.1Y.D2.80	2.3	100	141	200	245	62	84.0	18.0	28.2	2,2	64.0	3	3.5
	5B3.463.1Y.D5.20	3.3	230	325	460	563	143	111.0	25.0	52.3	3,0	90.0	5	5.4
	5B3.114.1Y.D1.80	1.4	30	42	60	74	19	42.0	9.0	18.2	2,2	28.0	1	2.2
	5B3.274.1Y.D2.20	2.3	75	106	150	184	47	84.0	18.0	22.2	2,2	64.0	2	3.0
	5B3.394.1Y.D2.80	3.0	145	205	290	355	90	84.0	18.0	28.2	2,2	64.0	3	5.0
	5B3.444.1Y.D5.20	3.2	200	283	400	490	124	111.0	25.0	52.3	3,0	90.0	5	5.2
	5B3.305.1Y.D2.20	1.9	90	127	180	221	56	84.0	18.0	22.2	2.2	64.0	2	3.5
	5B3.345.1Y.D2.80	2.1	115	163	230	282	71	84.0	18.0	28.2	2.2	64.0	3	5.0
	5B3.385.1Y.D3.40	2.2	140	198	280	343	87	84.0	18.0	34.3	2.2	64.0	4	5.2
	5B3.405.1Y.D3.40	2.4	160	226	320	392	99	84.0	18.0	34.3	2.2	64.0	4	5.2
	5B3.425.1Y.D2.80	2.8	180	255	360	441	112	84.0	18.0	28.2	2.2	64.0	3	5.2
	5B3.445.1Y.D4.00	2.7	205	290	410	502	127	84.0	18.0	40.3	2.2	64.0	4	5.4
	5B3.475.1Y.D3.40	3.1	235	332	470	576	146	84.0	18.0	34.3	2.2	64.0	4	5.4
	5B3.535.1Y.D5.20	3.6	335	474	670	821	208	111.0	25.0	52.3	3.0	90.0	5	5.6
5B3.605.1Y.D5.20	4.5	500	707	1,000	1,225	310	111.0	25.0	52.3	3.0	90.0	5	5.6	
	5B2.879.1Y.D0.80	0.8	8	11	15	18	5	37.0	9.0	8.2	2.2	20.0	1	2.0
	5B3.089.1Y.D1.20	1.0	25	35	50	61	16	42.0	9.0	12.2	2.2	28.0	1	2.2
	5B3.139.1Y.D1.20	1.6	33	46	65	80	20	42.0	9.0	12.2	2.2	28.0	1	2.3
	5B3.209.1Y.D1.80	1.5	50	71	100	123	31	42.0	9.0	18.2	2.2	28.0	1	2.5
	5B3.309.1Y.D2.20	1.7	90	127	180	221	56	84.0	18.0	22.2	2.2	64.0	2	3.5
	5B3.379.1Y.D2.80	2.1	130	184	260	318	81	84.0	18.0	28.2	2.2	64.0	3	5.2
	5B3.389.1Y.D4.00	2.1	140	198	280	343	87	84.0	18.0	40.3	2.2	64.0	4	5.2
	5B3.409.1Y.D3.40	2.3	160	226	320	392	99	84.0	18.0	34.2	2.2	64.0	4	5.2
	5B3.449.1Y.D2.80	3.0	205	290	410	502	127	84.0	18.0	28.2	2.2	64.0	3	5.4
	5B3.489.1Y.D3.40	2.9	255	361	510	625	158	84.0	18.0	34.2	2.2	64.0	4	5.5
	5B3.499.1Y.D4.00	2.8	270	382	540	661	168	84.0	18.0	40.3	2.2	64.0	4	5.5
	5B3.539.1Y.D5.20	3.2	335	474	670	821	208	111.0	25.0	52.3	3.0	90.0	5	5.6

Material Alloy 2.4602 (Alloy 22) available on request.

Detailed information can be found in our brochure "Tank and Equipment Cleaning" as well as at www.lechler.com/de-en/tankcleaningnozzles.

Pin	Ordering no.
1	095.013.1Y.06.55
2	095.013.1Y.06.58
3	095.013.1Y.06.56
4	095.013.1Y.06.59
5	095.013.1Y.06.57

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Information about slip-on connections


- Stainless steel 316L supplied.
- Depending on the diameter of the adapter, the flow rate can increase due to a leakage between the adapter and the spray ball.

Rotating cleaning nozzle PicoWhirly Series 500.234



Features:

- Cleaning with rotating solid jet
- Compact design for confined spaces
- Suitable for very high temperatures
- Made completely of stainless steel



Series 500.234

Male thread

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
2



Max. temperature
200 °C



Installation
Operation in every direction is possible



Bearing
Kolsterised slide bearing



Material
Stainless steel 316L



Recommended operating pressure
3 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.	Narrowest free cross section Ø [mm]	V̇ water [l/min]					Max. tank diameter [m]
	Type		p [bar] (p _{max} = 5 bar)					
			1.0	2.0	3.0	5.0	at 40 psi [US gal/min]	
300° 	500.234.G9.00	1.8	5.7	8.0	9.8	12.7	2.5	0.9

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Rotating cleaning nozzle MicroWhirly Series 566



Features:


- Cleaning with effective flat jets
- Robust slide bearing made of PEEK
- Equipped with a thread or slip-on connection
- Food grade compatibility




**ATEX version
on request**




Series 566



Male thread



Female thread



**Dimension of the
slip-on connection according to
ASME-BPE (OD tube)**

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
2



Max. temperature
150 °C



Installation
Operation in every direction is possible



Bearing
Slide bearing made of PEEK



Material
Stainless steel 316L, PEEK



Recommended operating pressure
2 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.				Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type	Code				p [bar] (p _{max} = 6 bar)				
		3/8 BSPP male	3/8 BSPP female	3/4"- Slip-on connection		1.0	2.0	3.0	at 40 psi [US gal/min]	
180° 	566.873.1Y	AE	AF	TF07	1.0	12	15	18	5	1.6
	566.933.1Y	AE	AF	TF07	2.4	15	21	26	7	1.7
180° 	566.874.1Y	AE	AF	TF07	1.0	12	15	18	5	1.6
	566.934.1Y	AE	AF	TF07	2.4	15	21	26	7	1.7
360° 	566.879.1Y	AE	AF	TF07	1.0	12	15	18	5	1.6
	566.939.1Y	AE	AF	TF07	2.4	15	21	26	7	1.7

NPT thread and weld-on version available on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Information about slip-on connections

- Stainless steel 316L pin supplied.
- Depending on the diameter of the adapter, the flow rate can increase due to a leakage between the adapter and the rotating cleaning nozzle.

Ordering	Type	+	Code	=	Ordering no.
example:	566.873.1Y	+	AE	=	566.873.1Y.AE

Rotating cleaning nozzle MiniWhirly Series 500.186




Features:

- Economical entry-level model
- Cleaning with effective flat jets
- Specifically designed for barrel and canister cleaning



Series 500,186



Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
2



Max. temperature
50 °C



Installation
Vertically facing downwards



Bearing
Ball bearing made of stainless steel 316



Material
POM, stainless steel 316



Recommended operating pressure
2 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.	Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type		p [bar] (p _{max} = 5 bar)				
			1.0	2.0	3.0	at 40 psi [US gal/min]	
300° 	500.186.56.AH	1.9	13	18	22	6	1.3

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.


Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Rotating cleaning nozzle PVDF MicroWhirly Series 500.191



Features:

- Developed for work in corrosive environments
- Good suitability for food contact and foam delivery
- Made completely of PVDF



Series 500.191

Female thread

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
2



Max. temperature
95 °C



Installation
Operation in every direction is possible



Bearing
Slide bearing made of PVDF



Material
PVDF



Recommended operating pressure
2 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.	Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type		p [bar] (p _{max} = 5 bar)				
			1.0	2.0	3.0	at 40 psi [US gal/min]	
180° 	500.191.5E.02	2.2	9	13	16	4	0.8
180° 	500.191.5E.01	2.2	9	13	16	4	0.8
270° 	500.191.5E.31	2.2	14	20	25	6	1.1
360° 	500.191.5E.00	2.2	14	20	25	6	1.1

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

The PVDF MicroWhirly is not suitable for operation with compressed air or any other gas. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Rotating cleaning nozzle NanoSpinner2 Series 5M1




Features:

- Compact design for confined spaces
- Hygienic design
- Suitable for high temperatures
- Made entirely of stainless steel



**ATEX version
on request**

Series 5M1



Female thread

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
2



Max. temperature
200 °C



Installation
Operation in every direction is possible



Bearing
Double ball bearing made of stainless steel 316L



Material
Stainless steel 316L



Recommended operating pressure
2 bar



Filtration
Line strainer with a mesh size of 0.1mm/170 mesh

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.	Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type 1/8 BSPP		p [bar] (p _{max} = 7 bar)				
			1.0	2.0	3.0	at 40 psi [US gal/min]	
360° 	5M1.879.1Y.AB	0.4	11	15	18	5	1.4
	5M1.929.1Y.AB	0.5	14	20	25	6	1.6

NPT thread, other slip-on connections, weld-on version and material 2.4602 (Alloy 22) available on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Rotating cleaning nozzle MicroSpinner 2

Series 5M2



Features:


- Hygienic design
- Suitable for high temperatures
- Made entirely of stainless steel




**ATEX version
on request**




Series 5M2



Female thread



**Dimensions of the
slip-on connection according
to ASME-BE (OD-tube)**



**Dimensions of the
slip-on connection
top view**

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



**Cleaning
efficiency class**
2



Max. temperature
200 °C



Installation
Operating in every direction
possible



Bearing
Double ball bearing made
of stainless steel 316L



Material
Stainless steel 316L



**Recommended
operating pressure**
2 bar



Filtration
Line strainer with a mesh
size of 0.1mm/170 mesh



Adapter
3/8 BSPP is compatible
with HygienicFit

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.			Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type	Connection			p [bar] (p _{max} = 7 bar)				
		3/8 BSPP	1/2"-Slip-on		1.0	2.0	3.0	at 40 psi [US gal/min]	
60° 	5M2.952.1Y	AF	TF05	1.5	16	23	28	7	–
	5M2.042.1Y	AF	TF05	3.0	28	40	49	12	–
180° 	5M2.004.1Y	AF	TF05	0.9	22	32	39	10	1.8
360° 	5M2.969.1Y	AF	TF05	0.8	18	25	31	8	1.7
	5M2.049.1Y	AF	TF05	0.9	28	39	48	12	1.8

NPT thread, other slip-on connections, weld-on version and material 2.4602 (Alloy 22) on request.

The max. tank diameter shown above applies for the recommended operating pressure and has to be seen as a recommendation.
The cleaning result is also affected by the type of soiling.

Operating with compressed air only for short-term usage. Operation above the recommended operating pressure has negative effects on the cleaning result and wear.

Information slip-on connection

- Pin made of stainless steel 316L included (ordering no. 05M.230.1Y.00.00).
- Depending on diameter of the adapter, the flow rate increase due to leakage between connecting pipe and rotating cleaning nozzle.
- Minimum insertion diameter (with mounted pin) is 48.5 mm.

Example	Type	+	Connection	=	Ordering no.
of ordering:	5M2.952.1Y	+	AF	=	5M2.952.1Y.AF

Rotating cleaning nozzle MiniSpinner 2 Series 5M3




Features:

- Hygienic design
- Suitable for high temperatures
- Made entirely of stainless steel




**ATEX version
on request**


Series 5M3




Female thread



Female thread



Dimensions of the
slip-on connection according
to ASME-BE (OD-tube)



Dimensions of the
slip-on connection
top view

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
2



Max. temperature
200 °C



Installation
Operating in every direction possible



Bearing
Double ball bearing made of stainless steel 316L



Material
Stainless steel 316L



Recommended operating pressure
2 bar



Filtration
Line strainer with a mesh size of 0.1mm/170 mesh



Adapter
1/2 BSPP and 3/4 BSPP are compatible with HygienicFit

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.				Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type	Connection				p [bar] (p _{max} = 7 bar)				
		1/2 BSPP	3/4 BSPP	3/4"- Slip-on		1.0	2.0	3.0	at 40 psi [US gal/min]	
60° 	5M3.122.1Y	AH		TF07	2.6	45	63	77	20	–
180° 	5M3.133.1Y		AL	TF07	1.2	47	67	82	21	2.6
180° 	5M3.134.1Y		AL	TF07	1.3	47	67	82	21	2.6
360° 	5M3.999.1Y		AL	TF07	0.4	21	30	37	9	1.8
	5M3.089.1Y		AL	TF07	0.7	35	49	60	15	2.1
	5M3.139.1Y		AL	TF07	0.8	49	69	85	21	2.3
	5M3.209.1Y		AL	TF07	1.5	71	100	122	31	2.6

NPT thread, other slip-on connections, weld-on version and material 2.4602 (Alloy 22) on request.

The max. tank diameter shown above applies for the recommended operating pressure and has to be seen as a recommendation.
The cleaning result is also affected by the type of soiling.

Operating with compressed air only for short-term usage. Operation above the recommended operating pressure has negative effects on the cleaning result and wear.

Information slip-on connection

- Pin made of stainless steel 316L included (Ordering no. 05M.330.1Y.00.00).
- Depending on diameter of the adapter, the flow rate increase due to leakage between connecting pipe and rotating cleaning nozzle.
- Minimum insertion diameter (with mounted pin) is 59 mm.

Example of ordering: Type 5M3.122. 1Y + Connection AH = Ordering no. 5M3.122.1Y.AH

Rotating cleaning nozzle MaxiSpinner 2 Series 5M4




Features:

- Hygienic design
- Suitable for high temperatures
- Made entirely of stainless steel




**ATEX version
on request**


Series 5M4




Female thread



Female thread



**Dimensions of the
1 1/2" slip-on connection according
to ASME-BE (OD-tube)**



**Dimensions of the
2" slip-on connection according
to ASME-BE (OD-tube)**

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
2



Max. temperature
200 °C



Installation
Operating in every direction possible



Bearing
Double ball bearing made of stainless steel 316L



Material
Stainless steel 316L



Recommended operating pressure
2 bar



Filtration
Line strainer with a mesh size of 0.1mm/170 mesh



Adapter
1 1/4 BSPP and 1 1/2 BSPP are compatible with HygienicFit

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.					Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type	Connection					p [bar] (p _{max} = 7 bar)*				
		1 1/4 BSPP	1 1/2 BSPP	1 1/2" Slip-on	2"- Slip-on		1,0	2,0	3.0	at 40 psi [US gal/min]	
360° 	5M4.279.1Y	AQ	AS	TF15	TF20	1.7	107	150	184	46	4.0
	5M4.329.1Y	AQ	AS	TF15	TF20	2.0	141	200	245	62	4.5
	5M4.369.1Y	AQ	AS	TF15	TF20	2.3	177	250	306	78	5.0

NPT thread, weld-on version and material 2.4602 (Alloy 22) available on request.

* Please note the maximum operating pressure of 4 bar for the 2" slip-on connection.

The max. tank diameter shown above applies for the recommended operating pressure and has to be seen as a recommendation.
The cleaning result is also affected by the type of soiling

Operating with compressed air only for short-term usage. Operation above the recommended operating pressure has negative effects on the cleaning result and wear.

Information slip-on connection

- Bolt with head incl. pin made of stainless steel 316L included (Ordering no. 05M.431.1Y.00.00).
- Depending on diameter of the adapter, the flow rate increase due to leakage between connecting pipe and rotating cleaning nozzle.
- Minimum insertion diameter (with mounted bolt) is the same as for the threaded variants 69 mm.

Example	Type	+	Connection	=	Ordering no.
of ordering:	5M4.369. 1Y	+	AQ	=	5M4.369.1Y.AQ

Rotating cleaning nozzle PTFE Whirly Series 573/583




Features:


- Made entirely of PTFE
- Slip-on connection conforms to 3-A
- Suitable for corrosive environments
- Suitable for very hygienic requirements (e.g. milk industry)




Series 573/583




Female thread
3/4 BSPP



Female thread
1 BSPP



3/4" and 1" slip-on connection
(conforms to 3-A)
Dimension of the slip-on
connection according to
ASME-BPE (OD tube)



1" slip-on connection pin 2
(3-A-compliant)
Dimensions of slip-on connection
according to ASME-BPE (OD tube)

Data in brackets refers to
1" version marked with "1".

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
2



Max. temperature
95 °C (version for higher temperatures [130 °C] available on request)



Installation
Operation in every direction is possible



Bearing
Slide bearing made of PTFE



Material
PTFE



Recommended operating pressure
2 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.					Narrowest free cross section Ø [mm]	V̇ water [l/min]				Pin	Max. tank diameter [m]
	Type	Code					p [bar] (p _{max} = 6 bar)					
		3/4 BSPP	1 BSPP	3/4" Slip-on connection	1" Slip-on connection		1.0	2.0	3.0	at 40 psi [US gal/min]		
	583.116.55	AL		TF07		2.4	47	67	82	21	1	2.5
	583.346.55				TF10	5.9	159	225	276	70	2	3.2
	573.116.55	AL		TF07		2.4	47	67	82	21	1	2.5
	583.119.55	AL		TF07	TF10 ¹	1.8	41	58	71	18	1	2.4
	583.209.55	AL		TF07	TF10 ¹	3.5	71	100	122	31	1	2.5
	583.269.55	AL		TF07		4.8	103	145	178	45	1	2.8
	583.279.55		AN		TF10	3.7	106	150	184	47	2	3.0
	583.349.55		AN		TF10	5.6	159	225	276	70	2	3.2

NPT thread available on request.

¹ See drawing 3 for details (Page 222).

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Information about slip-on connections

- Pin made of stainless steel 316L supplied (Ordering no. Pin 1: 095.013.17.06.60, Pin 2: 095.013.17.06.61).
- Depending on the diameter of the adapter, the flow rate can increase due to a leakage between the adapter and the rotating cleaning nozzle.

Ordering Type + Code = Ordering no.
example: 583.116.55 + AL = 583.116.55.AL

Rotating cleaning nozzle HygienicWhirly Series 594/595




Features:


- Cleaning with highly effective flat jets
- Effective cleaning even at low pressure
- Suitable for foam delivery




Series 594/595




Female thread
59x.xx9.1Y.AF



Female thread
595.139.1Y.AL



Dimension of the slip-on
connection according to
ASME-BPE (OD tube)
59x.xx9.1Y.67



Dimension of the slip-on
connection according to
ASME-BPE (OD tube)
595.139.1Y.67

 Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
--	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
3



Max. temperature
150 °C



Installation
Operation in every direction is possible



Bearing
Slide bearing made of PEEK



Material
Stainless steel 316L, PEEK, version with slip-on connection O-ring made of EPDM



Recommended operating pressure
3 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh

[Function video](#)

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.				Narrowest free cross section Ø [mm]	V̇ water [l/min]						Max. tank diameter [m]
	Type	Code				p [bar] (p _{max} = 5 bar)						
		3/8 BSPP	3/4 BSPP	3/4" slip-on connection		0.5	1.0	2.0	3.0	5.0	at 40 psi [US gal/min]	
360° 	594.829.1Y	AF		67	1.7	6	8	11	14	18	3	0.8
	594.879.1Y	AF		67	2.5	8	11	15	18	23	5	1.2
	595.009.1Y	AF		67	4.0	16	22	32	39	50	10	1.5
	595.049.1Y	AF		67	4.2	20	28	40	49	63	12	2.0
	595.139.1Y		AL	67	5.0	34	47	67	82	106	21	2.7

NPT thread available on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Information about slip-on connections

- Pin made of stainless steel 316L supplied (Ordering no.: 095.022.1Y.50.94.E).
- Depending on the diameter of the adapter, the flow rate can increase due to a leakage between the adapter and the rotating cleaning nozzle.

Ordering example: Type 594.829.1Y + Code AF = Ordering no. 594.829.1Y.AF

Rotating cleaning nozzle Whirly 2 Series 5W9




Features:

- Popular hygienic design
- Cleaning with effective flat jets
- Various connection options
- Available with a wide range of flow rates and spray angles




**ATEX version
on request**


Series 5W9




Female thread



Dimensions slip-on connection
according to ASME-BPE (OD-tube)



Dimensions slip-on connection
according to ASME-BPE (OD-tube)



Insertion diameter of
slip-on connection
Stainless steel 316L

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
3



Max. temperature
150 °C



Installation
Operation in every direction is possible



Bearing
Double ball bearing made of stainless steel



Material
Stainless steel 316L, PEEK



Recommended operating pressure
2 bar



Filtration
Line strainer with a mesh size of 0.1 mm/170 mesh



Adapter
3/4 BSPP is compatible with HygienicFit

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.				Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type	Code				p [bar] (p _{max} = 6 bar)				
		3/4 BSPP	3/4" Slip-on connection	1" Slip-on connection		1.0	2.0	3.0	at 40 psi [US gal/min]	
270° 	5W9.075.1Y	AL	TF07	TF10	2.0	34	48	59	15	1.8
	5W9.145.1Y	AL	TF07	TF10	2.8	50	71	87	22	2.1
	5W9.195.1Y	AL	TF07	TF10	3.3	69	97	119	30	2.6
270° 	5W9.076.1Y	AL	TF07	TF10	2.0	34	48	59	15	1.8
	5W9.106.1Y	AL	TF07	TF10	2.5	41	58	71	18	2.1
	5W9.196.1Y	AL	TF07	TF10	3.4	69	97	119	30	2.6
360° 	5W9.079.1Y	AL	TF07	TF10	1.6	34	48	59	15	1.8
	5W9.149.1Y	AL	TF07	TF10	2.4	50	71	87	22	2.1
	5W9.199.1Y	AL	TF07	TF10	3.0	69	97	119	30	2.6
	5W9.279.1Y	AL	TF07	TF10	3.5	103	145	178	45	3.0

NPT thread available on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Information about slip-on connections

- Pin made of stainless steel 316L supplied (Ordering no.: 095.013.1Y.06.72).
- Depending on the diameter of the adapter, the flow rate can increase due to a leakage between the adapter and the rotating cleaning nozzle.
- Minimum insertion diameter (with mounted pin) is 69.5 mm.

Ordering	Type	+	Code	=	Ordering no.
example:	5W9.075.1Y	+	AL	=	5W9.075.1Y.AL

Rotating cleaning nozzle Gyro Series 577




Features:


- Cleaning with powerful nozzle inserts
- Suitable for very large tanks
- Available with many different flow rates
- Clogging-resistant and large clear cross-sections



Series 577



Female thread



Female thread

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
3



Max. temperature
95 °C



Installation
Vertically facing downwards



Bearing
Slide bearing made of PTFE



Material
Stainless steel 316L,
PTFE



Recommended operating pressure
3 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh

[Function video](#)

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.			V̇ water [l/min]					Max. tank diameter [m]
	Type	Code		p [bar] (p _{max} = 5 bar)					
		1 BSPP	2 BSPP					at 40 psi [US gal/min]	
				1.0	2.0	3.0	5.0		
360° 	577.289.1Y	AN		115	163	200	258	50	3.4
	577.369.1Y	AN		182	258	316	408	80	3.9
	577.409.1Y		AW	228	322	394	509	100	4.2
	577.439.1Y		AW	273	386	473	610	120	4.6
	577.499.1Y		AW	380	538	659	851	170	5.4

NPT thread available on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Ordering example: Type 577.289.1Y + Code AN = Ordering no. 577.289.1Y.AN



Rotating cleaning nozzle XactClean HP 2 Series 5S6/5S7



Features:


- Flat fan nozzle with high impact
- Uniform cleaning
- High efficiency due to controlled rotation
- High operating reliability thanks to robust drive unit




**ATEX version
on request**




Series 5S6/5S7




**Insertion diameter D_1
and interference circle diameter D_2
of the threaded connection**




Female thread



**Dimensions of
1/2" slip-on connection
according to
ASME-BPE (OD tube)**



**Dimensions of
3/4" slip-on connection
according to
ASME-BPE (OD tube)**



**Insertion diameter D_1
and interference circle diameter D_2
of the slip-on connection**

EPDM O-rings	FKM O-rings	Connection	Dimensions [mm]			
			L_1	L_2	Insertion diameter D_1	Interference circle diameter D_2
AF	20	3/8 BSPP	141.0	9.0	50.0–66.0	50.0–67.0
AH	21	1/2 BSPP	143.0	13.0	50.0–74.0	50.0–76.0
AL	22	3/4 BSPP	143.0	13.2	50.0–79.0	50.0–81.0
AN	23	1 BSPP	140.0	16.5	51.0–79.0	53.0–80.0
TF05	30	1/2" slip-on connection	150.0	16.0	52.0–66.0	50.0–67.0
TF07	31	3/4" slip-on connection	160.0	30.0	66.0–79.0	50.0–81.0

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
-------------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
4



Max. temperature
150 °C



Installation
Operation in every direction is possible



Bearing
Double ball bearing



Material
Stainless steel 316L,
EPDM or FKM, PEEK



Recommended operating pressure
3 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh



Rotation monitoring
Sensor compatible,
for information:
See Page 253



Adapter
3/8 BSPP, 1/2 BSPP,
3/4 BSPP and 1 BSPP are compatible with HygienicFit

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.														Narrowest cross- section Ø [mm]	V̇ water [l/min]					Max. tank diameter [m]	
	Type	Connection														p [bar] (p _{max} = 15 bar)						
		3/8 BSPP		1/2 BSPP		3/4 BSPP		1 BSPP		1/2" slip-on connection		3/4" slip-on connection		2.0		3.0	5.0	10.0	at 40 psi [US gal/ min]			
		EPDM	FKM	EPDM	FKM	EPDM	FKM	EPDM	FKM	EPDM	FKM	EPDM	FKM									
	5S6.963.1Y	AF	20	AH	21					TF05	30			1.7	25	31	40	57	8	3.5		
	5S7.043.1Y			AH	21							TF07	31	2.0	41	50	65	92	13	4.0		
	5S7.113.1Y			AH	21	AL	22					TF07	31	2.0	60	73	94	133	18	6.0		
	5S7.183.1Y					AL	22					TF07	31	2.0	89	109	141	199	28	7.0		
	5S7.223.1Y					AL	22					TF07	31	2.0	111	136	175	248	34	7.5		
	5S7.253.1Y					AL	22	AN	23			TF07	31	2.0	135	165	213	301	42	8.0		
	5S6.964.1Y	AF	20	AH	21					TF05	30			1.7	25	31	40	57	8	3.5		
	5S7.044.1Y			AH	21							TF07	31	2.0	41	50	65	92	13	4.0		
	5S7.114.1Y			AH	21	AL	22					TF07	31	2.0	60	73	94	133	18	6.0		
	5S7.184.1Y					AL	22					TF07	31	2.0	89	109	141	199	28	7.0		
	5S7.224.1Y					AL	22					TF07	31	2.0	111	136	175	248	34	7.5		
	5S7.254.1Y					AL	22	AN	23			TF07	31	2.0	135	165	213	301	42	8.0		
	5S6.965.1Y	AF	20	AH	21					TF05	30			1.7	25	31	40	57	8	3.5		
	5S7.045.1Y			AH	21							TF07	31	2.0	41	50	65	92	13	4.0		
	5S7.115.1Y			AH	21	AL	22					TF07	31	2.0	60	73	94	133	18	6.0		
	5S7.185.1Y					AL	22					TF07	31	2.0	89	109	141	199	28	7.0		
	5S7.225.1Y					AL	22					TF07	31	2.0	111	136	175	248	34	7.5		
	5S7.255.1Y					AL	22	AN	23			TF07	31	2.0	135	165	213	301	42	8.0		
	5S6.966.1Y	AF	20	AH	21					TF05	30			1.7	25	31	40	57	8	3.5		
	5S7.046.1Y			AH	21							TF07	31	2.0	41	50	65	92	13	4.0		
	5S7.116.1Y			AH	21	AL	22					TF07	31	2.0	60	73	94	133	18	6.0		
	5S7.186.1Y					AL	22					TF07	31	2.0	89	109	141	199	28	7.0		
	5S7.226.1Y					AL	22					TF07	31	2.0	111	136	175	248	34	7.5		
	5S7.256.1Y					AL	22	AN	23			TF07	31	2.0	135	165	213	301	42	8.0		
	5S6.969.1Y	AF	20	AH	21					TF05	30			1.5	25	31	40	57	8	3.5		
	5S7.049.1Y			AH	21							TF07	31	2.0	41	50	65	92	13	4.0		
	5S7.119.1Y			AH	21	AL	22					TF07	31	2.0	60	73	94	133	18	6.0		
	5S7.189.1Y					AL	22					TF07	31	2.0	89	109	141	199	28	7.0		
	5S7.229.1Y					AL	22					TF07	31	2.0	111	136	175	248	34	7.5		
	5S7.259.1Y					AL	22	AN	23			TF07	31	2.0	135	165	213	301	42	8.0		

NPT thread available on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Information about slip-on connections

- Pin made of stainless steel 316L included (ordering no. 095.022.1Y.50.60.E (TF07), 095.013.1E.05.59 (TF05)).
- Depending on the diameter of the adapter, the flow rate can increase due to a leakage between the adapter and the rotating cleaning nozzle.

Ordering example: Type 5S6.963.1Y + Code AF = Ordering no. 5S6.963.1Y.AF

Rotating cleaning nozzle XactClean HP+ Series 5S5




Features:


- High impact and uniform cleaning due to specially developed flat fan nozzles
- Effective cleaning of larger tanks due to higher flow rates
- High operating reliability due to robust drive unit




Series 5S5




Female thread



Dimensions of slip-on connection according to ASME-BPE (OD tube)



Insertion diameter D_1 and interference circle diameter D_2 of the threaded connection



Insertion diameter and interference circle diameter of the slip-on connection

Connection		Dimensions [mm]		
		L	Insertion diameter D_1	Interference circle diameter D_2
AN	1 BSPP	185	81-92	82-98
AQ	1 1/4 BSPP	185	81-92	82-98
AS	1 1/2 BSPP	187	81-92	82-98

Max. tank diameter [m]	0	1	2	3	4	5	6	7	8	9
------------------------	---	---	---	---	---	---	---	---	---	---



Cleaning efficiency class
4



Max. temperature
150 °C



Installation
Operation in every direction is possible



Bearing
Double ball bearing



Material
Stainless steel 316L, stainless steel 316, PEEK, EPDM



Recommended operating pressure
3 bar



Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh



Rotation monitoring
Sensor compatible, for information: See Page 253



Adapter
1 BSPP, 1 1/4 BSPP and 1 1/2 BSPP are compatible with HygienicFit

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.					Narrowest free cross section Ø [mm]	V̇ water [l/min]				Max. tank diameter [m]
	Type	Code					p [bar] (p _{max} = 10 bar)				
		1 BSPP	1 1/4 BSPP	1 1/2 BSPP	1 1/2"- Slip-on connection		2.0	3.0	5.0	at 40 psi [US gal/min]	
180° 	5S5.293.1Y	AN			TF15	3.0	165	202	261	51	9.0
	5S5.323.1Y	AN	AQ		TF15	3.0	200	245	316	62	9.2
	5S5.363.1Y		AQ	AS	TF15	3.0	250	306	395	78	9.4
180° 	5S5.294.1Y	AN			TF15	3.0	165	202	261	51	9.0
	5S5.324.1Y	AN	AQ		TF15	3.0	200	245	316	62	9.2
	5S5.364.1Y		AQ	AS	TF15	3.0	250	306	395	78	9.4
270° 	5S5.295.1Y	AN			TF15	3.0	165	202	261	51	9.0
	5S5.325.1Y	AN	AQ		TF15	3.0	200	245	316	62	9.2
	5S5.365.1Y		AQ	AS	TF15	3.0	250	306	395	78	9.4
270° 	5S5.296.1Y	AN			TF15	3.0	165	202	261	51	9.0
	5S5.326.1Y	AN	AQ		TF15	3.0	200	245	316	62	9.2
	5S5.366.1Y		AQ	AS	TF15	3.0	250	306	395	78	9.4
360° 	5S5.299.1Y	AN			TF15	3.0	165	202	261	51	9.0
	5S5.329.1Y	AN	AQ		TF15	3.0	200	245	316	62	9.2
	5S5.369.1Y		AQ	AS	TF15	3.0	250	306	395	78	9.4
	5S5.399.1Y		AQ	AS	TF15	3.0	300	367	474	93	9.6

NPT thread available on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Information about slip-on connections

- Pin made of stainless steel 316L supplied (Ordering no.: 095.013.1Y.06.45).
- Depending on the diameter of the adapter, the flow rate can increase due to a leakage between the adapter and the rotating cleaning nozzle.

Ordering	Type	+	Code	=	Ordering no.
example:	5S5.293.1Y	+	AN	=	5S5.293.1Y.AN

High impact tank cleaning machine

MeshClean

Series 5T2/5T3




Features:


- High efficiency thanks to especially powerful solid jet nozzles
- Also suitable for smaller tanks
- with stubborn soiling
- Active self-cleaning through special nozzle geometry
- Particularly low-maintenance




**ATEX version
on request**




Series 5T2/5T3




Female thread



Dimensions of slip-on connection
according to ASME-BPE (OD tube)



Insertion diameter D_1 and
interference circle diameter D_2
of the threaded connection



Insertion diameter D_1 and
interference circle diameter D_2
of the slip-on connection

 Max. tank diameter [m]	0		3		6		9		12		15		18		21		24		27	
---	---	--	---	--	---	--	---	--	----	--	----	--	----	--	----	--	----	--	----	--



Cleaning efficiency class
5



Max. temperature
150 °C



Installation
Operation in every installation position



Bearing
Ball bearing



Material
Stainless steel 316L,
PTFE, PEEK,
EPDM or FKM



Recommended operating pressure
5 bar



Filtration
Line strainer with a mesh
size of 0.2 mm/80 mesh



Rotation monitoring
Sensor compatible,
for information:
See Page 253



Adapter
3/4 BSPP is compatible
with HygienicFit

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.						Narrowest free cross section Ø [mm]	Number, Ø Nozzles [mm]	V̇ water [l/min]						Dimensions [mm]						Max. tank diameter [m]
	Type	Connection				p [bar] (p _{max} = 15 bar)						Female thread			Slip-on connection						
EPDM	FKM	EPDM	FKM	2.0	3.0	5.0	10.0	at 40 psi [US gal/ min]	L	Ø D ₁	Ø D ₂	L	Ø D ₁	Ø D ₂							
	5T2.849.1Y	AL	22	TF07	31	1.75	4 × 1.75	13	15	20	28	4	142	68	82	157	77	82	11.5		
	5T2.969.1Y	AL	22	TF07	31	2.70	4 × 2.70	25	31	40	57	8	142	68	82	157	77	82	12.0		
	5T3.029.1Y	AL	22	TF07	31	3.20	4 × 3.20	35	43	55	78	11	142	68	82	157	77	82	12.5		
	5T3.089.1Y	AL	22	TF07	31	4.00	4 × 4.00	50	61	79	112	16	148	74	91	163	82	91	13.0		

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Ordering Type + Code = Ordering no.
example: 5T2.849.1Y + AL = 5T2.849.1Y.AL

High impact tank cleaning machine **MeshClean+** Series 5T5



Features:


- High efficiency thanks to especially powerful solid jet nozzles
- Also suitable for large tanks with persistent soiling
- Active self-cleaning through special nozzle geometry
- Particularly low-maintenance




**ATEX version
on request**




Series 5T5




Female thread



**Dimensions of slip-on connection
according to ASME-BPE (OD tube)**



**Insertion diameter and
interference circle diameter
of the threaded connection**



**Insertion diameter and
interference circle diameter
of the slip-on connection**

 Max. tank diameter [m]	0	3	6	9	12	15	18	21	24	27
--	---	---	---	---	----	----	----	----	----	----



Cleaning efficiency class
5



Max. temperature
150 °C



Installation
Operation in every installation position



Bearing
Ball bearing



Material
Stainless steel 316L,
PTFE, PEEK,
EPDM or FKM



Recommended operating pressure
5 bar



Filtration
Line strainer with a mesh size of 0.2 mm/80 mesh



Rotation monitoring
Sensor compatible,
for information:
See Page 253



Adapter
1 1/2" BSP is compatible with HygienicFit

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.

Function video



Spray angle	Ordering no.					Narrowest cross-section Ø [mm]	Quantity x Ø nozzle [mm]	V̇ water [l/min]					Max. tank diameter [m]
	Type	Connection						p [bar] (p _{max} = 15 bar)					
		1 1/2 BSP		1 1/2" slip-on connection									
		EPDM	FKM	EPDM	FKM			2.0	3.0	5.0	10.0	at 40 psi [US gal/min]	
360° 	5T5.149.1Y	AS	25	T5	34	4.40	4 × 4.40	70	86	111	157	21.8	15.2
	5T5.219.1Y	AS	25	T5	34	5.55	4 × 5.55	107	131	169	239	33.2	16.5
	5T5.259.1Y	AS	25	T5	34	6.45	4 × 6.45	132	162	209	296	41.0	17.3
	5T5.279.1Y	AS	25	T5	34	7.10	4 × 7.10	150	184	238	336	46.7	17.6
	5T5.299.1Y	AS	25	T5	34	7.75	4 × 7.75	170	209	269	380	52.8	16.9

NPT threads on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

Ordering example: Type 5T5.149.1Y + Code AS = Ordering no. 5T5.149.1Y.AS

High impact cleaner IntenseClean Series 5TM



Features:

- Very robust design
- High efficiency thanks to especially powerful solid jet nozzles
- High efficiency due to gear-controlled rotation
- Proven in the petrochemical industry





**ATEX version
on request**




FDA




Series 5TM



Female thread



**5TM.2xx.1Y.AS
(2 nozzles)**



**5TM.4xx.1Y.AS
(4 nozzles)**

 Max. tank diameter [m]	0	3	6	9	12	15	18	21	24	27
---	---	---	---	---	----	----	----	----	----	----



Cleaning efficiency class
5



Max. temperature
95 °C



Installation
Operation in every direction is possible



Bearing
Ball bearing



Material
Stainless steel 316L, stainless steel 304, stainless steel 302, PTFE, PEEK



Recommended operating pressure
5 bar



Filtration
Line strainer with a mesh size of 0.2 mm/80 mesh



Rotation monitoring
Sensor compatible, for information: See Page 253

[Function video](#)

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.	Narrowest free cross section Ø [mm]	Number, Ø Nozzles [mm]	V̇ water [l/min]					Max. tank diameter [m]
	Type			p [bar] (p _{max} = 7 bar)					
				2.0	3.0	5.0	7.0	at 40 psi [US gal/min]	
360° 	5TM.208.1Y.AS	8.0	2 × 8.0	125	153	198	234	39	24.0
	5TM.210.1Y.AS	10.0	2 × 10.0	160	196	253	299	50	24.0
	5TM.406.1Y.AS	6.0	4 × 6.0	140	171	221	261	43	18.0
	5TM.407.1Y.AS	7.0	4 × 7.0	170	208	269	318	53	20.0
	5TM.408.1Y.AS	8.0	4 × 8.0	200	245	316	374	62	22.0
	5TM.410.1Y.AS	10.0	4 × 10.0	260	318	411	486	81	23.0

NPT thread available on request.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

High pressure tank cleaning machine

PressureClean

Series 5TP





Features:

- Intensive cleaning with little water and high pressure
- Ideal for small tanks with the most persistent soiling
- Driven by an efficient 24 V motor
- "IP 65" certified motor housing
- Scope of delivery:
 - PressureClean
 - 5 m cable with matching plug and open cable end
 - Not included: power supply unit for power supply with 24 VDC/1.1 A



Series 5TP

Type	Dimensions [mm]		
	L ₁	L ₂	L ₃
5TP.xx9.1Y.01	566	250	219
5TP.xx9.1Y.02	816	500	469
5TP.xx9.1Y.03	1,310	923	892



Insertion diameter and interference circle diameter



Cleaning efficiency class
5



Max. temperature
90 °C



Installation
Operation in every direction is possible



Bearing
Ball bearing



Material
Process side:
Stainless steel 316L,
PTFE with carbon,
PEEK, Si₃N₄, EPDM



Recommended operating pressure
100 bar



Filtration
Line strainer with a mesh size of 0.1 mm/170 Mesh



Max. tank diameter
The specified maximum tank diameter applies to the recommended operating pressure and is indicative only. The type of soiling is also decisive for the cleaning result.

Type	Max. tank diameter for most persistent soiling [m]	Max. tank diameter for medium soiling [m]
5TP.469.1Y	1.0	2.5
5TP.589.1Y	1.2	3.0
5TP.659.1Y	1.4	3.5


Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Adapter for IBC containers:

- Suitable for all types of PressureClean
- Fits into a G 2 female thread
- Scope of delivery:
 - Adapter with Tri-Clamp as interface for PressureClean
 - IBC cover (DN 150, thread S165 x 7) made of HDPE
 - Stainless steel joint clamp with EPDM seal



Ordering no.: 05T.P30.00.00.00


Spray angle	Ordering no.				V̇ water [l/min]		
	Type	Lance length			p [bar] (p _{max} = 200 bar)		
		250 [mm]	500 [mm]	1,000 [mm] with adjustable flange	50	100	150
360° 	5TP.469.1Y	01	02	03	7	10	12
	5TP.589.1Y	01	02	03	14	20	24
	5TP.659.1Y	01	02	03	21	30	37

Information on operation

- The electric motor may only be switched on when liquid is flowing through the nozzle.

Ordering	Type	+	Lance length	=	Ordering no.
example:	5TP.469.1Y	+	01	=	5TP.469.1Y.01

Extendable rotating cleaning nozzle PopUp Whirly Series 5P2/5P3



Features:


- Pressure-dependent automatically extending rotating cleaning nozzle
- Can be installed flush in the tank wall
- Suitable for cleaning pipes and applications that use foam
- Particularly suitable for applications in the pharmaceutical, chemical, food and beverage industry




**ATEX version
on request**




Series 5P2




Male thread




Tri-Clamp connection¹




Series 5P3




Male thread




Tri-Clamp connection²



Installation situation



Via thread in idle position




Via Tri-Clamp in operating position

¹ A clamp according to DIN 32676-A with a connection diameter of 50.5 mm is required to connect the nozzle to the weld-in flange.


² A clamp according to DIN 32676-A with a connection diameter of 64.0 mm is required to connect the nozzle to the weld-in flange.

Weld-in flange for Tri-Clamp connection

A 2 mm thick gasket must be used if the PopUp Whirly is installed with the weld-in flange.



Ordering no.: 050.020.1Y.01.00
Material: Stainless steel 316L



Ordering no.: 050.020.1Y.01.01
Material: Stainless steel 316L



Max. temperature
140 °C



Installation
Operation in every
direction is possible



Bearing
Slide bearing



Material
Stainless steel 316L,
stainless steel 316Ti,
stainless steel 316,
FKM



**Recommended
operating pressure**
2 bar
5P2: Opening pressure
approx. 1.0 bar, closing
pressure approx. 0.5 bar,
5P3: Opening pressure
approx. 0.9 bar, closing
pressure approx. 0.5 bar



Filtration
Line strainer with a mesh
size of 0.3 mm/50 mesh

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.				Narrowest free cross section Ø [mm]	V̇ water [l/min]			
	Type	Code				p [bar] (p _{max} = 5 bar)			
		1 1/4 BSPP	1 1/2 BSPP	Tri-Clamp		1.0	2.0	3.0	at 40 psi [US gal/min]
	5P2.873.1Y.AP	●			2.5	11	15	18	5
	5P2.873.1Y.00			●	2.5	11	15	18	5
	5P2.923.1Y.AP	●			3.5	14	20	25	6
	5P2.923.1Y.00			●	3.5	14	20	25	6
	5P3.043.1Y.AR		●		3.3	28	40	49	12
	5P3.043.1Y.00			●	3.3	28	40	49	12


Detailed information can be found in our brochure "Tank and Equipment Cleaning" as well as at www.lechler.com/de-en/tankcleaningnozzles.

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Information on operation

- The PopUp Whirly is not suitable for operation with compressed air or any other gas.
- Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

>> Extendable rotating cleaning nozzle PopUp Whirly Air Series 5P8/5P9, Horizontal Duct




Features:


- Self-draining
- Dry blowing with compressed air possible
- Operation with steam possible (SIP)
- Vacuum in the container allowed, thanks to double-acting pneumatic cylinder
- Optional end position monitoring with sensors
- Particularly hygienic (all threads encapsulated by O-rings)




Series 5P8/5P9




Tri-Clamp connection 5P8



Tri-Clamp connection 5P9



Installation situation/ process-side installation



Tri-Clamp connection



Maximum operating temperature
150 °C



Maximum ambient temperature
150 °C



Installation
Operation in every installation position



Bearing
Slide bearing



Material
Process and media related:
Stainless steel 1.4404 (316L), Stainless steel 1.4571 (316Ti), PTFE, FKM oder EPDM



Weight
2.2 kg



Surface quality
 $Ra \leq 0,8 \mu m$



Surface quality
 $Ra \leq 1,6 \mu m$



Steam suitability
Suitable



Recommended filter
Line strainer with mesh size of 0.3 mm/50 mesh



Recommended operating pressure
2 bar
Opening pressure approx. 1.6 bar, closing pressure approx. 0.3 bar



Maintainable

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.			Narrowest cross-section Ø [mm]	V̇ water [l/min]			V̇ water
	Type	Material of the O-rings			p [bar] (p _{max} = 6 bar)			
		FKM	EPDM		1.0	2.0	3.0	at 2 bar [m³/h]
25° 	5P8.873.1Y.	10	20	2.3	11	15	18	0.9
	5P8.923.1Y.	10	20	2.5	14	20	25	1.2
	5P8.993.1Y.	10	20	2.7	21	30	37	1.8
	5P9.043.1Y.	10	20	3.7	28	40	49	2.4
	5P9.133.1Y.	10	20	4.0	42	60	73	3.6

Detailed information can be found in our brochure "Tank and Equipment Cleaning" as well as at www.lechler.com/de-en/tankcleaningnozzles.

Recommended accessories: see page 289 (Can be ordered separately).

Ordering example with FDA and (EC) 1935/2004 conformity.

FDA

All materials are suitable for contact with food.



Type + Material of the O-rings = Ordering no.
5P8.873.1Y + 10 = 5P8.873.1Y.10

Ordering example with ATEX approval. FDA and (EC) 1935/2004 conformity.



FDA

Unit group/Category/Zones:


Ex II 1G Ex h IIB T6...T3 Ga

Ex II 1D Ex h IIIC T85 °C...T170 °C Da



Type + Material of the O-rings + ATEX = Ordering no.
5P8.873.1Y + 10 + EX = 5P8.873.1Y.10.EX

>> Extendable rotating cleaning nozzle PopUp Whirly Air Series 5P8/5P9, Vertical Duct & Tower




Features:


- Self-draining
- For cleaning spray shadow areas
- Dry blowing with compressed air possible
- Operation with steam possible (SIP)
- Vacuum in the container allowed, thanks to double-acting pneumatic cylinder
- Optional end position monitoring with sensors
- Particularly hygienic (all threads encapsulated by O-rings)




Series




Tri-Clamp connection 5P8



Tri-Clamp connection 5P9



Installation situation/ prozessseitige Installation



Tri-Clamp connection



Maximum operating temperature
150 °C



Maximum ambient temperature
150 °C



Installation
Operation in every installation position



Bearing
Slide bearing



Material
Process and media contacting
Stainless steel 1.4404 (316L), Stainless steel 1.4571 (316Ti)
PTFE, FKM oder EPDM



Weight
2.2 kg



Surface quality
 $Ra \leq 0.8 \mu m$



Surface quality
 $Ra \leq 1,6 \mu m$



Steam suitability
Suitable



Recommended filter
Line strainer with mesh size of 0.3 mm/50 mesh



Recommended operating pressure
2 bar
Opening pressure approx. 1.6 bar, closing pressure approx. 0.3 bar



Maintainable

[Function video](#)

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.



Spray angle	Ordering no.			Narrowest cross-section Ø [mm]	V̇ water [l/min]			V̇ water
	Type	Material of the O-rings			p [bar] (p _{max} = 6 bar)			
		FKM	EPDM		1.0	2.0	3.0	at 2 bar [m³/h]
68° 	5P8.876.1Y.	10	20	1.3	11	15	18	0.9
	5P8.926.1Y.	10	20	1.6	14	20	25	1.2
	5P8.996.1Y.	10	20	2.3	21	30	37	1.8
	5P9.046.1Y.	10	20	2.5	28	40	49	2.4
	5P9.136.1Y.	10	20	4.0	42	60	73	3.6

Detailed information can be found in our brochure "Tank and Equipment Cleaning" as well as at www.lechler.com/de-en/tankcleaningnozzles.

Recommended accessories: see page 289 (Can be ordered separately).

Ordering example with FDA and (EC) 1935/2004 conformity.

All materials are suitable for contact with food.



Type + Material of the O-rings = Ordering no.
5P8.876.1Y + 10 = 5P8.876.1Y.10

Ordering example with ATEX approval. FDA and (EC) 1935/2004 conformity.

Unit group/Category/Zones:


Ex II 1 G Ex h IIB T6...T3 Ga

Ex II 1 D Ex h IIC T85 °C...T170 °C Da



Type + Werkstoff der O-Ringe + ATEX = Ordering no.
5P8.876.1Y + 10 + EX = 5P8.876.1Y.10.EX

Extendable rotating cleaning nozzle PopUp Whirly Air Hygienic Series 5P7




Features:


- Position indication by means of sensor (IO-link capable)
- Self-draining in almost any orientation
- Pneumatically extendable, independent of liquid pressure
- Flushable with air
- Installation flush with wall
- No additional installations in the process area




Series 5P7



Tri-Clamp flange




Installation situation



Weld-on nipple for threaded connection

To connect the nozzle on the process side, the weld-in flange 500.605.1Y.00.08 and the retaining nut 095.011.1Y.00.89 (can be ordered from Lechler as an option) are required. The O-ring in the front area of the nozzle in conjunction with the weld-in flange ensures a reliable and hygienic seal.



Weld-on nipple

Ordering no.: 500.605.1Y.00.08

Material: Stainless steel 1.4404 (316L)

Retaining nut

Ordering no.: 095.011.1Y.00.89

Material: Stainless steel 1.4404 (316L)

Technical data:



Maximum operating temperature
95 °C



Maximum ambient temperature
65 °C



Installation
Operation in every installation position



Bearing
Slide bearing made of PEEK



Material
Stainless steel 1.4404 (316L), stainless steel 1.4301 (304), PEEK, PTFE, FKM, EPDM



Weight:
4.5 kg



Surface quality
Ra ≤ 1.6 on process side



Surface quality
Ra ≤ 1.6 µm



Steam suitability
Not suitable



Recommended filter
Line strainer with a mesh size of 0.3 mm/50 mesh



Recommended operating pressure
2.5 bar



Maintainable

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.




Spray angle	Ordering no.	V̇ water [l/min]					V̇ water
	Type	p [bar] (p _{max} = 6 bar)					
		1.0	2.0	2.5	3.0	5,0	at 2.5 bar [m³/h]
60° 	5P7.074.1Y.00	34.2	48.3	54.0	59.2	76.4	3.2

Detailed information can be found in our brochure "Tank and Equipment Cleaning" as well as at www.lechler.com/de-en/tankcleaningnozzles.

Information on operation

Use above the recommended pressure will have a negative influence on the cleaning result and wear.

>> Extendable static cleaning nozzle PopUp Clean Series 5P5



Features:


- Cleaning nozzle extends automatically depending on pressure
- Flush wall installation possible
- For cleaning agitators and other spray shadow areas
- Compact, robust design




**ATEX version
on request**




Series 5P5




Male threaded connection



Male threaded connection




Tri-Clamp-Anschluss




Tri-Clamp connection

Installation situation




Threaded connection



Tri-Clamp connection

Weld-in socket for threaded connection


The thread is hygienically encapsulated with two O-rings (included in the scope of delivery of the PopUp Clean).



Ordering no.: 050.020.1Y.AQ.00
Material: Stainless steel 316L

Weld-in flange for Tri-Clamp connection

A joint clamp in accordance with DIN 32676-A DN50 with a connection diameter of 50.5 mm is required for connection of the nozzle at the weld-in flange. A gasket with a thickness of 2 mm is required if the flange is used in combination with the PopUp Clean.



Ordering no.: 050.020.1Y.01.00
Material: Stainless steel 316L



Max. temperature
95 °C



Installation
Operation in every direction is possible



Bearing
Slide bearing



Material
Stainless steel 316L,
stainless steel 316Ti,
FKM or 2.4602 (Alloy 22),
2.4610 (Alloy 4), FKM



Recommended operating pressure
2 bar
Opening pressure: approx.
0.3 bar, closing pressure:
approx. 0.3 bar



Filtration
Line strainer with a mesh
size of 0.3 mm/50 mesh

Function video

www.lechler.com/de-en/medialibrary/videos-general-industry

Or scan the QR code.



Spray angle	Ordering no.					V̇ water [l/min]				
	Type	Material no.		Connection		p [bar] (p _{max} = 5 bar)				
		1Y	21							
		1.4404 (316L)	2.4602 (Alloy 22)	1 1/4 BSPP male	Tri-Clamp	1.0	2.0	3.0	5.0	at 40 psi [US gal/min]
30° 	5P5.081	●	●	AP	00	35	50	61	79	16

Detailed information can be found in our brochure "Tank and Equipment Cleaning" as well as at www.lechler.com/de-en/tankcleaningnozzles.

Information on operation

- The PopUp Clean is not suitable for operation with compressed air or another gas.
- Use above the recommended pressure will have a negative influence on the cleaning result and wear.

Ordering Type + Material no. + Code = Ordering no.
example: 5P5.081 + 1Y + AP = 5P5.081.1Y.AP

Adapter HygienicFit Series 05C



Features:


- Hygienic threaded connection between equipment and nozzle
- Available for many thread sizes
- Weld-on side suitable for common pipe standards
- O-rings ensure a leak-tight connection
- O-rings fully encapsulate the thread

Note:

The HygienicFit adapter must not be used in conjunction with an ATEX-approved rotary cleaner in the ATEX area.



Series 05C



Max. temperature
150 °C



Installation
Operation in every direction is possible



Material
1.4404 (316L),
EPDM (O-Ring)



If you find this icon on our product pages, this means that the nozzle is compatible with the HygienicFit adapter.

Ordering no.		Dimensions [mm]						Pipe standard
Type	Connection thread BSPP male	L ₁	L ₂	L ₃	Ø D ₁	Ø D ₂	Ø D ₃	
05C.190.1Y.AE.16	3/8	48.00	35.70	18.00	19.05	15.80	21.50	DIN EN 10357 series D
05C.230.1Y.AE.15	3/8	48.00	35.70	18.00	23.00	20.00	21.50	DIN EN 10357 series A
05C.250.1Y.AE.12	3/8	48.00	35.70	17.00	25.00	22.60	21.50	DIN EN 10357 series D
05C.250.1Y.AG.12	1/2	56.00	39.00	18.00	25.00	22.60	31.00	DIN EN 10357 series D
05C.350.1Y.AK.15	3/4	55.00	37.80	21.00	35.00	32.00	33.50	DIN EN 10357 series A
05C.380.1Y.AK.12	3/4	55.00	37.80	18.00	38.00	35.60	33.50	ISO 2037
05C.381.1Y.AK.15	3/4	55.00	37.80	18.00	38.10	35.10	33.50	DIN EN 10357 series D
05C.381.1Y.AM.16	1	59.00	39.00	23.00	38.10	34.90	40.50	DIN EN 10357 series D
05C.508.1Y.AP.15	1 1/4	57.00	38.00	22.00	50.80	47.80	49.40	DIN EN 10357 series D
05C.635.1Y.AR.16	1 1/2	63.00	44.00	22.00	63.50	60.30	56.00	DIN EN 10357 series D

Spare parts set of O-rings, EPDM

Thread type BSPP	Ordering no.
3/8	05C.000.E9.AE.00
1/2	05C.000.E9.AG.00
3/4	05C.000.E9.AK.00
1	05C.000.E9.AM.00
1 1/4	05C.000.E9.AP.00
1 1/2	05C.000.E9.AR.00

O-ring set also available in FKM on request.



Features:

Cleaning procedures can be monitored easily and reliably with the Lechler rotation monitoring sensor. The sensor records the quantity of liquid flowing past the sensor tip. With the aid of software¹, the sensor function can be specifically adjusted to the tank size, pressure and nozzle.

Electrical data:

- Supply voltage:
U_b = 24 V +/-20% (18 to 32 VDC)
- Power requirements: < 20 mA
- Output signal: PNP, 50 mA, short circuit protected, active

Operating conditions:

- Ambient temperature:
-10 °C to +60 °C
- Process temperature:
0 °C to +100 °C

Materials:


- Socket (1/2 BSPP):
Stainless steel 316L
- Probe tip: PEEK
- Housing: Stainless steel 303

Operating principle:

- Capacitive

Advantages:

- Reliable recognition of any faults during the cleaning cycle
- The process connection of the sensor is in compliance with the hygiene guidelines of EHEDG
- Simple operation
- Can be connected to a PLC
- Only needs to be set up once using the software provided
- Can be specifically adapted to each cleaning task



Rotation monitoring sensor, incl. weld-in sleeve



Cable set for commissioning



Mains adapter



USB adapter with cable



Programming adapter Y-piece



Weld-in mandrel




If you find this icon on our product pages, this means that the nozzle is compatible with the rotation monitoring sensor.


Ordering data	Ordering no.
Rotation monitoring sensor, incl. weld-in sleeve	050.040.00.00.00
Cable set for commissioning	050.040.00.00.01

¹ Software download (free):
www.lechler.com/de-en/software/rotatingcontrolsystm






NOZZLE-VALVE COMBINATIONS



» NOZZLE-VALVE COMBINATIONS

VarioSpray SYSTEMS



Innovative and flexible spraying solutions opens up for new application areas.

Faster, precisely, more sustainable: The demand for more efficient production processes is increasing in almost every industry. Even already extremely efficient spraying technology processes are affected – particularly when spraying very small liquid volumes. Pneumatic systems are often used here, as very small flow rates can be achieved by using compressed air. However, the control and installation activities are extremely complex. Additionally, the use of air can have an unfavourable effect on operating costs. Aerosols may also be formed and liquid is lost due to the rebound effect. With the VarioSpray HP and VarioSpray II hydraulic pulse-width-modulated nozzle-valve systems, Lechler offers two alternatives that are as versatile as they are reliable.

With hydraulic nozzle systems, the narrowest cross section of the spray nozzle determines the liquid flow rate. Due to economical and production-related reasons, the narrowest cross section can't be randomly minimized. Instead, we use flexible timing of the spray duration to achieve minimal flow rates – without the need for an expensive and complex pneumatic atomizing system. In addition to the VarioSpray HP and

VarioSpray II nozzle-valve systems, a control unit is also required to permit simple modification of the pulse-width and cycle frequency.

Applications

- Oil application for applying seasoning
- Web humidification
- Application of separating agent
- Humidification
- Coating
- Anti-scaffing


Your advantages

- Simple adjustment of the pulse-width and the cycle frequency
- Modular design and modular system
- Start/Stop signal (e.g. via light barrier)
- Individual valve control for VarioSpray HP
- Rinsing function



Good to know

Detailed information can be found in our brochure "VarioSpray" as well as at www.lechler.com/de-en/variospray.



Minimal amounts

Thanks to the use of pulse-width-modulated valves, even the smallest liquid quantities can be hydraulically atomized with maximum precision.

This control method permits:

- **Flexible and immediate response to changed ambient parameters (e.g. belt speed)**
- **Uniform jet and spray quality**
- **Further application benefits due to a significantly increased turn-down ratio**

Resource and cost savings

The aerosol-free atomization of smallest liquid volumes offers specific benefits for spray nozzle operation. The fact that no atomizing air is used means a huge reduction in rebound effects.

The following costs are reduced as a result:


- **Equipment cleaning**
- **Operating costs of extraction systems**
- **Liquid losses because the liquid being atomized is applied to the product in a more targeted manner**

Flexibility

The Lechler VarioSpray system is completely modular, allowing it to be adapted to individual requirements as flexibly as possible.

The result is a perfectly coordinated product portfolio including:



- **Optimum valve control due to perfectly matched electronic components**
- **Modular spray bars**
- **Various predefined Lechler control concepts**
- **Individual advice from our sales staff**



What is pulse-width modulation?

Pulse-width modulation refers to the variation of the ON time t_{on} / OFF time t_{off} of a square-wave signal when the frequency f remains constant. Here, the frequency f corresponds to the reciprocal value of the period duration T .

The ratio of the ON time t_{on} to the period duration T is referred to as the pulse-width ratio (DC = duty cycle). The pulse-width ratio determines the flow rate. The valve is open during the ON time t_{on} . The shorter the DC, the less the flow rate. Depending on the frequency selected, the pulsation is barely visible to the human eye.



Which fluids can be sprayed?

The two innovative Lechler products VarioSpray HP and VarioSpray II can be used to precisely spray a wide range of different liquids. The two nozzle-valve systems are individually designed to optimally perform these tasks.


VarioSpray HP was developed to permit flexible spraying of a wide variety of liquids. Even high-viscosity media (up to 75 mPas, depending on the liquid density) can be easily atomized.

VarioSpray II is ideal for applying small volumes of low-viscosity, easily atomized liquids.

Sprayable liquids

VarioSpray HP	VarioSpray II
Water	
Low-viscosity separating agent	
Disinfectant	
Oils	–
Fats	–
Emulsions	–
Liquid egg	–
Milk	–
Sugar solutions	–
etc.	–

COMPARISON VarioSpray HP – VarioSpray II



VarioSpray HP High Performance

Flow rate: Up to 1,000 ml/min at 3 bar¹

For high viscosity media up to 75 mPa·s

Liquid supply at the rear

Flow-optimised liquid supply

Simple nozzle changeover

Turn-down ratio up to 29 : 1

Filter optionally available

**Push-in connection for
8 mm hose diameter**

**Voltage 12 V DC/24 V DC for Peak & Hold
activation**

Electrical connection via M8 slip-on connection

Control via colour touch panel

Two control unit versions:

- **SMART (max. 8 valves)**
- **FLEX (max. 16 valves)**

Individual valve control (FLEX)

Frequencies: 10/20/30/40/50/75/100/200 Hz

VarioSpray II

Flow rate: Up to 140 ml/min at 3 bar¹

For low viscosity media up to 15 mPa·s

Liquid supply at the side

Low liquid volume in the valve

Very small design

Turn-down ratio up to 11 : 1

Integrated last-chance filter

**Push-on connection
for 6 × 1 mm hose diameter**

Voltage 24 V DC

M8 slip-on connection


Compact control unit

**Simple operation
(max. 8 valves)**

All valves activated simultaneously

Frequencies: 25/50/75/100 Hz




¹ Nominal flow rate without nozzle.



VarioSpray HP

High Performance

The HP series can be used to atomise a wide variety of liquids. All parts that come into contact with liquids are made of stainless steel, thereby complying with Directives EC 1935/2004 and FDA regulations.



Components and combination options




Individual valve



Combination example
of the components


Good to know

Detailed information on VarioSpray HP along with the order numbers of the system components can be found in our brochure "VarioSpray". A PDF is available for download at www.lechler.com/de-en/variospray



VarioSpray II


Nozzle valves of the VarioSpray II series can efficiently atomise the smallest liquid volumes. Their size makes these valves ideal for use in tight spaces. The VarioSpray II system is also available as a food grade version, thereby complying with Directives EC 1935/2004 and FDA regulations.




Components and combination options



Individual valve



Assembly tool




Combination example of the components

Good to know

Detailed information on VarioSpray II along with the order numbers of the system components can be found in our brochure "VarioSpray". A PDF is available for download at www.lechler.com/de-en/variospray

NOZZLE VALVE SERIES 166H



The stainless steel housing in combination with a solenoid valve offers the possibility to clock the spray application flexibly.

Applications:


- Cleaning
- Surface treatment
- Humidification
- Lubrication processes

Scope of supply:

- Nozzle valve with housing, retaining nut and a 5 m long plugged power cable
- Nozzle must be ordered separately



Series 166H



Material:

Housing: Stainless steel 316L
Inner parts: Stainless steel 316L,
stainless steel 304,
stainless steel 434
Gasket material: FKM
(conforms to FDA)

Water flow rate:

Max. 6.5 l/min at 5 bar

Max. operating pressure:

10 bar

Power:

8 W

Voltage:

24 V DC

Protection class:

IP 65

Max. switching frequency:

500/min at 5 bar


	Type	Nozzle size up to	Spray character	Spray angle/Material
	652	64x	Flat fan	Page 118
	684	608	Flat fan (tongue-type nozzle)	Page 134
	468/494	68x	Full cone spray	Page 92
	226	285	Hollow cone	Page 67

Your advantages

- Quick and simple nozzle assembly using a retaining nut guarantees an easy nozzle changeover
- Simple spray alignment
- Flexible design that allows the use of flat fan nozzles, hollow cone nozzles and full cone nozzles
- With integrated gasket for sealing between the nozzle and the valve

Ordering no.
166.000.1Y.H1.00

POSITIONABLE FLAT FAN NOZZLE FOR SERIES 166H AND VarioSpray HP





Properties:

- Outer geometry of the nozzle housing fluidically optimised for pulsed operation
- Positioning takes place via the attached dovetail
- Nozzle sizes and spray angles identical to standard nozzle series 652



Series 652.xxx.16.56




Type	Nozzle size up to	Spray character	Spray angle	Material
652.xxx.16.56	64x	Flat fan	Page 118	303 SS

Please refer to the data of series 652 on w for the nozzle size (flow rate and spray angle).

Ordering Type + Nozzle size = Ordering no.
example: 652.xxx.16.56 + 301 = 652.301.16.56




ACCESSORIES




NOZZLE FASTENING ASSEMBLING OPTIONS FOR ALL PURPOSES




Assembly accessories for nozzles without thread or with female thread




Bayonet quick-release system for nozzles without thread or with bayonet connection



Bayonet quick-release system with ball joint for nozzles with male thread




Assembly accessories for nozzles with male thread







Assembly accessories for nozzles with dovetail version





Assembly accessories for nozzles with integrated ball joint



TWISTLOC quick-release system for nozzles without thread




MEMOSPRAY/Easy-Clip combination options



Eyelet clamps with male thread



Eyelet clamps with male thread




Series	Ordering no.				Screw (material)	G BSPP	Pipe Ø	Dimensions [mm]							Weight [g] (polyamide)	
	Type	Mat. no.						B ₁	B ₂	B ₃	H ₁	H ₂	Ø B _R ¹	Ø B ²		Ø D
		51 Black	53 White	5E Blue												
		Polyam- ide	Polypro- pylene	PVDF												
226/2TR/ 216/302/ 308/350/468/ 652/679/684	090.053	●	●	●	Stainless steel 304	3/8	3/8"	19.0	22.0	18.5	34.5	14.5	6.0	6.2-6.4	16.5–18.0	20.0
	090.003	●	●	●		3/8	1/2"	21.2	23.8	18.5	36.5	16.5	6.0	6.2-6.4	20.0–22.0	20.0
	090.013	●	●	●		3/8	3/4"	24.5	26.5	22.0	39.5	17.5	7.6	7.8-8.0	25.0–27.5	25.0
	090.023	●	●	●		3/8	1"	30.0	31.0	22.0	44.0	21.0	10.6	10.8-11.0	32.0–34.5	32.0
	090.033	●	●	●		3/8	1 1/4"	34.0	35.5	25.0	48.0	25.0	12.6	12.8-13.0	40.0–43.0	38.0

¹ Ø B_R = spigot diameter.

² Ø B = recommended bore diameter.

Retaining nuts for eyelet clamps



Series	Ordering no.						G BSPP	Dimensions [mm]				Weight [g]
	Type	Mat. no.						H ₁	H ₂	Ø D	Hex	
		16	17 ¹	30	56 Black	5E Blue						
		Stainless steel 303	Stainless steel 316Ti	Brass	POM	PVDF						
226/2TR/ 468/548/ 652/660/679/ 684	065.200	●	●	●			3/8	13.0	10.0	12.8	22	25.0 (Brass)
	065.200				●	●	3/8	14.5	11.5	12.8	22	5.0 (PVDF)

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.


Ordering Type + Material no. = Ordering no.
example: 090.053 + 51 = 090.053.51

Strainers and ball-type non-return valves can be found on Page 284/285.

Eyelet clamps with female thread



Eyelet clamps
with female thread



For all nozzles with	Ordering no.						Screw (material)	Pipe Ø	Dimensions [mm]									Weight [g] (polyam- ide)
	Type	Mat. no.			Code													
		51 Black	53 White	5E Blue														
		Poly- amide	Polypro- pylene		1/8 BSPP	1/4 BSPP			B ₁	B ₂	B ₃	H ₁	H ₂	L	Ø B _R ¹	Ø B ²	Ø D	
Male thread 1/8 BSPP 1/4 BSPP	090.100	●	●	●	AB	AD	Stainless steel 316	3/8"	20.0	23.0	18.5	28.0	14.0	12.0	6.0	6.2–6.4	16.5–18.0	18.0
	090.110	●	●	●	AB	AD		1/2"	22.0	25.0	18.5	31.0	16.0	12.0	6.0	6.2–6.4	20.0–22.0	19.0
	090.120	●	●	●	AB	AD		3/4"	25.0	28.0	22.0	33.0	19.0	12.0	7.6	7.8–8.0	25.0–27.5	24.0
	090.130	●	●	●	AB	AD		1"	30.0	33.0	22.0	36.0	23.0	12.0	10.6	10.8–11.0	32.0–34.5	34.0
	090.140	●	●	●	AB	AD		1 1/4"	34.0	37.0	25.0	40.0	28.0	12.0	12.6	12.8–13.0	40.0–43.0	39.0

¹ Ø B_R = spigot diameter.


² Ø B = recommended bore diameter.

Ordering Type + Material no. + Code = Ordering no.
example: 090.100 + 51 + AB = 090.100.51.AB

Eyelet clamps with bayonet connection



Eyelet clamps with bayonet quick-release system




Series	Ordering no.					Screw (material)	Pipe Ø	Dimensions [mm]								Weight [g] (Polyamide)
	Type	Mat. no.			Code											
		51 Black	53 White	5E Blue												
		Poly- amide	Polypro- pylene	PVDF				B ₁	B ₂	B ₃	H ₁	H ₂	Ø B _R ¹	Ø B ²	Ø D	
226/2TR/ 302 bayonet/ 422 bayonet/ 468/652/646/ 684/679	090.003	●	●	●	KA	Stainless steel 304	1/2"	21.2	23.8	18.5	49.5	16.5	6.0	6.2–6.4	20.0–22.0	22.0
	090.013	●	●	●	KA		3/4"	24.5	26.5	22.0	52.5	17.5	7.6	7.8–8.0	25.0–27.5	26.0
	090.023	●	●	●	KA		1"	30.0	31.0	22.0	57.0	21.0	10.6	10.8–11.0	32.0–34.5	32.0

¹ Ø B_R = spigot diameter.

² Ø B = recommended bore diameter.

Diaphragm non-return valve with bayonet quick-release system



Series	Ordering no.			Screw (material)	Pipe Ø	Ø D [mm]	Pressure [bar]		Dimensions [mm]				Weight [g]
	Type	Mat. no.	Code						H ₁	H ₂	Ø B _R ¹	Ø B ²	
		POM					Opening pressure	Closing pressure					
226/2TR/ 302 bayonet/ 422 bayonet/ 468/652/646/ 684/679	065.272	●	KH	Stainless steel 303	1/2"	20.0–22.0	0.8	0.6	59.0	84.0	6.0	6.2–6.4	48.0
	065.272	●	KL		3/4"	25.0–27.5	0.8	0.6	66.0	90.0	9.6	9.8–10.0	53.0

¹ Ø B_R = spigot diameter.

² Ø B = recommended bore diameter.


Material	Max. temperature [°C]	Max. pressure [bar]
PA, PP, PVDF, POM	65	10
PA, PP, PVDF, POM	80	8
PVDF	100	4

Notice: Please consider the material combination when using bayonet eyelet clamps with bayonet quick-release system nuts. The nuts may be difficult to turn when using different materials.

Accessories for bayonet system



Bayonet welded nipple




Twist angle to the right in relation to the pipe axis. Twist angle 10°. Other twist angles available on request.

Series	Ordering no.		Mat. no.		Dimensions [mm]		Weight [g]
			50	53			
	Type		PVC	Polypropylene	L	R	
226/2TR/302 bayonet/ 422 bayonet/468/ 652/646/684/679	095.016.xx.08.05 ¹		●	●	25.0	16.0	10.0

¹ Replace "xx" with the desired material no.

Strainer with gasket


Suitable for bayonet quick-release system nuts 065.202



Performance size	Ordering no.		Colour	Dimensions [mm]					Weight [g]
				Mesh size	H ₁	H ₂	Ø D ₁	Ø D ₂	
xxx.32x-xxx.44x	065.268.7J.25	●	Red	0.3	19.2	3.0	18.0	12.0	2.0
xxx.48x-xxx.56x	065.268.7J.60	●	Blue	0.5	19.2	3.0	18.0	12.0	2.0

Bayonet quick-release system nuts


Incl. gasket 065.242.73 (material: Rubber)



Series	Ordering no.				Colour	Weight [g]
	Type	Mat. no.				
		POM	Polypropylene	PVDF		
652/679	065.202.56.00	●			Red	10.0
	065.202.53.00		●		Grey	10.0
	065.202.5E.00			●	Blue	10.0

Bayonet quick-release system nuts

Incl. gasket 065.242.73 (material: Rubber)



Series	Ordering no.			Colour	Weight [g]
	Type	Mat. no.			
		POM	Polypropylene		
226/2TR/ 468/684	065.202.56.11	●		Black	10.0
	065.202.53.11		●	Grey	10.0


Notice: Please consider the material combination when using bayonet eyelet clamps with bayonet quick-release system nuts. The nuts may be difficult to turn when using different materials.



Ball joints for bayonet quick-release system

Ball joint system for nozzles with 1/8" and 1/4" male thread.


Ball joint for eyelet clamps with bayonet quick-release system




For all nozzles with 1/8" or 1/4" male thread	Ordering no.				Colour	Weight [g]
	Type	Mat. no.	Code			
		PVDF	1/8 BSPP	1/4 BSPP		
Ball joint	092.150	5E	AB	AD	Blue	5.0

Bayonet quick-release system nut for ball joint

Incl. O-ring
Ordering no. 095.015.7C.04.16
(material: 72 NBR 872)



For all nozzles with 1/8" or 1/4" male thread	Ordering no.		Colour	Weight [g]
	Type	Mat. no.		
		PVDF		
Quick-release system nut	092.150.5E.00	●	Blue	28.0



Max. temperature [°C]	Max. pressure [bar]
65	10
80	8
100	4

Ordering Type + Material no. + Code = Ordering no.
example: 092.150 + 5E + AB = 092.150.5E.AB

TWISTLOC Quick-change nozzle system






Lechler TWISTLOC, nozzle changing in less than no time.

Save time and money with the quick-change nozzle system.

- **Quick:**
It takes just one twist to install or remove the nozzle.
- **Easy:**
Can be installed without tools – even in difficult-to-access locations and in bad lighting conditions.
- **Safe:**
Installation errors are avoided, as the nozzles are always set to the correct direction.
- **Max. pressure:**
15 bar.




System components		Ordering no.							Inner Ø D [mm]	Weight [g]			
		Type	Mat. no.				Code						
			1C	16	5E	7A							
			Stainless steel 304	Stainless steel 303	PVDF	Viton	1/4 BSPT	3/8 BSPT				Welded connec- tion	
Threaded nipple		092.102		●			CC			8.0	25.0	 Non-return valves, strainers For installation in nipples with inner Ø 11.6 mm (see Page 284/285).	
		092.102		●				CE			11.6		25.0
		092.102			●			CE			8.0		10.0
Welded nipple		092.104	●						00	11.6	45.0		
Gasket for material 304 SS and 303 SS		092.113				●				–	1.0		
Gasket for material PVDF		092.115				●				–	1.0		
Gasket, incl. rubber gasket ring for use with non-return valves or strainers		092.116				●				–	2.0		
Gasket, incl. rubber gasket ring for use with non-return valves or strainers, for PVDF material		092.114				●				–	2.0		
Quick-release system For nozzle series 652/679		092.106		●	●					–	20.0 (stainless steel)		
Quick-release system For nozzle series 226/494/684		092.108		●	●						–	20.0 (stainless steel)	

Ordering Type + Material no. + Code = Ordering no.
example: 092.102 + 16 + CC = 092.102.16.CC




Sockets



For all nozzles with	Ordering no.					G BSPP	Dimensions [mm]				Weight [g] (Brass)
	Type	Mat. no.					H ₁	H ₂	Ø D	Hex	
		1Y	17	30	53						
		Stainless steel 316L	Stainless steel 316Ti	Brass	Polypropyl- ene						
1/8" male thread	040.270	●		●		1/8	20.0	10.0	13.8	14	20.0
1/4" male thread	061.220	●		●		1/4	20.0	10.0	16.8	17	20.0
3/8" male thread	040.271	●		●		3/8	20.0	10.0	21.8	22	25.0
	040.271				●	3/8	20.0	11.0	25.0	22	25.0
1/2" male thread	040.272		●	●		1/2	30.0	15.0	26.5	27	70.0
3/4" male thread	061.620		●	●		3/4	40.0	20.0	31.5	32	108.0

Notice: Sockets are also suitable for welding.

Sockets with radius




For all nozzles with	Ordering no.		G BSPP	Dimensions [mm]			Weight [g]
	Type	Mat. no.		H ₁	H ₂	Ø D	
		1Y					
		Stainless steel 316L					
1/4" male thread	040.228.1Y.yy ¹	●	1/4	18.0	12.0	17.0	16.0

¹ Replace "yy" with the desired radius R (R = 10/13/16/20/25 or 31 mm).

Ordering Type + Material no. = Ordering no.
example: 040.270 + 1Y = 040.270.1Y



Sockets



Connection components	Ordering no.			G ₁ BSPP	G ₂ BSPP	Dimensions [mm]			Weight [g] (Brass)
	Type	Mat. no.				L ₁	L ₂	Hex	
		17	30						
		Stainless steel 316Ti	Brass						
1/8" to 3/8"	040.211	●	●	1/8	3/8	20.0	10.0	22	40.0
1/4" to 3/8" short	065.221	●	●	1/4	3/8	23.0	10.0	22	40.0
1/4" to 3/8" long	065.228	●	●	1/4	3/8	36.0 ¹	14.0	19	45.0
3/8" to 3/8"	065.220	●	●	3/8	3/8	25.0	10.0	22	40.0
3/4" to 3/4"	065.620	●	●	3/4	3/4	35.0	14.0	32	280.0

¹ Mounting of nozzle filters and ball-type non-return valves possible (see Page 284/285).

Reduction socket




Connection components	Ordering no.			G ₁ BSPP	G ₂ BSPP	Dimensions [mm]			Weight [g]
	Type	Mat. no.							
		1Y	30						
		Stainless steel 316L	Brass			L ₁	L ₂	Hex	
3/8" to 1/4"	095.019.30.00.23			3/8	1/4	26.0	12.0	22	55.0

Ordering Type + Material no. = Ordering no.
example: 040.211 + 17 = 040.211.17




Welded nipple with dovetail guide



Series	Ordering no.		G BSPP	Dimensions [mm]				Weight [g]
	Type	Mat. no.		H ₁	H ₂	Ø D ₁	Ø D ₂	
		17						
		Stainless steel 316Ti						
660	066.011	●	3/8	18.0	11.5	16.5	8.0	21.0
664/665	066.410	●	3/4	27.0	15.5	28.0	14.0	65.0


Welded nipple



Series	Ordering no.					G BSPP	Dimensions [mm]				Weight [g] (Brass)
	Type	Mat. no.					H ₁	H ₂	Ø D ₁	Ø D ₂	
		02	17	30	53						
		Steel	Stainless steel 316Ti	Brass	Polypro- pylene						
226/216/2TR/302/308/350/ 468/652/684/548/679	065.210	●	●	●	●	3/8	18.0	10.0	17.2	11.6	20.0
306/307/502/ 503/656/657	065.610	●	●		●	3/4	27.0	14.0	28.0	18.0	61.0

Ordering Type + Material no. = Ordering no.
example: 066.011 + 17 = 066.011.17


Welded nipple with radius



Series	Ordering no.		G BSPP	Dimensions [mm]				Weight [g]
	Type	Mat. no.		H ₁	H ₂	Ø D ₁	Ø D ₂	
		17						
		Stainless steel 316Ti						
226/216/2TR/302/308/350/ 468/652/684/548/679	065.217.17.yy ¹	●	3/8 A	15.0	10.0	17.2	11.5	20.0
306/307/502/503/656/657	065.612.17.yy ¹	●	3/4 A	23.0	14.0	28.0	18.0	61.0

¹ Replace "yy" with the desired radius R (R = 10/13/16/20/25 or 31 mm).

Double nipple



Series	Ordering no.			G ₁ BSPP	G ₂ BSPP	Dimensions [mm]						Weight [g] (Brass)
	Type	Mat. no.				H ₁	H ₂	H ₃	Ø D ₁	Ø D ₂	Hex	
		17 Stainless steel 316Ti	30 Brass									
226/216/2TR/ 302/308/350/ 468/652/684/ 548/679	065.215 ¹	●	●	3/8	1/4	25.0	10.0	10.0	10.0	7.0	22	30.0
	065.215.xx.02 ²	●	●	3/8	1/4	35.0	10.0	10.0	11.6	7.0	22	32.0
	065.211	●	●	3/8	3/8	25.0	10.0	10.0	11.5	–	22	25.0
	065.211.xx.04 ²	●	●	3/8	1/2	30.0	10.0	14.0	11.5	–	27	62.0
306/307/502/503/ 656/657	065.611	●	●	3/4	3/4	35.0	14.0	14.0	18.0	–	32	90.0

¹ Not to be used with non-return valve or strainer.


² Replace "xx" with the desired material no.

Ordering Type + Material no. = Ordering no.
example: 065.217.17.yy + 17 = 065.217.17.yy.17

Ball joints with threaded connection




Ball joints with female thread




For all nozzles with	Ordering no.				G ₁ BSPP	G ₂ BSPP	Dimensions [mm]						Weight [g] (Brass)
	Type	Mat. no.		Code									
		16	30										
		Stainless steel 303	Brass				L	L _{G1}	L _{G2}	Hex ₁	Hex ₂	Flats	
1/8" male thread	092.010	●	●	AB	1/8	1/8	43.1	8.0	8.0	22	24	13	110.0
1/4" male thread	092.020	●	●	AD	1/4	1/4	60.3	12.0	11.5	27	27	17	200.0
	092.021	●	●	AF	3/8	1/4	58.3	12.0	11.5	27	27	17	160.0
3/8" male thread	092.030	●	●	AF	3/8	3/8	56.0	12.0	12.0	27	30	19	185.0
1/2" male thread	092.040	●	●	AH	1/2	1/2	71.0	15.5	15.5	36	41	24	425.0
3/4" male thread	092.050	●	●	AL	3/4	3/4	80.0	17.0	17.0	41	46	30	595.0

Ball joints with male thread



Series	Ordering no.				G ₁ BSPP	G ₂ BSPP	Dimensions [mm]						Weight [g] (Brass)
	Type	Mat. no.		Code									
		16	30										
		Stainless steel 303	Brass				L	L _{G1}	L _{G2}	Hex ₁	Hex ₂	Flats	
226/216/2TR/ 302/308/350/ 468/652/684/ 548/679	092.022	●	●	AD	1/4	3/8	64.0	12.0	10.0	27	27	17	135.0
	092.022	●	●	AF	3/8	3/8	62.0	12.0	10.0	27	27	17	165.0

Compact ball joints




For all nozzles with	Ordering no.				G ₁ BSPP	G ₂ BSPP	Dimensions [mm]					Weight [g] (Brass)
	Type	Mat. no.		Code								
		16	30									
		Stainless steel 303	Brass				L	L _{G1}	L _{G2}	Hex ₁	Hex ₂	
1/8" male thread	092.010	●	●	AA	1/8	1/8	29.3	8.0	8.0	22	24	70.0
1/4" male thread	092.024	●	●	AC	1/4	1/4	44.0	12.0	12.0	27	27	140.0
3/8" male thread	092.030	●	●	AE	3/8	3/8	44.0	12.0	12.0	27	30	160.0

Ordering Type + Material no. + Code = Ordering no.
example: 092.010 + 16 + AB = 092.010.16.AB

Ball joints with welding connection




Ball joints with
welding connection and
female thread



For all nozzles with	Ordering no.				G BSPP	Dimensions [mm]						Weight [g] (Brass)
	Type	Mat. no.		Code								
		16	30									
		Stainless steel 303/ 316Ti	Brass/ Stainless steel 1.0159			L	L _G	Ø D ₁	Ø D ₂	Hex	Flats	
1/8" male thread	092.010	●	●	SB	1/8	43.0	8.0	18.0	12.0	24	13	70.0
1/4" male thread	092.020	●	●	SD	1/4	64.5	11.5	20.0	15.0	27	17	150.0
3/8" male thread	092.030	●	●	SF	3/8	59.0	12.0	22.0	15.0	30	19	165.0
1/2" male thread	092.040	●	●	SH	1/2	71.1	15.5	22.0	15.0	41	24	350.0
3/4" male thread	092.050	●	●	SL	3/4	74.8	17.0	22.0	18.0	46	30	470.0

Ball joints with
welding connection and
male thread




Series	Ordering no.			G BSPP	Dimensions [mm]						Weight [g]
	Type	Mat. no.	Code								
		16									
		Stainless steel 303/316Ti									
				L	L _G	Ø D ₁	Ø D ₂	Hex	Flats		
226/216/2TR/ 302/308/350/ 468/652/684/ 548/679	092.022	●	SE	3/8 A	68.0	10.0	20.0	15.0	27	17	155.0

Ordering Type + Material no. + Code = Ordering no.
example: 092.010 + 16 + SB = 092.010.16.SB

Accessories for nozzle series 676 with integrated ball joint




Threaded sockets



Series	Ordering no.			G BSPP	Dimensions [mm]			Weight [g] (Brass)
	Type	Mat. no.						
		16	30					
		Stainless steel 303	Brass					
					L ₁	L ₂	Hex	
676	092.020.xx.AF.03 ¹	●	●	3/8	20.0	10.0	27	50.0

¹ Replace "xx" by material no.

Threaded nipple




Series	Ordering no.			G BSPP	Dimensions [mm]				Weight [g] (Brass)
	Type	Mat. no.			L ₁	L ₂	L ₃	Hex	
		16	30						
		Stainless steel 303	Brass						
676	092.024.xx.AC.03 ¹	●	●	1/4	32.0	12.0	10.0	27	70.0

¹ Replace "xx" by material no.


Order Type + Material no. = Ordering no.
example: 092.020.xx.AF.03 + 16 = 092.020.16.AF.03

Welded nipple



Series	Ordering no.		Dimensions [mm]						Weight [g]
	Type	Mat. no.							
		17							
		Stainless steel 316Ti	L ₁	L ₂	L ₃	Ø D ₁	Ø D ₂	Ø D ₃	
676	092.020.17.00.04	●	26.0	14.0	4.0	20.0	15.0	11.0	45.0

Retaining nuts



Series	Ordering no.			Dimensions [mm]			Weight [g] (Brass)
	Type	Mat. no.					
		16	30				
		Stainless steel 303	Brass	L ₁	L ₂	Hex	
676	092.020.xx.00.02 ¹	●	●	20.0	10.0	27	35.0


¹ Replace "xx" by material no.

Notice: The assembly accessories shown can be used with the low pressure flat fan nozzle with ball joint (series 676) (see Page 140/141).

Order Type + Material no. = Ordering no.
example: 092.020.xx.00.02 + 16 = 092.020.16.00.02




Filter




Series	Nozzle size	Ordering no.		Colour	Dimensions [mm]					Weight [g]
		Type	Mat. no.		Mesh size	H ₁	H ₂	Ø D ₁	Ø D ₂	
			56							
POM										
216/2TR/ 302/468/ 422 bayonet/ 652/646/684	xxx.32x-xxx.44x	065.257	●	Blue	0.3	21.4	2.0	14.8	11.0	2.0
	xxx.48x-xxx.56x	065.256	●	Red	0.5	21.4	2.0	14.8	11.0	2.0

Filter



Series	Nozzle size	Ordering no.		Colour	Dimensions [mm]					Weight [g]
		Type	Mat. no.		Mesh size	H ₁	H ₂	Ø D ₁	Ø D ₂	
			53							
			Polypropylene							
216/2TR/ 302/468/ 422 bayonet/ 652/646/684	xxx.14x-xxx.36x	095.016.53.15.62 Strainer insert 304 SS		Light pink	0.08	21.00	1.60	15.00	11.00	1.00

Cup strainer



Series	Nozzle size	Ordering no.		Dimensions [mm]					Weight [g]
		Type	Mat. no.						
			26						
			Monel/Copper	Mesh size	H ₁	H ₂	Ø D ₁	Ø D ₂	
216/2TR/ 302/468/ 422 bayonet/ 652/646/684	xxx.32x-xxx.44x	065.252	●	0.5	8.5	1.6	14.8	9.0	1.0


Ordering Type + Material no. = Ordering no.
example: 065.257 + 56 = 065.257.56

Filters

with ball-type non-return valve




Ball-type non-return valve
with integrated filter
 $p_{max} = 20 \text{ bar}$



Series	Nozzle size	Ordering no.		Colour	Pressure [bar]		Dimensions [mm]					Weight [g]
		Type	Mat. no.									
			56		Opening pressure	Closing pressure	Mesh size	H ₁	H ₂	Ø D ₁	Ø D ₂	
216/2TR/ 302/468/ 422 bayonet/ 652/646/684	xxx.32x-xxx.44x	065.265 Ball 420 SS Spring 302 SS	●	Blue	0.40-0.50	0.35-0.45	0.30	21.40	2.00	14.80	11.00	2.00
	xxx.48x-xxx.56x	065.266 Ball 420 SS Spring 302 SS	●	Red	0.40-0.50	0.35-0.45	0.50	21.40	2.00	14.80	11.00	2.00

Ball-type non-return valve
with integrated filter




Series	Nozzle size	Ordering no.		Colour	Pressure [bar]		Dimensions [mm]					Weight [g]
		Type	Mat. no.									
			53		Opening pressure	Closing pressure	Mesh size	H ₁	H ₂	Ø D ₁	Ø D ₂	
216/2TR/ 302/468/ 422 bayonet/ 652/646/684	xxx.14x-xxx.36x	095.016.53.11.00 Strainer insert/ Ball 304 SS Spring 302 SS	●	Blue	approx. 0.50	approx. 0.30	0.08	21.00	1.60	15.00	11.00	2.00
	xxx.14x-xxx.36x	095.016.53.14.63 Strainer insert/ Ball 304 SS Spring 302 SS	●	Green	approx. 2.80	approx. 1.60	0.08	21.00	1.50	15.00	11.00	2.00

Ordering Type + Material no. = Ordering no.
example: 065.265 + 56 = 065.265.56

Retaining nuts and gaskets




Retaining nuts



Series	Ordering no.							G BSPP	Dimensions [mm]				Weight [g] (Brass)
	Type	Mat. no.							H ₁	H ₂	Ø D	Hex	
		16	17 ¹	1Y	30	56 Black	5E Blue						
		Stainless steel 303	Stainless steel 316Ti	Stainless steel 316L	Brass	POM	PVDF						
226/2TR/ 468/652/660/ 684/548/679	065.200	●	●		●			3/8	13.0	10.0	12.8	22	25.0
	065.200					●	●	3/8	14.5	11.5	13.0	22	25.0
	069.000	●		●	●			UNF 11/16	14.3	9.7	13.1	20.6	25.0
656/657/ 664/665	065.600	●	●		●		●	3/4	16.0	13.0	20.1	32	60.0

¹ We reserve the right to supply material 316Ti or 316L under material no. 17.

Gaskets



Series	Nozzle Code	Ordering no.					Dimensions [mm]	Weight [g]
		Type	Mat. no.					
			55	71	72	73		
			PTFE	Cu. ISO PL. 7504	EWP 210 (asbestos-free)	Soft rubber		
610	1/8 BSPP	061.040			●		Ø 10.00 x Ø 14.00 x 1.00	0.13
220/612	1/4 BSPP	061.240	●	● ¹	●		Ø 13.20 x Ø 17.00 x 1.00	0.20
490/491/ 460/461/ 616/617/689	3/4 BSPP	061.640		● ²	●		Ø 26.50 x Ø 32.00 x 1.00	0.50
405	1 1/4 BSPP	062.140			●		Ø 42.00 x Ø 50.00 x 1.00	1.20
405	2 BSPP	062.540			●		Ø 60.00 x Ø 70.00 x 2.00	3.92
226/468/652/ 684/679	Retaining nut 3/8	065.240	●		●	●	Ø 11.00 x Ø 15.00 x 1.00	0.14
656/657	Retaining nut 3/4	065.640			●		Ø 18.00 x Ø 24.00 x 1.00	0.50
PTFE sealing tape For connecting cylindrical female threads and tapered male threads BSPT		095.009.55.09.30.0					12 mm x 0.1 mm x 12 m	–

¹ Dimensions [mm] for mat. no. 71: 13.20 x 17.00 x 2.00.

² Dimensions [mm] for mat. no. 71: 26.50 x 32.00 x 2.50.

Ordering Type + Material no. = Ordering no.
example: 065.200 + 16 = 065.200.16


Strainers

Max. 12 bar



Standard strainer for industrial application

- For operating pressure levels up to 12 bar.
With large filter surfaces
- Mesh size is colour coded:
 - 0.6 mm = red
 - 0.3 mm = blue
 - 0.2 mm = green
- Easy handling
- Robust version
- Slender design



Type		Code BSPP	Dimensions [mm]					Weight [g]
			A	B	C	E	Ø D	
S.GA2.	S.GI2.	1/2	27.0	97.0	140.0	118.0	74.0	200.0
S.GA3.	S.GI3.	3/4	27.0	97.0	140.0	118.0	74.0	200.0
S.GA4.	S.GI4.	1	40.0	112.0	175.0	143.0	86.0	300.0
S.GA5.	S.GI5.	1 1/4	39.0	146.0	280.0	239.0	116.0	630.0
S.GA6.	S.GI6.	1 1/2	39.0	146.0	280.0	239.0	116.0	630.0


Pressure/Temperature ranges

Max. temperature [°C]	p _{max} [bar]
20	12
60	7

	Ordering no.		Standard strainer insert/Standard filter		
	Type	Size	Mat. no.	Mesh size [mm]	Type (blue)
			53 Polypropylene		
Male thread	S.GA2.	012.	●	0.3	S.000.012.00.26.03
	S.GA3.	034.	●	0.3	S.000.012.00.26.03
	S.GA4.	100.	●	0.3	S.000.100.00.26.03
	S.GA5.	114.	●	0.3	S.000.114.00.26.03
	S.GA6.	112.	●	0.3	S.000.114.00.26.03
Female thread	S.GI2.	012.	●	0.3	S.000.012.00.26.03
	S.GI3.	034.	●	0.3	S.000.012.00.26.03
	S.GI4.	100.	●	0.3	S.000.100.00.26.03
	S.GI5.	114.	●	0.3	S.000.114.00.26.03
	S.GI6.	112.	●	0.3	S.000.114.00.26.03

Optional strainer inserts			
Mesh size [mm]	Type (red)	Mesh size [mm]	Type (green)
0.6	S.000.012.00.26.06	0.2	S.000.012.00.26.02
0.6	S.000.012.00.26.06	0.2	S.000.012.00.26.02
0.6	S.000.100.00.26.06	0.2	S.000.100.00.26.02
0.6	S.000.100.00.26.06	0.2	S.000.100.00.26.02
0.6	S.000.114.00.26.06	0.2	S.000.114.00.26.02
0.6	S.000.114.00.26.06	0.2	S.000.114.00.26.02
0.6	S.000.012.00.26.06	0.2	S.000.012.00.26.02
0.6	S.000.012.00.26.06	0.2	S.000.012.00.26.02
0.6	S.000.012.00.26.06	0.2	S.000.012.00.26.02
0.6	S.000.100.00.26.06	0.2	S.000.100.00.26.02
0.6	S.000.114.00.26.06	0.2	S.000.114.00.26.02
0.6	S.000.114.00.26.06	0.2	S.000.114.00.26.02

Notice: Standard strainer insert (blue) included in the scope of supply.



Correction factors for Δp


Viscosity [mPa·s]	Basket – mesh size [mm]		
	0.6	0.3	0.2
1.0 (water)	1.0	1.2	1.4
100.0	1.6	1.9	2.0
200.0	1.7	2.2	2.3

Ordering Type + Size + Material no. = Ordering no.
example: S.GA2. + 012. + 53 = S.GA2.012.53



Strainer with high flow rate and low resistance

- Integrated flow deflector prevents clogging of the filter insert
- Dirt particles can be removed via an offset outlet port
- Prepared for the install of two pressure gauges




Strainer with screen

Ordering no.			Screen mesh size [µm/mesh]
Type	Size	Mat. no.	
		53	
		Polypropylene	
S.GA2.	300.	●	594/32
S.GA3.	300.	●	365/50
S.GA4.	300.	●	173/100
S.GA5.	300.	●	144/120

Screen

Ordering no.		Mat. no.		Screen mesh size [µm/mesh]
Type	Size	26	5A	
		Stainless steel 304	Polyester/ Stainless steel	
S.002.	300.00.	●		594/32
S.003.	300.00.	●		365/50
S.004.	300.00.	●		173/100
S.005.	300.00.		●	144/120

Pressure loss chart



Technical data

Screening surface	860 cm ²
Screening insert Ø	145 mm
Height of screening insert	320 mm
Inflow/Outflow port Ø	3"
Pressure gauge connection Ø	1/4 BSPP
Max. operating pressure	8 bar

Ordering example for strainer:

Ordering Type + Size + Material no. = Ordering no.
example: S.GA2. + 300. + 53 = S.GA2.300.53

Ordering example for strainer insert:

Ordering Type + Size + Material no. = Ordering no.
example: S.002. + 300.00. + 26 = S.002.300.00.26

PopUp Whirly Air Series 5P8/5P9



Recommended accessories can be ordered separately.

Sensor Options

Two sensors can be used to detect both end positions (one mounting kit is required per sensor)

Sensor	Specifications	max. temperature in °C	Ordering no.
1	PNP or NPN, nO or nC, M8	85	095.009.00.18.67.0
2	ATEX, PNP, nO, M8	85	095.009.00.19.14.0
3	REED, open cable end	120	095.009.00.19.15.0

Mounting kit sensor

Ordering no.

095.016.00.17.44.0

Material:

Stainless steel 1.4404 (316L), zinc casting

Medium connection

Available medium connections, one adapter is required per PopUp Whirly Air.

Other connections are available on request.

Adapter

Ordering no. 05P.830.1Y.00.01.0

Material: Stainless steel 1.4404 (316L)

Tri-Clamp DIN 32676

Outer-Ø 50,5 mm

Adapter

Ordering no. 05P.830.1Y.00.02.0

Material: Stainless steel 1.4404 (316L)

Tri-Clamp DIN 32676

Outer-Ø 64 mm

Adapter

Ordering no. 05P.830.1Y.00.03.0

Material: Stainless steel 1.4404 (316L)

Female thread

3/4 BSPP

Adapter

Ordering no. 05P.830.1Y.00.04.0

Material: Stainless steel 1.4404 (316L)

Hose connector for Inner-Ø 25 mm

Hinge Bolt Clamp

Type	Material	Ordering no.
5P8	Stainless steel 1.4408	095.016.1Y.16.52.0
5P9	Stainless steel 1.4408	095.016.1Y.16.53.0

Welding Flange

Type	Material	Ordering no.
5P8	Stainless steel 1.4404 (316L)	050.020.1Y.01.00.0
5P9	Stainless steel 1.4404 (316L)	050.020.1Y.01.01.0

Weld flanges adapted to pipe curve are available on request.


Gasket

Type	Material	Ordering no.
5P8	FKM	095.015.79.12.24.0
	EPDM	095.015.E9.12.24.0
5P9	FKM	095.015.79.12.25.0
	EPDM	095.015.E9.12.25.0





PLANNING AIDS



» PLANNING AIDS YOU CAN COUNT ON OUR SUPPORT



To achieve the optimum spray pattern for your application, numerous influencing factors must be taken into account. The following provides an overview of the key parameters. Needless to say, we will be more than happy to help you find the ideal nozzle.

- **Flow rate**
- **Droplet size**
- **Spray angle**
- **Viscosity**
- **Impact**
- **Nozzle arrangement**
- **Determination of the pipe diameter**
- **Conversion tables**
- **Lechler online services**
- **Certificates and declarations**






Flow rate conversion

With single element nozzles, the flow rate is controlled exclusively via the connection pressure.
The following correlation applies:

	Axial-flow full cone nozzles	All other single element nozzles
Calculation of the flow rate $\dot{V}$ [l/min] at a given pressure p [bar]	$\dot{V}_2 = \left(\frac{p_2}{p_1}\right)^{0.4} \cdot \dot{V}_1$	$\dot{V}_2 = \sqrt{\frac{p_2}{p_1}} \cdot \dot{V}_1$
Calculation of the pressure p [bar] at a given flow rate $\dot{V}$ [l/min]	$p_2 = \left(\frac{\dot{V}_2}{\dot{V}_1}\right)^{2.5} \cdot p_1$	$p_2 = \left(\frac{\dot{V}_2}{\dot{V}_1}\right)^2 \cdot p_1$

Flow rate via pressure

Pressure-flow rate chart for two single element nozzles



- Flow rate axial-flow full cone nozzle
- Flow rate of all other single element nozzles

All pressure values refer to the difference Delta p between the connection pressure and the ambient pressure.

$$\Delta p = p_1 - p_2$$



To double the flow rate, four times the connection pressure is, thus, required for all single element nozzles, except for axial-flow full cone nozzles.

Flow rate as a function of the medium density

For media with a lower density than water, the volume rate increases.


$\dot{V}_W = \frac{\dot{V}_{FI}}{X}$						$\dot{V}_W$ = flow rate of water [l/min, l/h]													
$\dot{V}_{FI} = \dot{V}_W \sqrt{\frac{\rho_W}{\rho_{FI}}} = \dot{V}_W \cdot X$						$\dot{V}_{FI}$ = flow rate of the liquid whose density deviates from 1,000 [kg/m³]													
$X = \sqrt{\frac{\rho_W}{\rho_{FI}}}$						X = multiplier ρ = density [kg/m³]													
ρ_{FI}	500	600	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500	1,600	1,700	1,800	1,900	2,000			
X	1.41	1.29	1.20	1.12	1.06	1.00	0.95	0.91	0.88	0.85	0.82	0.79	0.77	0.75	0.73	0.71			




Each nozzle produces a spray of differently sized droplets (polydisperse spray). For many applications (e.g. evaporative cooling, absorption processes), the size of the total surface area of all the droplets is crucial. The Sauter mean diameter (D_{32}) was defined for this reason.

If you transform the total volume of the droplets of a spray into droplets of equal size, which in sum would have the identical volume/surface ratio as the actual spray, these droplets would have the Sauter mean diameter.

Monodisperse spray (quite rare in reality)




Typical droplet distribution of the spray of a single element nozzle




The sprays have varying droplet sizes. However, the ratio of surface area to volume is the same for both and thus also their Sauter mean diameter.

Rough classification of droplet sizes



Droplet diameter as a function of the operating pressure



Influences on the droplet size

The following applies in general to all single element nozzles:

- The higher the **operating pressure**, the finer the droplets.
- The smaller the **nozzle outlet bore**, the finer the droplets.
- The higher the **viscosity** of the medium being atomised, the larger the droplets.



Cone and flat fan nozzles are available with varying spray angles. The spray angle can significantly influence the result of the process and should, therefore, be chosen carefully. The angles specified in the tables apply to operation with water at the respective design pressure. In case of deviating operating conditions, the angle may deviate from this value.

Influences on the spray angle

The following factors influence the size of the spray angle:

- Pressure**

The operating pressure has a significant influence on the spray angle. At very low or very high pressure levels, the spray angle is smaller than at the optimum operating pressure.


- Distance**

At small distances, the spray width initially increases with the distance and can be determined easily using the trigonometric function. Straight-line pattern can be assumed. With greater spraying heights, the trajectory points increasingly downwards, thus reducing the effective spray angle.


- Viscosity**

The higher the viscosity of the liquid being sprayed, the smaller the spray angle. The viscosity of liquids can usually be reduced by heating them up.

Change in the spray pressure



Height of the nozzle position






The viscosity of a liquid has a significant influence on the spray behaviour of the nozzle. When selecting the right nozzle, the viscosity must, therefore, be taken into account.


Single element nozzle

Example: Hollow cone, full cone, flat fan nozzles




Pneumatic atomising nozzles (internal mixing)

Example: Series 136.1, 136.2, 136.4, 136.5, 166.1, 166.2, 166.4, 140




Pneumatic atomising nozzles (external mixing)

Example: Series 136.3, 136.6, 166.6, 176



- No influence on the spray pattern
- Influence on the spray pattern
- Significant influence on the spray pattern

Medium	Temperature [°C]	Viscosity [mPa·s]
Water	20	1
Milk	20	2
Olive oil	20	108
Olive oil	60	20
Sugar solution 65° Bx	20	120
Sugar solution 70° Bx	20	400
Gelatine	45	1,200



Impact is the pressure in N/mm^2 that the spray jet generates as it strikes the surface. This is crucial for the majority of cleaning tasks. The greater the impact, the better the cleaning result. Lechler high pressure nozzles are characterised by a uniformly high impact across the entire spray width.


$$I = \frac{\text{Impact force}}{\text{Impact surface}} = \frac{F}{A} \quad [\text{N/mm}^2]$$

Influences on the impact

The following factors influence the size of the impact:

- **Impact surface and jet shape**

The impact surface is the area where the spray jet strikes. The smaller the impact surface, the greater the impact. The highest impact values can be achieved with solid stream nozzles and flat fan nozzles with a small spray angle.




Comparison of the cleaning result of three nozzles at an identical pressure level and flow rate.

- **Pressure**

An increase in the connection pressure leads to an increase in the impact.

- **Flow rate**


An increase in the flow rate by using a larger nozzle leads to a higher impact with otherwise unchanged parameters (spray angle, pressure and medium).



Comparison of the cleaning result of three nozzles with an increase in the pressure level and flow rate.




Arrangement of flat fan nozzles with parabolic liquid distribution




Lechler flat fan nozzles ensure consistent, uniform coverage over the impact surface. For this purpose, the spray widths B should overlap by approx. $1/3$ to $1/4$. To stop the sprays interfering with each other, the nozzles should be aligned at an angle of approx. $5-15^\circ$ to the longitudinal axis of the pipe.

Arrangement of tongue-type nozzles



To achieve uniform impact surface coverage, the tongue-type nozzles must be arranged in such a way that the spray widths B overlap by $1/3$ to $1/4$. Therefore, the nozzles should be inclined at an angle of 15° to the vertical of the longitudinal axis of the pipe (either with a nipple welded on at an angle or a Lechler ball joint) to prevent interference of the spray.

Arrangement of full cone nozzles and hollow cone nozzles




With full cone and hollow cone nozzles, the size of the nozzle distance E must ensure that the circular impact surfaces overlap by approx. $1/3$ to $1/4$.

E = nozzle distance H = nozzle installation height B = spray width α = spray angle $\ddot{U}$ = overlapping of the spray angle D = spray diameter

Square and offset arrangement of full cone nozzles and hollow cone nozzles

Square arrangement




$$\text{Nozzle distance: } E = \frac{D}{\sqrt{2}}$$

$$\text{Overlapping: } \ddot{U} = D - E$$

In addition to these arrangement suggestions, please note the information on the spray angle on Page 296 and request a detailed spray width diagram, if required.

Offset arrangement



$$\text{Nozzle distance: } E_1 = \frac{D}{2} \cdot \sqrt{3}$$


$$\text{Nozzle distance: } E_2 = \frac{3}{4} \cdot D$$

$$\text{Overlapping: } \ddot{U} = D - E_1$$



PLANNING AIDS

DETERMINATION OF THE PIPE DIAMETER



The flow rate data in the diagram refers to gases and steam in operating condition.

Example

You want to atomise 100 litres of water a minute. The viscosity of water is $v \approx 1 \cdot 10^{-6} \text{ m}^2/\text{s}$. In the diagram above, look for the intersection of the corresponding viscosity curve and the flow rate lines. Using the coordinates of this point, you can discover the correct inner pipe diameter or pipe size and the most efficient speed.



All the flow rate data in this catalogue is based on measurements with water and takes into account the individual flow parameters of the various nozzle designs.

p pressure

Unit	Conversion			
	bar	Pa = N/m ²	psi	lb/sq ft.
1 bar	1	100,000	14.5	2,089
1 Pa	$1 \cdot 10^{-5}$	1	$14.5 \cdot 10^{-5}$	0.0209
1 psi	0.06895	6,895	1	144
1 lb/sq ft.	$0.479 \cdot 10^{-3}$	47.9	$6.94 \cdot 10^{-3}$	1






V volume

Unit	Conversion			
	l	m ³	Imp. gal	US gal
1 l (1 dm ³)	1	$1 \cdot 10^{-3}$	0.22	0.264
1 m ³	1,000	1	220	264.2
1 Imp. gal	4,546	$4,546 \cdot 10^{-3}$	1	1,201
1 US gal	3,785	$3,785 \cdot 10^{-3}$	0.8327	1

V flow rate

Unit	Conversion				
	l/s	l/min	m ³ /h	Imp. gal	US gal
1 l/s	1	60	3.6	15.85	13.2
1 l/min	0.0167	1	0.06	0.2642	0.22
1 m ³ /h	0.2778	16.67	1	4.4	3.66
1 Imp. gal/min	0.0631	3.785	0.227	1	0.8327
1 US gal/min	0.076	4.546	0.273	1.201	1

Determination of the external thread diameter

						
Nominal size of thread ["] for ISO 228 and EN 10226	1/8	1/4	3/8	1/2	3/4	1

ISO 228 threads are cylindrical and usually require a separate flat gasket or R-ring for sealing.
EN 10226 threads are conical and can be sealed with sealing tape, etc.



You can find all the latest information about Lechler, our products and services at any time at www.lechler.com.

3D design data

With the free 3D design data of Lechler nozzles and accessories, we support your design needs at every step.



After registering free of charge, you can download the required data packs in all common CAD formats at <http://lechler.partcommunity.com>.

- Time-saving, direct download of construction drawings and technical data
- Simple product selection similar to the Lechler print catalogue
- Preview function with product photo and 3D graphics
- Available in all common 3D file formats

Always at hand – the Lechler industry app

The Lechler industry app provides all important calculation and conversion programs combined in one interface:

- Unit calculator for pressure, volume and flow rate
- Pressure/Flow rate calculator for single element nozzles, including axial-flow full cone nozzles
- Determination of the pipe diameter



iOS (Apple)



Android (Google)

Available free of charge in the Apple App Store and the Google Play Store.



We can issue various certificates and attestations for our products. Whether the desired document can be issued for a specific product must be checked in advance. We will be more than happy to inform you of the conditions for the documents upon request.

Declaration of Compliance EN 10204 - 2.1

This declaration of compliance confirms that the products supplied have been manufactured and tested in accordance with the relevant specifications.

Test Report EN 10204 - 2.2

The test report can be issued either with regard to the material (including the non-specific material certificate of the supplier) or with regard to the spray parameters (spray angle and flow rate, without an additional document).

Inspection Certificate EN 10204 - 3.1

The inspection certificate is usually issued with regard to the material. In this case, the parts are manufactured order-related with re-stamping.

However, a specific certificate can also be issued with regard to the flow rate, spray angle, dimensions of nozzles, etc.

FDA Declaration of Conformity

Confirmation that the material used complies with FDA regulations.

Declaration of Conformity to regulation (EC) no. 1935/2004 and (EC) no. 10/2011

Confirmation that the product supplied is suitable for use with foodstuffs and that the material complies with the stated regulations.

Supplier's Declaration

Certificate issued by Lechler confirming that the products have been wholly produced or originate in the European Union. A supplier's declaration can be issued in relation to a specific order (individual supplier's declaration) or as a long-term supplier's declaration that remains valid for two years.

Certificate of Origin

Official confirmation of the origin of a product, certified by the Chamber of Commerce and Industry.

GREAT ATTENTION
TO DETAIL
PRECISION BY
LECHLER

**ENGINEERING
YOUR SPRAY SOLUTION**



Lechler GmbH · Precision Nozzles · Nozzle Systems
Paul-Lechler-Strasse 11 · 72555 Metzingen, Germany · Phone +49 7123 962-0 · info@lechler.de · www.lechler.com

Edition 09/25 · EN · 907164
Subject to technical modifications or mistakes.